

mbsm.pro , CUBIGEL Compressor GX21TB, 220-240 VOLTS, 5/8 HP , R134a

Category: Solutions,Tester ok
written by Jamila | 14 September 2018



GX21TB VE01
220-240V 50Hz ~1

COMPRESSOR		APPLICATION		
Displacement (cm3)	20.72	Application	High/Mid. back pressure	
Diameter (mm)	34.93	Refrigerant	R134a	
Stroke (mm)	21.62	Evaporating (°C)	-25 to 10	
Net Weight (Kg)	17	Expansion	Capillar/Valve	
Oil type	ISO VG 46 ESTER	Comp. cooling	Fan cooled	
Oil charge (cm3)	500	Max. ambient temp. (°C)	43	
MOTOR		NOMINAL PERFORMANCE	CYCLE C	CYCLE D
Approximate Power (CV)	5/8	Cooling capacity (W)	1550	1855
Voltage/Frequency (V/Hz)	220V 50Hz	Input power (W)	818	850
Voltage range (V)	187-264	EER (kcal/Wh)	1.62	1.87
Code	82.197	COP (W/W)	1.89	2.18
Type	CSIR	Current (A)	5.16	5.29
Phase number	1 PH	TEST CONDITIONS		
Locked rotor current (A)	26.0	Evaporating temp. (°C)	5.0	7.2
Main W. resist. at 25°C (Ω)	2.45	Condensing temp. (°C)	55.0	55.0
Start W. resist. at 25°C (Ω)	25.9	Liq.t. entering expan. (°C)	55.0	46.0
		Ambient t. and return (°C)	32.0	35.0
		Tens/Freq (V/Hz)	220V 50Hz	220V 50Hz
ELECTRICAL COMPONENTS				
Relay	9660 A 180	MTRP 16		
Pick-Up (A)	16,70	16,70		
Drop-Out (A)	14,00	14,00		
Protector	MRA38128	T0535/G.		
Current (A)	17.0	17.0		
Time check (seg)	7.5-14	7.5-14		
Disc temp. (Open/Close) (°C)	105.0 / 52.0	105.0 / 52.0		

PictureS Mbsm Dot Pro : www.mbsm.pro

mbsm.pro , CUBIGEL Compressor GX21TB, 220-240 VOLTS, 5/8 HP , R134a

CUBIGEL Compressor GX21TB

TECHNICAL DETAILS

- GX21TB
- 220-240/1/50 VOLTS
- 5/8 HP
- R134a

COMPRESSOR

Displacement (cm ³)	20.72
Diameter (mm)	34.93
Stroke (mm)	21.62
Net Weight (Kg)	17
Oil type	ISO VG 46 ESTER
Oil charge (cm ³)	500

MOTOR

Approximate Power (CV)	5/8
Voltage/Frequency (V/Hz)	220V 50Hz
Voltage range (V)	187-264
Code	82.197
Type	CSIR
Phase number	1 PH
Locked rotor current (A)	26.0
Main W. resist. at 25°C (Ω)	2.45
Start W. resist. at 25°C (Ω)	25.9

ELECTRICAL COMPONENTS

Relay	9660 A 180	MTRP 16
Pick-Up (A)	16,70	16,70
Drop-Out (A)	14,00	14,00
Protector	MRA38128	T0535/G.
Current (A)	17.0	17.0
Time check (seg)	7.5-14	7.5-14
Disc temp. (Open/Close) (°C)	105.0 / 52.0	105.0 / 52.0

APPLICATION

Application	High/Mid. back pressure
Refrigerant	R134a
Evaporating (°C)	-25 to 10
Expansion	Capillar/Valve
Comp. cooling	Fan cooled
Max. ambient temp. (°C)	43

NOMINAL PERFORMANCE

	CYCLE C	CYCLE D
Cooling capacity (W)	1550	1855
Input power (W)	818	850
EER (kcal/Wh)	1.62	1.87
COP (W/W)	1.89	2.18
Current (A)	5.16	5.29

TEST CONDITIONS

Evaporating temp. (°C)	5.0	7.2
Condensing temp. (°C)	55.0	55.0
Liq.t. entering expan. (°C)	55.0	46.0
Ambient t. and return (°C)	32.0	35.0
Tens/Freq (V/Hz)	220V 50Hz	220V 50Hz

