

MBSM.PRO , Compressor, Electrolux-Zem
GL60AA R134A ,1/6 HP , 1PH , 220-240
V 50 Hz

Category: Solutions,Tester ok
written by Jamila | 1 October 2018



PictureS Mbsm Dot Pro : www.mbsm.pro

MBSM.PRO , Compressor, Electrolux-Zem GL60AA R134A ,1/6 HP , 1PH , 220-240 V 50 Hz



PictureS Mbsm Dot Pro : www.mbsm.pro

- Puissance en cheval 1/6 CV
- Cylindrée 5.99 cm³
- 220-240 V 50 Hz
- Gaz R134a LBP
- Température d'utilisation max. 32°C
- Avec boîtier et système de démarrage

La photo montre l'aspect du compresseur, pas son étiquette réelle

Codes fabricants

- ACC-GL60AA
- ACC-GL60AB
- ACC-GL60AH
- CUBIGEL-GL60AA
- CUBIGEL-GL60AB
- CUBIGEL-GL60AH
- MONDIAL ELITE-4106004
- MONDIAL ELITE-1147031
- Embraco Aspera- B1112Z





PictureS Mbsm Dot Pro : www.mbsm.pro



PictureS Mbsm Dot Pro : www.mbsm.pro

Mbsm_dot_pro_private_PDF_GL60AATélécharger
Mbsm_dot_pro_private_PDF_-GL60AATélécharger

590689

GL60AA 99H27NA

GL60AA


08283

03254

267799

THERMALLY 220 - 240 V~ 50 Hz PH1
PROTECTED

R134a



Type: Hermetic piston compressors**Producer:** ACC**Series:** HMBP

Model: GL60AA

General data

Refrigerant: R134a

Discharge element: C

Cooling: S

Maximum ambient temperature [$^{\circ}\text{C}$]: 43

Compressor's data

Cylinder capacity [cm^3]: 6

Displacement [m^3/h]: 1

Weight [kg]: 9,1

Oil charge [cm^3]: 265

Oil type: ISO VG 19 ESTER

Engine's data

Engine type: RSIR

Power [KM]: 1/6

Starting element: LST

Power supply: 220V 50Hz

Voltage range: 187-264

Locked rotor current [A]: 9,9

Running winding resistance (25°C) [Ω]: 15,6

Starting winding resistance (25°C) [Ω]: 21,31

Electrical data

Relays: 3003

Shielding element: MRA38028, T0508, AF18FU

Starting capacitor volume [μF]:

Connections

milimeters inches

Suction tube: 6,5

Service tube: 6,5

Discharge tube: 4,9