## Austria ,RECIPROCATING ,COMPRESSOR ,SECOP ,HXD30AA ,0.04 1/25 HP ,R600a , 220v 50Hz

Category: Technologie, Tester ok written by www.mbsm.pro | 26 April 2020



PictureS Mbsm Dot Pro : WWW.mbsm.pro

| Model  |  |
|--|--|
| :Compressor type   | Round trip compressor                    |
| :Compressor model  | HXD30AA                                  |
| : Manufacturer   | Scoop                                    |
| : Manufacturing Country  | Slovakia                                 |
| Electrical specifications  |  |
| :Capacity (Hp)   | 0.04                                     |
| :Voltage / phase / hertz   | 50/1/220                                 |
| :Consumer amps   |  |
| :Number of solenoid valves   | (x) \\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\ |
| :Number of phases  | 1  |
| Technical Specifications   |  |
| :Dubai (CFM)   |  |
| Activer Windows :Dubai (M ^ 3 / hr) Accédez aux paramètres pour activer Wi |  |
| :Temperature application   |  |

PictureS Mbsm Dot Pro : www.mbsm.pro

|            |                |             |  | ASHRAE ASHRAE |     |   |                                    |    |                                   |       |                                  |       |                  | -                       |                    |  |     |
|------------|----------------|-------------|--|---------------|-----|---|------------------------------------|----|-----------------------------------|-------|----------------------------------|-------|------------------|-------------------------|--------------------|--|-----|
| Compressor | Code<br>number | Application | Capacity [W] Tc=45°C, Tuq=32.2°C, Tsuc=32.2°C Evaporating temperature [°C] |               |     |   | LBP rating point<br>-23.3°C / 45°C |    | MBP rating point<br>-6.7°C / 45°C |       | HBP rating point<br>7.2°C / 45°C |       | Displacement     | Voltage and frequencies | Compressor         |  |     |
|            |                | Appl        | -35  | -15           | -5  | 0 | 10                                 | 15 | Cooling capacity                  |       | Cooling capacity                 | COP   | Cooling capacity | COP                     | Disp               | (* dual frequency<br>type with 50/60 Hz) | Com |
|            |                |             |  |               |     |   |                                    |    | [W]                               | [W/W] | [W]                              | [W/W] | [W]              | [W/W]                   | [cm <sup>3</sup> ] |  |     |
| HTD30AA    | CD000052       | LBP         | 20   | 83            | 127 |   |                                    |    | 53                                | 1.84  |                                  |       |                  |                         | 3.00               | 187-264 V, 50 Hz                         |     |
| HTD35AA    | CD000053       | LBP         | 28   | 97            | 149 |   |                                    |    | 63                                | 1.86  |                                  |       |                  |                         | 3.50               | 187-264 V, 50 Hz                         |     |
| HTD40AA    | CD000054       | LBP         | 36   | 114           | 174 |   |                                    |    | 75                                | 1.90  |                                  |       |                  |                         | 4.00               | 187-264 V, 50 Hz                         |     |
| HTD45AA    | CD000055       | LBP         | 39   | 136           | 201 |   |                                    |    | 90                                | 1.89  |                                  |       |                  |                         | 4.80               | 187-264 V, 50 Hz                         |     |
| HTD55AA    | CD000056       | LBP         | 56   | 161           | 240 |   |                                    |    | 109                               | 1.92  |                                  |       |                  |                         | 5.50               | 187-264 V, 50 Hz                         |     |
| HTD60AA    | CD000073       | LBP         | 66   | 182           | 278 |   |                                    |    | 122                               | 1.91  |                                  |       |                  |                         | 6.20               | 187-264 V, 50 Hz                         |     |
| HTD30AG    | CD000118       | LBP         | 21   | 79            | 124 |   |                                    |    | 50                                | 1.71  |                                  |       |                  |                         | 3.00               | 198-253 V, 50 Hz *                       |     |
| HXD30AA    | CD000097       | LBP         | 22   | 80            | 128 |   |                                    |    | 51                                | 1.90  |                                  |       |                  |                         | 3.00               | 187-264 V, 50 Hz                         |     |
| HXD35AA    | CD000098       | LBP         | 27   | 94            | 148 |   |                                    |    | 61                                | 1.97  |                                  |       |                  |                         | 3.50               | 187-264 V, 50 Hz                         |     |
| HXD40AA    | CD000099       | LBP         | 34   | 112           | 175 |   |                                    |    | 73                                | 1.92  |                                  |       |                  |                         | 4.00               | 187-264 V, 50 Hz                         |     |
| HXD45AA    | CD000100       | LBP         | 42   | 131           | 203 |   |                                    |    | 86                                | 1.92  |                                  |       |                  |                         | 4.80               | 187-264 V, 50 Hz                         |     |
| HXD55AA    | CD000101       | LBP         | 52   | 153           | 229 |   |                                    |    | 101                               | 1.96  |                                  |       |                  |                         | 5.50               | 187-264 V, 50 Hz                         |     |
| HXD60AA    | CD000102       | LBP         | 59   | 171           | 261 |   |                                    |    | 115                               | 1.90  |                                  |       |                  |                         | 6.20               | 187-264 V, 50 Hz                         |     |
| HZD30AA    | CD000088       | LBP         | 21   | 79            | 125 |   |                                    |    | 49                                | 1.98  |                                  |       |                  |                         | 3.00               | 187-264 V, 50 Hz                         |     |
| HZD35AA    | CD000089       | LBP         | 27   | 95            | 149 |   |                                    |    | 61                                | 2.03  |                                  |       |                  |                         | 3.50               | 187-264 V, 50 Hz                         |     |
| HZD40AA    | CD000090       | LBP         | 33   | 110           | 172 |   |                                    |    | 72                                | 2.02  |                                  |       |                  |                         | 4.00               | 187-264 V, 50 Hz                         |     |
| HZD45AA    | CD000091       | LBP         | 43   | 132           | 204 |   |                                    |    | 87                                | 2.04  |                                  |       |                  |                         | 4.80               | 187-264 V, 50 Hz                         |     |
| HZDSSAA    | CDOODOGO       | IRP         | 50   | 15/           | 23% |   |                                    |    | 103                               | 2.05  |                                  |       |                  |                         | 5 50               | 187-264 V 50 Hz                          |     |

PictureS Mbsm Dot Pro : WWW.mbsm.pro