

Compressor ACC Cubigel Huayi  
Electrolux ZEM GP14FB, Low back  
pressure, 134a, 220 -240V/1/50Hz, 3/8  
HP ,CSIR

Category: compressor

written by [www.mbsm.pro](http://www.mbsm.pro) | 16 June 2020



Electrolux  
COMPRESSORS  
THERMALLY PROTECTED  
GP14FB  
220 - 240 V ~ 50 Hz PH1  
R 134 a  
02152  
00122  
359102

Private Picture Copyright : [WWW.MBSM.PRO](http://WWW.MBSM.PRO)

Private Picture Copyright : [WWW.MBSM.PRO](http://WWW.MBSM.PRO)

Compressor ACC Cubigel Huayi Electrolux ZEM GP14FB, LBP – 134a, 220  
-240V/1/50Hz, 3/8 HP, discharge 14.17 cm<sup>3</sup>, motor type CSIR, oil type ISO VG 22  
ester, oil charge 400 cm<sup>3</sup>, 229 W at -25 / +55 °, input power, current 256 W,  
1.75 A, expansion device: capillary or valve, fan cooling, weight 11.5 kg , the  
statutory warranty period shall apply (24 months), Delivery time Info: with  
“immediately available” and “scarce stock”, usually delivery within 2 days. For  
“currently not available” delivery time usually 2 weeks or delivery time in  
urgent cases contact us.

---

Refrigerant:	R134a
Power range(W):	201 – 300 W
Performance range (C):	-35 C to -10 C
Connecting size:	6,5 mm
Suction:	8,1 mm
Working area:	LBP
Design type:	Hermetic
Model series:	GP
Use with:	Expansion/Capillary
Power range(HP):	0-2
Power supply:	230 V
Oil type:	ISO VG 22 Ester
Engine type:	CSIR
Article condition:	New
Info:	Oil filled
Shipping weight:	13,50 Kg
Dimensions ( length × width × height ):	23,10 × 16,20 × 19,60 cm
Cooling capacity condition:	T0 -25 C, Tk +55 C
Manufacturer:	ACC Cubigel Huayi Electrolux ZEM
Model:	GP14FB
Stroke volume (cm <sup>3</sup> ):	14,17
Cooling capacity (W):	228
Power (HP):	0,4
Power consumption (W):	256
Max. Starting current (A):	12
Max. Operating current (A):	1,75
Engine type:	CSIR
COP:	0,9
Note:	Fan cooling necessary
Oil quantity (l):	0,4
Compressor type:	Piston
Kühlung:	Lüfter
Power range:	-35 C to -10 C
Alternative:	NE2130Z
Pressure line (mm):	6,5
Suction line (mm):	8,1
Refrigerant:	R134a

Discharge element: C-V  
Cooling: F  
Maximum ambient temperature [°C]: 43

#### Compressor's data

Cylinder capacity [cm<sup>3</sup>]: 14  
Displacement [m<sup>3</sup>/h]: 2,4  
Weight [kg]: 11,5  
Oil charge [cm<sup>3</sup>]: 400  
Oil type: ISO VG 22 ESTER

#### Engine's data

Engine type: CSIR  
Power [KM]: 3/8  
Starting element: HST  
Power supply: 220V 50Hz  
Voltage range: 198-264  
Locked rotor current [A]: 12  
Running winding resistance (25°C) [Ω]: 6,53  
Starting winding resistance (25°C) [Ω]: 23,76

#### Electrical data

Relays: 9660 A 145, MTRP 46  
Shielding element: MRT40AMK, T0137  
Starting capacitor volume [μF]:

#### Connections

milimeters inches

Suction/service tube: 8,1  
Service/suction tube: 8,1  
Discharge tube: 6,55

[Mbsm\\_dot\\_pro\\_private\\_PDF\\_danfoss\\_GP14FB\\_R134a\\_220\\_50Télécharger](#)

[Mbsm\\_dot\\_pro\\_private\\_PDF\\_GP14FBTélécharger](#)



Équivalent /<https://www.mbsm.pro/44542.html>

Compresseur-ACC-Cubigel-Huayi-Electrolux-ZEM-GP14FB-Basse-contre-  
pression-134a-220-240V-1-50Hz-3-8-CV-CSIRDownload

