Compressor ACC Cubigel Huayi Electrolux ZEM GP14FB, Low back pressure, 134a, 220 -240V/1/50Hz, 3/8 HP ,CSIR

Category: compressor
written by www.mbsm.pro | 16 June 2020

Private Picture Copyright : WWW.MBSM.PRO
Private Picture Copyright : WWW.MBSM.PRO

Compressor ACC Cubigel Huayi Electrolux ZEM GP14FB, LBP – 134a, 220 -240V/1/50Hz, 3/8 HP, discharge 14.17 cm3, motor type CSIR, oil type ISO VG 22 ester, oil charge 400 cm3, 229 W at -25 / +55 °, input power, current 256 W, 1.75 A,expansion device: capillary or valve, fan cooling, weight 11.5 kg , the statutory warranty period shall apply (24 months), Delivery time Info: with “immediately available” and “scarce stock”, usually delivery within 2 days. For “currently not available” delivery time usually 2 weeks or delivery time in urgent cases contact us.

Refrigerant:	R134a
Power range(W):	201 – 300 W
Performance range (C):	-35 C to -10 C
Connecting size:	6,5 mm
Suction:	8,1 mm
Working area:	LBP
Design type:	Hermetic
Model series:	GP
Use with:	Expansion/Capillary
Power range(HP):	0-2
Power supply:	230 V
Oil type:	ISO VG 22 Ester
Engine type:	CSIR
Article condition:	New
Info:	Oil filled
Shipping weight:	13,50 Kg
Dimensions (length × width × height):	23,10 × 16,20 × 19,60 cm
Cooling capacity condition:	T0 -25 C, Tk +55 C
Manufacturer:	ACC Cubigel Huayi Electrolux ZEM
Model:	GP14FB
Stroke volume (cm3):	14,17
Cooling capacity (W):	228
Power (HP):	0,4
Power consumption (W):	256
Max. Starting current (A):	12
Max. Operating current (A):	1,75
Engine type:	CSIR
COP:	0,9
Note:	Fan cooling necessary
Oil quantity (l):	0,4
Compressor type:	Piston
Kühlung:	Lüfter
Power range:	-35 C to -10 C
Alternative:	NE2130Z
Pressure line (mm):	6,5
Suction line (mm):	8,1

Refrigerant: R134a

Discharge element:	C-V
Cooling:	F
Maximum ambient temperature [ºC]:	43

Compressor’s data

Cylinder capacity [cm³]:	14
Displacement [m³/h]:	2,4
Weight [kg]:	11,5
Oil charge [cm³]:	400
Oil type:	ISO VG 22 ESTER

Engine’s data

Engine type:	CSIR
Power [KM]:	3/8
Starting element:	HST
Power supply:	220V 50Hz
Voltage range:	198-264
Locked rotor current [A]:	12
Running winding resistance (25ºC) [Ω]:	6,53
Starting winding resistance (25ºC) [Ω]:	23,76

Electrical data

Relays:	9660 A 145, MTRP 46
Shielding element:	MRT40AMK, T0137
Starting capacitor volume [µF]:	

Connections

	milimeters	inches
Suction/service tube:	8,1	
Service/suction tube:	8,1	
Discharge tube:	6,55	

Mbsm_dot_pro_private_PDF_danfoss_GP14FB_R134a_220_50Télécharger
Mbsm_dot_pro_private_PDF_GP14FBTélécharger

Private Picture Copyright : WWW.MBSM.PRO

Équivalent /https://www.mbsm.pro/44542.html
Compresseur-ACC-Cubigel-Huayi-Electrolux-ZEM-GP14FB-Basse-contre-pression-134a-220-240V-1-50Hz-3-8-CV-CSIRDownload