

# ZMC, zanussi, Made in Egypt, Compressors

Category: compressor

written by [www.mbsm.pro](http://www.mbsm.pro) | 8 April 2021

## R134a

Model	Refr.	HP	Ambient Temp C	Rated Voltage	Cooling Capacity		COP without RC		COP with RC	
					ASHRAE	CECOMAF	ASHRAE	CECOMAF	ASHRAE	CECOMAF
					-23.3°C kcal/h	-25°C W	-23.3°C W/W	-25°C W/W	-23.3°C W/W	-25°C W/W
<input type="checkbox"/> <a href="#">GL45AA</a>	LBP::R134a	1/8	43	A	96	82	1.06	0.82		
<input type="checkbox"/> <a href="#">GL45AN</a>	LBP::R134a	1/8	50	C	96	81	1.05	0.8		
<input type="checkbox"/> <a href="#">GL60AA</a>	LBP::R134a	1/6	43	A	132	114	1.14	0.89		
<input type="checkbox"/> <a href="#">GL60AF</a>	LBP::R134a	1/6	43	D	132	113	1.07	0.82		
<input type="checkbox"/> <a href="#">GL60AH</a>	LBP::R134a	1/6	43	A	133	114	1.31	1.01		
<input type="checkbox"/> <a href="#">GL60AN</a>	LBP::R134a	1/6	50	C	132	114	1.07	0.83		
<input type="checkbox"/> <a href="#">GL70AA</a>	LBP::R134a	1/5	43	A	149	128	1.18	0.92		
<input type="checkbox"/> <a href="#">GL70AN</a>	LBP::R134a	1/5	50	D	150	129	1.08	0.83		
<input type="checkbox"/> <a href="#">GL70AT</a>	LBP::R134a	1/5	43	E	144	122	1.09	0.84		
<input type="checkbox"/> <a href="#">GL75AA</a>	LBP::R134a	1/5	43	A	155	133	1.18	0.92		
<input type="checkbox"/> <a href="#">GL80AA</a>	LBP::R134a	1/5	43	A	173	148	1.19	0.93		
<input type="checkbox"/> <a href="#">GL80AF</a>	LBP::R134a	1/5	43	D	166	141	1.14	0.88		
<input type="checkbox"/> <a href="#">GL80AH</a>	LBP::R134a	1/5	43	A	175	150	1.35	1.06		
<input type="checkbox"/> <a href="#">GL80AN</a>	LBP::R134a	1/4	43	A	196	168	1.36	1.06		
<input type="checkbox"/> <a href="#">GL90AA</a>	LBP::R134a	1/4	43	A	195	167	1.19	0.93		
<input type="checkbox"/> <a href="#">GL90AH</a>	LBP::R134a	1/4	43	A	215	182	1.39	1.08		
<input type="checkbox"/> <a href="#">GL90AN</a>	LBP::R134a	1/4	50	D	190	163	1.1	0.85		
<input type="checkbox"/> <a href="#">GL90AT</a>	LBP::R134a	1/4	43	E	190	161	1.19	0.92		
<input type="checkbox"/> <a href="#">GL99AA</a>	LBP::R134a	1/4	43	A	214	182	1.24	0.96		
<input type="checkbox"/> <a href="#">GL99AH</a>	LBP::R134a	1/4	43	A	215	182	1.39	1.08		
<input type="checkbox"/> <a href="#">GL80AD</a>	LBP::R134a	1/5	43	W	0	0	0	0		
<input type="checkbox"/> <a href="#">GL90AD</a>	LBP::R134a	1/4	43	W	0	0	0	0		

## R134a

Model	Refr.	HP	Ambient Temp C	Rated Voltage	Cooling Capacity		COP without RC		COP with RC	
					ASHRAE	CECOMAF	ASHRAE	CECOMAF	ASHRAE	CECOMAF
					-23.3°C kcal/h	-25°C W	-23.3°C W/W	-25°C W/W	-23.3°C W/W	-25°C W/W
▶ <input type="checkbox"/> <a href="#">GL45AA</a>	LBP::R134a	1/8	43	A	96	82	1.06	0.82		
▶ <input type="checkbox"/> <a href="#">GL45AN</a>	LBP::R134a	1/8	50	C	96	81	1.05	0.8		
▶ <input type="checkbox"/> <a href="#">GL60AA</a>	LBP::R134a	1/6	43	A	132	114	1.14	0.89		
▶ <input type="checkbox"/> <a href="#">GL60AF</a>	LBP::R134a	1/6	43	D	132	113	1.07	0.82		
▶ <input type="checkbox"/> <a href="#">GL60AH</a>	LBP::R134a	1/6	43	A	133	114	1.31	1.01		
▶ <input type="checkbox"/> <a href="#">GL60AN</a>	LBP::R134a	1/6	50	C	132	114	1.07	0.83		
▶ <input type="checkbox"/> <a href="#">GL70AA</a>	LBP::R134a	1/5	43	A	149	128	1.18	0.92		
▶ <input type="checkbox"/> <a href="#">GL70AN</a>	LBP::R134a	1/5	50	D	150	129	1.08	0.83		
▶ <input type="checkbox"/> <a href="#">GL70AT</a>	LBP::R134a	1/5	43	E	144	122	1.09	0.84		
▶ <input type="checkbox"/> <a href="#">GL75AA</a>	LBP::R134a	1/5	43	A	155	133	1.18	0.92		
▶ <input type="checkbox"/> <a href="#">GL80AA</a>	LBP::R134a	1/5	43	A	173	148	1.19	0.93		
▶ <input type="checkbox"/> <a href="#">GL80AF</a>	LBP::R134a	1/5	43	D	166	141	1.14	0.88		
▶ <input type="checkbox"/> <a href="#">GL80AH</a>	LBP::R134a	1/5	43	A	175	150	1.35	1.06		
▶ <input type="checkbox"/> <a href="#">GL80AN</a>	LBP::R134a	1/4	43	A	196	168	1.36	1.06		
▶ <input type="checkbox"/> <a href="#">GL90AA</a>	LBP::R134a	1/4	43	A	195	167	1.19	0.93		
▶ <input type="checkbox"/> <a href="#">GL90AH</a>	LBP::R134a	1/4	43	A	215	182	1.39	1.08		
▶ <input type="checkbox"/> <a href="#">GL90AN</a>	LBP::R134a	1/4	50	D	190	163	1.1	0.85		
▶ <input type="checkbox"/> <a href="#">GL90AT</a>	LBP::R134a	1/4	43	E	190	161	1.19	0.92		
▶ <input type="checkbox"/> <a href="#">GL99AA</a>	LBP::R134a	1/4	43	A	214	182	1.24	0.96		
▶ <input type="checkbox"/> <a href="#">GL99AH</a>	LBP::R134a	1/4	43	A	215	182	1.39	1.08		
▶ <input type="checkbox"/> <a href="#">GL80AD</a>	LBP::R134a	1/5	43	W	0	0	0	0		
▶ <input type="checkbox"/> <a href="#">GL90AD</a>	LBP::R134a	1/4	43	W	0	0	0	0		

## R12

Model	Refr.	HP	Ambient Temp C	Rated Voltage	Cooling Capacity		COP without RC		COP with RC	
					ASHRAE	CECOMAF	ASHRAE	CECOMAF	ASHRAE	CECOMAF
					-23.3°C kcal/h	-25°C W	-23.3°C W/W	-25°C W/W	-23.3°C W/W	-25°C W/W
▶ <input type="checkbox"/> <a href="#">L45AV</a>	LBP::R12	1/8	43	B	221	192	0.91	0.71		
▶ <input type="checkbox"/> <a href="#">L55AV</a>	LBP::R12	1/6	43	B	115	101	0.99	0.78		
▶ <input type="checkbox"/> <a href="#">L55BV</a>	LBP::R12	1/6	43	B	115	101	0.99	0.78		
▶ <input type="checkbox"/> <a href="#">L76AV</a>	LBP::R12	1/5	43	B	145	127	1.05	0.84		
▶ <input type="checkbox"/> <a href="#">L76BV</a>	LBP::R12	1/5	43	B	145	127	1.05	0.84		
▶ <input type="checkbox"/> <a href="#">L88AV</a>	LBP::R12	1/4	43	B	171	150	1.02	0.81		
▶ <input type="checkbox"/> <a href="#">L88BV</a>	LBP::R12	1/4	43	B	171	150	1.02	0.81		
▶ <input type="checkbox"/> <a href="#">LT45AV</a>	LBP::R12	1/8	50	B	94	83	1.04	0.83		
▶ <input type="checkbox"/> <a href="#">LT55AV</a>	LBP::R12	1/6	50	B	115	102	1.06	0.85		
▶ <input type="checkbox"/> <a href="#">LT55BV</a>	LBP::R12	1/6	50	B	115	102	1.06	0.85		
▶ <input type="checkbox"/> <a href="#">LT76BV</a>	LBP::R12	1/5	50	B	155	137	1.14	0.91		
▶ <input type="checkbox"/> <a href="#">LT88BV</a>	LBP::R12	1/4	50	B	190	169	1.16	0.93		
▶ <input type="checkbox"/> <a href="#">P12BW</a>	LBP::R12	1/3	43	A	221	192	0.91	0.71		

Private Picture Copyright: [WWW.MBSM.PRO](http://WWW.MBSM.PRO)

Mbsm\_dot\_pro\_private\_PDF\_catalogo\_cubigel\_R134aTélécharger

## R600a

Model	Refr.	HP	Ambient Temp C	Rated Voltage	Cooling Capacity		COP without RC		COP with RC	
					ASHRAE	CECOMAF	ASHRAE	CECOMAF	ASHRAE	CECOMAF
					-23.3°C kcal/h	-25°C W	-23.3°C W/W	-25°C W/W	-23.3°C W/W	-25°C W/W
▶ <input type="checkbox"/> <a href="#">HL80AH</a>	LBP::R600a	1/7	43	A	104	89	1.37	1.06		
▶ <input type="checkbox"/> <a href="#">HL90AH</a>	LBP::R600a	1/7	43	A	115	99	1.38	1.08		
▶ <input type="checkbox"/> <a href="#">HL99AH</a>	LBP::R600a	1/6	43	A	120	103	1.34	1.03		

Private Picture Copyright: [WWW.MBSM.PRO](http://WWW.MBSM.PRO)

Model	Refr.	HP	Ambient Temp C	Rated Voltage	Cooling Capacity		COP <sub>a</sub> 7.2 <sub>a</sub>
					CECOMAF 5°C	ASHRAE 7.2°C	
					W	kcal/h	
▶ <input type="checkbox"/> <a href="#">GL45PB</a>	HMBP::R.134a	1/6	43	A			
▶ <input type="checkbox"/> <a href="#">GL45PB</a>	HMBP::R.134a	1/6	0	300			
▶ <input type="checkbox"/> <a href="#">GL45TB</a>	HMBP::R.134a	1/6	43	A			
▶ <input type="checkbox"/> <a href="#">GL60PB</a>	HMBP::R.134a	1/5	43	A			
▶ <input type="checkbox"/> <a href="#">GL60TB</a>	HMBP::R.134a	1/5	43	A			
▶ <input type="checkbox"/> <a href="#">GL80PB</a>	HMBP::R.134a	1/5	43	A			
▶ <input type="checkbox"/> <a href="#">GL80TB</a>	HMBP::R.134a	F	0	300			
▶ <input type="checkbox"/> <a href="#">GL90TB</a>	HMBP::R.134a	1/4	43	A			
▶ <input type="checkbox"/> <a href="#">GP12TB</a>	HMBP::R.134a	3/8	43	A			