

# High, Efficiency, R134a, Hermetic, Compressor, GPY16AF, RoHS, 3/8hp, csir, lbp, 220v, 380w

Category: compressor

written by [www.mbsm.pro](http://www.mbsm.pro) | 21 December 2021



Private Picture Copyright : [WWW.MBSM.PRO](http://WWW.MBSM.PRO)

## **R134a GPY16AF series sealed refrigeration compressor 220-240v/50Hz**

The main feature:

strong loading capacity,  
high efficiency,  
low noise,  
light vibration,  
good reliability.

suitable for mid-size refrigerators, freezers, displayers, beer displayers and other mid-size refrigeration appliances. The structure form is hermetical crank connecting-rod reciprocating piston type.

They are the best selling high-tech compressors sold in the world. They are ideal for domestic refrigeration and also for small commercial applications. They are small, have low noise and vibration levels, they achieve the highest levels of efficiency available in the market for this category.

<b>KONOR</b>	<b>Displ. power</b>	<b>Motor type</b>	<b>V/Hz</b>	<b>Cooling capacity</b>	<b>Net W</b>	<b>Weight</b>	<b>KG</b>
GQR60AA 6	1/6	RSIR	220-240V/50Hz	140	9.4		
GQR70AA 6.6	1/5	RSIR	220-240V/50Hz	165	9.4		
GQR80AA 8.1	1/4	RSIR	220-240V/50Hz	198	9.4		
GQR90AA 9.1	1/4	RSIR	220-240V/50Hz	220	10.1		
GQY99AA 9.9	1/4	RSIR	220-240V/50Hz	270	10.9		
GQY12AF 11.8	1/3	CSIR	220-240V/50Hz	325	10.56		
GQY16AF 16.2	3/8	CSIR	220-240V/50Hz	380	12.1		
GP16MG 16.2	5/8	CSIR	220-240V/50Hz	870	12.5		
GP12MG 11.8	5/8	CSIR	220-240V/50Hz	656	10.9		
GP12TG 11.8	3/8	CSIR	220-240V/50Hz	1140	11.8		
GQR80TG 8.1	1/4	CSIR	220-240V/50Hz	730	9.8		
GQR90TG 9.1	1/4	CSIR	220-240V/50Hz	830	10.5		
GQR60TG 6	1/5	CSIR	220-240V/50Hz	520	9.8		

### **Specification**

Hermetic motor driven the piston connecting rod type compressor. With relay start-up of hammer type, and equipped with overload protector.

### **Application**

Widely used in home and commercial refrigerator, air-curtain cabinet, display showcase, ice maker, chiller freezer, dehumidifier, etc.

### **R134a LBP Fan Cooling Compressor**

**Model: GPY16AF**

**Power: 3/8HP**

**Displacement: 16.2cm<sup>3</sup>**

**Capacity: 380w**

**COP: 1.3W**

**Voltage: 200-240V/50HZ**

**Motor Way: CSIR**

**Application: LBP**

**Cooling Type: Fan Cooling**

**Height: 210mm**

**Net Weight: 12.9kg**

**Dimension: 210\*162\*237.2(mm)**

**Test Conditions (ASHRAE)**

**Evaporating temperature -23.3°C**

**Condensing temperature 54.4°C**

Subcooling temperature 32.2°C

Suction temperature 32.2°C

Ambient temperature 32.2°C

Conversion:

1watt=3.41Btu/h=0.86kcal/h



●○ REDMI NOTE 9  
∞ AI QUAD CAMERA

Private Picture Copyright : [WWW.MBSM.PRO](http://WWW.MBSM.PRO)

Mbsm\_dot\_pro\_private\_PDF\_gpy16fTélécharger