

Mbsm.pro, COMPRESSOR, ZEL, Zanussi, refrigerator, CUBIGEL/ ACC , HML140A, HDL140A, LBP, R600A, 220-240V, 1 /8hp, 140w

written by Lilianne | 1 January 2022



Compressor ZEL HDL140A, LBP – R600a, 220-240V, 8.1 cm³.
R600, LBP. 220 / 240V, 1 /8hp, 50Hz. Stroke volume: 8.10 cm³.
Cooling capacity according to Ashrae (-23.3C °): 136kcal / h,
Cecomaf (-25 ° C): 102W. Operation with expansion valve /
capillary tube ..

Compresseur de liquide de refroidissement R600A ZEL HML140A
HS-384

Model HML140A 1/8
Voltage/Frequence 220~240V/50Hz
Refrigerant R600a
Type RSIR/RSCR
Capacitance 3μF

Refrigeration oil mineral oil

Weight $7.1\text{kg} \pm 0.4\text{kg}$

Starting performance 187V (0.3MPa,abs,surrounding temperature 43°C)

Starting electric current 8.46A

Cylinder capacity (cm^3)8.0cc

Refrigerating capacity (W)145

Input power (W)97

Working electric current (A)0,5

COP1,51

16/04/2018



2 4 1 0 2 0 0 4 4 3 6 4 0 3

TREDCO
For Engineering Industries

Model : ES241	R600 a	50 g
Voltage: 220V/ (50-60)HZ	Energy: 1.41 Kw/day	
Capacity: 203 L	Weight: 42Kg	Power: 130W
Chest Freezer	Protection Degree(IPX0)	Class: F
Double insulation	ES 6000/2007	Made in Egypt



REDMI NOTE 9S
SAYED

2022/1/26 18:09



Shipping Class	Standard
Scope Of Application	LBP
Lieferzeit	3 Wochen
Maker	ZEL
Manufacturer No.	HDL140A
Displacement In Cm3	8.1
Style	1
Refrigerants	R600a
Condensing Units Compressors	Compressors
Suspense	220-240V
Weight In Kg	832

Compresseur de liquide de refroidissement R600A ZEL HML140A
HS-384

Voltage/Frequency 220~240V/50Hz

Refrigerant R600a

Type RSIR/RSCR

Capacitance 3μF

Refrigeration oil mineral oil

Weight 7.1kg±0.4kg

Starting performance 187V (0.3MPa,abs,surrounding temperature 43℃)

Starting electric current 8.46A

Cylinder capacity (cm³)8.0cc

Refrigerating capacity (W)145

Input power (W)97

Working electric current (A)0,5

COP1,51

		cc	hp		hz	w	w	w	w/w	w/w	μF	mm	kg
220-240V/50Hz													
普效系列 Standard Efficiency Range													
HML140A	Al	8.0	1/8	RSIR/RSCR	50	140	96	90	1.46	1.56	3	152	6.3
中效系列 Medium Efficiency Range													
HDL100A	Al	5.7	1/10	RSIR/RSCR	50	98	65	60	1.50	1.64	2.5	161	6.9
HDL125A	Al	7.0	1/10	RSIR/RSCR	50	125	77	71	1.62	1.75	2.5	164	7.2
HDL140A	Al	8.0	1/8	RSIR/RSCR	50	140	86	80	1.63	1.76	2.5	164	7.2
高效系列 High Efficiency Range													
HXL100A	Cu	5.7	1/15	RSCR	50	98		52		1.88	2	161	7.3
HXL125A	Cu	7.0	1/10	RSCR	50	125		65		1.91	2	161	7.3
HXL140A	Cu	8.0	1/10	RSCR	50	140		73		1.91	2	161	7.3
HXL170A*	Cu	9.3	1/8	RSCR	50	170		89		1.91	2	161	7.3
超高效系列 Top Efficiency Range													
HPL100A*	Cu	5.7	1/14	CSCR	50	100		50		2.00	2	161	7.3
HPL125A*	Cu	7.0	1/12	CSCR	50	125		63		2.00	2	161	7.3
HPL140A*	Cu	8.0	1/10	CSCR	50	140		70		2.00	2	161	7.3

220-240V/60Hz



Private Picture Copyright: WWW.MBSM.PRO

Mbsm_dot_pro_private_PDF_catalogo-compresores-ZEL-pdfTélécharger