

# Mbsm.pro, Pdf, Book, Catalog, Electrolux, Compressor, r12, R22

Category: Files

written by [www.mbsm.pro](http://www.mbsm.pro) | 2 January 2022



Model / Modelo Modell / Modèle	Power / Potencia Leistung / Puissance	Cyl. cooling / Enfriamiento Kühlung; Refroidissement	Displacement / Cilindrada	Minimum / Cylindrada	<b>Refrigerating capacity</b> Capacidad frigorífica Kälteleistung Production frigorifique COP <sub>25</sub> /MW / W = 0,854 kcal/h = 3,413 Btu/h  <b>Evaporating temp. / Temp. de evaporación</b> Verdampfungstemp. / Temp. d'évaporation °C	Expansion / Expansión Empujando / Chocando	Oil / Aceite Öl / Huile	Weight / Peso Gewicht / Poids	Motor / Motor Motor / Moteur	Starting / Arranque Anlauf / Démarrage
-----------------------------------	--	---	------------------------------	----------------------	---	---	----------------------------	----------------------------------	---------------------------------	---

  

HMBP															
R22 50 Hz	CECOMAF (W)						ASHRAE		R22 50 Hz						
	-20		-15		5		T.3								
	W	COP	W	COP	W	COP	W	COP		W	COP				
<b>110-240V 50Hz ~1</b>															
L40TNa	1,6	F	4,04	149	194	45,8	1,48	544	460	1,91	C	300	9,5	Ran	P
L40TNb	1,6	F	4,04	149	194	45,8	1,48	544	460	1,91	CV	300	9,5	CSR	R
L45TN	1,5	F	4,50	156	206	49,7	1,68	592	500	1,81	CV	300	9,5	CSR	R
LS7TNa	1,5	F	5,67	194	255	61,2	1,72	728	615	1,93	C	300	9,5	95R	P
LS7TNb	1,5	F	5,67	194	255	61,2	1,72	728	615	1,93	CV	300	9,5	CSR	R
L76TN	3,9	F	7,57	268	347	81,6	1,72	971	800	1,95	CV	470	10,0	CSR	R
L88TN	3,8	F	8,85	322	418	97,5	1,74	1161	960	1,97	CV	400	10,6	CSR	R
P10TN	3,7	F	10,18	394	509	119,4	2,03	1421	1200	2,31	CV	400	13,3	CSR	R
P12TN	1,2	F	12,00	412	537	130,2	2,00	1574	1323	2,36	CV	400	12,3	CSR	R
R18TN	3,9	F	18,10	554	755	202,2	2,16	2454	2050	2,46	CV	640	20,3	CSR	R
S18TN	3,9	F	18,10	554	755	202,2	2,16	2454	2050	2,46	CV	640	21,8	CSR	R



Private Picture Copyright : [WWW.MBSM.PRO](http://WWW.MBSM.PRO)

Mbsm\_dot\_pro\_private\_PDF-Electrolux-Compressor-r12-R22-1ph-1Télécharger