Mbsm.pro, Daikin, compressor , R22/R407C

Category: compressor
written by www.mbsm.pro | 24 January 2022



Private Picture Copyright : WWW.MBSM.PRO

High Performance Scroll

-◎ Model Standard Dimension (Refrigerant R22/R407C)

Model	A	B	C	D	E	F	G	H
JT71/90/A-TY/YE1	454	89	89	89	89	89	454	89.6
JT71/90/A-TY/YE2 JT71/90/A-TYE	454	89	89	89	89	89	454.2	89.5
JT95-106B-TY1/YE1	457	89	89	89	89	89	458	89.5
JT95-106B-TY2/YE2	457	89	89	89	89	89	458.2	89.5

-◎ Model Compressor Range (Refrigerant R22)

OUTPUT (HP)	POWER SOURCE	MODEL	ARI STANDARD CAPACITY (POWER SOURCE)		INPUT W	CURRENT A	EER W/W	CAPACITY BTU/H	TUBE CONNECTIONS	
			BTU/H	CAPACITY W					SUCTION TUBE in	DISCHARGE TUBE in
7	380V/50Hz 3 PHASE	JT212G-Y1L	180V/50Hz	22.3	6400	6.56	11.2	3.25	117.3	5/8.4
7.5		JT236G-Y1L	380V/50Hz	23.8	6800	7.27	12.4	3.27	121	5/8.4
8.5		JT265G-Y1L	380V/50Hz	26.5	7600	8.05	13.7	3.3	144.7	7/8.4
10		JT300G-Y1L	380V/50Hz	29.8	8530	9.38	15.2	3.33	162.7	7/8.4
11		JT335G-Y1L	380V/50Hz	31.7	9050	10.23	16.7	3.33	160.5	7/8.4
12		JT355G-Y1L	380V/50Hz	33.2	10000	10.89	17.2	3.38	184.2	7/8.4
7	380-415V/ 460-480V 3 PHASE 50/60Hz	JT212G-YE	380V/50Hz	22.3	6400	6.56	11.2	3.25	117.1	5/8.4
			460/60Hz	26.8	7680	7.88	13.6	3.32		
7.5		JT236G-YE	380V/50Hz	23.8	6800	7.27	12.4	3.27	121	5/8.4
			460/60Hz	28.5	8160	8.72	14.9	3.27		
8.5		JT265G-YE	380V/50Hz	26.5	7600	8.05	13.7	3.3	144.7	7/8.4
			460/60Hz	31.8	9120	9.66	16.5	3.29		
10		JT300G-YE	380V/50Hz	29.8	8530	9.38	15.2	3.33	162.7	7/8.4
			460/60Hz	35.8	10240	11.26	18.5	3.32		
11		JT335G-YE	380V/50Hz	31.7	9050	10.23	16.7	3.33	160.5	7/8.4
			460/60Hz	38.1	10860	12.05	19.7	3.32		
12		JT355G-YE	380V/50Hz	33.2	10000	10.89	17.2	3.38	184.2	7/8.4
			460/60Hz	39.8	12000	13.07	20.6	3.35		
7		JT212G-PYE	380V/50Hz	22.3	6400	6.56	11.2	3.25	117.3	5/8.4
			460/60Hz	26.8	7680	7.88	13.6	3.32		
7.5		JT236G-PYE	380V/50Hz	23.8	6800	7.27	12.4	3.27	121	5/8.4
			460/60Hz	28.5	8160	8.72	14.9	3.27		
8.5		JT265G-PYE	380V/50Hz	26.5	7600	8.05	13.7	3.3	144.7	7/8.4
			460/60Hz	31.8	9120	9.66	16.5	3.29		
10		JT300G-PYE	380V/50Hz	29.8	8530	9.38	15.2	3.33	162.7	7/8.4
			460/60Hz	35.8	10240	11.26	18.5	3.32		
11		JT335G-PYE	380V/50Hz	31.7	9050	10.23	16.7	3.33	160.5	7/8.4
			460/60Hz	38.1	10860	12.05	19.7	3.32		
12		JT355G-PYE	380V/50Hz	33.2	10000	10.89	17.2	3.38	184.2	7/8.4
			460/60Hz	39.8	12000	13.07	20.6	3.35		

TEST CONDITION OF COMPRESSOR					
	EVAPORATOR TEMPERATURE	CONDENSATION TEMPERATURE	DEGREE OF SUPERHEAT	DEGREE OF SUBCOOLING	SUCTION TEMPERATURE
PERFORMANCE	7.2C	54.4C	11.1K	8.3K	18.3C

-◎ Model Compressor Range (Refrigerant R407C)

OUTPUT (HP)	POWER SOURCE	MODEL	ARI STANDARD CAPACITY (POWER SOURCE)		INPUT W	CURRENT A	EER W/W	CAPACITY BTU/H	TUBE CONNECTIONS	
			BTU/H	CAPACITY W					SUCTION TUBE in	DISCHARGE TUBE in
7	380-415V 3 PHASE 50Hz	JT212DA-Y1	360/50Hz	20.9	6300	7.07	12.7	2.75	123.3	5/8.4
8.5	380-415V 3 PHASE 50Hz	JT265DA-Y1	360/50Hz	25.3	7600	8.36	14.1	3.0	144.7	7/8.4
10	380-415V 3 PHASE 50Hz	JT300DA-Y1	360/50Hz	29.3	8900	9.64	16	3.01	162	7/8.4
8	460V 3 PHASE 60Hz	JT212DA-Y1	460/60Hz	24.9	7300	8.7	12.9	2.78	144.2	7/8.4
10	460V 3 PHASE 60Hz	JT300DA-Y1L	460/60Hz	29.6	10000	9.55	16.4	3.1	183	7/8.4
12	460V 3 PHASE 60Hz	JT335DA-Y1L	460/60Hz	35.3	10800	11.01	18.3	3.12	184.2	7/8.4

TEST CONDITION OF COMPRESSOR					
	EVAPORATOR TEMPERATURE	CONDENSATION TEMPERATURE	DEGREE OF SUPERHEAT	DEGREE OF SUBCOOLING	SUCTION TEMPERATURE
COMPRESSOR	7.2C	54.4C	11.1K	8.3K	18.3C

-◎ Model Tandem Compressor Standard Dimension (Refrigerant R22)

- Capacity Range(25HP~120HP)re Connection
- Reliable and Simple Oil Rtance Design
- Low Noise/Low Vibration

Model	A	B	C	D	E	F	G	H
JT140-P4Y1/P4YE1	710	89	89	89	89	89	710	89.6
JT140-P4Y2/P4YE2 JT140-P4YE2	714	89	89	89	89	89	714	89.5

-◎ Model Tandem Compressor Range (Refrigerant R22)

OUTPUT (HP)	POWER SOURCE	MODEL	ARI STANDARD CAPACITY (POWER SOURCE)		INPUT W	CURRENT A	EER W/W	CAPACITY BTU/H	TUBE CONNECTIONS	
			BTU/H	CAPACITY W					SUCTION TUBE in	DISCHARGE TUBE in
14	380V/50Hz 3 PHASE	JT212G-TY1L	360/50Hz	41.3	12400	12.58	21.3	3.25	117.3	5/8.4
15		JT236G-TY1L	360/50Hz	43.8	13500	13.27	22.4	3.27	121	5/8.4
16.5		JT265G-TY1L	360/50Hz	46.5	14300	14.05	23.7	3.3	144.7	7/8.4
20		JT300G-TY1L	360/50Hz	49.8	15300	15.38	25.2	3.33	162	7/8.4
22		JT335G-TY1L	360/50Hz	54.8	16200	16.74	26.7	3.33	160.5	7/8.4
24		JT355G-TY1L	360/50Hz	51.7	16000	15.68	27.2	3.34	184.2	7/8.4
14	380-415V/ 460-480V 3 PHASE 50/60Hz	JT212G-TYE	360/50Hz	41.3	12400	12.58	21.2	3.25	117.3	5/8.4
			460/60Hz	49.8	14700	15.1	25.5	3.27		
15		JT236G-TYE	360/50Hz	43.8	13500	13.27	22.4	3.27	121	5/8.4
			460/60Hz	52.6	16200	16.05	27.2	3.27		
16.5		JT265G-TYE	360/50Hz	46.5	14300	14.05	23.7	3.3	144.7	7/8.4
			460/60Hz	55.8	17200	16.86	28.5	3.31		
20		JT300G-TYE	360/50Hz	49.8	15300	15.38	25.2	3.33	162	7/8.4
			460/60Hz	59.8	18400	18.07	30.4	3.32		
22		JT335G-TYE	360/50Hz	54.8	16200	16.74	26.7	3.33	160.5	7/8.4
			460/60Hz	65.7	19400	20.09	32.4	3.34	162.7	7/8.4
24		JT355G-TYE	360/50Hz	51.7	16000	15.68	27.2	3.34	184.2	7/8.4
			460/60Hz	62.4	19300	19.03	32.4	3.28		

CONDITION OF COMPRESSOR					
	EVAPORATOR TEMPERATURE	CONDENSATION TEMPERATURE	DEGREE OF SUPERHEAT	DEGREE OF SUBCOOLING	SUCTION TEMPERATURE
COMPRESSOR	7.2C	54.4C	11.1K	8.3K	18.3C

TUBECONNECTIONS
TUBECONNECTIONS
TUBECONNECTIONS

JT150BCBY1L JT150BK-YE JT160BCBY1L JT170GABY1L JT170FDKYE JT300D-YE JT300D-P1YE JT300D-YE @ JT315D-Y1L JT335D-Y1L JT100BHVYE JT100BHV JT100BCBV1L JT100GABV1L 2YC45BXD 2YC45JXD 2YC45BXD 1GDY23AXD 2YC32VXD JT1FCVDKTYR JT1GCVDKYR 6T55TAC5YE 6T55WACSYE JT170G-K1YE JT170G-KYE@BA etc. Mainly used for refrigeration equipment such as air conditioners. Varieties ***, ***, ***, service is exhausted, welcome to call to discuss!

Daikin Compressor Features: JT170G-K1YE JT170G-KYE@BA
Daikin Compressor Features: Small and light. High reliability and easy to use.
?Due to the small diameter and slenderness of the compressor cylinder, it provides a good choice for the small and lightweight outdoor unit.
?In order to save the flexibility of space and location design, a new model with three-legged chassis is added on the basis of the original four-legged chassis. Give users more choices.
?The number of compressor parts is small and the reliability is high.
?Compressors can withstand the most brutal tests of heat pump systems.
?Only the protection device of the motor in the compressor is built-in, and other protections are matched by the system. This allows system designers to set protections in the system as needed, allowing product designers to better control the compressors used.
JT300DJT160B-NYE JT160B-NFYE New original Daikin marine air conditioner refrigeration equipment compressor A-Y1L JT335DA-Y1L New original Daikin compressor R407CJT100BDVTYE JT100FBVD JT100FAVD New original Daikin inverter air conditioner compressor JT170G-K1YE JT170FDKYE JT170FBKYE New original Daikin air conditioner compressor Machine JT160BCBY1L JT160GABY1L Original Daikin 5 HP Central Air Conditioning Compressor VRV3 generation RHXYQ14PY1 inverter compressor original new JT160GAJY1L Daikin 5 hp central air conditioning compressor three feet return air pipe upward R22 original 12 hp JT335D-P1YE JT300D-P1YE Daikin central air conditioning compressor 10 hp JT315D Original 5 HP JT160GABY1L JT170GABY1L Daikin Air Conditioning Compressor Heat Pump Straight Tube Daikin Parallel Compressor JT300DA-YE Daikin 10P12 HP Air Conditioning Compressor R40JT100FBVD JT100BHV JT100G-VDL@S Original Daikin Inverter Air Conditioning Refrigeration Compressor JT140G-P4Y1@K Brand New Original 5 Daikin Fixed Frequency Air Conditioning Compressor R410A 3 Foot Daikin 5P JT160BCBY1L Panasonic C-SB373H8A Air Conditioning Air Energy Heat Pump Compressor C-SB453



Private Picture Copyright : WWW.MBSM.PRO