

Mbsm.pro, Compressor, 1/11 Hp, 67 W, 110-120V, R600A

Category: compressor

written by www.mbsm.pro | 6 February 2022



Description

Basic Info

- Model NO.: QD35Y11G
- Door Number: Single Door
- Door Type: Swing Door
- Temperature Control: Mechanical Thermostat
- Defrost Type: Auto Defrost
- Certification: CE, RoHS, UL, ISO, CCC, CB, ETL
- Motor Type: Rscr
- Frequency: 50-60Hz
- Cooling Capacity: 67W
- Starting Capacitor: No
- Cooling Type: Static
- Transport Package: 1PC/CTN, 100ctns/Pallet
- Origin: China
- Capacity: 101-200L
- Type: Chest/Deep Freezer
- Power Source: Electricity
- Temperature Type: Double-temperature
- Function: Freezing
- Displacement: 3.5cm³

- Voltage: 110-120V
- Refrigerant: R600A
- Starting Device: PTC
- Running Capacitor: 6UF
- Trademark: SIKELAN
- Specification: 1/12hp
- HS Code: 8414301100

Product Description

1. Product Performance

- 1)QD35Y11G, L series, use R600A refrigerant;
- 2)Voltage application 110V to 120V;
- 3)Frequency for 50/60HZ;
- 4)Motor type: RSCR;
- 5)Cooling type: ST;
- 6)Starting device is PTC Relay;
- 7)Application: Low Back Pressure;
- 8)Nominal power is 1/12 HP;
- 9)COP is 1.20 with the cooling capacity 67W.

Basing on Test Condition(ASHRAE)

- Evaporating Temperature: -23.3 degree
- Ambient Temperature: 32.2 degree
- Subcooling Temperature: 32.2 degree
- Condensing Temperature: 54.4 degree
- Suction Temperature: 32.2 degree

2.Compressor Specification

		Cooling Capacity ASHRAE										Test Conditions:-23.3°C(-10°F)										-20°C(-4°F) -15°C(5°F) -10°C(10°F) -5°C(23°F) 0°C(32°F)										Motor type	Starting Device	Starting Capacitor (uF)	Running capacitor (uF)	Cooling Type
Serial	Model	HP	Voltage/ Frequency (V/Hz)	Displacement (cm3)	-35°C (-31°F)		-30°C (-22°F)		-25°C (-13°F)		Capacity (W)	Capacity (Btu/h)	Input Power (W)	Current (A)	COP	EER	-20°C(-4°F)		-15°C(5°F)		-10°C(10°F)		-5°C(23°F)		0°C(32°F)											
					W	Btu/h	W	Btu/h	W	Btu/h													Btu/h	Btu/h	W	Btu/h	W	Btu/h	W	Btu/h	W					
MS	QD035Y11G 1/12			3.5	31	106	40	136	52	177	67	229	56	0.4	1.2	4.0884	287	105	358	131	447	164	560	205	699	RSCR	/	/	6	6	ST					
	QD43Y11G 1/11			4.3	41	140	53	181	69	235	90	307	75	0.6	1.2	4.09113	386	141	481	176	601	220	751	275	938	RSCR	/	/	6	6	ST					
	QD53Y11G 1/9			5.3	47	160	61	208	79	270	102	348	78	1.1	1.3	4.46128	437	159	543	199	679	249	850	311	1061	RSCR	/	/	6	6	ST					
	QD65Y11G 1/7			6.5	60	205	78	266	102	348	132	450	101	1.45	1.3	4.46165	563	206	703	258	880	322	1099	403	1375	RSCR	/	/	6	6	ST					
	QD75Y11G 1/6-			7.5	71	242	92	314	120	409	156	532	120	1.65	1.3	4.44195	665	244	833	305	1041	381	1300	476	1624	RSCR	/	/	6	6	ST					
LH	QD43Y11G 1/11			4.3	41	140	53	181	69	235	90	307	75	0.6	1.2	4.09113	386	141	481	176	601	220	751	275	938	RSCR	/	/	6	6	ST					
	QD53Y11G 1/9			5.3	47	160	61	208	79	270	102	348	78	1.1	1.3	4.46128	437	159	543	199	679	249	850	311	1061	RSCR	/	/	6	6	ST					
	QD65G11G 1/7			6.5	60	205	78	266	102	348	132	450	102	1.45	1.3	4.42165	563	206	703	258	880	322	1099	403	1375	RSCR	PTC	/	/	6	6	ST				
	QD75Y11G 1/6-110-120V/50-60Hz			7.5	71	242	92	314	120	409	156	532	120	1.65	1.3	4.44195	665	244	833	305	1041	381	1300	476	1624	RSCR	Starting/Relay	/	/	6	6	ST				
	QD85Y11G 1/6			8.5	79	270	103	351	134	457	174	594	134	1.68	1.3	4.43218	744	272	928	340	1160	425	1450	531	1812	RSCR	/	/	6	6	ST					
MK	QD91Y11G 1/5			9.1	85	290	110	375	143	488	186	635	124	1.7	1.5	5.12233	795	291	993	363	1239	454	1549	568	1938	RSCR	/	/	6	6	ST					
	QD103Y11G1/4-			10.3	92	314	119	406	155	529	201	686	134	1.83	1.5	5.12251	856	314	1071	393	1341	491	1675	613	2092	RSCR	/	/	6	6	ST					
	QD110Y11G1/4			11.0	100	341	130	444	169	577	220	751	147	1.95	1.5	5.11275	938	344	1174	430	1467	537	1832	671	2289	RSCR	/	/	6	6	ST					
	QD128Y11G1/3-			12.8	120	409	156	532	203	693	264	901	182	2.05	1.454	95330	1126	413	1409	516	1761	645	2201	806	2750	RSCR	/	/	6	6	F					
	QD142Y11G1/3			14.2	130	444	169	577	219	747	285	972	197	2.16	1.454	94356	1215	445	1518	557	1900	696	2375	870	2968	RSCR	/	/	6	6	F					
WQ	QD153Y11G1/3+			15.3	142	485	185	631	240	819	312	1065	215	2.25	1.454	95390	1331	485	1655	609	2078	762	2600	952	3248	RSCR	/	/	6	6	F					



120VAC
307BTU



1/11HP

R600A

USA SELLER , FAST SHIPPING

Private Picture Copyright : WWW.MBSM.PRO



Private Picture Copyright : WWW.MBSM.PRO

Description de Produit

Information d'Entreprise

Info de Base.

N° de Modèle.	QD43Y11G	Displacement	4.3cm3
Refrigerant	R600A	Voltage	110-120V
Frequency	50/60Hz	Motor Type	Rscr
Application Type	Lbp	Cop	1.20
Input Power	90W	Starting Device	PTC
Cooling Type	Static	Paquet de Transport	1PC/CTN, 100 or 120PCS/Plt
Spécifications	QD43Y11G	Marque Déposée	SIKELAN
Origine	China	Code SH	841430119
Capacité de Production	7000PCS/Day		