

Mbsm.pro, Compressor, Turk Elektrik,
AZ 90 YT, TEE compressor, R134a, 90
Kcal/h, refrigerator with 240 liter,
lbp , 220 v

Category: compressor

written by www.mbsm.pro | 16 February 2022



❏ ❏❏❏❏ ❏❏❏ ❏❏❏❏ ❏❏❏❏❏❏❏ ❏❏❏❏❏❏❏ ❏❏❏❏❏❏❏ .. *The Only Correct And Reliable Way To Calculate The Capacity Of TEE Compressors.*



Private Picture Copyright: WWW.MBSM.PRO



Refrigerant Application	Model	Displacement	Net Wt.	Oil Charge	Cooling (41°C Max. Amb. Temp.)	Motor Type	Voltage and Frequency	Refrigerating Capacity								COP	
								Ashrae						Cecomaf	Ashrae	Cecomaf	
								-35°C	-30°C	-25°C	-23,3°C	-20°C	-15°C	-10°C	-25°C	-23,3°C	-25°C
		cc	kg	cc				Kcal/h	Kcal/h	Kcal/h	Kcal/h	Kcal/h	Kcal/h	W	W/W	W/W	
STANDARD EFFICIENCY RANGE																	
R134a LBP	AZ 47 YD	2.80	6.9	270	S	1	2-3-4-6	20	29	42	47	58	78	99	40	0.90	0.69
	AZ 47 YP	2.80	6.9	270	S	2	2-3-4-6									0.90	0.69
	AZ 47 YT	2.80	6.6	220	S	3	4									0.92	0.71
	AZ 68 YD	3.59	7.2	240	S	1	2-3-6	29	42	61	68	84	111	143	58	1.01	0.78
	AZ 68 YP	3.59	7.2	240	S	2	2-3-4									1.01	0.78
	AZ 68 YT	3.59	6.8	270	S	3	4-6									1.07	0.82
	AZ 82 YD	4.00	7.2	240	S	1	2-3-6	35	52	74	82	100	131	169	70	1.00	0.77
	AZ 82 YP	4.00	7.2	240	S	2	2-3									1.00	0.77
	AZ 82 YT	4.00	7.2	240	S	3	4									1.11	0.86
	AZ 90 YD	5.00	7.4	300	S	1	2-3	39	57	81	90	110	144	185	77	0.99	0.76
	AZ 90 YP	5.00	7.4	300	S	2	2-3									0.99	0.76
	AZ 90 YT	5.00	7.4	300	S	3	4									1.07	0.82
	AZ 107 YD	5.59	7.4	300	S	1	2-3	47	70	96	107	131	169	216	91	1.00	0.77
	AZ 107 YP	5.59	7.4	300	S	2	2-3									1.00	0.77
	AZ 107 YT	5.59	7.4	300	S	3	4									1.12	0.87
	AZ 121 YD	5.90	7.4	300	O*	1	2-3	54	79	109	121	148	192	246	103	1.05	0.81
AZ 121 YP	5.90	7.4	300	O*	2	2-3	1.05									0.81	
AZ 121 YT	5.90	7.4	300	O*	3	4	1.12									0.87	

Private Picture Copyright : WWW.MBSM.PRO

Mbsm_dot_pro_private_PDF_compresorsTélécharger