
Mbsm.pro, Compressor, D77C18RAX5, RSIR , 1/4 Hp, D Series, r134a, LBP, 186 W, Toshiba, Refrigerator, 14 Feet, GR-EF40, 2 Doors, New Compressor, PE75H1C, 250 w, 1/4 hp

written by Lilianne | 28 February 2022



Performance

Application : Low Back Pressure
Refrigerant : R134a (CF_3CH_2F)
Evaporator Temperature Range : -35°C to -5°C

Series	Model	Displacement (cm^3)	Voltage / Frequency	Motor Type	ASHRAE		CECOMAF	
					Capacity	COP	Capacity	COP
					W	W/W	W	W/W
	D77C15RAW5	7.7	220/240V 50Hz	RSIR	186 / 186	1.27 / 1.24	-	-
				RSCR	186 / 186	1.32 / 1.27	-	-
	D77C17GAX6	7.7	220V 60Hz	RSIR	236	1.25	-	-
				RSCR	-	-	-	-
	D77C17RAT6	7.7	110V 60Hz	CSIR	-	-	-	-
				CSCR	236	1.34	-	-
	D77C18RAX5	7.7	220V 50Hz	RSIR	186	1.24	-	-
				RSCR	186	1.31	-	-
	D91C18RAW5	9.1	220/240V 50Hz	RSIR	227 / 227	1.29 / 1.24	-	-
				RSCR	227 / 227	1.37 / 1.31	-	-
	D91C18TA00	9.1	100V 50/60Hz	CSIR	-	-	-	-


www.mbsm.pro
Private Picture Copyright : WWW.MBSM.PRO

Item	Performance characteristics
Refrigerant	R134a
Displacement (cm^3)	7.7
Voltage (V)	220
Frequency (Hz)	50
Motor Type	RSIR

Item	Performance characteristics
Capacity@ASHRAE	186
COP@ASHRAE	1.24
Capacity hp	1/4 hp



Private Picture Copyright : WWW.MBSM.PRO
Private Picture Copyright : WWW.MBSM.PRO



Private Picture Copyright : WWW.MBSM.PRO

TOSHIBA NO FROST REFRIGERATOR

MODEL	GR-EF40P
RATED VOLTAGE	220 V
RATED FREQUENCY	50 Hz
RATED INPUT	134 W
RATED INPUT OF HEATING ELEMENT	170 W
DEFROSTING INPUT	170 W
RATED MAXIMUM INPUT OF LAMP	1.6 W
RATED CURRENT	0.65 A
CLIMATIC CLASS	T
ENERGY CONSUMPTION	1.3 KWH/24H
INSULATION TYPE	I
REFRIGERANT	R-134a
CHARGING VOLUME	130 g
FREEZING CAPACITY	5 Kg/24 H
WEIGHT	68 kg
STORAGE VOLUME (L)	
FREEZER	356
REFRIGERATOR	110
TOTAL GROSS VOLUME (L)	246
PERFORMANCE TEST SPEC.	378
PROTECTION DEGREE	IEC2007/62552 ,3793/2006
	IPx 0


تحذير : لايستخدم هذا الجهاز الا فى حالة وجود توصيلات ارضى بالمبنى أو باضافة لبطية تيار متبقى (RCD) مع قيمة ثابتة

Made in EGYPT

Produced by EL ARABY Co. for ENGINEERING Ind., Under License of TOSHIBA Corporation JAPAN

4YDQF09633

WIRING DIAGRAM



WIRING COLOR

Bl:	Blue-White or Blue
Bk:	Black-White or Black
Br:	Brown-White or Brown
Pp:	Purple-White or Purple
Cy:	Gray-White or Gray
R:	Red-White or Red
Pi:	Pink
Or:	Orange-White or Orange
Wh:	White

Private Picture Copyright : WWW.MBSM.PRO

Performance

Application : Low Back Pressure
Refrigerant : R134a (CF_3CH_2F)
Evaporator Temperature Range : -35°C to -5°C

Series	Model	Displacement (cm^3)	Voltage / Frequency	Motor Type	ASHRAE		CECOMAF	
					Capacity	COP	Capacity	COP
					W	W/W	W	W/W
	D77C15RAW5	7.7	220/240V 50Hz	RSIR	186 / 186	1.27 / 1.24	-	-
				RSCR	186 / 186	1.32 / 1.27	-	-
	D77C17GAX6	7.7	220V 60Hz	RSIR	236	1.25	-	-
				RSCR	-	-	-	-
	D77C17RAT6	7.7	110V 60Hz	CSIR	-	-	-	-
				CSCR	236	1.34	-	-
	D77C18RAX5	7.7	220V 50Hz	RSIR	186	1.24	-	-
				RSCR	186	1.31	-	-
	D91C18RAW5	9.1	220/240V 50Hz	RSIR	227 / 227	1.29 / 1.24	-	-
				RSCR	227 / 227	1.37 / 1.31	-	-
	D91C18TA00	9.1	100V 50/60Hz	CSIR	-	-	-	-

www.mbsm.pro
Private Picture Copyright : WWW.MBSM.PRO

Mbsm_dot_pro_private_PDF_PE75H1CTélécharger
Mbsm_dot_pro_private_PDF_d77c18rax5Télécharger