

Mbsm.pro, Compressor, Donper, L65CZ1, 220-244V, 50Hz, 1/5 hp, R134a, lbp

Category: compressor

written by www.mbsm.pro | 3 March 2022



Private Picture Copyright : WWW.MBSM.PRO

Data Sheet

Power supply	220/240 V-50 Hz-1 Ph
Horsepower	1/5 hp
Displacement	6,50 cm ³
Cooling capacity at ASHRAE LT conditions, R134a	0,16 kW
Refrigerant	R134a
Suction pipe	1/4"
Discharge pipe	1/4"

Weight	6,80 kg
Rated current	1,10 A
LRA	12,80 A
MCC	124,00 A
Type of oil	Ester
Other remarks	Electrical components are included
Sound level	42 dB
Application	LBP
Technology	Fixed speed
Maximum shell bottom temperature	95 °C
Maximum discharge temperature	120 °C
Maximum winding temperature	120 °C
Type of motor cooling	Suction gas
Motor type	1-Ph Induction motor (RSIR)
Motor protection type	External
Speed	2920 rpm
Vibration	0,7 m/s ²



Private Picture Copyright : WWW.MBSM.PRO

Mbsm_dot_pro_private_PDF_L65CZ1Télécharger

Compresores herméticos pistón AREA baja temperatura **R134a** | Monofásicos a 220-240V/50Hz

MODELO	CV	CM3	GAS	RENDIMIENTOS (COND. MHBP) (W)				CONEX. ASPIR. (")	CONEX. DESCAR. (")	TIPO DE MOTOR	CODIGO	PVP (€)
				-10°C	-15°C	-20°C	-25°C					
S36CZ	1/8	3,6	R134a	180	139	104	75	1/4	1/4	CSIR	0011085100	102,13
S43CZ1	1/7	4,3	R134a	196	152	114	84	1/4	1/4	RSIR	0011140000	103,67
S53CZ	1/6	5,3	R134a	246	195	145	106	1/4	1/4	RSIR	0011090100	106,12
L58CZ	1/6	5,8	R134a	291	223	169	130	1/4	1/4	RSIR	00110109500	124,86
L65CZ1	1/5	6,5	R134a	323	251	191	141	1/4	1/4	RSIR	00110110201	131,11
L72CZ1	1/4	7,2	R134a	377	296	225	163	6,1	4,1	RSIR	00110110601	137,33
E1120CZA	1/3	8,2	R134a	520	407	303	206	1/4	1/4	RSIR	0011085901	141,53
E1130CZA	3/8	12,1	R134a	736	550	400	284	3/8	1/4	RSIR	0011086001	158,16

Private Picture Copyright : WWW.MBSM.PRO