

Samsung 55A250JTAEM-SS 25300 btu Compressor

Category: pro

written by www.mbsm.pro | 11 September 2022



Private Picture Copyright : WWW.MBSM.PRO

Mbsm.pro, Samsung, 55A250JTAEM-SS, 55A250JTAEM, 25300 btu, Compressor, 3 hp, r22

55A250JTAEM

220-240V~ 50Hz 1Ph LRA60.3

FLA11.5

THERMALLY PROTECT

RoHS Comp

SAMSUNG

WARNING/DANGER

FAILURE TO FOLLOW THESE INSTRUCTIONS WILL RESULT IN
SERIOUS PERSONAL INJURY

1. SECURE THE EQUIPMENT SECURELY
2. TURN OFF POWER BEFORE SERVICE
3. MOUNT THE TERMINAL COVER IN PLACE WHEN POWER IS APPLIED TO THIS COMPRESSOR
4. WEAR PROTECTIVE GOGGLES WHEN BRAZING
5. BEFORE BRAZING, REMOVE PRESSURE FROM BOTH HIGH AND LOW SIDES
6. DO NOT USE THIS COMPRESSOR TO COMPRESS AIR
7. USE ONLY APPROVED REFRIGERANTS AND LUBRICANTS
8. DO NOT TOUCH WITH BARE HANDS DURING RUNNING OR AFTER STOPPING INSTANTLY



55A250JTAEM

220-240V~50Hz
FLA11.5

1Ph

LRA60.3

R22

THERMALLY PROTECTED
RoHS Compliant

SAMSUNG

WARNING/DANGER



FAILURE TO FOLLOW THESE INSTRUCTIONS COULD RESULT IN
SERIOUS PERSONAL INJURY.
1. GROUND THE EQUIPMENT SECURELY.
2. TURN OFF POWER BEFORE SERVICING.
3. REMOVE THE TERMINAL COVER IN PLACE WHENEVER POWER IS APPLIED TO THIS COMPRESSOR.
4. WEAR PROTECTIVE GOGGLES WHEN SERVICING.
5. BEFORE BRAZING, REMOVE PRESSURE FROM BOTH HIGH AND LOW SIDE.
6. DO NOT USE THIS COMPRESSOR TO COMPRESS AIR.
7. USE ONLY APPROVED REFRIGERANTS AND LUBRICANTS.
8. DO NOT TOUCH WITH BARE HANDS DURING RUNNING OR AFTER STOPPING INSTANTLY.



MADE BY SAMSUNG

Model	Cooling Capacity	Efficiency	Motor Type	Cooling Type	NetWeight [kg]	OilQty. [cc]				
Kcal/h	Watt	Btu/h	EFF	COP	EER					
Kcal/Wh	W/W	Btu/Wh								
HPL21YE-5-K	155	180	615	1.00	1.16	3.97	RSCR	ST/OC/FC	9	290
HPL21YE-5-L	155	180	615	1.04	1.2	4.11	RSCR	ST/OC/FC	8.9	290
HSL21YE-5	155	180	615	1.04	1.21	4.13	RSIR	ST/OC/FC	9	290
HPL23YE-5	171	199	635	1.1	1.27	4.35	RSCR	ST/OC/FC	9.5	290
HPL23YE-5-K	171	199	679	1.14	1.19	4.52	RSCR	ST/OC/FC	9	290
HSL23YE-5	171	199	679	1.06	1.16	4.21	RSIR	ST/OC/FC	9.3	290
HGH23YE-5	581	676	2306	1.94	2.25	7.69	CSIR	OC/FC	9.3	290
HKL25YE-5	180	209	714	0.97	1.19	3.84	CSIR	ST/OC/FC	9.5	290
HPL25YE-5-K	180	209	714	1.22	1.29	4.86	RSCR	ST/OC/FC	9	290

55A250JTAEM

220-240V~ 50Hz 1Ph LRA60.3 R22
FLA11.5 THERMALLY PROTECTED
RoHS Compliant

SAMSUNG




WARNING/DANGER

FAILURE TO FOLLOW THESE INSTRUCTIONS COULD RESULT IN
SERIOUS PERSONAL INJURY.

1. GROUND THE EQUIPMENT SECURELY.
2. TURN OFF POWER BEFORE SERVICING.
3. MOUNT THE TERMINAL COVER IN PLACE WHENEVER POWER IS APPLIED TO THIS COMPRESSOR.
4. WEAR PROTECTIVE GOGGLES WHEN SERVICING.
5. BEFORE BRAZING, REMOVE PRESSURE FROM BOTH HIGH AND LOW SIDE.
6. DO NOT USE THIS COMPRESSOR TO COMPRESS AIR.
7. USE ONLY APPROVED REFRIGERANTS AND LUBRICANTS.
8. DO NOT TOUCH WITH BARE HANDS DURING RUNNING OR AFTER STOPPING INSTANTLY.

MADE BY SAMSUNG X704ARQC0095475





Private Picture Copyright : WWW.MBSM.PRO

Mbsm_dot_pro_private_PDF_55A250JTAEM-SSTélécharger