

Mbsm.pro, Compressor, Cubigel, GL90TB, GU80TG, GU80TB, R134a, 1/4 hp, hmbp, csir

Category: compressor

written by www.mbsm.pro | 6 April 2024



Product information "CUBIGEL / HUAYI GU80TB Compressor, HMBP – R134A, 200 – 240V, 50HZ"

CUBIGEL / HUAYI GU80TB hermetic, HMBP – R134A, 200 – 240V, 50HZ

Compression 8,10 [cm3],

CSIR type engine,

Öltyp POE,

Öinflation 220 cm3, 686 W in +5 / +55 C°; according to CECOMAF,

Input power 346 W, 2.14 A,

Expansion device: capillary or expander, cooling by fan,

Weight 9.23 kg

Replacing: GL80TB

Power supply: 230 V

For use with: Capillary/expansion

COP: 1,82

Cooling capacity (W) at -5°C: 727

Cooling capacity (W) at -10°C:	390
Cooling capacity (W) at -15°C:	290
Cooling capacity (W) at -20°C:	215
Cooling capacity (W) at -25°C:	165
Cooling capacity (W) at 0°C:	615
Cooling capacity (W) at 5°C:	500
Cooling capacity (W) at 10°C:	840
Champ d'application:	HMBP, MBP/HBP
Suction line (mm):	6,5
Pressure line (mm):	4,9
Content:	1,00 pc
Max current Starting current (A):	9,7
Max current Operating current (A):	1,79
Suction side:	6,5 mm
Dimensions (length × width × height):	24,00 × 16,20 × 19,10 cm
Maker:	ACC Cubigel Huayi Electrolux ZEM
Power Range (CV):	0-2
Power Range (W):	501 – 700 W
Condensing units Compressors:	Compressor
Info:	Pre-filled oil
Model series:	GU
Power range (C):	-25 C to +10 C
Power consumption (W):	302
Cooling power (W):	554
Rated power (hp):	0,25
Quantity of oil (l):	0,3
Refrigerant:	R134a
Series:	GL
Connection size:	4,9 mm
Tension:	220-240V
Type / Series:	GU80TB
Oil type:	ISO VG 22 Ester
Compressor type:	Alternative piston
Type of construction:	Hermetic , Reciprocating piston
Type of engine:	CSIR
Stroke volume (cm3):	7,57
Discharge and suction volume (m3):	1,3



Mbsm_dot_pro_private_PDF_GU80TBDownload