

# Siberia GFF93AA Compressor 1/3+ hp R134a 270W Technical Specifications and Professional Replacements Review

Category: Refrigeration

written by [www.mbsm.pro](http://www.mbsm.pro) | 7 February 2026



Private Picture Copyright : [WWW.MBSM.PRO](http://WWW.MBSM.PRO)

Mbsmpro.com, Siberia Compressor, GFF93AA, 1/3+ hp, Motech, Cooling, R134a, 270 W, 1.4 A, 1Ph 160-260V 50Hz, LBP, RSIR/RSCR, -35°C to -10°C, Freezing

The world of refrigeration depends on robust components that can survive harsh conditions, and in many regions, power instability is the biggest killer of cooling systems. The Siberia GFF93AA, often branded under the Motech engineering umbrella, is a compressor designed precisely for these high-stress environments. Known as the "Siberia Copper" series, it prides itself on having 100% copper

windings—a massive advantage over the aluminum windings found in cheaper units that often succumb to internal heat and early insulation breakdown. As an engineer who has worked in the field for years, I have seen many compressors fail when line voltages dip below 180V. What sets the GFF93AA apart is its massive operating window of 160V to 260V. This wide-voltage design means it can maintain refrigeration cycles during brownouts where other motors would simply stall and overheat. Utilizing the stable R134a refrigerant and pushing a displacement of 9.3cc, this unit is a powerhouse for large domestic refrigerators and mid-sized commercial chest freezers.

## Complete Technical Specifications

| Parameter                         | Data Detail  |
|-----------------------------------|--|
| <b>Model</b>                      | GFF93AA  |
| <b>Utilisation (mbp/hbp/lbp)</b>  | LBP (Low Back Pressure)  |
| <b>Domaine (Freezing/Cooling)</b> | Heavy-duty Freezing & Deep Cold Storage                              |
| <b>Cooling wattage at -23.3°C</b> | 270 Watts  |
| <b>Cubic feet capacity</b>        | 18 to 22 Cubic Feet  |
| <b>Litres capacity</b>            | 450 to 600 Litres  |
| <b>Kcal/h</b>                     | 232 Kcal/h   |
| <b>Oil Type and quantity</b>      | Ester / POE RL 10H (230 cc)  |
| <b>Horsepower (HP)</b>            | 1/3+ HP  |
| <b>Refrigerant Type</b>           | R134a  |
| <b>Power Supply</b>               | 1Ph / 160-260V / 50Hz  |
| <b>Cooling Capacity BTU</b>       | 921 BTU/h  |
| <b>Motor Type</b>                 | RSIR / RSCR  |
| <b>Displacement</b>               | 9.3 cc   |
| <b>Winding Material</b>           | 100% High-Grade Copper   |
| <b>Pression Charge</b>            | Low side 0.5 – 5 PSI / High side 150 PSI (operating)                 |
| <b>Capillary Recommendation</b>   | 0.036" to 0.040"   |
| <b>Applicable Models</b>          | Double-door large fridges, commercial chest freezers                 |
| <b>Temperature function</b>       | -35°C to -10°C   |
| <b>Fan Cooling Required</b>       | Recommended for ambient above 35°C, otherwise Static                 |
| <b>Commercial Application</b>     | Yes (Light commercial / Household heavy duty)                        |
| <b>Amperage (Working)</b>         | 1.25 A to 1.54 A   |
| <b>LRA (Locked Rotor Amps)</b>    | 14.0 A   |
| <b>Relay Type</b>                 | PTC QP2-15   |
| <b>Capacitor Value</b>            | 4 µF (450 V) optional for RSCR configuration                         |
| <b>Origin &amp; Exporting</b>     | Manufactured by Motech (China) – Exported globally via Agent Alfardi |

---

## Efficiency Metrics (COP) & Load Performance

Efficiency isn't just a number; it is how well a machine handles the physics of heat exchange. The GFF93AA shows high stability at standard boiling points for R134a.

| Evaporating Temp (°C)    | Cooling Capacity (Watts) | Power Consumption (Watts) | COP (W/W)   |
|--------------------------|--------------------------|---------------------------|-------------|
| -35                      | 135                      | 115                       | 1.17        |
| -30                      | 174                      | 142                       | 1.22        |
| -25                      | 230                      | 168                       | 1.37        |
| <b>-23.3 (Rated LBP)</b> | <b>270</b>               | <b>185</b>                | <b>1.46</b> |
| -20                      | 310                      | 205                       | 1.51        |
| -15                      | 390                      | 235                       | 1.66        |
| -10                      | 519                      | 265                       | 1.96        |

## Comparison: Why Choose Siberia over Standard Alternatives?

In many markets, you might see comparisons between the GFF93AA and models from Jiaxipera or Secop.

1. **Torque Handling:** Compared to the Jiaxipera NT series, the Siberia GFF series typically provides better starting torque at low voltage (LST/HST characteristics). While standard units might struggle to restart a system after a short power trip (short-cycling), the GFF93AA is engineered to push against the head pressure more effectively.
2. **Material Science:** Many modern compressors use Copper-Clad Aluminum (CCA). The “Copper Suction” and “Copper Winding” designation here is vital for field technicians because it offers 40% better thermal conductivity, which keeps the motor shell cooler during 24/7 operations in tropical climates.

## Engineering Conseil, Notices, and Maintenance

From an field engineer’s desk:

- **Vacuum Requirement:** Since this unit uses POE (Polyolester) oil, it is incredibly thirsty for moisture. If you leave the ports open for more than 10-15 minutes, you risk acidity in the oil. I strongly recommend a triple-vacuum down to at least 250 microns before gas charge.
- **Notice:** The wide-voltage feature is excellent, but if you frequently operate at 170V, add a 4µF run capacitor. This will significantly drop the operating temperature of the main winding and increase its life by years.
- **Benefits:** Choosing the 9.3cc displacement model for a fridge designed for 7.5cc is an “upgrading” move. It allows the system to reach cut-off temperature faster, actually reducing total power consumption over the day by decreasing the motor’s total run-time.

### What size capacitor is recommended for the Siberia GFF93AA?

While it can operate as a standard RSIR (no capacitor) system, it is designed with the option for RSCR (Run Start Capacitor Run). A 4µF 450V capacitor is the ideal specification. It will improve electrical efficiency by 10-15% and smooth out the starting arc on the PTC relay, prolonging the life of the starting kit.

---

# Compressor Replacements and Equivalents

## 5 Direct Replacements (R134a – Same Characteristics):

1. **Secop/Danfoss:** FR11G or GL90AA
2. **Embraco:** FFI 12 HBK or FFU 130 HAK
3. **Tecumseh:** TPH1410Y
4. **Huayi:** GQR90AA
5. **ZMC:** GL90AA

## 5 Cross-Refrigerant Alternatives (Requires Full Flush/Purge):

1. **Donper (R600a):** LU140CY
2. **Embraco (R290):** NEK2134U (Note: Higher starting torque)
3. **Wanbao (R600a):** DQH140Y
4. **LG (R600a):** CMA121H
5. **Jiaxipera (R600a):** NT1114Y

---

**Focus keyword:** Siberia GFF93AA Compressor 1/3+ hp R134a 270W Technical Specifications and Professional Replacements Review

**SEO title:** Mbsmpro.com | Siberia GFF93AA Compressor | 1/3+ hp | R134a | 9.3cc

**Meta description:** Professional guide for the Siberia GFF93AA 1/3+ HP Compressor. Explore R134a cooling capacity, COP efficiency charts, 160-260V wide voltage data, and field engineering advice for experts.

**Slug:** siberia-gff93aa-compressor-1-3hp-r134a-specifications

**Add Tags:** Siberia, GFF93AA, Alfardi, Motech, R134a, 1/3+ HP, Mbsmgroup, Mbsm.pro, mbsmpro.com, mbsm, GL90AA, FFI12HBK, TPH1410Y, GQR90AA, Compressor replacement, Refrigeration engineering.

**Excerpt:** The heart of any reliable industrial or home refrigerator is the compressor. The Siberia GFF93AA stands out as a high-displacement 1/3+ HP unit featuring genuine copper windings and a massive wide-voltage tolerance from 160V to 260V. For technicians working in harsh power zones, this R134a unit provides 270W of efficient, stable cooling power...



Private Picture Copyright : [WWW.MBSM.PRO](http://WWW.MBSM.PRO)

1/3+ HP, Alfardi, Compressor Replacement, FFI12HBK, GFF93AA, GL90AA, GQR90AA, mbsm, mbsm.pro, mbsmgroup, mbsmpro.com, Motech, R134a, Siberia, TPH1410Y  
[GFF93AADownload](#)

This is a full transcription of the Motech GFF93AA Data Sheet.

# MOTECH GFF93AA Data Sheet

Refrigeration parts and equipment

## 1. BASIC DATA

### 1.1 OPERATION

- **Application:** LBP (Low Back Pressure)
- **Refrigerant:** R134a
- **Expansion device:** Capillary tube
- **Cooling:** Static
- **Evaporating Temperature Range:** -35 to -10°C (-34 to +14 °F)

- **Max Ambient Temperature:** 43°C (110°F)
- **Max Operating Discharge Temperature (1):** 120°C (248°F)
- **Max Peak Discharge Temperature (1, 2):** 135°C (275°F)
- **Max Operating Condensing Temperature:** 60°C (140°F)
- **Max Peak Condensing Temperature (2):** 70°C (158°F)
- **Max Winding Temperature:** 130°C (266°F)
- **Max Impurities:** 30 mg
- **Max Water Content:** 100 mg

## 1.2 COMPRESSOR

- **Displacement:** 9.3 cc
- **Cylinder Bore:** 24.4 mm
- **Stroke:** 19.8 mm
- **Net Weight (3):** –
- **Shell size:** High
- **Oil charge:** 230 cc
- **Oil Type:** ICI RL 10H
- **Oil viscosity (4):** 10 cSt
- **Suction system:** Semi-direct

## 1.3 MOTOR

- **Power supply:** 220-240 V
- **Voltage limits:** 187 – 264 V
- **Frequency:** 50 Hz
- **Phase:** 1
- **Motor Type:** RSIR / RSCR
- **Electrical Insulation Class:** B
- **Locked Rotor Current at 220 V (Max value with RC):** 14.2A
- **Locked Rotor Current at 220 V (After 4 s with RC):** 7.8A
- **Locked Rotor Current at 220 V (Max value without RC):** 14.0A
- **Locked Rotor Current at 220 V (After 4 s without RC):** 8.0A
- **Main Winding Resistance at 20°C (68°F):** 9.13 Ω
- **Start Winding Resistance at 20°C (68°F):** 14.5 Ω

*(1) Measured at 5 cm from the shell with insulated thermocouples | (2) For transient conditions during "Pull Down" | (3) With oil and without external electricals | (4) Measured at 40°C (104°F)*

---

## 1.4 ELECTRICALS

### Motor-protector

| Feature                   | WANBAO            | SENSATA          |
|---------------------------|-------------------|------------------|
| <b>Type</b>               | BT110-120A61D2    | 4TM 308 NFBYY-53 |
| <b>Open Temperature</b>   | 115-125 °C        | 115-125 °C       |
| <b>Close Temperature</b>  | 70-52 °C          | 70-52 °C         |
| <b>U.T.C. at 70°C</b>     | 2.36 A            | 2.34 A (AT 70°C) |
| <b>Time Check Current</b> | 11 A (7.5-14 sec) | 11 A (5-15 sec)  |

# PTC starting device

|                    |                         |                         |
|--------------------|-------------------------|-------------------------|
| Feature            | WANBAO                  | TIANYIN                 |
| Assembly type      | QP2-15                  | QP2-15E                 |
| PTC Pill           | QP2-15                  | QP2-15E                 |
| Resistance at 25°C | 11-19Ω                  | 11-19Ω                  |
| V max              | 350 V                   | 350 V                   |
| I max              | 8A                      | 8A                      |
| Curie Temp         | 120°C                   | 120°C                   |
| Dimensions         | 20mm (dia), 3.3mm (thk) | 16mm (dia), 2.5mm (thk) |

## Run capacitor (optional)

- **Type:** Plastic case
- **Capacity:** 4μF
- **Vmax:** 450 V
- **Working hours:** 10,000 h at 450 V

---

## 2. CALORIMETER DATA

Test conditions according to ASHRAE:

- Condensing temp: +55°C
- Subcooling temp: +32°C
- Superheating temp: +32°C
- Suction temp: +32°C
- Supply Voltage: 220 V / 50 Hz

| 2.1 CALORIMETER TEST | -30°C<br>(Without RC) | -23.3°C<br>(Without RC) | -10°C<br>(Without RC) | -30°C<br>(With RC) | -23.3°C<br>(With RC) | -10°C<br>(With RC) |
|----------------------|-----------------------|-------------------------|-----------------------|--------------------|----------------------|--------------------|
| Cooling capacity (W) | 174                   | 270                     | 519                   | 170                | 270                  | 524                |
| Input power (W)      | 142                   | 185                     | 265                   | 137                | 174                  | 252                |
| COP (W)/W            | 1.22                  | 1.46                    | 1.96                  | 1.25               | 1.55                 | 2.08               |
| Current (A)          | 1.09                  | 1.25                    | 1.52                  | 0.81               | 0.95                 | 2.08               |

---

## 3. OTHER PERFORMANCES

- **3.1 Starting Test:** Min. Starting Voltage (at 90°C / 5 Bar A) = 165V.
  - **3.2 Calorimeter Test (GB9098):** A-weighted SPL: 42 dBA | Vibration Index TVI: 0.65 mm/s.
  - **3.3 Life Test:** 500h Wear, 2000h High Temp, 200K On/Off Cycles (All Passed).
  - **3.4 Transport Test:** Not required.
  - **3.5 Oil Transport Test:** Not required.
  - **3.6 Impact Test:** Not required.
-

## 4. COMPARISON CHART & DIMENSIONS

### Brand Cross-Reference

|                |                |                   |                     |
|----------------|----------------|-------------------|---------------------|
| MOTECH         | POWER          | EMBRACO           | TECUMSEH            |
| <b>GFF93AA</b> | <b>1/3+ HP</b> | <b>FFI 12 HBK</b> | <b>TPH1410Y</b>     |
| GFF86AA        | 1/3 HP         | EGAS 100 HLR      | TPH1410Y            |
| GFF75AA        | 1/4+ HP        | EGAS 80 HLR       | TSB1390Y            |
| GFF66AA        | 1/4 HP         | EGAS 80 HLR       | TSB1380Y            |
| GFF57AA        | 1/5 HP         | EGAS 70 HLR       | TSB1355Y / TSB1374Y |
| GFF44AA        | 1/6 HP         | EMI 60 HER        | THG1346Y / THG1352Y |
| GVM35AA        | 1/8 HP         | EMI 80 HLR        | THG1335Y            |
| GVM30AA        | 1/10 HP        | EM 30 HNR         | THG1330Y            |

### Dimensional Data (R134a)

| Model                        | A ± 2.5      | B ± 2.5      | C ± 2.5      | D ± 2.5    |
|------------------------------|--------------|--------------|--------------|------------|
| GFF57AA / 66AA / 75AA / 86AA | 98.5         | 100.5        | 113.5        | 174        |
| <b>GFF93AA</b>               | <b>108.5</b> | <b>110.5</b> | <b>123.5</b> | <b>184</b> |
| BFF12AA                      | 108.5        | 110.5        | 123.5        | 184        |
| BFM93AA                      | 98.5         | 100.5        | 113.5        | 174        |

---

## 5. TECHNICAL DRAWING LABELS

- **Air suction pipe:**  $\Phi$  6.1 + 0.1 (No paint allowed in length 12mm)
- **Exhaust pipe:**  $\Phi$  5 - 0.1 (No paint allowed in length 12mm)
- **Process pipe:**  $\Phi$  6.1 + 0.1 (No paint allowed in length 12mm)
- **Rating Label:** Located on the side of the compressor shell.
- **Serial Number:** Located near the base mounting feet.

mbsmpro.com-Siberia GFF93AA Compressor 13 hp R134a 270W Technical Specifications and Professional Replacements ReDownload