

Mbsm.pro, Codes and capacities of ZEL all compressors, pistons, motors, and refrigeration and air conditioning motors

Category: compressor

written by www.mbsm.pro | 21 September 2023

意大利扎努西 ZEL — R134a
220—240V / 50Hz

GML200A	输入功率.152W	制冷量.200W
GML180A	输入功率.144W	制冷量.187W
GML160G	输入功率.129W	制冷量.168W
GML140A	输入功率.108W	制冷量.140W
GML110A	输入功率.90W	制冷量.112W

WOMA 旺码
广州旺码制冷设备有限公司
Email: davidhu815@gmail.com

广州旺码制冷设备



Private Picture Copyright : WWW.MBSM.PRO

A method of knowing and determining the capacity of compressors, pistons, motors, and refrigeration engines using the cooling watts

GVY61AA GVY75AA GVY75AG GTH86AA GTH93AA GTT66AA GTT75AA GKD86AA GKD93AA GXL140F
GXL200F MODEL GML70A GML90A GML110A GML125A GML140A GML140A/I GML160A
GML180A GML200A GML200A/I GTM26AA GTM75AA GDL160A GDL200A GXL100A GXL125A
GXL140A GXL160A GXL200A GXL240A GL60TP GL80TP GL90TP GL90TP/I GL10TP GL12TP
GHP16AA GHP18AA GHP21AA MODEL HML100A HML125A HML140A HML155A HML170A
HML190A HML200A HDL100A HDL125A HDL140A HDL155A HDL170A HDL200A HXL100A HXL125A
HXL140A HXL155A HXL170A HXL190A HPL100A HPL125A HPL140A HML125A(T) HML140A(T)
HML170A(T) HMK12AA MODEL HDL125F HDL140F HDL160F HDL180F HDL190F HXL140F
HXL160F HXL190F HML125G HML140G HML170G HDL140G HDL170G HXL155G HXL185G
MODEL GML70A GML80A GML90A GML110A GML125A GML140A GML180A GML200A(M)
GML200A GDL140A GDL160A GDL200A(M) GDL200A GXL125A GXL140A GXL160A GXL200A
MODEL GML70G GML80G GML90G GML125G GML140G GML160G GXL125G GXL140G
GXL160G GML110A(T) GML140A(T) GML200A(T) MODEL HDZ100A(M) HDZ100A HDZ125A
HDZ140A HDZ155A HDZ170A HXZ100A HXZ125A HXZ140A HXZ155A HXZ170A HPZ100A HPZ125A
HPZ140A HPZ155A HPZ170A HDZ100F HDZ125F HDZ140F HDZ160F HDZ190F MODEL

HMM70A HMM80A HMM90A HMM100A HDM80A HDM90A HDM100A HDM110A MODEL GL90TB
 GL90TB(B) GL10TB GL12TB GL60TG GL90TG GTM93AA GTM10AA GTM12AA GTM93AG
 GMM70A GMM80A GMM90A GMM110A MODEL NLT44AA NLT53AA NLT57AA NLT61AA
 NLT66AA NLT75AA NLT80AA NLT86AA NLT93AA NLT44AA(I) NLT53AA(I) NLT57AA(I)
 NLT61AA(I) NLT66AA(I) NLT75AA(I) NLT80AA(I) NLL160A NLL200A NLL200A(I) NMT53AA
 NMT57AA NMT66AA NMT75AA MODEL HTT11AA HPKD190A HPKX190A HTH14AA HTH14AA(I)
 HKD14AA HYV67AA.02 HTK12AA.02 HPKD180G HPKD200G MODEL GVV57AA GVV61AA
 GVV66AA GVV75AA GTH86AA GTH93AA GTM93AA GTT66AA GTT75AA GKD86AA GKD86AA(I)
 GKD93AA GVV53AG GVV57AG GVV75AG GKD86AG GKD93AG

نوع التبريد	سعة التبريد	الفريون	التطبيق	220 / 240 / 50 HZ					الإزاحة	الأمبير	Freq	القدرة المسحوبة		MODEL		
				COOLING CAPACITY				Displ.CC				RLA	H Z		W	H P
				W 7.2+	W -6.7	W -23	B T U									
-	4.0	R134	LBP			160	548	138	5.7		5.7	113		GVY57AA		
-	4.0	R134	LBP			170	579	146	6.1		6.1	113		GVY61AA		
-	4.0	R134	LBP			180	615	155	6.6		6.6	124		GVY66AA		
-	4.0	R134	LBP			200	682	172	7.5		7.5	140		GVY75AA		
-	5.0	R134	LBP			240	817	206	8.6		8.6	163		GTH86AA		
-	5	R134	LBP			260	889	224	9.3		9.3	174		GTH93AA		
-	5	R134	LBP			260	889	224	9.3		9.3	176		GTM93AA		
-	4	R134	LBP			200	682	172	6.6		6.6	125		GTT66AA		
-	4	R134	LBP			210	718	181	7.5		7.5	134		GTT75AA		
-	6	R134	LBP			240	817	206	8.6		8.6	144		GKD86AA		
-	6	R134	LBP			240	817	206	8.6		8.6	141		GKD86AA(I)		
-	6	R134	LBP			270	921	232	9.3		9.3	163		GKD93AA		
-	3.0	R134a	LBP			138	440	119	5.3		5.3	93		GVY53AG		
						160	510	138				110				
-	4.0	R134a	LBP			154	488	132	5.7		5.7	111		GVY57AG		
						179	569	154				125				
-	5.0	R134a	LBP			201	640	173	7.5		7.5	139		GVY75AG		
						232	740	200				157				
-	5.0	R134a	LBP			245	837	211	8.6		8.6	163		GKD86AG		
						280	956	241				175				
-	5.0	R134a	LBP			290	988	249	9.3		9.3	193		GKD93AG		
						340	1159	292				213				

Private Picture Copyright : WWW.MBSM.PRO

220 / 240 / 50 HZ														MODEL
مكيف التبريد	مكيف التدفئة	البريدون	التطبيق	COOLING CAPACITY					الإزاحة	الأمبير	Freq	القدرة المسحوبة		
				W 7.2+	W -6.7	W-23	B T U	k CAL/HR	Displ.CC	RLA	HZ	W	H P	
-	6.0	R290	LBP			210	716	181	4.4		50	131		NLT44AA
-	6.0	R290	LBP			250	853	215	5.3		50	161		NLT53AA
-	5.0	R290	LBP			265	904	228	5.7		50	171		NLT57AA
-	5.0	R290	LBP			295	1007	254	6.1		50	187		NLT61AA
-	5.0	R290	LBP			308	1051	265	6.6		50	195		NLT66AA
-	5.0	R290	LBP			349	1191	300	7.5		50	221		NLT75AA
-	8.0	R290	LBP			380	1297	327	8.0		50	238		NLT80AA
-	8.0	R290	LBP			420	1433	361	8.6		50	275		NLT86AA
-	8.0	R290	LBP			450	1535	387	9.3		50	292		NLT93AA
-	6.0	R290	LBP			210	716	181	4.4		50	118		NLT44AA(I)
-	5.0	R290	LBP			260	887	224	5.3		50	144		NLT53AA(I)
-	6.0	R290	LBP			270	921	232	5.7		50	152		NLT57AA(I)
-	6.0	R290	LBP			300	1024	258	6.1		50	171		NLT61AA(I)
-	6.0	R290	LBP			325	1109	279	6.6		50	186		NLT66AA(I)
-	5.0	R290	LBP			349	1191	300	7.5		50	199		NLT75AA(I)
-	8.0	R290	LBP			380	1297	327	8.0		50	217		NLT80AA(I)
-	4.0	R290	LBP			165	563	142	4.1		50	110		NLL160A
-	5.0	R290	LBP			210	716	181	4.4		50	133		NLL200A
-	5.0	R290	LBP			210	716	181	4.4		50	124		NLL200A(I)
-	-	R290	M/HBP		420		1433	361	5.3		50	236		NMT53AA
-	-	R290	M/HBP		450		1535	387	5.7		50	214		NMT57AA
-	-	R290	M/HBP		530		1808	456	6.6		50	241		NMT66AA
-	-	R290	M/HBP		570		1945	490	7.5		50	259		NMT75AA

220 / 240 / 50 HZ													
MODEL	القدرة المسحوبة		Freq	الأمبير	الإزاحة	COOLING CAPACITY				التطبيق	البريدون	مكيف التبريد	مكيف التسخين
	W	H P				W 7.2+	W -6.7	W -23	B T U				
HTT11AA	50	106	50	11.0		185	631	159	11.4	LBP	R600	5.0	-
HPKD190A	50	118	50	11.4		201	686	173	11.4	LBP	R600	5.0	-
HPKX190A	50	109	50	11.4		208	710	179	14.0	LBP	R600	5.0	-
HTH14AA	50	168	50	14.0		235	802	202	14.0	LBP	R600	5.0	-
HTH14AA(I)	50	149	50	14.0		235	802	202	14.0	LBP	R600	5.0	-
HKD14AA	50	140	50	14.0		240	817	206	6.8	LBP	R600	6.0	-
HYV67AA.02	50		50	6.8		107	365	92	11.2	LBP	R600	3.0	-
HTK12AA.02	50		50	11.2		198	676	170		LBP	R600		-
HPKD180G	50	106	50	10.6		185	631	159	12.0	LBP	R600	5.0	-
	60	117	60			215	734	185		LBP	R600		-
HPKD200G	50	139	50	12.0		201	686	173		LBP	R600	5.0	-
	60	142	60			245	837	211		LBP	R600		-

220 / 240 / 50 HZ													MODEL	
نظف التبريد	نظف التبريد	الفريرين	التطبيق	COOLING CAPACITY				الإزاحة Displ.CC	الأسير RLA	Freq Hz	القدرة المسبوبة			
				W 7.2+	W -6.7	W -23	B T U x CAL/HR				W	H P		
-	2.0	R600	LBP			92	313	79	5.4		50	52		HDZ100A(M)
-	2.0	R600	LBP			98	333	84	5.7		50	55		HDZ100A
-	2.5	R600	LBP			126	429	108	7.0		50	70		HDZ125A
-	3.0	R600	LBP			135	460	116	7.5		50	75		HDZ140A
-	4.0	R600	LBP			155	528	133	8.6		50	87		HDZ155A
-	4.0	R600	LBP			170	579	146	9.2		50	96		HDZ170A
-	2.0	R600	LBP			98	333	84	5.7		50	53		HXZ100A
-	2.5	R600	LBP			126	429	108	7.0		50	68		HXZ125A
-	3.0	R600	LBP			135	460	116	7.5		50	73		HXZ140A
-	4.0	R600	LBP			155	528	133	8.6		50	84		HXZ155A
-	4.0	R600	LBP			170	579	146	9.2		50	93		HXZ170A
-	2.0	R600	LBP			98	333	84	5.7		50	51		HPZ100A
-	2.5	R600	LBP			126	429	108	7.0		50	65		HPZ125A
-	2.5	R600	LBP			135	460	116	7.5		50	68		HPZ140A
-	4.0	R600	LBP			155	528	133	8.6		50	79		HPZ155A
-	4.0	R600	LBP			170	579	146	9.2		50	88		HPZ170A
-	1.5	R600	LBP			97	329	83	4.9		60	55		HDZ100F
-	2.0	R600	LBP			126	429	108	5.7		60	71		HDZ125F
-	2.5	R600	LBP			144	492	124	7.0		60	80		HDZ140F
-	3.0	R600	LBP			170	579	146	8.0		60	96		HDZ160F
-	4.0	R600	LBP			190	647	163	9.2		60	107		HDZ190F

220 / 240 / 50 HZ													MODEL	
نظف التبريد	نظف التبريد	الفريرين	التطبيق	COOLING CAPACITY				الإزاحة	الأسير	Freq	القدرة المسبوبة			
				W 7.2+	W -6.7	W -23	B T U				k CAL/HR	Displ.PCC		W
-	2.0	R600	LBP			70	238	60	4.5	50	48			HMM70A
-	2.0	R600	LBP			80	274	69	4.9	50	55			HMM80A
-	2.0	R600	LBP			90	306	77	5.3	50	62			HMM90A
-	2.0	R600	LBP			100	341	86	6.0	50	69			HMM100A
-	2.0	R600	LBP			80	274	69	4.9	50	50			HDM80A
-	2.0	R600	LBP			90	306	77	5.3	50	55			HDM90A
-	2.0	R600	LBP			100	341	86	6.0	50	61			HDM100A
-	2.5	R600	LBP			112	381	96	6.3	50	70			HDM110A

220 / 240 / 50 HZ													MODEL
نظف التبريد	نظف التبريد	الفريرين	التطبيق	COOLING CAPACITY				الإنزاحة Displ.CC	الأسير RLA	Freq HZ	القدرة المسبوبة		
				W 7.2+	W -6.7	W -23	B T U k CAL/HR				W	H P	
50	-	R134a	HMBP	760			2593	653	7.5	50	335		GL90TB
50	-	R134a	HMBP	870			2968	748	8.6	50	387		GL90TB(B)
50	-	R134a	HMBP	930			3173	800	9.3	50	413		GL10TB
50	-	R134a	HMBP	1100			3753	946	12.0	50	489		GL12TB
50	-	R134a	HMBP	540			1842	464	5.3	50	240		GL60TG
				640			2184	550		60	262		
				740			2525	636	7.5	50	240		GL90TG
50	-	R134a	HMBP	880			3002	757		60	262		

-	-	R134a	LBP			280	955	241	10.0	50	207		GTM93AA
50.0	-	R134a	LBP			300	1024	258	10.6	50	226		GTM10AA
50.0	-	R134a	LBP			320	1092	275	12.0	50	241		GTM12AA

50	-	R134a	LBP			248	846	213	9.3	50	216		GTM93AG
						290	989	249		60	220		

-	2.0	R134a	LBP			70	238	60	2.8	50	52		GMM70A
-	2.0	R134a	LBP			80	274	69	3.1	50	59		GMM80A
-	2.0	R134a	LBP			90	306	77	3.4	50	67		GMM90A
-	2.5	R134a	LBP			110	377	95	4.1	50	81		GMM110A

220 / 240 / 50 HZ														MODEL
مكثف التبريد	مكثف التبريد	الفرغون	التطبيق	COOLING CAPACITY					الإزاحة	الأمبير	Freq	القدرة المسحوبة		
				W 7.2+	W -6.7	W-23	B T U	k CAL/HR	Displ.CC	RLA	HZ	W	H P	
-	2.0	R134a	LBP			70	70	60	2.9		50	52		GML70A
-	2.0	R134a	LBP			80	80	69	3.1		50	62		GML80A
-	2.0	R134a	LBP			94	94	81	3.4		50	67		GML90A
-	2.5	R134a	LBP			113	113	97	4.1		50	84		GML110A
-	3.0	R134a	LBP			121	121	104	4.3		50	88		GML125A
-	3.0	R134a	LBP			140	140	120	4.5		50	104		GML140A
-	4.0	R134a	LBP			178	178	153	6.0		50	125		GML180A
-	5.0	R134a	LBP			190	190	163	6.5		50	128		GML200A(M)
-	5.0	R134a	LBP			205	205	176	7.0		50	139		GML200A
-	3.0	R134a	LBP			148	148	127	4.9		50	102		GDL140A
-	4.0	R134a	LBP			167	167	144	5.7		50	108		GDL160A
-	5	R134a	LBP			190	190	163	6.5		50	119		GDL200A(M)
-	5	R134a	LBP			205	205	176	7.0		50	135		GDL200A
-	5	R134a	LBP			123	123	106	4.3		50	72		GXL125A
-	5	R134a	LBP			138	138	119	4.3		50	80		GXL140A
-	4	R134a	LBP			167	167	144	5.7		50	98		GXL160A
-	5	R134a	LBP			195	195	168	7.0		50	115		GXL200A

220 / 240 / 50 HZ														
مكثف التبريد	مكثف التبريد	الفرغون	التطبيق	COOLING CAPACITY					الإزاحة	الأمبير	Freq	القدرة المسحوبة		MODEL
				W 7.2+	W -6.7	W-23	B T U	k CAL/HR	Displ.CC	RLA	HZ	W	H P	
-	2.0	R134a	LBP			72	246	62	2.9		50	52		GML70G
-						86	294	74			60	59		
-	2.0	R134a	LBP			80	274	69	3.1		50	58		GML80G
-						92	313	79			60	63		
-	2.5	R134a	LBP			94	321	81			50	72		GML90G
-						110	377	95	3.4		60	76		
-	3.0	R134a	LBP			122	417	105			50	90		GML125G
-						145	496	125	4.3		60	100		
-	3.0	R134a	LBP			136	464	117			50	97		GML140G
-						157	536	135	4.5		60	101		
-	4.0	R134a	LBP			162	552	139			50	114		GML160G
-						195	667	168	5.7		60	128		
-	3.0	R134a	LBP			123	421	106			50	74		GXL125G
-						143	488	123	4.3		60	83		
-	3.0	R134a	LBP			150	512	129			50	90		GXL140G
-						176	599	151	4.9		60	102		
-	4.0	R134a	LBP			167	571	144			50	103		GXL160G
-						204	694	175	5.7		60	122		
-	2.5	R134a	LBP			113	385	97	4.1		50	87		GML110A(T)
-	3	R134a	LBP			140	476	120	4.9		50	110		GML140A(T)
-	5	R134a	LBP			195	667	168	6.5		50	135		GML200A(T)

نوع التبريد	مستوى التشغيل	البريدون	التطبيق	220 / 240 / 50 HZ										MODEL
				COOLING CAPACITY					الراحة	الأمبير	Freq	القدرة المسحوبة		
				W 7.2+	W -6.7	W -23	B T U	k CAL/HR				Displ.CC	RLA	
-	2.0	R600	LBP			104	353	89	6.0		50	71		HML100A
-	2.0	R600	LBP			121	413	104	7.0		50	83		HML125A
-	3.0	R600	LBP			140	476	120	8.0		50	90		HML140A
-	3.0	R600	LBP			155	528	133	8.6		50	107		HML155A
-	3.0	R600	LBP			170	579	146	9.5		50	115		HML170A
-	3.0	R600	LBP			190	648	163	10.5		50	131		HML190A
-	4.0	R600	LBP			200	682	172	12.0		50	133		HML200A
-	2.5	R600	LBP			98	333	84	5.7		50	60		HDL100A
-	2.5	R600	LBP			123	421	106	7.0		50	72		HDL125A
-	2.5	R600	LBP			140	476	120	8.0		50	81		HDL140A
-	4.0	R600	LBP			155	528	133	8.6		50	91		HDL155A
-	4.0	R600	LBP			170	579	146	9.5		50	100		HDL170A
-	4.0	R600	LBP			195	667	168	11.0		50	117		HDL200A
-	2	R600	LBP			98	333	84	5.7		50	52		HXL100A
-	2	R600	LBP			126	429	108	7.0		50	65		HXL125A
-	2	R600	LBP			140	476	120	8.0		50	73		HXL140A
-	2	R600	LBP			155	528	133	8.5		50	82		HXL155A
-	2	R600	LBP			176	599	151	9.3		50	93		HXL170A
-	3	R600	LBP			195	667	168	10.5		50	105		HXL190A
-	2	R600	LBP			100	341	86	5.7		50	51		HPL100A
-	2	R600	LBP			126	429	108	7.0		50	64		HPL125A
-	2	R600	LBP			140	476	120	8.0		50	71		HPL140A
-	2	R600	LBP			130	444	112	7.5		50	87		HML125A(T)
-	3	R600	LBP			140	476	120	8.0		50	97		HML140A(T)
-	3	R600	LBP			170	579	146	9.5		50	118		HML170A(T)
-		R600	LBP			198	676	170	11.2		50			HMK12AA

نوع التبريد	حاجت التشغيل	البريون	التطبيق	220 / 240 / 50 HZ					التردد	الأمبير	FREQ	القدرة المسحوبة		MODEL	
				COOLING CAPACITY								Displ.CC	W		H P
				W 7.2+	W -6.7	W -23	B T U	k CAL/HR							
-	2.0	R600	LBP			130	444	112	6.3		60	79		HDL125F	
-	3.0	R600	LBP			145	496	125	7.0		60	90		HDL140F	
-	3.0	R600	LBP			160	548	138	7.5		60	98		HDL160F	
-	5.0	R600	LBP			180	615	155	8.6		60	106		HDL180F	
-	5.0	R600	LBP			200	682	172	9.2		60	118		HDL190F	
-	3.0	R600	LBP			140	476	120	7.0		60	74		HXL140F	
-	3.0	R600	LBP			160	548	138	7.5		60	84		HXL160F	
-	3.0	R600	LBP			190	647	163	8.6		60	103		HXL190F	
-	2.0	R600	LBP			130	444	112	7.5		50	87		HML125G	
					154	524	132			60	96				
					140	476	120			50	97				
-	4.0	R600	LBP			167	571	144	8.0		60	108		HML140G	
					165	563	142			50	114				
					192	655	165			60	124				
-	4.0	R600	LBP			145	4	125	9.2		50	90		HML170G	
					170	4	146			60	99				
					167	4	144			50	102				
-	4.0	R600	LBP			200	4	172	8.0		60	116		HDL140G	
					155	528	133			50	89				
					183	623	157			60	98				
-	4.0	R600	LBP			185	631	159	8.6		50	106		HDL170G	
					215	734	185			60	117				

220 / 240 / 50 HZ															MODEL	
نصف التبريد	نصف التدفق	البريدون	التطبيق	COOLING CAPACITY					الإزاحة	الأمبير	Freq	القدرة المسحوبة				
				W 7.2+	W -6.7	W -23	B T U	k CAL/HR	Displ.CC	RLA	HZ	W	H P			
-		R134a	LBP			90	307	77	3.4			50		1/9	OF60S	
	2	R134a	LBP			100	341	86	3.9			50		1/8	OF700	
	3	R134a	LBP			110	375	95	3.9			50		1/7	OF789	
		R134a	LBP			140	478	120	5.3			50		1/5	OF1033A	
		R134a	LBP			180	614	155	7.0			50		1/5	OF1350A	
	2	R134a	LBP			80	273	69	3.4			50		0	GVY35AA	
	3	R134a	LBP			109	372	94	4.0			50		1/9	GVY40AA	
	3	R134a	LBP			130	444	112	4.4			50		1/8	GVY44AA	
		R134a	LBP			132	450	113	4.4			50		1/8	GVY44AG	
	3	R134a	LBP			140	478	120	5.3			50		1/7	GVY53AA	
		R134a	LBP			138	471	119	5.3			50		1/7	GVY53AG	
	4	R134a	LBP			160	546	138	5.7			50		1/6	GVY57AA	
		R134a	LBP			154	525	132	5.7			50		1/6	GVY57AG	
	4	R134a	LBP			170	580	146	6.1			50		1/6	GVY61AA	
	4	R134a	LBP			206	703	177	7.5			50		1/5	GVY75AA	
		R134a	LBP			201	686	173	7.5			50		1/5	GVY75AG	
	5	R134a	LBP			240	819	206	8.6			50		1/4	GTH86AA	
	5	R134a	LBP			260	887	224	9.3			50		1/4	GTH93AA	
	4	R134a	LBP			200	682	172	6.6			50		1/6	GTT66AA	
	4	R134a	LBP			210	716	181	7.5			50		1/5	GTT75AA	
	6	R134a	LBP			255	870	219	8.6			50		1/4	GKD86AA	
	6	R134a	LBP			270	921	232	9.3			50		1/4	GKD93AA	
		3	R134a	LBP			148	488	123	4.3			60	85		GXL140F
		4	R134a	LBP			200	682	172	5.7			60	120		GXL200F

220 / 240 / 50 HZ														MODEL
نصف التبريد	نصف التدفق	الفريرون	التطبيق	COOLING CAPACITY					الإزاحة	الأمبير	Freq	القدرة المسحوبة		
				W 7.2+	W -6.7	W -23	BTU	k CAL/HR				W	H P	
		R134a	LBP			68	232	58	2.8		50			GML70A
	2	R134a	LBP			92	314	79	3.4		50			GML90A
	3	R134a	LBP			113	386	97	4.1		50			GML110A
		R134a	LBP			120	409	103	4.1		50			GML125A
		R134a	LBP			140	478	120	4.9		50		1/6	GML140A
	5	R134a	LBP			140	478	120	4.9		50		1/6	GML140A/I
						160	546	138	5.7		50		1/6	GML160A
	5	R134a	LBP			180	614	155	6.5		50		1/5	GML180A
	5	R134a	LBP			200	682	172	7.0		50		1/5	GML200A
	6	R134a	LBP			210	716	181	7.0		50		1/5	GML200A/I
		R134a	LBP			65	222	56	2.6		50		1/9	GTM26AA
		R134a	LBP			200	682	172	7.5		50		1/5	GTM75AA
	4	R134a	LBP			167	570	144	5.7		50			GDL160A
	5	R134a	LBP			165	563	142	6.5		50			GDL200A
	4	R134a	LBP			106	362	91	4.1		50			GXL100A
	5	R134a	LBP			123	420	106	4.3		50			GXL125A
	5	R134a	LBP			138	471	119	4.6		50			GXL140A
	4	R134a	LBP			160	546	138	5.7		50			GXL160A
	5	R134a	LBP			195	665	168	7.0		50			GXL200A
	5	R134a	LBP			240	819	206	8.6		50			GXL240A
		R134a	HBP	540			1842	464	5.3		50		1/3	GL60TP
		R134a	HBP	740			2525	636	7.5		50		1/2	GL80TP
50		R134a	HBP	860			2934	739	9.3		50		1/2	GL90TP
50		R134a	HBP	860			2934	739	9.3		50		1/2	GL90TP/I
50		R134a	HBP	880			3002	757	9.3		50		1/2	GL10TP
50		R134a	HBP	1130			3855	972	12.0		50			GL12TP
100		R134a	HBP	1300			4435	1118	16.0		50			GHP16AA
100		R134a	HBP	1600			5459	1376	18.0		50			GHP18AA
100		R134a	HBP	1900			6483	1634	21.0		50			GHP21AA

意大利扎努西 ZEL — R134a

220—240V / 50Hz

GML200A	输入功率.152W	制冷量.200W
GML180A	输入功率.144W	制冷量.187W
GML160G	输入功率.129W	制冷量.168W
GML140A	输入功率.108W	制冷量.140W
GML110A	输入功率.90W	制冷量.112W

WOMA 旺码
广州旺码制冷设备有限公司
Email: davidhu815@gmail.com



C 63010440



广州旺码制冷设备