

# Mbsm.pro, GL90TB , COMPRESSEUR ACC CUBIGEL ELECTROLUX, R134A ,1/4HP 230V

Category: Solutions, Tester ok  
written by Jamila | 9 October 2018



PictureS Mbsm Dot Pro : [www.mbsm.pro](http://www.mbsm.pro)

Mbsm.pro, GL90TB , COMPRESSEUR ACC CUBIGEL ELECTROLUX, R134A ,1/4HP 230V

- Puissance en cheval 1/4 CV
- Alimentation 220-240 V 50 Hz
- Gaz R134a HMBP
- Cylindrée du compresseur 8,8 cm<sup>3</sup>
- Température d'utilisation max. 32°C
- Complet avec starter, condensateur, boîtier et système de fixation

La photo montre l'aspect du compresseur, pas son étiquette réelle



PictureS Mbsm Dot Pro : [www.mbsm.pro](http://www.mbsm.pro)

Codes fabricants

- ACC-GL90TB
- ALPENINOX-83718
- ANGELO PO-34D6510
- CEM-340
- CUBIGEL-GL90TB
- DEXION-022260-00
- ELECTROLUX-83718
- FRIULINOX-995783
- ICEMATIC-19165548
- MARENO-25016599

- MONDIAL ELITE-4106073
- MONDIAL ELITE-4106073+1147212
- NECTA VENDING-986934
- ZANUSSI-83718

Documentation technique du compresseur frigorifique Cubigel [regarder en dessous](#)



## Mbsm.pro , Compressors ZMC, EGL90AA, R-134a ,1/4 HP LBP, 220 – 240 V

Category: Solutions, Tester ok  
 written by www.mbsm.pro | 9 October 2018



Mbsm.pro , Compressors ZMC, EGL90AA, R-134a ,1/4 HP LBP, 220 – 240 V

### BRAND

- – ZMC

## TECHNICAL SPECIFICATIONS :

- MODEL: EGL 90 AA
- POWER: 1/4 Hp
- VOLTAGE: 220 - 240 V
- WATT: 227.00 W
- REFRIGERANT GAS: R 134
- K.CAL: 195.00 Cal.

**Features :** The compressors form the basis of the refrigerant system and function to compress the gas from the evaporation to the condensation pressure.

## USAGE PLACES :

It is used in Refrigerator devices belonging to all brands and models.

## INSTRUCTIONS FOR USE:

**Zmc EGL90AA;**It is recommended to be used by a specialist authorized or authorized service.



PictureS Mbsm Dot Pro : [www.mbsm.pro](http://www.mbsm.pro)

[Mbsm\\_dot\\_pro\\_private\\_PDF\\_catalogo\\_cubigel\\_R134aTélécharger](#)

[Mbsm\\_dot\\_pro\\_private\\_PDF\\_cubigel-katalogTélécharger](#)

Mbsm.pro, DAEW00 Compressor ,  
HSL27YE-5, 1/4HP , 1PH, R134a  
,220-240V 50Hz,Puissance frigorifique  
244 W, 833 Btu / h

Category: Solutions,Tester ok  
written by Jamila | 9 October 2018



Mbsm.pro, DAEW00 Compressor , HSL27YE-5, 1/4HP , 1PH, R134a ,220-240V  
50Hz,Puissance frigorifique 244 W, 833 Btu / h

---

Mbsm.pro, QA57C12GAX5 , 1PH , 1/6 HP  
,Panasonic ,Matsushita Electric,  
Company, Malaysia , R134a , 220/240V  
50Hz

Category: Solutions,Tester ok  
written by Jamila | 9 October 2018



PictureS Mbsm Dot Pro : [www.mbsm.pro](http://www.mbsm.pro)

Mbsm.pro, QA57C12GAX5 , 1PH , 1/6 HP ,Panasonic ,Matsushita Electric, Company, Malaysia , R134a , 220/240V 50Hz



PictureS Mbsm Dot Pro : [www.mbsm.pro](http://www.mbsm.pro)

---

Mbsm.pro , L76AV ,Compresseur, 1/5 HP  
,149W, R12 ,E80101 ,Zem ,HMBP  
,Hermetic piston compressors ,

# 220V/50 , 1PH(phase)

Category: Solutions,Tester ok  
written by Jamila | 9 October 2018



PictureS Mbsm Dot Pro : [www.mbsm.pro](http://www.mbsm.pro)

Mbsm.pro , L76AV ,Compresseur, 1/5 HP ,149W, R12 ,E80101 ,Zem ,HMBP ,Hermetic piston compressors , 220V/50 , 1PH(phase)

---

## MBSM.PRO , HYE69YL ,Compressor (LBP) , China R134a ,Huayi Compressor Co. , Ltd, 69 YL ,1/4 Hp ,168Kcal , 220V

Category: Solutions,Tester ok  
written by Jamila | 9 October 2018



Picture5 Mbsm Dot Pro : www.mbsm.pro

MBSM.PRO , HYE69YL ,Compressor (LBP) , China R134a ,Huayi Compressor Co., Ltd, 69 YL ,1/4 Hp ,168Kcal , 220V

Test conditions	According to ASHRAE
Evaporating temperature	-23.3[°C]
Condensing temperature	54.4[°C]
Subcooling temperature	32.2[°C]
Suction temperature	32.2[°C]
Ambient temperature	32.2[°C]
Working condition limit:R134a	
Max ambient temperature	43[°C]
Evaporation temperature range	-35~-15[°C]
Working voltage range.	187~254/98~127[V]
Max discharge pressure	2.0[Mpa](gauge pressure)
Max allowable housing temperature	95[°C]
Max discharge temperature	125[°C]
Max pressure housing endured	2.7[Mpa](gauge pressure)
Low voltage start	0.4/0.4Mpa(gauge pressure)187V/98V

Product model:HYE69YL  
 Cooling capacity:195W  
 COP[W/W]:1.15  
 Voltage[V]:220-240~  
 Frequency(Hz):50



PictureS Mbsm Dot Pro : www.mbsm.pro

**Products**

- R134a Compressor (LBP)
  - HYE Serie
  - HY Serie
  - HYB Serie
  - HYS Serie
- R600a Compressor (LBP)
  - HYE Serie
  - HY Serie
  - HYB Serie
  - HYS Serie
- R134a Compressor (MBP,HBP)
  - HY Serie
  - HYE Serie

[Newest Catalog Download](#)

Product model:HYE69YL  
 Cooling capacity:195W  
 COP (W/W) :1.15  
 Voltage (V) :220-240~  
 Frequency(Hz):50

Test conditions	According to ASHRAE
Evaporating temperature	-23.3°C
Condensing temperature	54.4°C
Subcooling temperature	32.2°C
Suction temperature	32.2°C
Ambient temperature	32.2°C
<b>Working condition limit:R134a</b>	
Max ambient temperature	43[°C]
Evaporation temperature range	-35~-15[°C]
Working voltage range.	187~254/98~127[V]
Max discharge pressure	2.0[Mpa](gauge pressure)
Max allowable housing temperature	95[°C]
Max discharge temperature	125[°C]
Max pressure housing endured	2.7[Mpa](gauge pressure)
Low voltage start	0.40.4Mpa(gauge pressure)187V/98V

PictureS Mbsm Dot Pro : www.mbsm.pro



**AE 1330 Y**

**1 / 12 HP**



**AE 1340 Y**

**1 / 6 HP**



**AE 1350 Y**

**1 / 6 HP**



**AE 1360 Y**

**1 / 5 HP**



**AE 1370 Y**

**1 / 4 HP**



**AE 1390 Y**

**1 / 4 HP**



**HY 81 Y**

**1 / 4 HP**



**HYE 55 YL 63**

**1 / 6 HP**



**HYE 60 YL 63**

**1 / 5 HP**



**HYE 69 YL**

**1 / 4 HP**



**HYE 125 MSU**

**1 / 4 HP**





Huayi HYE 69 YL 1/4 Hp 168Kcal R134a 220V

Huayi - Huayi

---

Huayi HYE 55 YL 63 1/6 Hp 129Kcal R134a 220V

Huayi - Huayi

---

Huayi HYE 60 YL 63 1/5 Hp 146Kcal R134a 220V

Huayi - Huayi

---

Huavi HY 81 Y 1/4+ Hp 202Kcal R134a 220V

PictureS Mbsm Dot Pro : [www.mbsm.pro](http://www.mbsm.pro)



---

HYE 125 MSU

HYE 69 YL

HYE 60 YL 63

HYE 55 YL 63

HY 81 Y

AE 1390 Y

AE 1370 Y

AE 1360 Y

AE 1350 Y

AE 1340 Y

AE 1330 Y

PictureS Mbsm Dot Pro : [www.mbsm.pro](http://www.mbsm.pro)





Mbsm.pro , COMPRESSOR TECUMSEH,  
CAJ4511Y, R134a, HMBP(HBP – High Back  
Pressure),1 HP, 1PH, 220-240 VOLTS ,  
High Start Torque (HST) ,

Category: Solutions,Tester ok  
written by Jamila | 9 October 2018



PictureS Mbsm Dot Pro : [www.mbsm.pro](http://www.mbsm.pro)

Mbsm.pro , COMPRESSOR TECUMSEH,

## L'unité hermetique Compressor

CAJ4511Y, R134a, HMBP(HBP – High Back Pressure), 1 HP, 1PH, 220-240 VOLTS , High Start Torque (HST)

Condensateur Perm./ Run capacitor : 15  $\mu$ F / 400 V

### Données techniques

- Modèle: **CAJ4511Y**
- Gaz: **R-134a**
- Température/Pression: **Haute Pression**
- Puissance: **1 HP**
- Voltage: **230 V**
- Type De Courant: **Monophasé**
- Fréquence: **50 Hz**
- Type De Compresseur: **Hermétique**
- Décalage: **32.7 cm<sup>3</sup>**
- Cons.Énergie -5°C: **920 W**
- Cons.Énergie 0°C: **1030 W**
- Cons.Énergie +5°C: **1140 W**
- Cons.Énergie +10°C: **1250 W**
- T° De Condensation: **55 °C**
- Capacité Frigorífica -5°C: **1376 Kcal/h**
- Capacité Frigorífica 0°C: **1737 Kcal/h**
- Capacité Frigorífica 5°C: **2150 Kcal/h**
- Capacité Frigorífica 7.2°C: **2347 Kcal/h**
- Capacité Frigorífica 10°C: **2614 Kcal/h**
- Tipo Test: **EN.12900**



PictureS Mbsm Dot Pro : [www.mbsm.pro](http://www.mbsm.pro)



PictureS Mbsm Dot Pro : [www.mbsm.pro](http://www.mbsm.pro)

Mbsm.pro, ZEL GTM93AG, 1/3 Hp ,  
Compressor for wine coolers

, 200-220V/50Hz 220-230V/60Hz, R134A

Category: Solutions, Tester ok  
written by Jamila | 9 October 2018



Mbsm.pro, ZEL GTM93AG, 1/3 Hp , Compressor for wine coolers , 200-220V/50Hz  
220-230V/60Hz, R134A



نموذج	محرك	Displ	قوة	نوع المحرك	التكرار	قدرة التبريد	مدخل الطاقة	مطابقة الإدخال (RC)
GTM93AG	التحاسب	9.3	1/3	مضغطة	60	290	220	0
GTM93AG	التحاسب	9.3	1/3	مضغطة	50	248	216	0
GTM12AA	التحاسب	12	1/3	مضغطة	50	320	241	0
GTM10AA	التحاسب	10.6	1/3	مضغطة	50	300	226	0
GTM93AA	التحاسب	10	1/3	RSIR	50	280	207	0
GTM75AA	شركة	7.5	1/5	مضغطة			160	0

Place of Origin: China

## Product Description

## Product Description

ZEL GTM93AG Compressor for wine coolers 200-220V/50Hz 220-230V/60Hz R134A  
Specifications

Refrigeration Compressor

Refrigerator, freezer, drinking fountains and home ice cream,

Refrigeration Compressor

Application: Refrigerator, freezer, drinking fountains and home ice cream, ice-making machines and other products

Production Standard: CCC, DVE, RoHS, UL certificate

Packing: Carton

Household Applications

- Freezers
- Refrigerators
- Wine Coolers

Commercial Applications

- Horizontal Freezers
- Merchandisers
- Equipment for professional kitchens
- Dispenser
- Water Coolers
- Wine Coolers
- Ice makers
- Vending Machines
- Minibar

They are the best selling high-tech compressors sold in the world. They are ideal for domestic refrigeration and also for small commercial applications.

They are small, have low noise and vibration levels, they achieve the highest levels of efficiency available in the market for this category.

For more details of the refrigeration compressor, please contact us.

Model	Displacement cm <sup>3</sup>	Height MM	Motor Type	Cooling capacity W	COP	Power W/W	Supply V/Hz
GTM93AG	9.3	183	CSIR	248	1.15	200-220/50	
		183	CSIR	290	1.30	220-230/60	

Related Keywords

Compressor Wine Coolers , Coolers For Wine Bottles , Air Compressor For Engineerin

China Compressor Wine Coolers , China Coolers For Wine Bottles , China Air Compressor For Engineerin

Model	Lamp Power	Refrigerant	CH650	Mode
240 grams	134 a	240 grams	134 a	Mode
سعة التجميد Freezing Capacity	650 لتر 650 Lit.	الحجم الشامل الكلي المقنن Gross Volume	50 هرتز 50 Hz.	التردد Frequency
درجة الحماية Protection Degree	547 لتر 547 Lit.	حجم تخزين حيز التجميد Freezer Storage Volume	216 وات 216 Watt	قدرة المقتنن Rated Power
المواصفات القياسية المصرية Standards	547 لتر (19.3 قدم <sup>3</sup> ) 547 Lit. (19.3 ft <sup>3</sup> )	حجم تخزين غير الاطعمة الطازجة Fresh Food Storage Volume	220 فولت 220 Volt	قدرة المقتنن Rated Voltage
		حجم التخزين الكلي (السمه) Rated Storage Volume	1.9 أمبير 1.9 Ampere	التيار المقنن Rated Current
نوع العزل Insulation	مجمد طراز A Freezer type	النوع Type	التصنيف Class	السخان Heater
Egypt	2205	الرقم المسلسل Serial Number	2016	تاريخ الانتاج Production



Mbsm.pro , Compressor ACC , Cubigel Huayi, Electrolux ZEM, GP12TG, HMBP-R134a, 220-230V , 50/60Hz, 3.8 HP

Category: Solutions, Tester ok  
written by Jamila | 9 October 2018



PictureS Mbsm Dot Pro : [www.mbsm.pro](http://www.mbsm.pro)

Mbsm.pro , Compressor ACC ,Cubigel Huayi, Electrolux ZEM, GP12TG, HMBP-R134a, 220-230V ,50/60Hz, 3.8 HP



**cubigel**

compressors

**THERMALLY  
PROTECTED**

**R134a**

**GP12TG**

200-220V~50Hz PH1

220-230V~60Hz

CE

MADE IN  
SPAIN

72081480231000

2  
272



---

MBSM.PRO , Compressor, Electrolux-Zem  
GL60AA R134A ,1/6 HP , 1PH , 220-240  
V 50 Hz

Category: Solutions,Tester ok  
written by Jamila | 9 October 2018



PictureS Mbsm Dot Pro : [www.mbsm.pro](http://www.mbsm.pro)

MBSM.PRO , Compressor, Electrolux-Zem GL60AA R134A ,1/6 HP , 1PH , 220-240 V 50 Hz



- Puissance en cheval 1/6 CV
- Cylindrée 5.99 cm<sup>3</sup>
- 220-240 V 50 Hz
- Gaz R134a LBP
- Température d'utilisation max. 32°C
- Avec boîtier et système de démarrage

La photo montre l'aspect du compresseur, pas son étiquette réelle

#### Codes fabricants

- ACC-GL60AA
- ACC-GL60AB
- ACC-GL60AH
- CUBIGEL-GL60AA
- CUBIGEL-GL60AB
- CUBIGEL-GL60AH
- MONDIAL ELITE-4106004
- MONDIAL ELITE-1147031
- Embraco Aspera- B1112Z





PictureS Mbsm Dot Pro : [www.mbsm.pro](http://www.mbsm.pro)



PictureS Mbsm Dot Pro : [www.mbsm.pro](http://www.mbsm.pro)

Mbsm\_dot\_pro\_private\_PDF\_GL60AATélécharger  
Mbsm\_dot\_pro\_private\_PDF\_-GL60AATélécharger

590689

GL60AA 99H271A

**GL60AA**

08283

03254

267799

THERMALLY 220 - 240 V~ 50 Hz PH1  
PROTECTED

**R134a**



CE H



**Type: Hermetic piston compressors** **Producer: ACC** **Series: HMBP**

**Model: GL60AA**

### **General data**

Refrigerant: R134a  
Discharge element: C  
Cooling: S  
Maximum ambient temperature [°C]: 43

### **Compressor's data**

Cylinder capacity [cm<sup>3</sup>]: 6  
Displacement [m<sup>3</sup>/h]: 1  
Weight [kg]: 9,1  
Oil charge [cm<sup>3</sup>]: 265  
Oil type: ISO VG 19 ESTER

### **Engine's data**

Engine type: RSIR  
Power [KM]: 1/6  
Starting element: LST  
Power supply: 220V 50Hz  
Voltage range: 187-264  
Locked rotor current [A]: 9,9  
Running winding resistance (25°C) [Ω]: 15,6  
Starting winding resistance (25°C) [Ω]: 21,31

### **Electrical data**

Relays: 3003  
Shielding element: MRA38028, T0508, AF18FU  
Starting capacitor volume [μF]:

### **Connections**

	milimeters	inches
Suction tube:	6,5	
Service tube:	6,5	
Discharge tube:	4,9	