

# ZMC, zanussi, Made in Egypt, Compressors

Category: compressor

written by [www.mbsm.pro](http://www.mbsm.pro) | 8 April 2021

## R134a

Model	Refr.	HP	Ambient Temp C	Rated Voltage	Cooling Capacity		COP without RC		COP with RC	
					ASHRAE	CECOMAF	ASHRAE	CECOMAF	ASHRAE	CECOMAF
					-23.3°C kcal/h	-25°C W	-23.3°C W/W	-25°C W/W	-23.3°C W/W	-25°C W/W
<input type="checkbox"/> <a href="#">GL45AA</a>	LBP::R134a	1/8	43	A	96	82	1.06	0.82		
<input type="checkbox"/> <a href="#">GL45AN</a>	LBP::R134a	1/8	50	C	96	81	1.05	0.8		
<input type="checkbox"/> <a href="#">GL60AA</a>	LBP::R134a	1/6	43	A	132	114	1.14	0.89		
<input type="checkbox"/> <a href="#">GL60AF</a>	LBP::R134a	1/6	43	D	132	113	1.07	0.82		
<input type="checkbox"/> <a href="#">GL60AH</a>	LBP::R134a	1/6	43	A	133	114	1.31	1.01		
<input type="checkbox"/> <a href="#">GL60AN</a>	LBP::R134a	1/6	50	C	132	114	1.07	0.83		
<input type="checkbox"/> <a href="#">GL70AA</a>	LBP::R134a	1/5	43	A	149	128	1.18	0.92		
<input type="checkbox"/> <a href="#">GL70AN</a>	LBP::R134a	1/5	50	D	150	129	1.08	0.83		
<input type="checkbox"/> <a href="#">GL70AT</a>	LBP::R134a	1/5	43	E	144	122	1.09	0.84		
<input type="checkbox"/> <a href="#">GL75AA</a>	LBP::R134a	1/5	43	A	155	133	1.18	0.92		
<input type="checkbox"/> <a href="#">GL80AA</a>	LBP::R134a	1/5	43	A	173	148	1.19	0.93		
<input type="checkbox"/> <a href="#">GL80AF</a>	LBP::R134a	1/5	43	D	166	141	1.14	0.88		
<input type="checkbox"/> <a href="#">GL80AH</a>	LBP::R134a	1/5	43	A	175	150	1.35	1.06		
<input type="checkbox"/> <a href="#">GL80AN</a>	LBP::R134a	1/4	43	A	196	168	1.36	1.06		
<input type="checkbox"/> <a href="#">GL90AA</a>	LBP::R134a	1/4	43	A	195	167	1.19	0.93		
<input type="checkbox"/> <a href="#">GL90AH</a>	LBP::R134a	1/4	43	A	215	182	1.39	1.08		
<input type="checkbox"/> <a href="#">GL90AN</a>	LBP::R134a	1/4	50	D	190	163	1.1	0.85		
<input type="checkbox"/> <a href="#">GL90AT</a>	LBP::R134a	1/4	43	E	190	161	1.19	0.92		
<input type="checkbox"/> <a href="#">GL99AA</a>	LBP::R134a	1/4	43	A	214	182	1.24	0.96		
<input type="checkbox"/> <a href="#">GL99AH</a>	LBP::R134a	1/4	43	A	215	182	1.39	1.08		
<input type="checkbox"/> <a href="#">GL80AD</a>	LBP::R134a	1/5	43	W	0	0	0	0		
<input type="checkbox"/> <a href="#">GL90AD</a>	LBP::R134a	1/4	43	W	0	0	0	0		

## R134a

Model	Refr.	HP	Ambient Temp C	Rated Voltage	Cooling Capacity		COP without RC		COP with RC	
					ASHRAE -23.3°C	CECOMAF -25°C	ASHRAE -23.3°C	CECOMAF -25°C	ASHRAE -23.3°C	CECOMAF -25°C
					kcal/h	W	W/W	W/W	W/W	W/W
▶ <input type="checkbox"/> <a href="#">GL45AA</a>	LBP::R134a	1/8	43	A	96	82	1.06	0.82		
▶ <input type="checkbox"/> <a href="#">GL45AN</a>	LBP::R134a	1/8	50	C	96	81	1.05	0.8		
▶ <input type="checkbox"/> <a href="#">GL60AA</a>	LBP::R134a	1/6	43	A	132	114	1.14	0.89		
▶ <input type="checkbox"/> <a href="#">GL60AF</a>	LBP::R134a	1/6	43	D	132	113	1.07	0.82		
▶ <input type="checkbox"/> <a href="#">GL60AH</a>	LBP::R134a	1/6	43	A	133	114	1.31	1.01		
▶ <input type="checkbox"/> <a href="#">GL60AN</a>	LBP::R134a	1/6	50	C	132	114	1.07	0.83		
▶ <input type="checkbox"/> <a href="#">GL70AA</a>	LBP::R134a	1/5	43	A	149	128	1.18	0.92		
▶ <input type="checkbox"/> <a href="#">GL70AN</a>	LBP::R134a	1/5	50	D	150	129	1.08	0.83		
▶ <input type="checkbox"/> <a href="#">GL70AT</a>	LBP::R134a	1/5	43	E	144	122	1.09	0.84		
▶ <input type="checkbox"/> <a href="#">GL75AA</a>	LBP::R134a	1/5	43	A	155	133	1.18	0.92		
▶ <input type="checkbox"/> <a href="#">GL80AA</a>	LBP::R134a	1/5	43	A	173	148	1.19	0.93		
▶ <input type="checkbox"/> <a href="#">GL80AF</a>	LBP::R134a	1/5	43	D	166	141	1.14	0.88		
▶ <input type="checkbox"/> <a href="#">GL80AH</a>	LBP::R134a	1/5	43	A	175	150	1.35	1.06		
▶ <input type="checkbox"/> <a href="#">GL80AN</a>	LBP::R134a	1/4	43	A	196	168	1.36	1.06		
▶ <input type="checkbox"/> <a href="#">GL90AA</a>	LBP::R134a	1/4	43	A	195	167	1.19	0.93		
▶ <input type="checkbox"/> <a href="#">GL90AH</a>	LBP::R134a	1/4	43	A	215	182	1.39	1.08		
▶ <input type="checkbox"/> <a href="#">GL90AN</a>	LBP::R134a	1/4	50	D	190	163	1.1	0.85		
▶ <input type="checkbox"/> <a href="#">GL90AT</a>	LBP::R134a	1/4	43	E	190	161	1.19	0.92		
▶ <input type="checkbox"/> <a href="#">GL99AA</a>	LBP::R134a	1/4	43	A	214	182	1.24	0.96		
▶ <input type="checkbox"/> <a href="#">GL99AH</a>	LBP::R134a	1/4	43	A	215	182	1.39	1.08		
▶ <input type="checkbox"/> <a href="#">GL80AD</a>	LBP::R134a	1/5	43	W	0	0	0	0		
▶ <input type="checkbox"/> <a href="#">GL90AD</a>	LBP::R134a	1/4	43	W	0	0	0	0		

## R12

Model	Refr.	HP	Ambient Temp C	Rated Voltage	Cooling Capacity		COP without RC		COP with RC	
					ASHRAE	CECOMAF	ASHRAE	CECOMAF	ASHRAE	CECOMAF
					-23.3°C kcal/h	-25°C W	-23.3°C W/W	-25°C W/W	-23.3°C W/W	-25°C W/W
<input type="checkbox"/> <a href="#">L45AV</a>	LBP::R12	1/8	43	B	221	192	0.91	0.71		
<input type="checkbox"/> <a href="#">L55AV</a>	LBP::R12	1/6	43	B	115	101	0.99	0.78		
<input type="checkbox"/> <a href="#">L55BV</a>	LBP::R12	1/6	43	B	115	101	0.99	0.78		
<input type="checkbox"/> <a href="#">L76AV</a>	LBP::R12	1/5	43	B	145	127	1.05	0.84		
<input type="checkbox"/> <a href="#">L76BV</a>	LBP::R12	1/5	43	B	145	127	1.05	0.84		
<input type="checkbox"/> <a href="#">L88AV</a>	LBP::R12	1/4	43	B	171	150	1.02	0.81		
<input type="checkbox"/> <a href="#">L88BV</a>	LBP::R12	1/4	43	B	171	150	1.02	0.81		
<input type="checkbox"/> <a href="#">LT45AV</a>	LBP::R12	1/8	50	B	94	83	1.04	0.83		
<input type="checkbox"/> <a href="#">LT55AV</a>	LBP::R12	1/6	50	B	115	102	1.06	0.85		
<input type="checkbox"/> <a href="#">LT55BV</a>	LBP::R12	1/6	50	B	115	102	1.06	0.85		
<input type="checkbox"/> <a href="#">LT76BV</a>	LBP::R12	1/5	50	B	155	137	1.14	0.91		
<input type="checkbox"/> <a href="#">LT88BV</a>	LBP::R12	1/4	50	B	190	169	1.16	0.93		
<input type="checkbox"/> <a href="#">P12BW</a>	LBP::R12	1/3	43	A	221	192	0.91	0.71		

Private Picture Copyright: [WWW.MBSM.PRO](http://WWW.MBSM.PRO)

Mbsm\_dot\_pro\_private\_PDF\_catalogo\_cubigel\_R134aTélécharger

## R600a

Model	Refr.	HP	Ambient Temp C	Rated Voltage	Cooling Capacity		COP without RC		COP with RC	
					ASHRAE	CECOMAF	ASHRAE	CECOMAF	ASHRAE	CECOMAF
					-23.3°C kcal/h	-25°C W	-23.3°C W/W	-25°C W/W	-23.3°C W/W	-25°C W/W
<input type="checkbox"/> <a href="#">HL80AH</a>	LBP::R600a	1/7	43	A	104	89	1.37	1.06		
<input type="checkbox"/> <a href="#">HL90AH</a>	LBP::R600a	1/7	43	A	115	99	1.38	1.08		
<input type="checkbox"/> <a href="#">HL99AH</a>	LBP::R600a	1/6	43	A	120	103	1.34	1.03		

Private Picture Copyright: [WWW.MBSM.PRO](http://WWW.MBSM.PRO)

Model	Refr.	HP	Ambient Temp C	Rated Voltage	Cooling Capacity		COP <sub>a</sub> 7.2 <sub>a</sub>
					CECOMAF 5°C W	ASHRAE 7.2°C kcal/h	
					<input type="checkbox"/> <a href="#">GL45PB</a>	HMBP::R134a	
<input type="checkbox"/> <a href="#">GL45PB</a>	HMBP::R134a	1/6	0	300			
<input type="checkbox"/> <a href="#">GL45TB</a>	HMBP::R134a	1/6	43	A			
<input type="checkbox"/> <a href="#">GL60PB</a>	HMBP::R134a	1/5	43	A			
<input type="checkbox"/> <a href="#">GL60TB</a>	HMBP::R134a	1/5	43	A			
<input type="checkbox"/> <a href="#">GL80PB</a>	HMBP::R134a	1/5	43	A			
<input type="checkbox"/> <a href="#">GL80TB</a>	HMBP::R134a	F	0	300			
<input type="checkbox"/> <a href="#">GL90TB</a>	HMBP::R134a	1/4	43	A			
<input type="checkbox"/> <a href="#">GP12TB</a>	HMBP::R134a	3/8	43	A			

Private Picture Copyright: [WWW.MBSM.PRO](http://WWW.MBSM.PRO)

## ALL COMPRESSOR HERMÉTIC EMBRACO IN ONE FILE

Category: compressor

written by [www.mbsm.pro](http://www.mbsm.pro) | 8 April 2021

### COMPRESORES R404A/ R452A BAJA TEMPERATURA. MONOFÁSICAS 220V

MODELO	CM3	EXP	C.V	INT (A)	REFR COMP	MOTOR	TEMP. DE EVAPORACIÓN			PRECIO
							-10°C	-25°C	-30°C	
EMT2117GK	4,50	C	1/4	1,15	F	CSIR	408	210	164	143,00
EMT2121GK	5,20	C	1/3	1,33	F	CSIR	487	258	204	146,00
EMT2125GK	5,96	C-V	1/3	1,57	F	CSIR	562	301	238	158,00
EMT2130GK	6,76	C-V	1/2	1,70	F	CSIR	605	326	257	165,00
NEU2140GK	8,78	C-V	1/2	2,63	F	CSIR	801	421	326	182,00
NEU2155GK	12,11	C-V	3/4	3,79	F	CSIR	1067	557	432	201,00
NEU2168GJ	14,28	C-V	3/4	3,48	F	CSIR	1213	642	496	240,00
NEU2178GK	16,80	C-V	1	4,27	F	CSIR	1416	753	586	287,00
NT2180GK	20,44	C-V	1	3,12	F	CSIR	1573	814	625	330,00
NT2192GK	22,40	C-V	1	4,92	F	CSIR	1693	865	669	365,00
NT2192GK(r)	22,40	C-V	1	4,92	F	CSIR	1693	865	669	345,00
NT2210GK	26,20	C-V	1 1/2	6,43	F	CSIR	2041	1052	804	375,00
NT2210GK(r)	26,20	C-V	1 1/2	6,43	F	CSIR	2041	1052	804	355,00
NT2212GK	27,78	C-V	1 1/2	5,30	F	CSIR	2174	1125	876	380,00
NJ2212GK	34,37	C-V	1 1/2	5,80	F	CSIR	2487	1276	961	419,00
NJ2212GK(r)	34,37	C-V	1 1/2	5,80	F	CSIR	2487	1276	961	394,00



Private Picture Copyright: [WWW.MBSM.PRO](http://WWW.MBSM.PRO)

EMT22HLP 3,00 C 1/12 0,44 S RSIR 151 69 50 98,00  
 EMT36HLP 3,97 C 1/10 0,56 S RSIR 203 94 71 102,00  
 EMY3111Z 4,85 C 1/8 0,71 S RSIR 247 117 86 105,00  
 EMT49HLP 5,56 C 1/6 0,76 S RSIR 274 131 98 111,00  
 EMY3115Z 6,76 C 1/6 0,99 S RSIR 341 158 117 112,00  
 NEK1116Z 7,37 C 1/5 0,60 S RSIR 367 172 126 129,00  
 NEK1118Z 8,39 C 1/4 0,74 S RSIR 417 195 144 133,00  
 NE2121Z 9,26 C/V 1/4 1,41 F CSIR 465 217 163 172,00  
 NE2130Z 12,11 C/V 1/3 2,07 F CSIR 613 298 227 186,00  
 NE2134Z 14,28 C/V 1/3 2,30 F CSIR 662 313 234 190,00  
 NEK2140Z 16,80 C/V 1/2 2,35 F CSIR 801 377 284 207,00  
 MODELO CM3 EXP C.V INT

(A)

REFR

COMP MOTOR TEMP. DE EVAPORACIÓN PRECIO +5°C 0°C -5°C -10°C

EMT37HDP 3,40 C 1/8 0,85 S RSIR 343 245 228 181 113,00  
 EMT45HDR 3,97 C 1/8 0,95 S CSIR 402 284 229 184 121,00  
 EMT50HDP 4,50 C 1/6 1,05 S RSIR 456 374 303 242 120,00  
 EMT6144Z 5,20 C/V 1/5 1,38 F RSIR 549 395 367 294 123,00  
 EMT6160Z 6,76 C/V 1/4 1,74 F RSIR 696 504 469 377 127,00  
 EMT6170Z 7,69 C/V 1/4 2,03 F RSIR 771 559 522 418 134,00  
 NEU6187Z 10,00 C/V 1/3 2,61 F RSIR 918 654 600 477 151,00  
 NEU6210Z 12,12 C/V 1/3 3,15 F RSIR 1170 955 770 615 163,00  
 NEU6212Z 14,30 C/V 1/2 3,90 F RSIR 1365 1114 894 707 174,00  
 NEU6214Z 16,80 C/V 1/2 4,21 F RSIR 1569 1292 1047 836 199,00  
 NT6217Z 20,44 C/V 3/4 4,73 F RSIR 1795 1256 1173 938 292,00  
 NT6220Z 22,37 C/V 3/4 5,24 F RSIR 1897 1554 1260 1010 323,00  
 NJ6220Z 26,11 C/V 3/4 5,71 F RSIR 2202 1780 1419 1104 386,00  
 NJ6220Z ( ) 26,11 C/V 3/4 5,71 F RSIR 2202 1780 1419 1104 379,00 NJ6226Z 34,38  
 C/V 1 5,95 F CSR 2852 2340 1892 1497 439,00 NJ6226Z ( ) 34,38 C/V 1 5,95 F CSR  
 2852 2340 1892 1497 410,00

COMPRESORES R404A/ R452A BAJA TEMPERATURA. MONOFÁSICAS 220V

MODELO	CM3	EXP	C.V	INT (A)	REFR COMP	MOTOR	TEMP. DE EVAPORACIÓN			PRECIO
							-10°C	-25°C	-30°C	
EMT2117GK	4,50	C	1/4	1,15	F	CSIR	408	210	164	143,00
EMT2121GK	5,20	C	1/3	1,33	F	CSIR	487	258	204	146,00
EMT2125GK	5,96	C-V	1/3	1,57	F	CSIR	562	301	238	158,00
EMT2130GK	6,76	C-V	1/2	1,70	F	CSIR	605	326	257	165,00
NEU2140GK	8,78	C-V	1/2	2,63	F	CSIR	801	421	326	182,00
NEU2155GK	12,11	C-V	3/4	3,79	F	CSIR	1067	557	432	201,00
NEU2168GJ	14,28	C-V	3/4	3,48	F	CSIR	1213	642	496	240,00
NEU2178GK	16,80	C-V	1	4,27	F	CSIR	1416	753	586	287,00
NT2180GK	20,44	C-V	1	3,12	F	CSIR	1573	814	625	330,00
NT2192GK	22,40	C-V	1	4,92	F	CSIR	1693	865	669	365,00
NT2192GK(*)	22,40	C-V	1	4,92	F	CSIR	1693	865	669	345,00
NT2210GK	26,20	C-V	1 1/2	6,43	F	CSIR	2041	1052	804	375,00
NT2210GK(*)	26,20	C-V	1 1/2	6,43	F	CSIR	2041	1052	804	355,00
NT2212GK	27,78	C-V	1 1/2	5,30	F	CSIR	2174	1125	876	380,00
NJ2212GK	34,37	C-V	1 1/2	5,80	F	CSIR	2487	1276	961	419,00
NJ2212GK(*)	34,37	C-V	1 1/2	5,80	F	CSIR	2487	1276	961	394,00



Private Picture Copyright: WWW.MBSM.PRO

Mbsm\_dot\_pro\_private\_PDF8compresores\_hermeticos\_embraco\_2019Télécharger

Refrigerator, compressor, E1134CZA, 1/2 hp, E1130CZA, E1121CZA, 3/8HP, commercial, freezer, R134a

Category: compressor

written by www.mbsm.pro | 8 April 2021

 **E1121CZA**   
220-240V-50Hz 1PH  
THERMALLY PROTECTED

RoHS   SUCTION → 2  
<http://www.dongper.com> A000583 R134a

  
D123810213206602016

Refrigerator, compressor, E1134CZA, E1130CZA, E1121CZA, 3/8HP, commercial, freezer, R134a

## COMPRESSOR, MX21TBa, R404A, 1HP, CUBIGEL, HMBP, 220/240V, 50Hz, 20,72 cm<sup>3</sup>

Category: compressor

written by [www.mbsm.pro](http://www.mbsm.pro) | 8 April 2021



Private Picture Copyright : [WWW.MBSM.PRO](http://WWW.MBSM.PRO)

### *Détails techniques*

220/240V 50Hz

puissance 1 HP – cylindrée 21,75 cc

gaz R404a/R507 HMBP

...et d'autres dispositifs

MX21TB – ACC – CELLI

MX21TB – CUBIGEL – ELECTROLUX

605093 – GEV – ITV



Private Picture Copyright: [WWW.MBSM.PRO](http://WWW.MBSM.PRO)

Mbsm\_dot\_pro\_private\_PDF\_danfoss\_MX21TBa\_R404A\_220\_50Télécharger

<b>Brand:</b>	Cubigel
<b>UPC:</b>	3070063
<b>Manufacturer reference:</b>	MX21TBa
<b>Application:</b>	HMBP
<b>Power supply:</b>	220/240V 50Hz
<b>Cooling capacity:</b>	3047 W
<b>Horsepower:</b>	1 Hp
<b>Displacement:</b>	21.7 cm <sup>3</sup>
<b>Refrigerant:</b>	R404a/R507
<b>Weight:</b>	17.5 kg
<b>Motor type:</b>	CSR
<b>Type:</b>	Hermetic reciprocating compressor

---

## MBSM.PRO, All Compressor in One File , Pdf and Print

Category: compressor

written by [www.mbsm.pro](http://www.mbsm.pro) | 8 April 2021



Private Picture Copyright : WWW.MBSM.PRO

MBSM.PRO, All Compressor in One File , Pdf and Print

RÉFRIGÉRATEUR NIKAI, nrf480fn4, 165W,  
Compressor, ATD60L, Wanbao Huaguang  
Refrigerator, 1/5Hp, R134A, 120G,  
1.25A, 220V/50HZ

Category: compressor

written by www.mbsm.pro | 8 April 2021

# NIKAI®

## REFRIGERATOR MODEL: NRF480FN4


Rated Voltage	220-240V~
Rated Frequency	50Hz
Rated Current	1.25A
Rated Input Power	165W
Defrosting Power	150W
Electricity Consumption	1.385kw.h/24h
Climate Classification	T
Classification of Protection Against Electric Shock	Class I
Lamp Power	≤15W
Foaming Agent	CsH <sub>14</sub> (CP)
Refrigerant and Inject Amount	R134a/120g
Freeze Capacity	5.0kg/24h
Weight	65kg

MADE IN CHINA

صنع في الصين

CB

### ELECTRIC DIAGRAM



NIKAI GULF FZCO

PO BOX 9200 DUBAI UAE

نيكاي جلف فزكو

مستودع بريد 9200 دبي دولة الإمارات العربية المتحدة



REDMI NOTE 8 PRO  
AI QUAD CAMERA



480FN487170700

Private Picture Copyright : [WWW.MBSM.PRO](http://WWW.MBSM.PRO)

RÉFRIGÉRATEUR NIKAI, nrf480fn4, 165W, Compressor, ATD60L, Wanbao Huagang Refrigerator, 1/6Hp, R134A, 120G, 1.25A, 220V/50HZ