

**Mbsm.pro, compressor,  
Panasonic, 1/3 hp, Lbp, E  
Series, R134a, ETI57C13DCH,  
ENI68C13DCH, Reciprocating,  
Compressors, Variable Speed,  
inverter, BLCD, from 63 to  
240 w, 240v+-, from 60 to 268  
hz, from 25 rps to 72 rps**

written by Jamila | 28 November 2022



Private Picture Copyright : [WWW.MBSM.PRO](http://WWW.MBSM.PRO)

Mbsm.pro, compressor, Panasonic, Lbp, E Series, R134a,

ETI57C13DCH, ENI68C13DCH, Reciprocating, Compressors, Variable Speed, inverter, from 63 to 240 w, 240v+-, from 60 to 268 hz, from 25 rps to 72 rps

---

**Mbsm.pro, Compressor, GL60AA,  
GL60AB, GL50AA, GL50AB,  
AZ107Y, AZ90, YGVM44AA,  
GLY45AA, GLY45AA, TLS5F, 1/6  
hp, 1bp**

written by Jamila | 28 November 2022



Private Picture Copyright : [WWW.MBSM.PRO](http://WWW.MBSM.PRO)

Mbsm.pro, Compressor, GL60AA, GL60AB, GL50AA, GL50AB, AZ107Y, AZ90Y, GVM44AA, GLY45AA, 1/6 hp, 1bp

---

**Mbsm.pro, Compressor,  
Eateron, E100HL, R-134,  
23.3C, 280W, HUAYI, LBP**

written by Jamila | 28 November 2022



Private Picture Copyright : [WWW.MBSM.PRO](http://WWW.MBSM.PRO)

Mbsm.pro, Compressor, Eateron, E100HL, R-134, 23.3C, 280W, HUAYI, LBP

---

**Mbsm.pro, Dongbei compressor,  
aluminum wire, R600a, R134a,  
S65CY1, S75CY1, S80CY1,  
S96CY1, H170CY1, L118CY1,  
L126CY1, L140CY1, K270CY1,  
D40CY1, D53CY1, D65CY1,  
A80CY1, A100CY1, A120CY**

written by mahdi miled | 28 November 2022





Mbsm.pro, Dongbei compressor, aluminum wire, R600a, R134a, S65CY1, S75CY1, S80CY1, S96CY1, H170CY1, L118CY1, L126CY1, L140CY1, K270CY1, D40CY1, D53CY1, D65CY1, A80CY1, A100CY1, A120CY

---

# Mbsm.pro, compressor, Highly, hitachi, rotary, SHX33 , 2 hp, 17750 btu, R22

written by Jamila | 28 November 2022



Private Picture Copyright : [WWW.MBSM.PRO](http://WWW.MBSM.PRO)

Mbsm.pro, compressor, Highly, hitachi, rotary, SHX33 , 2 hp, 17750 btu, R22

# Mbsm.pro, Danfoss, Reciprocating, compressor, NLX11KK.2, 105H6971, NLX11KK.2 105H6971, 1/4 hp++, 1/3 hp-, r600a

written by mahdi miled | 28 November 2022

			-35	-30	-20	-15	-10	-5	0	5	[W]	[W/W]	[W/W]	[W]	[kcal/h]	[W/W]	[kcal/Wh]
Energy-optimized	1.	PLE35K	101H0360		38	52	68	87	109		27		0.68	38	33		
		TLES4KK.3	102H4438	19	29	57	75	96			42	0.90		57	49	1.18	
		TLES4.8KK.3	102H4538	28	40	73	94	119			55	1.00		74	65	1.30	
		TLES5.7KK.3	102H4638	36	50	89	114	144			68	1.02		91	79	1.32	
		TLES6.5KK.3	102H4738	45	61	105	134	168			81	1.02		108	94	1.31	
		TLES7.5KK.3	102H4838	53	71	122	155	194			94	1.02	1.07	126	108	1.32	1.14
		TLES8.7KK.3	102H4938	62	83	143	181	228			110	1.03	1.08	147	126	1.33	1.14
		TLES10KK.3	102H4038								130	1.04		172	148	1.35	1.15
		NLE8.8KK.4	105H6800	63	84	141	179	223			110	1.18	1.22	147	127	1.51	1.30
		NLE10KK.4	105H6867	74	98	164	207	257			128	1.19	1.23	170	151	1.51	1.30
High Energy-optimized	4.	NLE11KK.4	105H6952	82	109	184	232	290			143	1.19	1.22	191	165	1.52	1.31
		NLE13KK.4	105H6959	99	131	217	274	340			170	1.18	1.23	226	194	1.50	1.29
		NLE15KK.4	105H6968	110	146	243	307	382			190	1.20	1.25	253	213	1.53	1.32
		TLY4 KK.3	102H4442	19	29	57	74	95			42	0.96	0.99	57	49	1.26	1.08
		TLY4.8KK.3	102H4542	28	40	73	94	119			55	1.04	1.06	74	65	1.35	1.16
		TLY5.7KK.3	102H4642	36	51	89	114	144			68	1.03	1.06	91	79	1.33	1.15
		TLY6.5KK.3	102H4742	46	62	106	135	170			82	1.10	1.14	110	94	1.42	1.22
		TLY7.5KK.3	102H4842	53	71	122	155	194			94	1.09	1.14	126	108	1.41	1.22
		TLY8.7KK.3	102H4942	65	86	144	182	227			112	1.12	1.16	149	126	1.44	1.24
		TLX4KK.3	102H4447	21	32	59	76	95			45		1.15***	60	52		
High Energy-optimized	3.	TLX4.8KK.3	102H4547	36	52	90	116	146			57		1.24***	76	65		
		TLX5.7KK.3	102H4647	37	52	91	115	143			70		1.28***	93	80		
		TLX6.5KK.3	102H4747	46	63	106	133	165			83		1.30***	110	95		
		TLX7.5KK.3	102H4847	55	75	125	157	195			98		1.32***	130	112		
		TLX8.7KK.3	102H4947	65	88	146	184	227			115		1.31***	152	131		
		NLX8.8KK	105H6874	60	83	144	182	227			111		1.35	148	127		
		NLX10KK	105H6871	74	100	169	215	269			131		1.36	174	150		
		NLX11KK	105H6984	84	112	189	240	300			147		1.36	195	168		
		NLX13KK	105H6983	98	133	223	282	350			174		1.36	231	199		
		NLX15KK	105H6981	110	147	249	317	397			193		1.34	257	221		
High Energy-optimized	2.	NLX8.0KK.2	105H6010	52	73	130	167	210			99		1.47***	133	115		
		NLX8.8KK.2	105H6011	62	85	147	187	234			113		1.49***	151	130		
		NLX10KK.2	105H6101	75	101	171	217	271			133		1.49***	178	153		
		NLX11KK.2	105H6971	86	115	192	242	301			150		1.49***	200	172		

Private Picture Copyright : WWW.MBSM.PRO

Description

## Product details

Gross weight	12.47 kg
--------------	----------



<b>Net weight</b>	12.47 kg
<b>Gross weight</b>	12.47 kg
<b>Net weight</b>	12.47 kg

<b>Application energy level</b>	High Energy-optimized
<b>Applications</b>	LBP
<b>Auxiliary winding resistance (start winding) for single-phase compressors alt [0hm]</b>	31.8 0hm
<b>Base plate type</b>	EU small
<b>Brand technique</b>	Reciprocating compressor
<b>Capacity control</b>	Fixed speed
<b>Colour</b>	Black
<b>Compressor power supply [V/Ph/Hz]</b>	220-240/1/50
<b>Configuration code</b>	Single
<b>Cut in current LST [A]</b>	6.4 A
<b>Description</b>	NLX11KK.2
<b>Discharge connection angle [Â°]</b>	21 Â°
<b>Discharge connection comments</b>	Al-cap
<b>Discharge connection diameter [mm]</b>	5 mm
<b>Discharge connection material</b>	Cu-plated steel
<b>Economizer</b>	No
<b>Free gas volume [cm3]</b>	2360 cm3
<b>Frequency [Hz]</b>	50
<b>Height from baseplate [mm]</b>	197 mm
<b>High value of nominal voltage at 50Hz [V]</b>	240 V
<b>High value of voltage range at 50Hz [V]</b>	255 V

<b>Length [mm]</b>	252 mm
<b>Liquid injection</b>	No
<b>Low value of nominal voltage at 50Hz [V]</b>	220 V
<b>Low value of voltage range at 50Hz [V]</b>	187 V
<b>LRA LST [A]</b>	3.5 A
<b>Main winding resistance for single-phase compressors [0hm]</b>	18.5 0hm
<b>Model number</b>	NLX11KK.2
<b>Motor type</b>	RSCR
<b>No. of phases (compressor)</b>	1
<b>Oil quantity [cm3]</b>	270 cm3
<b>Oil type</b>	P0E
<b>Packing format</b>	Industrial pack
<b>Packing quantity</b>	80
<b>Process connection angle [°]</b>	25 °
<b>Process connection comments</b>	Al-cap
<b>Process connection diameter [mm]</b>	6.2 mm
<b>Process connection material</b>	Cu-plated steel
<b>Refrigerant</b>	R600a
<b>Refrigerant charge [kg] [Max]</b>	0.15 kg
<b>RLA</b>	0.70 A
<b>Rotational speed at 50Hz [rpm]</b>	3000 rpm
<b>Run capacitor capacitance</b>	2 µF
<b>Segment usage</b>	Refrigeration LT
<b>Speed Platform</b>	Fixed-speed
<b>Suction connection angle [°]</b>	2 °
<b>Suction connection comments</b>	Al-cap
<b>Suction connection diameter [mm]</b>	6.2 mm


<b>Suction connection material</b>	Cu-plated steel
<b>Swept volume [cm3]</b>	11.15 cm3
<b>Technology</b>	Reciprocating
<b>Total height [mm]</b>	203 mm
<b>Type</b>	NL
<b>Type designation</b>	Compressor
<b>Voltage 50Hz [V]</b>	220 V
<b>Voltage 50Hz [V] [Max]</b>	240 V
<b>Width [mm]</b>	166 mm
<b>Winding temperature short term [Â°C] [Max]</b>	110 Â°C
<b>Winding temperature stat [Â°C] [Max]</b>	95 Â°C
<b>Application energy level</b>	High Energy-optimized
<b>Applications</b>	LBP
<b>Auxiliary winding resistance (start winding) for single-phase compressors alt [0hm]</b>	31.8 0hm
<b>Base plate type</b>	EU small
<b>Brand technique</b>	Reciprocating compressor
<b>Capacity control</b>	Fixed speed
<b>Colour</b>	Black
<b>Compressor power supply [V/Ph/Hz]</b>	220-240/1/50
<b>Configuration code</b>	Single
<b>Cut in current LST [A]</b>	6.4 A
<b>Description</b>	NLX11KK.2
<b>Discharge connection angle [Â°]</b>	21 Â°
<b>Discharge connection comments</b>	Al-cap
<b>Discharge connection diameter [mm]</b>	5 mm
<b>Discharge connection material</b>	Cu-plated steel
<b>Economizer</b>	No

<b>Free gas volume [cm3]</b>	2360 cm3
<b>Frequency [Hz]</b>	50
<b>Height from baseplate [mm]</b>	197 mm
<b>High value of nominal voltage at 50Hz [V]</b>	240 V
<b>High value of voltage range at 50Hz [V]</b>	255 V
<b>Length [mm]</b>	252 mm
<b>Liquid injection</b>	No
<b>Low value of nominal voltage at 50Hz [V]</b>	220 V
<b>Low value of voltage range at 50Hz [V]</b>	187 V
<b>LRA LST [A]</b>	3.5 A
<b>Main winding resistance for single-phase compressors [0hm]</b>	18.5 0hm
<b>Model number</b>	NLX11KK.2
<b>Motor type</b>	RSCR
<b>No. of phases (compressor)</b>	1
<b>Oil quantity [cm3]</b>	270 cm3
<b>Oil type</b>	P0E
<b>Packing format</b>	Industrial pack
<b>Packing quantity</b>	80
<b>Process connection angle [Â°]</b>	25 Â°
<b>Process connection comments</b>	Al-cap
<b>Process connection diameter [mm]</b>	6.2 mm
<b>Process connection material</b>	Cu-plated steel
<b>Refrigerant</b>	R600a
<b>Refrigerant charge [kg] [Max]</b>	0.15 kg
<b>RLA</b>	0.70 A

<b>Rotational speed at 50Hz [rpm]</b>	3000 rpm
<b>Run capacitor capacitance</b>	2 µF
<b>Segment usage</b>	Refrigeration LT
<b>Speed Platform</b>	Fixed-speed
<b>Suction connection angle [°]</b>	2 °
<b>Suction connection comments</b>	Al-cap
<b>Suction connection diameter [mm]</b>	6.2 mm
<b>Suction connection material</b>	Cu-plated steel
<b>Swept volume [cm<sup>3</sup>]</b>	11.15 cm <sup>3</sup>
<b>Technology</b>	Reciprocating
<b>Total height [mm]</b>	203 mm
<b>Type</b>	NL
<b>Type designation</b>	Compressor
<b>Voltage 50Hz [V]</b>	220 V
<b>Voltage 50Hz [V] [Max]</b>	240 V
<b>Width [mm]</b>	166 mm
<b>Winding temperature short term [°C] [Max]</b>	110 °C
<b>Winding temperature stat [°C] [Max]</b>	95 °C

Refrigerant: R600a, Segment usage: Refrigeration LT,  
Compressor power supply [V/Ph/Hz]:  
220 - 240/1/50Mbsm\_dot\_pro\_private\_PDF\_nlx11kk.2





			-35	-30	-20	-10	-5	0	5	(W)	(W/W)	(W/W)	(W)	(kcal/h)	(W/W)	(kcal/h)
Energy optimized	A	TL25K	102H0360			36	52	68	87	109		27	0.68	36	33	
		TL25K0K.3	102H0430	19	29	57	75	96			42	0.90		57	49	1.18
		TL25K0K.3	102H0430	28	40	72	94	119			55	1.00		74	65	1.30
		TL25K70K.3	102H0430	56	50	89	114	144			68	1.02		91	79	1.52
		TL25K0K.3	102H0730	45	61	105	134	168			81	1.02		106	94	1.51
		TL25K70K.3	102H0730	53	71	122	155	194			94	1.02	1.07	126	108	1.52
		TL25K70K.3	102H0930	62	83	143	181	228			110	1.03	1.08	147	126	1.53
		TL25K0K.3	102H0930								130	1.04		172	148	1.55
		TL25K0K.4	102H0805	63	84	145	179	223			110	1.18	1.22	147	127	1.55
		TL25K0K.4	102H0807	74	98	164	207	257			128	1.19	1.23	170	151	1.55
High Energy optimized	A	TL25K0K.4	102H0952	82	109	184	232	290			143	1.19	1.22	191	165	1.52
		TL25K0K.4	102H0959	99	137	217	274	340			170	1.18	1.23	226	194	1.50
		TL25K0K.4	102H0968	110	146	243	307	382			190	1.20	1.25	253	215	1.53
		TL24K0K.3	102H0442	19	29	57	74	95			42	0.96	0.99	57	49	1.08
		TL24K0K.3	102H0542	28	40	72	94	119			55	1.04	1.06	74	65	1.35
		TL24K0K.3	102H0642	56	51	89	114	144			68	1.03	1.06	91	79	1.55
		TL24K0K.3	102H0742	46	62	106	135	170			82	1.10	1.14	110	94	1.42
		TL24K0K.3	102H0842	53	71	122	155	194			94	1.09	1.14	126	108	1.41
		TL24K0K.3	102H0942	65	86	144	182	227			112	1.12	1.16	149	126	1.44
		TL24K0K.3	102H0447	21	32	59	76	95			45	1.15***		60	52	
High Energy optimized	A	TL24K0K.3	102H0547	36	52	90	116	146			57	1.24***		76	65	
		TL24K0K.3	102H0647	37	52	91	115	143			70	1.28***		93	80	
		TL24K0K.3	102H0747	46	63	106	133	165			83	1.30***		110	95	
		TL24K0K.3	102H0847	55	75	125	157	195			98	1.32***		130	112	
		TL24K0K.3	102H0947	65	88	146	186	227			113	1.31***		152	131	
		TL23K0K	102H0674	60	83	144	182	227			111	1.35		148	127	
		TL23K0K	102H0671	74	100	169	215	269			131	1.36		174	150	
		TL2110K	102H0984	84	112	189	240	300			147	1.36		195	168	
		TL2110K	102H0985	98	133	223	282	350			174	1.36		231	199	
		TL2110K	102H0981	110	147	249	317	387			193	1.34		257	221	
High Energy optimized	A	TL23K0K.2	102H0710	52	73	130	167	210			99	1.40***		133	115	
		TL23K0K.2	102H0711	62	85	147	187	234			113	1.40***		151	130	
		TL23K0K.2	102H0710	75	101	171	217	271			133	1.40***		176	153	
		TL2110K.2	102H0971	88	115	192	242	301			150	1.40***		200	172	

Private Picture Copyright : [WWW.MBSM.PRO](http://WWW.MBSM.PRO)

Mbsm.pro, compressor,  
PW3.5VK, DFV4.0HF, DFV4.5HF,  
DFV5.5HF, DFV6.5HF, DFV6.5HF,  
DFV7.5HF,

written by mahdi miled | 28 November 2022



Private Picture Copyright : [WWW.MBSM.PRO](http://WWW.MBSM.PRO)

Mbsm.pro, compressor, PW3.5VK, DFV4.0HF, DFV4.5HF, DFV5.5HF, DFV6.5HF, DFV6.5HF, DFV7.5HF,

---

**Mbsm.pro, Compressor, nf10fx,  
Danfoss, 1/3 hp, LBP, MBP,  
1046 btu, 115 v**

written by Jamila | 28 November 2022



Mbsm.pro, Compressor, nf10fx, Danfoss, 1/3 hp, LBP, MBP, 1046  
btu, 115 v