

Mbsm.pro, compressor, Embraco, Aspera, 1/3 hp++, 1/2 hp–, emt2130GK

Category: compressor

written by www.mbsm.pro | 25 March 2023



Private Picture Copyright : WWW.MBSM.PRO

- Compresseur Embraco Aspera EMT2130GK, LBP – R404A, R507, 220 – 240V/1/50Hz, 1/2- HP, refoulement 6,76 cm³, moteur type CSIR, lubrifiant type POE 22, charge lubrifiant 180 ml , LRA 12,4 A, 380 W à -23,3 / +54,4 °C, refroidissement : refroidissement par ventilateur, débit d'air 520 m³/h, dispositif d'expansion : capillaire a ventilem, poids 8 kg
- Alimentation 220-240 V
- Frequency 50/60 Hz
- Displacement 6.74 cm³
- Power 1/3 HP
- Height 190 mm
- Weight 7.8kg
- Area of use LBP
- Gas R290
- CSIR engine system
- Complete with starter, capacitor, box without fixing system

• Technical characteristics



Private Picture Copyright : WWW.MBSM.PRO

EMT2117GK	Compressore Embraco LBP	1/4	4,50	R404A	220	EMBRACO
EMT2117U	Compressore Embraco LBP	1/5	3,97	R290	220	EMBRACO
EMT2121GK	Compressore Embraco LBP	1/3	5,19	R404A	220	EMBRACO
EMT2121U	Compressore Embraco LBP	1/4	5,57	R290	220	EMBRACO
EMT2125GK	Compressore Embraco LBP	1/3	5,96	R404A	220	EMBRACO
EMT2125U	Compressore Embraco LBP	1/3	5,96	R290	220	EMBRACO
EMT2130U	Compressore Embraco LBP	1/3	6,76	R290	220	EMBRACO
EMT22HLP	Compressore Embraco LBP	1/12	3	R134A	220	EMBRACO
EMT36HLP	Compressore Embraco LBP	1/8	3,97	R134A	220	EMBRACO
EMT37HDP	Compressore Aspera MBP/HP	1/10	3,30	R134A	220	ASPERA
EMT43HLP	Compressore Embraco LBP	1/6	4,85	R134A	220	EMBRACO
EMT45HDP	Compressore Aspera MBP/HP	1/8	3,77	R134A	220	ASPERA
EMT49HLP	Compressore Aspera LBP	1/6	6,84	R134A	220	ASPERA
EMT50HDP	Compressore Aspera MBP/HP	1/6	4,99	R134A	220	ASPERA
EMT60HLP	Compressore Aspera LBP	1/5	7,87	R134A	220	ASPERA

Private Picture Copyright : WWW.MBSM.PRO

BRAND	EMBRACO
COMPRESSOR TYPE	ALTERNATIVE HERMETIC
APPLICATION	PSL (-23.3°C / +54.4°C)
H. POWER	1/2-
POWER SOURCE	220-240V
REFRIGERANT	R404A
FREQUENCY (HZ)	50
SHIFT:	6.76CM3
COMPRESSOR COOLING:	FAN
TYPE OF TECHNOLOGY:	ON OFF
EXPANSION DEVICE:	CAPILLARY TUBE OR REGULATOR
PACKING QUANTITY:	100
MARRY:	22,5 MM
STROKE:	17 MILLIMETERS
OIL CHARGE:	180 ML
OIL TYPE SETUP:	ESTER
VISCOSITY OF OIL TYPE:	ISO22

READING:

8 KG

FOR ADVICE