



Mbsm.pro, Original, Huaguang,
refrigerator, compressor, ETA95,
EHK95, EHT95, EKA95, ETY95, EHB95,
r600a, lbp, 1/5 hp

Category: compressor


written by www.mbsm.pro | 19 November 2023

BT4730EAK

 **HUAGUANG** [®]

  **THERMALLY PROTECTED**

A068962
Wanbao Group Compressor Co., Ltd.

   **R600a**

Caution: risk of fire



RoHS

SUCTION

2169 572



型号 Model	气缸容积 Displacement cm ³	冷却方式 Cooling	电机类型 Motor Type	制冷量 Cooling Capacity			
				ASHRAE		CECOMAF	ASH
				-23.3℃		-25℃	-23.
				W	Btu	W	W/W

LBP

220-240V 50HZ R600a

T系列 T Series

ETK80	8.1	ST	RSCR	138	471	103.2	1.55
ETK95	9.6	ST	RSCR	165	563	123.4	1.55
ETY72	7.2	ST	RSCR	125	427	93.7	1.6
ETY80	8.1	ST	RSCR	140	471	103.3	1.65
ETY95	9.6	ST	RSCR	165	563	123.5	1.60
ETZ55	5.6	ST	RSCR	96	328	72.0	1.74
ETZ60	6.0	ST	RSCR	102	348	77.3	1.68
ETZ66	6.6	ST	RSCR	110	375	83.3	1.68
ETZ72	7.2	ST	RSCR	125	427	94.7	1.70
ETZ80	8.1	ST	RSCR	138	471	104.0	1.70
ETZ86	8.6	ST	RSCR	150	512	113.5	1.70
ETZ95	9.6	ST	RSCR	165	563	124.0	1.70
ETZ110	10.7	ST	RSCR	185	631	139.1	1.70
ETZ120	12.0	ST	RSCR	210	717	157.5	1.70
ETH50	5.1	ST	RSCR	82	280	62.1	1.76
ETH55	5.6	ST	RSCR	96	328	72.2	1.76
ETH60	6.0	ST	RSCR	102	348	77.1	1.76
ETH66	6.6	ST	RSCR	110	375	83.1	1.76

Private Picture Copyright : WWW.MBSM.PRO

R134a Compressors

型号 Model	气缸容积 Displacement cm ³	冷却方式 Cooling	电机类型 Motor Type	制冷量 Cooling Capacity			COP			认证 Certification	最大高度 "A" Max. Height "A"
				ASHRAE		CECOMAF	ASHRAE		CECOMAF		
				-23.3°C		-25°C	-23.3°C		-25°C		
				W	Btu	W	W/W	EER	W/W		
LBP											
220-240V 50HZ R134a											
T 系列 T Series											
ATA72X	7.2	ST/OC	RSIR	205	699	155.3	1.35	4.6	1.05	CCC/CB/VDE	185/188
ATA80X	8.1	ST/OC	RSIR	230	785	174.2	1.35	4.6	1.05	CCC/CB	185/188
ATK72X	7.2	ST/OC	RSCR	205	699	154.0	1.40	4.8	1.09	CCC/CB/VDE/CE	185/188
ATK80X	8.1	ST/OC	RSCR	230	785	174.0	1.40	4.8	1.09	CCC/CB	185/188
▲ ATD50V	5.0	ST	RSIR	140	478	105.2	1.25	4.3	0.98	CCC/CB	182
ATD66X	6.6	ST/OC	RSIR	190	648	142.8	1.25	4.3	0.98	CCC/CB	182
△ ATA50K	5.0	ST	RSIR	144	491	108.9	1.35	4.6	1.05	CCC/CB	182/185
△ ATA66K	6.6	ST	RSIR	190	648	142.8	1.25	4.3	0.98	CCC/CB	182
ATA66K(OC)	6.6	OC	RSIR	190	648	143.7	1.35	4.6	1.05	CCC/CB	188
ATA72K(OC)	7.2	OC	RSIR	205	699	154.0	1.35	4.6	1.05	CCC/CB	188
ATK55	5.5	ST	RSCR	160	546	121.0	1.35	4.6	1.05	CCC/CB	185
ATK60	6.0	ST	RSCR	170	580	128.3	1.51	5.2	1.18	CCC/CB/CE	185
ATK66	6.6	ST	RSCR	192	655	144.0	1.55	5.3	1.21	CCC/CB/CE	185
ATK72	7.2	ST	RSCR	205	699	154.0	1.50	5.1	1.17	CCC/CB	185
ATK80	8.1	ST	RSCR	230	785	174.0	1.50	5.1	1.17	CCC/CB	185
ATZ55	5.5	ST	RSCR	170	580	128.3	1.62	5.5	1.26	CB	185
S 系列 S Series											
ASF43X	4.3	ST	RSCR	117	399	87.7	1.35	4.6	1.05	CCC/CB	162.5
ASF51X	5.1	ST	RSCR	144	491	108.0	1.35	4.6	1.05	CCC/CB	162.5
△ ASD43K	4.3	ST	RSIR	117	399	87.8	1.15	3.9	0.88	CCC/CB/VDE	167
△ ASD53K	5.1	ST	RSIR	144	491	108.1	1.20	4.1	0.94	CCC/CB/VDE	171
△ ASF43K	4.3	ST	RSCR	117	399	87.4	1.40	4.8	1.10	CB	162.5
△ ASF53K	5.1	ST	RSCR	144	491	107.8	1.41	4.8	1.10	CB	171
△ ASF65K	6.5	ST	RSCR	176	601	132.0	1.41	4.8	1.10	CB	171
Y 系列 Y Series											
AYA25X	2.5	ST	RSIR	66	225	49.4	1.10	3.8	0.87	CCC/CB	141
AYA30X	3.0	ST	RSIR	80	273	59.9	1.10	3.8	0.87	VDE	141
N 系列 N Series											
ANA80	8.0	ST/OC	RSIR	235	802	176.0	1.35	4.6	1.06	CCC/VDE	193
ANA90	8.8	ST/OC	RSIR	250	853	187.3	1.35	4.6	1.06	CCC/VDE	193
ANZ80	8.0	ST	RSCR	235	802	176.0	1.62	5.5	1.28	CCC	196
ANZ90	8.8	ST	RSCR	250	853	187.3	1.62	5.5	1.28	CCC	196
△ ANA90K	8.8	F/OC	CSIR	250	853	187.3	1.30	4.4	1.02	CB	196

型号 Model	气缸容积 Displacement	冷却方式 Cooling	电机类型 Motor Type	制冷量 Cooling Capacity				COP				认证 Certification	最大高度 "A" Max. Height "A"
				ASHRAE		AHAM	CECOMAF	ASHRAE		AHAM	CECOMAF		
				-23.3℃		-23.3/ 40.5℃	-25℃	-23.3℃		-23.3/ 40.5℃	-25℃		
	W			Btu	W	W	EER	W/W	W/W				
LBP													
115V 60HZ R600a													
T 系列 T Series													
ETZ50U6	5.0	ST	RSCR	96	328	104.9	71.9	1.70	5.8	2.00	1.33	UL	182
ETZ60U6	6.0	ST	RSCR	120	409	131.1	89.9	1.70	5.8	2.00	1.33	UL	182
ETZ72U6	7.2	ST	RSCR	142	485	154.5	107.3	1.70	5.8	2.00	1.33	UL	182
ETZ80U6	8.0	ST	RSCR	165	563	179.5	124.7	1.70	5.8	2.00	1.33	UL	182
ETB60U6	6.0	ST	RSCR	120	409	130.6	90.7	1.83	6.2	2.16	1.43	UL	185
ETB72U6	7.2	ST	RSCR	145	495	157.8	109.6	1.83	6.2	2.16	1.43	UL	185
ETB80U6	8.1	ST	RSCR	167	570	181.7	126.5	1.83	6.2	2.16	1.43	UL	185
ETB90U6	9.0	ST	RSCR	190	648	206.7	143.9	1.83	6.2	2.16	1.43	UL	185
ETB110U6	10.7	ST	RSCR	220	751	239.4	166.7	1.81	6.1	2.14	1.42	UL	185
S 系列 S Series													
ESD60U6	6.0	ST	RSIR	120	409	/	89.7	1.45	4.9	/	1.13	UL	162.5
ESD72U6	7.2	ST	RSIR	145	495	/	109.3	1.45	4.9	/	1.13	UL	162.5
ESD80U6	8.0	ST	RSIR	165	563	/	124.6	1.45	4.9	/	1.13	UL	162.5
ESY60U6	6.0	ST	RSCR	120	409	/	90.8	1.60	5.5	/	1.25	UL	171
ESY80U6	8.0	ST	RSCR	165	563	/	124.5	1.60	5.5	/	1.25	UL	171
Y 系列 Y Series													
EYA40U6	4.0	ST	RSIR	70	239	76.1	52.8	1.40	4.8	1.66	1.09	UL	153
EYA55U6	5.5	ST	RSIR	105	358	114.2	79.5	1.40	4.8	1.66	1.09	UL	153
220 ~ 240V 60HZ R600a													
T 系列 T Series													
ETH46X6	4.5	ST	RSCR	85	290	/	64.2	1.76	6.0	/	1.38	VDE/CB	185
100V 50HZ R600a													
T 系列 T Series													
ETD50F	5.0	ST	RSCR	80	273	/	60.2	1.40	4.8	/	1.09	——	179
ETD72F	7.2	ST	RSCR	125	427	/	94.3	1.40	4.8	/	1.10	——	179
ETD80F	8.1	ST	RSCR	145	495	/	108.5	1.40	4.8	/	1.10	——	179
100V 60HZ R600a													
T 系列 T Series													
ETD50F	5.0	ST	RSCR	95	324	/	71.8	1.50	5.1	/	1.17	——	179
ETD72F	7.2	ST	RSCR	145	495	/	109.8	1.50	5.1	/	1.18	——	179
ETD80F	8.1	ST	RSCR	165	563	/	124.0	1.50	5.1	/	1.17	——	179
127V 60HZ R600a													
T 系列 T Series													
ETH46Y6	4.5	ST	RSCR	85	290	/	63.7	1.76	6.0	/	1.38	VDE/CB	185

型号 Model	气缸容积 Displacement	冷却方式 Cooling	电机类型 Motor Type	制冷量 Cooling Capacity			COP			认证 Certification	最大高度 "A" Max. Height "A"
				ASHRAE		CECOMAF	ASHRAE		CECOMAF		
	-23.3℃			-25℃	-23.3℃		-25℃				
	W			Btu	W	W/W	EER	W/W			
ETC72A	7.2	ST	RSCR	128	437	96.9	1.96	6.7	1.54	CCC	185
ETX55	5.6	ST	RSCR	96	328	71.9	1.98	6.8	1.56	CCC/VDE	185
ETX60	6.0	ST	RSCR	102	348	76.3	1.98	6.8	1.56	CCC/CB/VDE	185
ETX66	6.6	ST	RSCR	115	392	86.0	1.98	6.8	1.56	CCC/CB/VDE	185
△ ETD110K	10.7	ST	RSCR	185	631	139.1	1.45	4.9	1.71	CCC/CB	178
△ ETK80K	8.1	ST	RSCR	138	471	103.8	1.58	5.4	1.24	CB	178
△ ETK95K	9.6	ST	RSCR	165	563	123.4	1.52	5.2	1.18	CCC/CB	182
△ ETY110K	10.7	ST	RSCR	185	631	139.1	1.60	5.5	1.25	CCC/CB	185
△ ETZ95K	9.6	ST	RSCR	165	563	123.4	1.70	5.8	1.33	CCC/CB	182
S 系列 S Series											
ESF60	6.0	ST	RSCR	100	341	75.3	1.55	5.3	1.21	CCC/CB/VDE	162.5
ESF72	7.2	ST	RSCR	120	409	90.0	1.55	5.3	1.21	CCC/CB/VDE	162.5
ESF80	8.0	ST	RSCR	140	478	105.5	1.55	5.3	1.21	CCC/CB/VDE	162.5
ESZ51	5.1	ST	RSCR	85	290	64.0	1.62	5.5	1.27	CCC/CB/VDE	171
ESZ60	6.0	ST	RSCR	100	341	75.7	1.65	5.6	1.29	CCC/CB/VDE	171
ESZ65	6.5	ST	RSCR	110	375	82.6	1.65	5.6	1.29	CCC/CB/VDE	171
ESZ72	7.2	ST	RSCR	120	409	90.8	1.65	5.6	1.29	CCC/CB/VDE	171
ESZ80	8.0	ST	RSCR	140	478	105.0	1.65	5.6	1.29	CCC/CB/VDE	171
ESH51	5.1	ST	RSCR	88	300	66.1	1.72	5.9	1.34	CCC/CB/VDE	174
ESH60	6.0	ST	RSCR	100	341	75.7	1.72	5.9	1.34	CCC/CB/VDE	174
ESH72	7.2	ST	RSCR	120	409	91.0	1.72	5.9	1.34	CCC/CB/VDE	174
ESH80	8.0	ST	RSCR	140	478	105.7	1.72	5.9	1.34	CCC/CB/VDE	174
△ ES65K	6.5	ST	RSIR	110	375	82.6	1.24	4.2	0.96	CB	162.5
△ ES65AK	6.5	ST	RSIR	110	375	82.6	1.32	4.5	1.03	CB	162.5
△ ESD65AK	6.5	ST	RSCR	110	375	82.6	1.40	4.8	1.10	CB	162.5
△ ESF65K	6.5	ST	RSCR	108	368	81.4	1.58	5.4	1.24	CCC/CB	167
Y 系列 Y Series											
EYK40	4.0	ST	RSCR	62	212	46.9	1.55	5.3	1.21	CCC/CB/VDE	153
EYY50	5.0	ST	RSCR	80	273	60.6	1.62	5.5	1.27	VDE	153
EYY60	6.0	ST	RSCR	96	328	72.4	1.62	5.5	1.27	VDE	153
△ EY60K	6.0	ST	RSIR	96	328	72.0	1.20	4.1	0.98	VDE	148
N 系列 N Series											
ENA130	13.1	ST	RSIR	225	768	168.8	1.35	4.6	1.05	CCC	186
ENK130	13.1	ST	RSCR	225	768	168.8	1.50	5.1	1.17	CCC	186
ENK150	15.1	ST	RSCR	258	880	193.5	1.50	5.1	1.17	CCC	193
ENY120	12.1	ST	RSCR	205	699	153.8	1.62	5.5	1.27	CCC	193
ENY130	13.1	ST	RSCR	225	768	168.8	1.62	5.5	1.27	CCC/VDE	196
ENY150	15.1	ST	RSCR	258	880	193.5	1.62	5.5	1.27	CCC/VDE	196
ENZ130	13.1	ST	RSCR	225	768	168.8	1.70	5.8	1.33	CCC	196
ENB130	13.1	ST	RSCR	225	768	168.8	1.80	6.1	1.41	CCC	196
ENB150	15.1	ST	RSCR	258	880	193.5	1.80	6.1	1.40	CCC	196
△ ENA130K	13.1	ST/OC	RSIR	225	768	168.8	1.30	4.4	1.02	CCC/CB	193
△ ENA150K	15.1	ST/OC	RSCR	258	880	193.5	1.50	5.1	1.17	CCC/CB	193

型号 Model	气缸容积 Displacement	冷却方式 Cooling	电机类型 Motor Type	制冷量 Cooling Capacity		COP				认证 Certification	最大高度 "A" Max. Height "A"		
				ASHRAE		CECOMAF		ASHRAE				CECOMAF	
				-23.3℃		-25℃		-23.3℃				-25℃	
	W			Btu	W		W/W	EER	W/W				
ETC72A	7.2	ST	RSCR	128	437	96.9		1.96	6.7	1.54	CCC	185	
ETX55	5.6	ST	RSCR	96	328	71.9		1.98	6.8	1.56	CCC/VDE	185	
ETX60	6.0	ST	RSCR	102	348	76.3		1.98	6.8	1.56	CCC/CB/VDE	185	
ETX66	6.6	ST	RSCR	115	392	86.0		1.98	6.8	1.56	CCC/CB/VDE	185	
△ ETD110K	10.7	ST	RSCR	185	631	139.1		1.45	4.9	1.71	CCC/CB	178	
△ ETK80K	8.1	ST	RSCR	138	471	103.8		1.58	5.4	1.24	CB	178	
△ ETK95K	9.6	ST	RSCR	165	563	123.4		1.52	5.2	1.18	CCC/CB	182	
△ ETY110K	10.7	ST	RSCR	185	631	139.1		1.60	5.5	1.25	CCC/CB	185	
△ ETZ95K	9.6	ST	RSCR	165	563	123.4		1.70	5.8	1.33	CCC/CB	182	
S 系列 S Series													
ESF60	6.0	ST	RSCR	100	341	75.3		1.55	5.3	1.21	CCC/CB/VDE	162.5	
ESF72	7.2	ST	RSCR	120	409	90.0		1.55	5.3	1.21	CCC/CB/VDE	162.5	
ESF80	8.0	ST	RSCR	140	478	105.5		1.55	5.3	1.21	CCC/CB/VDE	162.5	
ESZ51	5.1	ST	RSCR	85	290	64.0		1.62	5.5	1.27	CCC/CB/VDE	171	
ESZ60	6.0	ST	RSCR	100	341	75.7		1.65	5.6	1.29	CCC/CB/VDE	171	
ESZ65	6.5	ST	RSCR	110	375	82.6		1.65	5.6	1.29	CCC/CB/VDE	171	
ESZ72	7.2	ST	RSCR	120	409	90.8		1.65	5.6	1.29	CCC/CB/VDE	171	
ESZ80	8.0	ST	RSCR	140	478	105.0		1.65	5.6	1.29	CCC/CB/VDE	171	
ESH51	5.1	ST	RSCR	88	300	66.1		1.72	5.9	1.34	CCC/CB/VDE	174	
ESH60	6.0	ST	RSCR	100	341	75.7		1.72	5.9	1.34	CCC/CB/VDE	174	
ESH72	7.2	ST	RSCR	120	409	91.0		1.72	5.9	1.34	CCC/CB/VDE	174	
ESH80	8.0	ST	RSCR	140	478	105.7		1.72	5.9	1.34	CCC/CB/VDE	174	
△ ES65K	6.5	ST	RSIR	110	375	82.6		1.24	4.2	0.96	CB	162.5	
△ ES65AK	6.5	ST	RSIR	110	375	82.6		1.32	4.5	1.03	CB	162.5	
△ ESD65AK	6.5	ST	RSCR	110	375	82.6		1.40	4.8	1.10	CB	162.5	
△ ESF65K	6.5	ST	RSCR	108	368	81.4		1.58	5.4	1.24	CCC/CB	167	
Y 系列 Y Series													
EYK40	4.0	ST	RSCR	62	212	46.9		1.55	5.3	1.21	CCC/CB/VDE	153	
EYY50	5.0	ST	RSCR	80	273	60.6		1.62	5.5	1.27	VDE	153	
EYY60	6.0	ST	RSCR	96	328	72.4		1.62	5.5	1.27	VDE	153	
△ EY60K	6.0	ST	RSIR	96	328	72.0		1.20	4.1	0.98	VDE	148	
N 系列 N Series													
ENA130	13.1	ST	RSIR	225	768	168.8		1.35	4.6	1.05	CCC	186	
ENK130	13.1	ST	RSCR	225	768	168.8		1.50	5.1	1.17	CCC	186	
ENK150	15.1	ST	RSCR	258	880	193.5		1.50	5.1	1.17	CCC	193	
ENY120	12.1	ST	RSCR	205	699	153.8		1.62	5.5	1.27	CCC	193	
ENY130	13.1	ST	RSCR	225	768	168.8		1.62	5.5	1.27	CCC/VDE	196	
ENY150	15.1	ST	RSCR	258	880	193.5		1.62	5.5	1.27	CCC/VDE	196	
ENZ130	13.1	ST	RSCR	225	768	168.8		1.70	5.8	1.33	CCC	196	
ENB130	13.1	ST	RSCR	225	768	168.8		1.80	6.1	1.41	CCC	196	
ENB150	15.1	ST	RSCR	258	880	193.5		1.80	6.1	1.40	CCC	196	
△ ENA130K	13.1	ST/OC	RSIR	225	768	168.8		1.30	4.4	1.02	CCC/CB	193	
△ ENA150K	15.1	ST/OC	RSCR	258	880	193.5		1.50	5.1	1.17	CCC/CB	193	

R600a Compressors

型号 Model	气缸容积 Displacement	冷却方式 Cooling	电机类型 Motor Type	制冷量 Cooling Capacity			COP			认证 Certification	最大高度 "A" Max. Height "A"
				ASHRAE		CECOMAF	ASHRAE		CECOMAF		
	-23.3℃			-25℃	-23.3℃		-25℃				
	W			Btu	W	W/W	EER	W/W			
LBP											
220-240V 50HZ R600a											
T 系列 T Series											
ETK80	8.1	ST	RSCR	138	471	103.2	1.55	5.3	1.21	CCC/CB	178
ETK95	9.6	ST	RSCR	165	563	123.4	1.55	5.3	1.21	CCC/CB/VDE	178
ETY72	7.2	ST	RSCR	125	427	93.7	1.6	5.5	1.25	CCC/CB/VDE	174
ETY80	8.1	ST	RSCR	138	471	103.3	1.65	5.6	1.29	CCC	185
ETY95	9.6	ST	RSCR	165	563	123.5	1.60	5.5	1.25	CCC/CB/VDE	178
ETZ55	5.6	ST	RSCR	96	328	72.0	1.74	5.9	1.36	CCC	185
ETZ60	6.0	ST	RSCR	102	348	77.3	1.68	5.7	1.32	CCC/CB/VDE	178
ETZ66	6.6	ST	RSCR	110	375	83.3	1.68	5.7	1.32	CCC/CB/VDE	185
ETZ72	7.2	ST	RSCR	125	427	94.7	1.70	5.8	1.33	CCC/CB/VDE	178
ETZ80	8.1	ST	RSCR	140	478	104.0	1.70	5.8	1.33	CCC/CB/VDE	178
ETZ86	8.6	ST	RSCR	150	512	113.5	1.70	5.8	1.33	CCC/CB/VDE	185
ETZ95	9.6	ST	RSCR	165	563	124.0	1.70	5.8	1.33	CCC/CB/VDE	185
ETZ110	10.7	ST	RSCR	185	631	139.1	1.70	5.8	1.33	CCC/CB/VDE	185
ETZ120	12.0	ST	RSCR	210	717	157.5	1.70	5.8	1.33	——	185
ETH50	5.1	ST	RSCR	82	280	62.1	1.76	6.0	1.38	CCC/CB/VDE	185
ETH55	5.6	ST	RSCR	96	328	72.2	1.76	6.0	1.38	CCC/CB/VDE	185
ETH60	6.0	ST	RSCR	102	348	77.1	1.76	6.0	1.38	CCC/CB/VDE	185
ETH66	6.6	ST	RSCR	110	375	83.1	1.76	6.0	1.38	CCC/CB/VDE	185
ETH72	7.2	ST	RSCR	125	427	94.4	1.76	6.0	1.38	CCC/CB/VDE	185
ETH80	8.1	ST	RSCR	140	478	105.2	1.76	6.0	1.38	CCC/CB/VDE	185
ETH95	9.6	ST	RSCR	170	580	127.6	1.78	6.1	1.40	CCC/CB/VDE	185
ETH110	10.7	ST	RSCR	190	648	142.2	1.78	6.1	1.40	CCC/CB/VDE	185
ETB50	5.1	ST	RSCR	82	280	61.5	1.83	6.2	1.44	CCC/CB/VDE	185
ETB55	5.6	ST	RSCR	96	328	72.1	1.83	6.2	1.44	CCC/CB/VDE	185
ETB60	6.0	ST	RSCR	102	348	76.8	1.83	6.2	1.44	CCC/CB/VDE	185
ETB66	6.6	ST	RSCR	112	382	84.0	1.83	6.2	1.44	CCC/CB/VDE	185
ETB72	7.2	ST	RSCR	125	427	94.0	1.83	6.2	1.44	CCC/CB/VDE	185
ETB80	8.1	ST	RSCR	140	478	105.1	1.83	6.2	1.44	CCC/CB/VDE	185
ETB95	9.6	ST	RSCR	170	580	128.7	1.83	6.2	1.44	CCC/VDE	185
ETB110	10.7	ST	RSCR	190	648	142.2	1.83	6.2	1.44	CCC/VDE	185
ETJ66	6.6	ST	RSCR	115	375	82.7	1.88	6.4	1.47	CCC	185
ETJ90	9.0	ST	RSCR	155	529	116.3	1.88	6.4	1.47	CCC/VDE	185
ETJ110	10.7	ST	RSCR	190	648	142.3	1.88	6.4	1.47	CCC/VDE	185
ETC55	5.6	ST	RSCR	96	328	71.8	1.91	6.5	1.50	CCC	185
ETC60	6.0	ST	RSCR	102	348	77.1	1.91	6.5	1.50	CCC	185
ETC72	7.2	ST	RSCR	128	437	96.2	1.91	6.5	1.50	CCC/VDE	185
ETC86	8.6	ST	RSCR	150	512	113.0	1.91	6.5	1.50	CCC/VDE	185
ETC95	9.6	ST	RSCR	170	580	128.4	1.91	6.5	1.50	CCC/VDE	185
ETC55A	5.6	ST	RSCR	96	328	72.5	1.95	6.7	1.53	CCC	185
ETC60A	6.0	ST	RSCR	105	358	79.4	1.95	6.7	1.53	——	185

