

Donper, New, L58CZ1, 220V-240V, 50Hz,
R134A ,Refrigerator, Compressor,
1/6++HP, 1/5 hp-, power 116 w, input
145 w



Category: compressor

written by www.mbsm.pro | 16 November 2023



L58CZ1

220-240V~50Hz 1PH
THERMALLY PROTECTED



<http://www.donper.com>



201120003251202363

R134a

SYS12200901

BCD-270 (M)



027002201212000064

Type □ tradition Model □ L58CZ1
 Refrigerant □ R134a Voltage □ 160-260V
 Frequency □ 50Hz Application □ LBP
 HP □ 1/6 Displacement (cm³) □ 5.8
 Cooling □ S Lubricant Type □ RL22H
 Lubricant (ml) □ 200±5 Motor Type □ RSIR
 Starting Type □ LST Starter □ PTC

展示柜/冷饮类应用

FOR SHOW CASE/COLD DRINK MACHINE

R134a 160-260V~50Hz

系列 SERIES	压机型号 MODEL	排量 cm ³ DISPLACEMENT (cm ³)	商业 标称 HP	背压 APPLICATION CATEGORY	电机类型 MOTOR TYPE	冷却方式 COOLING TYPE	启动电容 STARTING CAPACITOR (μF)	运行电容 RUNNING CAPACITOR (μF)	安全认证 APPROVAL
L	L58CZ1	5.8	1/6+	L/MBP	RSIR	S	-	-	CCC, VDE
L	L65CZ1	6.5	1/5+	L/MBP	RSIR	S	-	-	CCC, VDE
L	L72CZ1	7.2	1/4-	L/MBP	RSIR	S	-	-	CCC, VDE
L	L072WZ1	7.2	1/4-	L/MBP	RSCR	S	-	4	CCC, VDE

°C			°C									
-35	-30	-25	-23.3		-20	-15	-10	-5	0	5	7.2	10
W	W	W	W	Btu/h	COP (W/W)	W	W	W	W	W	W	W
71	98	131	145	495	1.25	173	220	278	351	-	-	-
84	115	154	170	580	1.25	202	258	326	411	-	-	-
96	132	177	195	665	1.30	232	296	373	471	-	-	-
96	132	177	195	665	1.55	232	296	373	471	-	-	-

R134a 220-240V~50/60Hz

系列 SERIES	压机型号 MODEL	排量 cm ³ DISPLACEMENT (cm ³)	商业 标称 HP	背压 APPLICATION CATEGORY	电机类型 MOTOR TYPE	冷却方式 COOLING TYPE	启动电容 STARTING CAPACITOR (μF)	运行电容 RUNNING CAPACITOR (μF)	安全认证 APPROVAL
L	L056DZ1	5.6	1/5+	L/MBP	RSIR	S	-	-	CCC, CB
L	L063DZ1	6.3	1/4-	L/MBP	RSIR	S	-	-	CCC, CB
L	L065DZ1	6.5	1/4+	L/MBP	RSIR	S	-	-	-
L	L070DZ1	7.0	1/3-	L/MBP	RSCR	S	-	4	CCC, CB
L	L088DZ1	8.8	1/3-	L/MBP	RSCR	S	-	5	CCC, VDE
K	KK325DZ1	9.6	1/3-	L/MBP	RSCR	F	-	5	CCC, VDE
K	K390DZ1	11.4	1/2+	L/MBP	CSIR	F	50	-	CCC, VDE

°C			°C									
-35	-30	-25	-23.3		-20	-15	-10	-5	0	5	7.2	10
W	W	W	W	Btu/h	COP (W/W)	W	W	W	W	W	W	W
83	114	152	168	573	1.40	200	255	322	406	-	-	-
93	128	171	195	665	1.40	225	287	362	457	-	-	-
103	142	190	210	717	1.55	250	319	402	507	-	-	-
110	153	205	235	802	1.66	269	343	433	546	-	-	-
125	172	225	250	853	1.60	295	376	480	566	-	-	-
151	218	296	325	1109	1.50	389	487	623	784	-	-	-
179	259	352	385	1314	1.30	462	578	740	931	-	-	-

R134a 220-240V~50/60Hz

系列 SERIES	压机型号 MODEL	排量 cm ³ DISPLACEMENT (cm ³)	商业 标称 HP	背压 APPLICATION CATEGORY	电机类型 MOTOR TYPE	冷却方式 COOLING TYPE	启动电容 STARTING CAPACITOR (μF)	运行电容 RUNNING CAPACITOR (μF)	安全认证 APPROVAL
L	L6170DZ1	7.9	1/4	M/HBP	CSIR	F	50	-	CCC
K	K6210DZ1	11.4	3/8	M/HBP	CSIR	F	75	-	CCC

°C			°C										
-35	-30	-25	-23.3	-20	-15	-10	-5	0	5	7.2			10
W	W	W	W	W	W	W	W	W	W	W	W	W	W
-	-	-	-	405	535	609	710	939	950	3241	2.30	1089	-
-	-	-	-	368	454	548	832	1160	1300	4435	2.10	1508	-

R134a 220-240V~50Hz

系列 SERIES	压机型号 MODEL	排量 cm ³ DISPLACEMENT (cm ³)	商业 标称 HP	背压 APPLICATION CATEGORY	电机类型 MOTOR TYPE	冷却方式 COOLING TYPE	启动电容 STARTING CAPACITOR (μF)	运行电容 RUNNING CAPACITOR (μF)	安全认证 APPROVAL
S	S6160CZ1	7.2	1/4-	M/HBP	CSIR	F	50	-	CCC
L	L6170CZ1	7.9	1/4	M/HBP	CSIR	F	50	-	CCC, VDE
NE	NE6188CZ1	12.0	3/8	M/HBP	CSIR	F	75	-	CCC
K	K6210CZ1	11.4	3/8	M/HBP	CSIR	F	75	-	CCC
NE	NE6210CZ1	14.2	3/8	M/HBP	CSIR	F	75	-	CCC

°C			°C										
-35	-30	-25	-23.3	-20	-15	-10	-5	0	5	7.2			10
W	W	W	W	W	W	W	W	W	W	W	W	W	W
-	-	-	-	346	384	441	608	705	750	2559	2.30	837	-
-	-	-	-	380	421	484	667	774	850	2900	2.30	918	-
-	-	-	-	400	520	665	830	1010	1100	3753	2.30	1230	-
-	-	-	-	415	540	680	865	1030	1200	4436	2.40	1360	-
-	-	-	-	431	575	758	965	1190	1200	4436	2.30	1445	-



Model No.	L58CZ1
Vol./Freq.:	220V-240V/50Hz
Refrigerant:	R134a refrigeration compressor
Cooling Capacity:	145W
C.O.P.:	1.25 W/W
Horse Power:	1/6+
Displ.	5.8 cm ³
Application:	Low Back Pressure Compressors (LBP)
Evaporating Temperature (W):	LMBP: -23.3°C , HMBP: 7.2°C
Net Weight:	7.2KGS





L58CZ1

220-240V~50Hz 1PH
THERMALLY PROTECTED



<http://www.donper.com>



201120003251202363

R134a

SYS12200901

BCD-270 (M)



027002201212000064

Réfrigérant	Type De demande	Modèle	Série	HP	Refroidissement	Type de moteur	Alimentation	Capacité de refroidissement		FLIC W/W	
								*ASHRAE -23.3	*CECOMAF-25	*ASHRAE -23.3	*CECOMAF-25
Ordinaire											
R134a	LBP	W25CZ	W	1/14	S	RSIR	220/50	60	42	0.85	0.65
R134a	LBP	W30CZ	W	1/12	S	RSIR	220/50	66	48	0.85	0.68
R134a	LBP	W25BZ	W	1/14	S	RSIR	115/60	65	47	0.8	0.62
R134a	LBP	W30BZ	W	1/10	S	RSIR	115/60	72	53	0.83	0.65
R134a	LBP	S30CZ	S	1/12	S	RSIR	220/50	66	48	0.95	0.73
R134a	LBP	S36CZ	S	1/8	S	RSIR	220/50	90	66	1.05	0.81
R134a	LBP	S43CZ	S	1/7	S	RSIR	220/50	106	77	1.07	0.82
R134a	LBP	S53CZ	S	1/6-	S	RSIR	220/50	118	86	1.15	0.89
R134a	LBP	S30BZ	S	1/10	S	RSIR	115/60	72	53	0.96	0.74
R134a	LBP	S43BZ	S	1/6-	S	RSIR	115/60	125	91	1.16	0.89
R134a	LBP	S53BZ	S	1/6+	S	RSIR	115/60	145	106	1.18	0.91
R134a	LBP	L58CZ	L	1/6+	S	RSIR	220/50	140	102	1.2	0.94
R134a	LBP	L65CZ	L	1/5	S	RSIR	220/50	160	117	1.23	0.95
R134a	LBP	E1112CE	B	1/6+	S	RSIR	220/50	140	102	1.18	0.91
R134a	LBP	E1114CZ	B	1/5	S	RSIR	220/50	160	117	1.2	0.92
R134a	LBP	E1116CZ	B	1/4	S	RSIR	220/50	180	131	1.2	0.92
R134a	LBP	E1118CAZ	E	1/4+	S	RSIR	220/50	207	151	1.16	0.95
R134a	LBP	E1120CAZ	E	1/3	F1	RSIR	220/50	230	168	1.15	0.9
R134a	LBP	E1121CAZ	E	3/8	F1	RSIR	220/50	270	197	1.16	0.96
R134a	LBP	E1130CZA	E	3/8+	F1	RSIR	220/50	325	237	1.16	0.96
R134a	LBP	E1134CZA	E	1/2	F1	RSIR	220/50	375	273	1.25	0.96
R134a	LBP	E1118BZ	E	1/4+	S	RSIR	115/60	207	151	1.16	0.89
R134a	LBP	E1121BZ	E	3/8	F1	RSIR	115/60	270	197	1.16	0.89
R134a	LBP	E1130BZ	E	3/8	F1	RSIR	115/60	325	237	1.2	0.92
R134a	LBP	NE1118BZ	NE	1/4+	S	RSIR	220/50	207	151	1.16	0.95
R134a	LBP	NE1121BZ	NE	3/8	F1	RSIR	220/50	270	197	1.16	0.96
R134a	LBP	NE1130BZ	NE	3/8+	F1	RSIR	220/50	325	237	1.16	0.96
R134a	LBP	CT2134CZ	CT	1/2	F2	RSIR	220/50	395	288	1.08	0.83
R134a	LBP	CJ2140CZ	CJ	3/4	F3	RSIR	220/50	450			
R134a	LBP	CJ2152CZ	CJ	1	F3	RSIR	220/50	760			

Aperçus de produit