

Mbsm.pro, Compressor, Aspera, NEU2168U, 3/4 hp, r290, LBP

Category: compressor

written by www.mbsm.pro | 11 September 2022



Private Picture Copyright : WWW.MBSM.PRO

Product information "Compressor Aspera NEU2168U CSR, LBP – R290, 220-240V, 50-60Hz" Compressor Aspera NEU2168U CSR, LBP – R290, 220-240V, 50-60Hz, engine type: CSR, displacement: 16.80cm³, power: 3/4hp, nominal cooling capacity: 457-788 W

Refrigerant:	R290
Dimensions (length × width × height):	24,20 × 17,80 × 20,60 cm
Scope of application:	LBP
Cooling capacity (W):	2256
starting torque:	HST
Design type:	Hermetic , reciprocating
Manufacturer:	Aspera , Embraco Aspera
Hubvolumen (cm3):	16.8
Info:	Oil pre-filled
Power range (hp):	0-2
Power range (W):	2 – 3 kW
Engine type:	CSR
Rated power (hp):	0.75
Series:	OR
Tension:	220-240V
Power supply:	230 V
Compressor type:	reciprocating
Condensing Units Compressors:	compressor
To be used with:	Capillary/Expansion
Oilmenge (l):	0.35
Oil type:	ISO22, POE22

Downloads



Private Picture Copyright : WWW.MBSM.PRO

NEU2155U	13,5	3/4	115-127V 60Hz 1 ~	CSIR	HST	LBP	758	1,44	600	1,14	45
NEU2155U	13,5	3/4	115-127V 60Hz 1 ~	CSR	HST	LBP	766	1,56	608	1,22	55
NEU2168U	16,8	3/4	115-127V 60Hz 1 ~	CSR	HST	LBP	950	1,51	748	1,19	45
NEU2168U	16,8	3/4	208-230V 60Hz 1 ~	CSIR	HST	LBP	911	1,36	736	1,1	55
NEU2168U	16,8	3/4	208-230V 60Hz 1 ~	CSR	HST	LBP	933	1,52	748	1,21	45
NT2160U(V)	17,4	3/4	208-230V 60Hz 1 ~	CSIR	HST	LBP	828	1,34	604	1,00	55
NT2160UV	17,4	3/4	115V 60Hz 1~	CSR	HST	LBP	827	1,42	638	1,1	45
NEU2178U	18,7	1	208-230V 60Hz 1 ~	CSR	HST	LBP	1052	1,5	846	1,21	55
NEU2178U	18,7	1	115-127V 60Hz 1 ~	CSR	HST	LBP	1054	1,47	841	1,21	45

Private Picture Copyright : WWW.MBSM.PRO

Mbsm_dot_pro_private_PDF_NEU2168uTélécharger