Mbsm.pro, PDF, LG, compressor, msa43lbeg, 116 w, 1/8 hp, lbp, r134a

written by Lilianne | 2 June 2022



Mbsm.pro, PDF, LG, compressor, msa43lbeg, 116 w, 1/8 hp, lbp

Mbsm.pro, Compressor, DONPER, NE 2125 CE, NE2125CE, r22, 3/8hp++, HMBP, 266 w



Private Picture Copyright : WWW.MBSM.PRO

Mbsm.pro, Compressor, DONPER, NE 2125 CE, NE2125CE, r22, 3/8hp++, lbp HMBP

Mbsm.pro, compressor, CUBIGEL, ELECTOLUX, ACC, R404a, R507, MP14FB, 220-240V 50Hz, LBP, 1/2HP



Private Picture Copyright: WWW.MBSM.PRO

Mbsm.pro, compressor, CUBIGEL, ELECTOLUX, ACC, R404a, R507, MP14FB, 220-240V 50Hz, LBP, 1/2HP

Mbsm.pro, Secop, Freezer, Compressor, Sc18cl, 104L2123, 104L2123, 5/8HP++, 1/2-, R404A, Secop SCxxCL Series, LMBP, 495 w



Private Picture Copyright: WWW.MBSM.PRO

Mbsm.pro, Secop, Freezer, Compressor, Sc18cl, 104L2123, 5/8HP++, 1/2-, R404A, Secop SCxxCL Series, LMBP, 495 w

Mbsm.pro, Compressor, DB110C19RAW5, 1/3 hp, LBP, R134a, 200g, D series, Refrigerators, Smeg, 2 Doors, 18 feet, no-frost freezer



Private Picture Copyright : WWW.MBSM.PRO

Mbsm.pro, Compressor, DB110C19RAW5, 1/3 hp, LBP, R134a, 200g, D series, Refrigerators, Smeg, 2 Doors, 18 feet, no-frost freezer

Mbsm.pro, Kiriazi, K500, No-Frost, Refrigerator, 500 Liters, 18 feet, Compressor, 1/3 hp, R134a, 190g



Mbsm.pro, Kiriazi, K500, No-Frost, Refrigerator, 500 Liters, 18 feet, Compressor, 1/3 hp, R134a, 190g

Mbsm.pro, compressor, EM Series, Embraco, EMY75HLC, 211 w, 1/4 hp, lbp, 750 btu, r134a

written by Lilianne | 2 June 2022

| | C.I.I.C | Control Control Control of Control of Control Control of Control o | | | | | | | | | | | | | |
|-----|---------|--|------------|-------|-----|-------|------|------|-----|----|--------|---------|-----|------|---|
| | | EMZ 66 CLP | 220~240/50 | 10.61 | 190 | 163.4 | 1.74 | 1.50 | 4 | | ISO 5 | CCC/VDE | 171 | 6.73 | |
| | ЕМХ | EMX 32 CLC | 220~240/50 | 5.96 | 102 | 87.7 | 1.78 | 1.53 | 2.5 | | ISO 5 | CCC | 166 | 6.54 | |
| | | EMX 40 CLC | 220-240/50 | 7.24 | 128 | 110.1 | 1.80 | 1.55 | 4 | | ISO 5 | CCC | 166 | 6.54 | |
| | | EMB 32 CLC | 220-240/50 | 5.96 | 103 | 88.6 | 1.88 | 1.62 | 2.5 | | ISO 5 | CCC | 166 | 6.54 | n |
| | | EMB 40 CLC | 220~240/50 | 7.24 | 128 | 110.1 | 1.92 | 1.65 | 4 | | ISO 5 | CCC/VDE | 171 | 6.73 | 4 |
| | EMB | EMB 46 CLC | 220-240/50 | 7.96 | 142 | 122.1 | 1.90 | 1.63 | 4 | | ISO 5 | CCC/VDE | 171 | 6.73 | |
| | | EMB 55 CLC | 220240/50 | 9.05 | 163 | 140.2 | 1.88 | 1.62 | 4 | | ISO 5 | CCC/VDE | 171 | 6.73 | |
| | | EMB 66 CLC | 220-240/50 | 10.61 | 190 | 163.4 | 1.87 | 1.61 | 4 | | ISO 5 | CCC/VDE | 171 | 6.73 | |
| | EMT | EMT 45 HLP | 220~240/50 | 4.85 | 145 | 124.7 | 1.40 | 1.20 | | | ISO 7 | CCC/VDE | 158 | 6.22 | |
| | | EMU 45 HLP | 220240/50 | 4.85 | 145 | 124.7 | 1.50 | 1.29 | | | ISO 7 | CCC/VDE | 158 | 6.22 | |
| | | EMU 55 HLP | 220~240/50 | 5.20 | 161 | 138.5 | 1.50 | 1.29 | | | ISO 7 | CCC/VDE | 166 | 6.54 | |
| | | EMU 65 HLP | 220-240/50 | 5.96 | 185 | 159.1 | 1,47 | 1.26 | | | ISO 7 | CCC/VDE | 166 | 6.54 | |
| | EMU | EMU 45 HLP | 200~230/50 | 4.85 | 145 | 124.7 | 1.45 | 1.25 | | | ISO 22 | CCC/VDE | 158 | 6.22 | |
| | | EMU 55 HLP | 200-230/50 | 5.20 | 161 | 138.5 | 1.45 | 1.25 | | | ISO 22 | CCC/VDE | 166 | 6.54 | |
| | | EMU 65 HLP | 200-230/50 | 5.96 | 185 | 159.1 | 1.45 | 1.25 | | | ISO 22 | CCC/VDE | 166 | 6.54 | |
| 34a | | EMU 55 HLP | 115-127/60 | 4,15 | 148 | 127.3 | 1.46 | 1.26 | | | ISO 7 | UL | 158 | 6.22 | |
| | | EMY 55 HLC | 220240/50 | 5.20 | 161 | 138.5 | 1.60 | 1,38 | 4 | | ISO 7 | CCC/VDE | 166 | 6.54 | |
| | | EMY 65 HLC | 220~240/50 | 5.96 | 185 | 159.1 | 1.60 | 1.38 | 4 | | ISO 7 | CCC/VDE | 166 | 6.54 | |
| | EMY | EMY 75 HLC | 220-240/50 | 7.00 | 215 | 184.9 | 1.60 | 1.38 | 4 | | ISO 7 | CCC/VDE | 171 | 6.73 | |
| | EIMT | EMY 50 HLP | 115~127/60 | 4.15 | 140 | 120.4 | 1.60 | 1.38 | 12 | | ISO 7 | UL | 158 | 6.22 | |
| | | EMY 55 HLP | 115-127/60 | 4.50 | 160 | 137.6 | 1.60 | 1.38 | 12 | | ISO 7 | UL | 158 | 6.22 | |
| | | EMY 60 HLP | 115-127/60 | 4.85 | 180 | 154.8 | 1.60 | 1.38 | 12 | | ISO 7 | UL | 166 | 6.54 | |
| | EMH | EMH 60 HER | 115-127/60 | 5.19 | 189 | 162.5 | 1.47 | 1.26 | | | ISO 7 | ccc | 166 | 6,54 | |
| 90 | EMT | EMT 2121 U | 220~240/50 | 5.57 | 256 | 220.0 | 1.42 | 1.22 | | 48 | ISO 22 | CCC/VDE | 166 | 6.54 | |
| 40 | CIMI | EMT 2125 U | 220-240/50 | 5.96 | 301 | 259.0 | 1.48 | 1.28 | | 58 | ISO 22 | CCC/VDE | 166 | 6.54 | |

测试条件:蒸发-23.3 °C(-10 °F) 冷凝54.4 °C (130 °F) 吸气/环境32.2 °C (90 °F) 液体32.2 °C (90 °F) Test Conditions: Evaporating: -23.3 °C (-10 °F) | Condensing: 54.4 °C (130 °F) | Gas and Ambient: 32.2 °C (90 °F) | Liquid: 32.2 °C (90 °F)

Private Picture Copyright: WWW.MBSM.PRO

Mbsm.pro, compressor, EM Series, Embraco, EMY75HLC, 211 w, 1/4 hp, lbp, 750 btu, r134a

Mbsm.pro, Compressor, AW700ET-111-P2, Tecumseh 1-1/4 HP, 208-230V, 1 PH, 15,200 BTU, R22, Hermetic Compressor Replacement



Mbsm.pro, Compressor, AW700ET-111-P2, Tecumseh 1-1/4 HP, 208-230V, 1 PH, 15,200 BTU, R22, Hermetic Compressor Replacement

Mbsm.pro, Freezer, 420 L, regeneration, using Cooling, Aluminium Plated, Roll Bonded, Evaporator Plate, Compressor, L72cZ1 , 1/4 hp, r134a, capillarie 3 M, 0.032

written by Lilianne | 2 June 2022



Mbsm.pro, Freezer, 420 L, regeneration, using Cooling, Aluminium Plated, Roll Bonded, Evaporator Plate, Compressor, L72cZ1 , 1/4 hp, r134a, capillarie 3 M, 0.032

Mbsm.pro,

Refrigerator,

Fridge-Freezer, RT511JSPN, No Frost, Sumsung, 441 L, 309 L, Compressor, Mk172Q-L2U, 1/4 Hp, 205 W, 699 BTu/H, Samsung Compressor, Mk Serie, R134A, 7.21 cc, 220-240 v, LBP, Static Compressor, RSIR

written by Lilianne | 2 June 2022



Private Picture Copyright : WWW.MBSM.PRO

Mbsm.pro, Refrigerator, Fridge-Freezer, RT511JSPN, No Frost, Sumsung, 441 L, 309 L, Compressor, Mk172Q-L2U, 1/4 Hp, 205 W, 699 BTu/H, Samsung Compressor, Mk Serie, R134A, 7.21 cc, 220-240 v, LBP, Static Compressor, RSIR