

Mbsm.pro, Compressor, BP1072Z,
221CA32, 1/10 Hp, 66W, EMBRACO,
ASPERA, r134A, Lbp, HERMETIC
COMPRESSORS, Oil 200 cc, 220 V/ 60 Hz

Category: compressor

written by www.mbsm.pro | 2 February 2022



Private Picture Copyright : WWW.MBSM.PRO

Mbsm.pro, Compressor, BP1072Z, 221CA32, 1/10 Hp, 66W, EMBRACO, ASPERA, r134A, Lbp, HERMETIC COMPRESSORS, Oil 200 cc, 220 V/ 60 Hz

Mbsm.pro, Compressor, R600a, PZ59E1C, 1/8 Hp, 95 W, Lbp

Category: compressor

written by www.mbsm.pro | 2 February 2022



Private Picture Copyright: WWW.MBSM.PRO

Mbsm.pro, Compressor, R600a, PZ59E1C, 1/8 Hp, 95 W, Lbp

Mbsm.pro, Compressor, Samsung, MSV162AL1J/TS, MSV162, MSV162A-L1B, Compressor Inverter, Block DC, 1200/4000 RPM, 70/244 W, 238/834 BTU, Lnb, 1/3 hp, R134A, Blcd

Category: compressor

written by www.mbsm.pro | 2 February 2022



Mbsm.pro, Compressor, Samsung, MSV162AL1J/TS, MSV162, MSV162A-L1B, Compresseur Inverter, Block DC, 1200/4000 RPM, 70/244 W, 238/834 BTU, Lnb, 1/3 hp, R134A, Blcd

Mbsm.pro, Compressor, Tecumseh, TAH4518A, 1.5 Hp, HBp, R12, 440V 3~ 60Hz 400V 3~ 50Hz, 1684 W, 14048 btu

Category: compressor

written by www.mbsm.pro | 2 February 2022



Private Picture Copyright : WWW.MBSM.PRO

Mbsm.pro, Compressor, Tecumseh, TAH4518A, 1.5 Hp, HBp, R12, 440V 3~ 60Hz 400V 3~ 50Hz, 1684 W, 14048 btu

الطريقة الصحيحة والوحيدة لحساب قدرة The Only Correct And Reliable Way To Calculate The Capacity Of TEE Compressors.

Category: Arabe,Chaud&Froid

written by www.mbsm.pro | 2 February 2022



Picture Private Copyright: WWW.MBSMGROUP.TN

Private Picture Copyright: WWW.MBSM.PRO

.. الطريقة الصحيحة والوحيدة لحساب قدرة ضواغط تي
The Only Correct And Reliable
Way To Calculate The Capacity Of TEE Compressors.

Mbsm.pro, Compressor, 4ec-6.2-4os,
6HP, Bitzer Piston Compressor,
4ces-6, Refrigeration Compressor ,
4ec-6.2/4ees-6, Cold Room. R22, R404

Category: compressor

written by www.mbsm.pro | 2 February 2022



Typ 4EC-6.2-40S
S.Nr. 1679004388



ER KÜHLMASCHINENBAU GMBH
Made in E.C.

Anspannung Δ 3Ph~ V Y 3Ph~	Frequ. Hz	Max. Betr. strom		Anlaufstrom		Fördervol. m ³ /h	Drehzahl min
		A(Δ)	A(Y)	A(Δ)	A(Y)		
20-240	380-420	22,9	13,2	107,7	62,2	22,7	1450
265-290	440-480	22,9	13,2	107,7	62,2	27,4	1750

IP 65 ND/HD max 19 / 28 bar



Mbsm.pro, Compressor, 4ec-6.2-4os, 6HP, Bitzer Piston Compressor, 4ces-6, Refrigeration Compressor , 4ec-6.2/4ees-6, Cold Room. R22, R404

Mbsm.pro, Compressor, inverter, LG Refrigerator, BMG110NHMV, BMG/BMA LG, Lbp, 1/4 Hp , R600A

Category: compressor

written by www.mbsm.pro | 2 February 2022



Mbsm.pro, Compressor, inverter, LG Refrigerator, BMG110NHMV, BMG/BMA LG, Lbp, 1/4 Hp , R600A

Mbsm.pro, Compressor, AJE4511YTZ , R134a, hbp, TAJ4511Y, R-12/R-409A, lbp, 1HP, 3hp, 400V U.H., CAJ4511A, 1ph, R-12, lbp, 220v

Category: compressor

written by www.mbsm.pro | 2 February 2022



Private Picture Copyright : WWW.MBSM.PRO

Mbsm.pro, Compressor, AJE4511YTZ , R134a, TAJ4511Y, R-12/R-409A, 1HP, 3hp, 400V U.H., CAJ4511A, 1ph, R-12, 220v

Mbsm.pro, Compressor, R290, 0.110Kg,

SC15CNX.2, Secop, DANFOSS, SC15CNX,
15,28cm³, LBP, 230V, Hermetic piston
compressors, 5/8 Hp, 104h 8568,
104h8568

Category: compressor

written by www.mbsm.pro | 2 February 2022



Private Picture Copyright : WWW.MBSM.PRO

Mbsm.pro, Compressor, R290, 0.110Kg, SC15CNX, 15,28cm³, LBP, 230V, Hermetic piston compressors, 5/8 Hp, 104h 8568, 104h8568

Mbsm.pro, Daikin, compressor , R22/R407C

Category: compressor

written by www.mbsm.pro | 2 February 2022

3 Model Standard Dimension (Refrigerant R22/R600a)

Model	Capacity (kW)	Capacity (ton)	Capacity (Btu/h)	Capacity (kcal/h)	Capacity (hp)	Capacity (CV)	Capacity (PS)	Capacity (kW)	Capacity (ton)	Capacity (Btu/h)	Capacity (kcal/h)	Capacity (hp)	Capacity (CV)	Capacity (PS)
JT90GAJV1L	9.0	2.6	30800	13200	40.0	29.8	29.8	9.0	2.6	30800	13200	40.0	29.8	29.8
JT95BHHY1L	9.5	2.7	32000	13600	41.0	30.0	30.0	9.5	2.7	32000	13600	41.0	30.0	30.0
JT100GABY1L	10.0	2.8	33200	14000	42.0	30.2	30.2	10.0	2.8	33200	14000	42.0	30.2	30.2

3 Model Standard Dimension (Refrigerant R22)

Model	Capacity (kW)	Capacity (ton)	Capacity (Btu/h)	Capacity (kcal/h)	Capacity (hp)	Capacity (CV)	Capacity (PS)	Capacity (kW)	Capacity (ton)	Capacity (Btu/h)	Capacity (kcal/h)	Capacity (hp)	Capacity (CV)	Capacity (PS)
JT100GABY1L 10000 BTU/h	JT100-05	5.0	1.4	13200	5600	14.0	10.2	10.2	5.0	1.4	13200	5600	14.0	10.2
	JT100-06	6.0	1.7	16400	6800	17.0	12.3	12.3	6.0	1.7	16400	6800	17.0	12.3
	JT100-08	8.0	2.2	21600	9000	22.0	15.8	15.8	8.0	2.2	21600	9000	22.0	15.8
	JT100-10	10.0	2.8	26800	11200	28.0	20.3	20.3	10.0	2.8	26800	11200	28.0	20.3
	JT100-12	12.0	3.3	32000	13400	33.0	23.8	23.8	12.0	3.3	32000	13400	33.0	23.8
JT120GABY1L 12000 BTU/h	JT120-05	5.0	1.4	13200	5600	14.0	10.2	10.2	5.0	1.4	13200	5600	14.0	10.2
	JT120-06	6.0	1.7	16400	6800	17.0	12.3	12.3	6.0	1.7	16400	6800	17.0	12.3
	JT120-08	8.0	2.2	21600	9000	22.0	15.8	15.8	8.0	2.2	21600	9000	22.0	15.8
	JT120-10	10.0	2.8	26800	11200	28.0	20.3	20.3	10.0	2.8	26800	11200	28.0	20.3
	JT120-12	12.0	3.3	32000	13400	33.0	23.8	23.8	12.0	3.3	32000	13400	33.0	23.8
JT140GABY1L 14000 BTU/h	JT140-05	5.0	1.4	13200	5600	14.0	10.2	10.2	5.0	1.4	13200	5600	14.0	10.2
	JT140-06	6.0	1.7	16400	6800	17.0	12.3	12.3	6.0	1.7	16400	6800	17.0	12.3
	JT140-08	8.0	2.2	21600	9000	22.0	15.8	15.8	8.0	2.2	21600	9000	22.0	15.8
	JT140-10	10.0	2.8	26800	11200	28.0	20.3	20.3	10.0	2.8	26800	11200	28.0	20.3
	JT140-12	12.0	3.3	32000	13400	33.0	23.8	23.8	12.0	3.3	32000	13400	33.0	23.8
JT160GABY1L 16000 BTU/h	JT160-05	5.0	1.4	13200	5600	14.0	10.2	10.2	5.0	1.4	13200	5600	14.0	10.2
	JT160-06	6.0	1.7	16400	6800	17.0	12.3	12.3	6.0	1.7	16400	6800	17.0	12.3
	JT160-08	8.0	2.2	21600	9000	22.0	15.8	15.8	8.0	2.2	21600	9000	22.0	15.8
	JT160-10	10.0	2.8	26800	11200	28.0	20.3	20.3	10.0	2.8	26800	11200	28.0	20.3
	JT160-12	12.0	3.3	32000	13400	33.0	23.8	23.8	12.0	3.3	32000	13400	33.0	23.8
JT180GABY1L 18000 BTU/h	JT180-05	5.0	1.4	13200	5600	14.0	10.2	10.2	5.0	1.4	13200	5600	14.0	10.2
	JT180-06	6.0	1.7	16400	6800	17.0	12.3	12.3	6.0	1.7	16400	6800	17.0	12.3
	JT180-08	8.0	2.2	21600	9000	22.0	15.8	15.8	8.0	2.2	21600	9000	22.0	15.8
	JT180-10	10.0	2.8	26800	11200	28.0	20.3	20.3	10.0	2.8	26800	11200	28.0	20.3
	JT180-12	12.0	3.3	32000	13400	33.0	23.8	23.8	12.0	3.3	32000	13400	33.0	23.8
JT200GABY1L 20000 BTU/h	JT200-05	5.0	1.4	13200	5600	14.0	10.2	10.2	5.0	1.4	13200	5600	14.0	10.2
	JT200-06	6.0	1.7	16400	6800	17.0	12.3	12.3	6.0	1.7	16400	6800	17.0	12.3
	JT200-08	8.0	2.2	21600	9000	22.0	15.8	15.8	8.0	2.2	21600	9000	22.0	15.8
	JT200-10	10.0	2.8	26800	11200	28.0	20.3	20.3	10.0	2.8	26800	11200	28.0	20.3
	JT200-12	12.0	3.3	32000	13400	33.0	23.8	23.8	12.0	3.3	32000	13400	33.0	23.8
JT220GABY1L 22000 BTU/h	JT220-05	5.0	1.4	13200	5600	14.0	10.2	10.2	5.0	1.4	13200	5600	14.0	10.2
	JT220-06	6.0	1.7	16400	6800	17.0	12.3	12.3	6.0	1.7	16400	6800	17.0	12.3
	JT220-08	8.0	2.2	21600	9000	22.0	15.8	15.8	8.0	2.2	21600	9000	22.0	15.8
	JT220-10	10.0	2.8	26800	11200	28.0	20.3	20.3	10.0	2.8	26800	11200	28.0	20.3
	JT220-12	12.0	3.3	32000	13400	33.0	23.8	23.8	12.0	3.3	32000	13400	33.0	23.8
JT240GABY1L 24000 BTU/h	JT240-05	5.0	1.4	13200	5600	14.0	10.2	10.2	5.0	1.4	13200	5600	14.0	10.2
	JT240-06	6.0	1.7	16400	6800	17.0	12.3	12.3	6.0	1.7	16400	6800	17.0	12.3
	JT240-08	8.0	2.2	21600	9000	22.0	15.8	15.8	8.0	2.2	21600	9000	22.0	15.8
	JT240-10	10.0	2.8	26800	11200	28.0	20.3	20.3	10.0	2.8	26800	11200	28.0	20.3
	JT240-12	12.0	3.3	32000	13400	33.0	23.8	23.8	12.0	3.3	32000	13400	33.0	23.8
JT260GABY1L 26000 BTU/h	JT260-05	5.0	1.4	13200	5600	14.0	10.2	10.2	5.0	1.4	13200	5600	14.0	10.2
	JT260-06	6.0	1.7	16400	6800	17.0	12.3	12.3	6.0	1.7	16400	6800	17.0	12.3
	JT260-08	8.0	2.2	21600	9000	22.0	15.8	15.8	8.0	2.2	21600	9000	22.0	15.8
	JT260-10	10.0	2.8	26800	11200	28.0	20.3	20.3	10.0	2.8	26800	11200	28.0	20.3
	JT260-12	12.0	3.3	32000	13400	33.0	23.8	23.8	12.0	3.3	32000	13400	33.0	23.8
JT280GABY1L 28000 BTU/h	JT280-05	5.0	1.4	13200	5600	14.0	10.2	10.2	5.0	1.4	13200	5600	14.0	10.2
	JT280-06	6.0	1.7	16400	6800	17.0	12.3	12.3	6.0	1.7	16400	6800	17.0	12.3
	JT280-08	8.0	2.2	21600	9000	22.0	15.8	15.8	8.0	2.2	21600	9000	22.0	15.8
	JT280-10	10.0	2.8	26800	11200	28.0	20.3	20.3	10.0	2.8	26800	11200	28.0	20.3
	JT280-12	12.0	3.3	32000	13400	33.0	23.8	23.8	12.0	3.3	32000	13400	33.0	23.8
JT300GABY1L 30000 BTU/h	JT300-05	5.0	1.4	13200	5600	14.0	10.2	10.2	5.0	1.4	13200	5600	14.0	10.2
	JT300-06	6.0	1.7	16400	6800	17.0	12.3	12.3	6.0	1.7	16400	6800	17.0	12.3
	JT300-08	8.0	2.2	21600	9000	22.0	15.8	15.8	8.0	2.2	21600	9000	22.0	15.8
	JT300-10	10.0	2.8	26800	11200	28.0	20.3	20.3	10.0	2.8	26800	11200	28.0	20.3
	JT300-12	12.0	3.3	32000	13400	33.0	23.8	23.8	12.0	3.3	32000	13400	33.0	23.8

JT150BCBY1L JT150BK-YE JT160BCBY1L JT170GABY1L JT170FDKYE JT300D-YE JT300D-P1YE
JT300D-YE @ JT315D-Y1L JT335D-Y1L JT100BHVYE JT100BHV JT100BCBV1L JT100GABV1L
2YC45BXD 2YC45JXD 2YC45BXD 1GDY23AXD 2YC32VXD JT1FCVDKTYR JT1GCVDKYR 6T55TAC5YE
6T55WAC5YE JT170G-K1YE JT170G-KYE@BA etc. Mainly used for refrigeration
equipment such as air conditioners. Varieties ***, ***, ***, service is
exhausted, welcome to call to discuss!

Daikin Compressor Features: JT170G-K1YE JT170G-KYE@BA

Daikin Compressor Features: Small and light. High reliability and easy to use.

?Due to the small diameter and slenderness of the compressor cylinder, it
provides a good choice for the small and lightweight outdoor unit.

?In order to save the flexibility of space and location design, a new model with
three-legged chassis is added on the basis of the original four-legged
chassis. Give users more choices.

?The number of compressor parts is small and the reliability is high.

?Compressors can withstand the most brutal tests of heat pump systems.

?Only the protection device of the motor in the compressor is built-in, and
other protections are matched by the system. This allows system designers to set
protections in the system as needed, allowing product designers to better
control the compressors used.

JT300DJT160B-NYE JT160B-NFYE New original Daikin marine air conditioner
refrigeration equipment compressor A-Y1L JT335DA-Y1L New original Daikin
compressor R407CJT100BDVTYE JT100FBVD JT100FAVD New original Daikin inverter air
conditioner compressor JT170G-K1YE JT170FDKYE JT170FBKYE New original Daikin air
conditioner compressor Machine JT160BCBY1L JT160GABY1L Original Daikin 5 HP
Central Air Conditioning Compressor VRV3 generation RHXYQ14PY1 inverter
compressor original new JT160GAJY1L Daikin 5 hp central air conditioning
compressor three feet return air pipe upward R22 original 12 hp JT335D-P1YE
JT300D-P1YE Daikin central air conditioning compressor 10 hp JT315D
Original 5 HP JT160GABY1L JT170GABY1L Daikin Air Conditioning Compressor Heat
Pump Straight Tube Daikin Parallel Compressor JT300DA-YE Daikin 10P12 HP Air
Conditioning Compressor R40JT100FBVD JT100BHV JT100G-VDL@S Original Daikin
Inverter Air Conditioning Refrigeration Compressor JT140G-P4Y1@K Brand New
Original 5 Daikin Fixed Frequency Air Conditioning Compressor R410A 3 Foot
Daikin 5P JT160BCBY1L Panasonic C-SB373H8A Air Conditioning Air Energy Heat Pump
Compressor C-SB453



DAIKIN
COMPRESSOR

MODEL
POWER
SOURCE

JT3550J-TY1@K2
THREE PHASE
380-415 V 50 Hz

REF. OIL
REF. NO.
DP-AP
SP

R410A
DAPHNE FVC68D
06001952

H
H

4.17 MPa L 2.5 MPa
15.0 MPa L 7.0 MPa

MADE IN CHINA
XIAN DAIKIN QING AN COMPRESSOR CO., LTD.

U
V
W

PHASE ARRANGEMENT

CEC RoHS

WARNING

ELECTRIC SHOCK HAZARD
USE THIS COMPRESSOR ON A GROUNDING SYSTEM ONLY.
TURN POWER OFF BEFORE MAINTENANCE.
REPLACE TERMINAL COVER BEFORE REPAIR.

INJURY HAZARD
WEAR PROTECTIVE GLOVES.

EXPLOSION OR FIRE HAZARD
DO NOT USE TOOLS.
DO NOT USE OPEN FLAME.
DO NOT CONTAIN REFRIGERANT GAS IN VESSEL.
DO NOT EXPOSE VESSEL TO HIGH TEMPERATURE.
DO NOT USE VESSEL TO STORE FLAMMABLE GAS.
DO NOT USE VESSEL TO STORE TOXIC GAS.

BURN HAZARD
DO NOT TOUCH OR BURN HAND DURING USE.
DO NOT TOUCH OR BURN HAND DURING USE.