

Mbsm.pro, Danfoss, Compressor, MT100HS4D, 8.3HP, R22, 380V, 3PH

Category: compressor

written by www.mbsm.pro | 13 January 2022



Private Picture Copyright: WWW.MBSM.PRO

Mbsm.pro, Danfoss, Compressor, MT100HS4D, 8.3HP, R22, 380V, 3PH

Mbsm.pro, COMPRESSOR, 1/3 HP ++ (big), HERMETIC, TECUMSEH, CAE4440Y, AE4440Y, HBP, R134a, 220-240V, 50 Hz, 1 PH, CSIR

Category: compressor

written by www.mbsm.pro | 13 January 2022




Private Picture Copyright: WWW.MBSM.PRO

Mbsm.pro, COMPRESSOR, 1/3 HP ++ (big), HERMETIC, TECUMSEH, CAE4440Y, AE4440Y, HBP, R134a, 220-240V, 50 Hz, 1 PH, CSIR

FIVE method of CONNECTING wires

Category: Pictures

written by www.mbsm.pro | 13 January 2022



Mbsm.pro, DL25YE-4, 1/4 hp , 1Ph,
DAEW00,COMPRESSOR R12, CSR,
compressor, LBp, 220V 60hz

Category: compressor
written by www.mbsm.pro | 13 January 2022



Private Picture Copyright : WWW.MBSM.PRO

Private Picture Copyright : WWW.MBSM.PRO

Mbsm.pro, DL25YE-4, 1/4 hp , 1Ph, DAEWOO,COMPRESSOR, R12, CSR, compressor, LBp, 220V 60hz

Mbsm.pro, Compressor, Embraco, Aspera, EMY26CLC, LBP, R600a, 220 – 240V/1/50Hz, 1/12 HP, RSIR, LRA 7.8 A, 83 Wat

Category: compressor

written by www.mbsm.pro | 13 January 2022



Private Picture Copyright: WWW.MBSM.PRO

Compressor, Embraco, Aspera, EMY26CLC, LBP, R600a, 220 – 240V/1/50Hz, 1/12 HP, RSIR, LRA 7.8 A, 83 Wat

Mbsm.pro, compressor, 1/4HP,
Refrigeration, R134A , Refrigerator,
freezer, QD91H, LBP

Category: compressor

written by www.mbsm.pro | 13 January 2022


Mbsm.pro, compressor, 1/4HP, Refrigeration, R134A , Refrigerator, freezer,
QD91H, LBP

Mbsm.pro, Freezer no frost, Alaska,
Freezer vertical, 7 gavetas, 239L,
Compressor 1/4 Hp, HSL27YE-5, DAEW00

COMPRESSOR, R134a, 220G, 220V, 180W, 1hp, CSIR

Category: compressor, Freezer

written by www.mbsm.pro | 13 January 2022



Private Picture Copyright : WWW.MBSM.PRO

Freezer no frost, Alaska, Freezer vertical, 7 gavetas, 239L, Compressor 1/4 Hp, HSL27YE-5, DAEWOO COMPRESSOR, R134a, 220G, 220V, 180W

Mbsm.pro, Compressor Necchi, Esm5, 1/5 Hp, R12, Replaced by , COMPRESSOR, DANFOSS, TL 5G, 1/6++ (1/5 hp) HP, MBP / HBP -R134a, 220-240V/1/50/60Hz, displacement 5.08 cm³, motor type RSCR

Category: compressor

written by www.mbsm.pro | 13 January 2022

Mbsm.pro, Compressor Necchi, Esm5, 1/5 Hp, R12, Replaced by , COMPRESSOR,

DANFOSS,TL 5G, 1/6++ (1/5 hp) HP, MBP / HBP -R134a, 220-240V/1/50/60Hz, displacement 5.08 cm3, motor type RSCR

Mbsm.pro, original, jiaXipera, compressor, NB1113Y, NT1113Y, T1113Y, TX1113Y, 1/6 hp, 154w, r600, RSIR

Category: compressor

written by www.mbsm.pro | 13 January 2022

Product Description

Refrigeration R600A Jiaxipera Domestic Refrigerator Commercial Compressor
supply refrigeration parts refrigerator compressor
fridge compressor, refrigerator compressor, freezer compressor,refrigeration compressor.

Compressor Model	Displ. (cm3)	Cooling Type	Motor Type	Vol./Fre. / (V~/Hz)	Capacity(W)	COP (W/W)	Capacitor (μF)	Certificate				
ASHRAE (-23.3℃)	CECOMAF (-25℃)	SWP (-28/40℃)	ASHRAE (-23.3℃)	CECOMAF (-25℃)	SWP (-28/40℃)							
N1080Y	5.5	ST	RSIR	220-240~/50	95	71	/	1.40	1.09	/	/	VDE,CCC
N1090Y	6.0	ST	RSIR	220-240~/50	100	75	/	1.40	1.09	/	/	VDE,CCC
N1110Y	6.7	ST	RSIR	220-240~/50	114	86	/	1.40	1.09	/	/	VDE,CCC
N1111Y	7.2	ST	RSIR	220-240~/50	130	98	/	1.40	1.09	/	/	VDE,CCC
N1112Y	8.1	ST	RSIR	220-240~/50	140	105	/	1.40	1.09	/	/	VDE,CCC
N1113Y	8.9	ST	RSIR	220-240~/50	154	114	/	1.40	1.09	/	/	VDE,CCC
N1114Y	9.6	ST	RSIR	220-240~/50	168	126	/	1.42	1.11	/	/	VDE,CCC
NT1112Y	8.10	ST	RSCR	220-240~/50	140	105	/	1.56	1.22	/	4.0	VDE,CCC
NT1113Y	8.9	ST	RSCR	220-240~/50	154	116	/	1.56	1.22	/	4.0	VDE,CCC
NT1114Y	9.6	ST	RSCR	220-240~/50	170	128	/	1.56	1.22	/	4.0/4.5	VDE,CCC
NT1117Y	11.2	ST	RSCR	220-240~/50	198	149	/	1.56	1.22	/	4.0	CCC
NU1080Y	5.5	ST	RSCR	220-240~/50	95	71	/	1.55	1.21	/	3.0	VDE,CCC
NU1090Y	6.0	ST	RSCR	220-240~/50	102	77	/	1.58	1.23	/	4.0	VDE,CCC
NU1110Y	6.70	ST	RSCR	220-240~/50	115	86	/	1.58	1.23	/	4.0	VDE,CCC
NU1111Y	7.2	ST	RSCR	220-240~/50	130	98	/	1.62	1.26	/	3.5/4.0	VDE,CCC
NU1112Y	8.10	ST	RSCR	220-240~/50	140	105	/	1.62	1.26	/	4.0	VDE,CCC
NU1113Y	8.9	ST	RSCR	220-240~/50	154	116	/	1.62	1.26	/	4.0	VDE,CCC
NU1114Y	9.6	ST	RSCR	220-240~/50	170	128	/	1.62	1.26	/	4.0/4.5	VDE,CCC
NU1116Y	10.5	ST	RSCR	220-240~/50	186	140	/	1.60	1.25	/	4.5	VDE,CCC
NU1112GY	8.10	ST	RSIR/RSCR	220-240~/50	140	105	/	1.54/1.62	1.20/1.26	/	3.5/4.0	VDE,CCC
NU1113GY	8.90	ST	RSIR/RSCR	220-240~/50	154	116	/	1.54/1.62	1.20/1.26	/	4.0	VDE,CCC
NS1060Y	4.2	ST	RSCR	220-240~/50	65	49	/	1.60	1.25	/	2.0	VDE,CCC
NS1080Y	5.5	ST	RSCR	220-240~/50	95	71	/	1.62	1.26	/	3.0	VDE,CCC
NS1090Y	6.0	ST	RSCR	220-240~/50	105	79	/	1.66	1.29	/	2.0/3.0	VDE,CCC
NS1110Y	6.7	ST	RSCR	220-240~/50	116	87	/	1.66	1.29	/	3.0/4.0	VDE,CCC
NS1111Y	7.2	ST	RSCR	220-240~/50	130	98	/	1.66	1.29	/	3.5/4.0	VDE,CCC
NS1112Y	8.1	ST	RSCR	220-240~/50	142	107	/	1.68	1.31	/	3.5/4.0	VDE,CCC
NS1113Y	8.9	ST	RSCR	220-240~/50	155	116	/	1.68	1.31	/	4.0	VDE,CCC
NS1114Y	9.6	ST	RSCR	220-240~/50	172	129	/	1.68	1.31	/	4.0	VDE,CCC
NS1116Y	10.5	ST	RSCR	220-240~/50	186	140	/	1.68	1.31	/	4.0/5.0	VDE,CCC
NS1117Y	11.2	ST	RSCR	220-240~/50	198	149	/	1.68	1.31	/	4.0	CCC
NC1090Y	6.0	ST	RSCR	220-240~/50	105	79	/	1.73	1.35	/	2.5	VDE,CCC
NC1110Y	6.7	ST	RSCR	220-240~/50	116	87	/	1.75	1.37	/	3.0/4.0	VDE,CCC
NC1111Y	7.2	ST	RSCR	220-240~/50	128	96	/	1.75	1.37	/	4.0	VDE,CCC
NC1112Y	8.1	ST	RSCR	220-240~/50	142	107	/	1.75	1.37	/	4.0	VDE,CCC
NC1113Y	8.9	ST	RSCR	220-240~/50	155	116	/	1.75	1.37	/	4.0	VDE,CCC
NC1114Y	9.6	ST	RSCR	220-240~/50	172	129	/	1.75	1.37	/	3.0/4.0	VDE,CCC

NC1116Y	10.5	ST	RSCR	220-240~/50 186	140	/	1.75	1.37	/	3.0	VDE,CCC
NX1080Y	5.5	ST	RSCR	220-240~/50 96	72	/	1.83	1.43	/	2.0	VDE,CCC
NX1090Y	6.0	ST	RSCR	220-240~/50 108	81	/	1.83	1.43	/	2.5	VDE,CCC
NX1110Y	6.7	ST	RSCR	220-240~/50 117	88	/	1.83	1.43	/	2.5	VDE,CCC
NX1111Y	7.2	ST	RSCR	220-240~/50 130	98	/	1.83	1.43	/	3.0	VDE,CCC
NX1112Y	8.1	ST	RSCR	220-240~/50 145	109	/	1.83	1.43	/	3.0	VDE,CCC
NX1113Y	8.9	ST	RSCR	220-240~/50 155	116	/	1.83	1.43	/	2.5	VDE,CCC
NX1114Y	9.6	ST	RSCR	220-240~/50 172	129	/	1.83	1.43	/	4.0	VDE,CCC
NB1080Y	5.5	ST	RSCR	220-240~/50 96	72	84	1.88	1.47	2.02	2.0	VDE,CCC
NB1090Y	6.0	ST	RSCR	220-240~/50 108	81	95	1.88	1.47	2.02	2.5	VDE,CCC
NB1110Y	6.7	ST	RSCR	220-240~/50 117	88	105	1.90	1.48	2.02	2.5	VDE,CCC
NB1111Y	7.2	ST	RSCR	220-240~/50 130	98	114	1.90	1.48	2.02	3.0	VDE,CCC
NB1112Y	8.1	ST	RSCR	220-240~/50 145	109	127	1.90	1.48	2.02	3.0	VDE,CCC
NB1113Y	8.9	ST	RSCR	220-240~/50 155	116	136	1.90	1.48	2.02	2.5	VDE,CCC
NB1114Y	9.6	ST	RSCR	220-240~/50 172	129	151	1.90	1.48	2.02	4.0	VDE,CCC
NB1116Y	10.5	ST	RSCR	220-240~/50 186	140	163	1.90	1.48	2.02	4.0	VDE,CCC
NE1080Y	5.5	ST	RSCR	220-240~/50 96	72	84	1.93	1.51	2.04	2.0	CCC
NE1090Y	6.0	ST	RSCR	220-240~/50 108	81	95	1.93	1.51	2.04	2.5	
NE1110Y	6.7	ST	RSCR	220-240~/50 117	88	105	1.95	1.52	2.04	2.5	CCC
NE1111Y	7.2	ST	RSCR	220-240~/50 130	98	114	1.95	1.52	2.04	3.0	CCC
NE1112Y	8.1	ST	RSCR	220-240~/50 145	109	127	1.95	1.52	2.04	3.0	CCC

Le modèle que nous pouvons fournir:

Fiche
 technique du
 compresseur
 frigorifique
 série T
 R600a (LBP)

Compresseur	Dépl.	Type De moteur	Vol./Fre.	Capacité de refroidissement	CONFÉRENCE des parties	Matériel deD'enroulement	Certificat					
ASHRAE	CECOMAF	ASHRAE	CECOMAF									
W	BTU/h (Cm3)	Kcal	W (V ~/Hz)	W/W Principal/Auxiliaire.	BTU/Wh	W/W						
T1090Y	6	RSIR	220 ~ 240/50	100	341	86	75	1.42	4.85	1.11	Al/Al VDE, CCC	
T1110Y	6.7	RSIR	220 ~ 240/50	115	392	99	86	1.45	4.95	1.13	Al/Al VDE, CCC	
T1111Y	7.2	RSIR	220 ~ 240/51	126	430	108	95	1.4	4.78	1.09	Al/Al VDE, CCC	
T1112Y	8.1	RSIR	220 ~ 240/50	140	478	120	105	1.42	4.85	1.11	Al/Al VDE, CCC	
T1113Y	8.9	RSIR	220 ~ 240/50	152	519	131	114	1.42	4.85	1.11	Al/Al VDE, CCC	
T1114Y	9.6	RSIR	220 ~ 240/50	168	573	144	126	1.42	4.85	1.11	Al/Al VDE, CCC	
T1116Y	10.5	RSIR	220 ~ 240/50	184	628	158	138	1.4	4.78	1.09	Al/Al VDE, CCC	



Private Picture Copyright: WWW.MBSM.PRO



Private Picture Copyright: WWW.MBSM.PRO

Mbsm_dot_pro_private_PDF_nt1113yTélécharger

Mbsm.pro, Scroll, Danfoss,
HRP051T4LP6, compressors, Hermetic,
49.15 kBtu/h, R22, R407C, 4 1/4Hp,
3Ph, POE, Lra 60A

Category: compressor

written by www.mbsm.pro | 13 January 2022

bsm.pro, Scroll, Danfoss, HRP051T4LP6, compressors, Hermetic, 49.15 kBtu/h, R22,
R407C, 4 1/4Hp, 3Ph, POE, Lra 60A