

Mbsm.pro, Toshiba, R22, pH170g1c-4dzde, Air Conditioner, Compressor, 1 ton, 12000 btu, 1.5 hp

Category: air conditioner

written by www.mbsm.pro | 8 May 2023



Private Picture Copyright : WWW.MBSM.PRO

SPECIFICATIONS FOR PH170G1C-3FTDU1

Products Details	Models: PH170G1C-3FTDU1 Type Hermetic	
	Power	Phase 1
	Horse Power	HP 1.5

Main performance parameters	Input Power	W	208-230/1/60
	REFRIGERANT		R22
	SIZE		54.0/35.0
Physial parameters	Height	MM	285
	Weight	KG	160
	Q'ty / Pallet	PIECE	18

- Température d'évaporation : 7,2 °/45 °F
- Temp. de condensation : 54,4 °/ 130 °F
- Temp. de gaz de retour : 35,0 °/ 95 °F
- Temp. ambiante : 35,0 °/ 95 °F
- F 115 °F
- Table de conversion : Kcal/hx 1,163 = W W x 3,412 = Btu/h

COMPRESSORS ARE PERFECT FOR RESIDENTIAL AND COMMERCIAL AIR CONDITIONING.

FEATURES:

- Evaporating temp: 7.2°/45°F
- Condensing temp: 54.4°/ 130°F
- Return gas temp: 35.0°/ 95°F
- Ambient temp: 35.0°/ 95°F
- Liquid temp: 46.1°/ 115°F
- Conversion table:
Kcal/h x 1.163 = W
W x 3.412 = Btu/h

R22 COMPRESSOR MODEL

REF COMPRESSOR MODEL	POWER	CAPACITY (Tons)	ERA	RLA (A)	LLR (A)	CAPACITOR	MOTOR TYPE
PH100010-000001	11000Btu/h 1 phase	8010	10.01	7.36	37.6	30	PSC
PH170010-0001	11000Btu/h 1 phase	11042	10.00	9.58	57	50	PSC
PH130110-000002	20000Btu/h 1 phase	8434	10.70	8.40	30	30	PSC
PH170010-000001	20000Btu/h 1 phase	12007	10.00	9.21	36.7	30	PSC
PH160020-07101	20000Btu/h 1 phase	17047	10.00	7.8	29.0	40	PSC
PH160020-07101	20000Btu/h 1 phase	21022	10.0	9.72	33.0	50	PSC
PH131230-000001	20000Btu/h 1 phase	24133	10.00	10.0	44	50	PSC
PH161230-0070	20000Btu/h 1 phase	26219	10.70	11.65	50	50	PSC
PH160020-0070	20000Btu/h 1 phase	28786	10.00	11	50.00	50	PSC

R22 COMPRESSOR MODEL

REF COMPRESSOR MODEL	DIMENSION (IN)					LOADING QUANTITY PER PALLET	CERTIFICATIONS
	A	B	C	D	E		
PH100010-000001	10.47	9.06	4.01	2.17	3.70	80	UL & CSA
PH170010-0001	11.22	10.10	4.37	2.17	3.70	80	UL & CSA
PH130110-000002	11.22	9.04	4.01	2.17	3.70	80	UL
PH170010-000001	11.22	9.04	4.37	2.17	3.70	80	UL
PH160020-07101	11.00	9.01	5.10	3.10	4.55	40	UL & CSA
PH160020-07101	12.24	8.00	5.00	3.10	4.55	40	UL
PH160020-0000	13.11	12.04	5.70	3.10	4.00	40	UL & CSA
PH161230-0070	13.08	13.10	5.70	3.10	4.00	40	UL & CSA
PH160020-0070	14.01	13.10	5.70	3.10	4.00	40	UL

ENVIRONMENTALLY SMART

Private Picture Copyright : WWW.MBSM.PRO



Private Picture Copyright : WWW.MBSM.PRO