

Mbsm.pro, American, Gibson,
refrigerator, SE209-12, SE 209-12,
SE209, R12, 527 L, 260 w, Compressor,
1/4 hp++, 1/3 hp-, AEA3430AXA /
AEA4430AXA

Category: compressor, Refrigerator

written by www.mbsm.pro | 3 October 2022



Private Picture Copyright : WWW.MBSM.PRO

Replaces Copeland AFG2-0026-SAA and JFC1-0025-SAA, Embraco FF10BKW, and Tecumseh AEA1410AXA and AEA3430AXA.

Motor: Resistive Start Inductive Run & Captive Start Inductive Run (RSIR/CSIR)

Evaporating Temperatures: -10°F to 45°F

The same compressor Embraco Universal FF10BK1 R12 Refrigeration

Compressor. Low, Medium & High Back Pressure. 1/4+ Nominal Motor HP. For use with refrigerators, ice makers, frozen food cabinets, frozen food display cases, display windows, etc.

Product Specifications

Volts (V):	220
Motor Type:	RSIR/CSIR
Locked Rotor Amps (LRA):	14.5
Horsepower (HP):	1/4+
HP (Nominal):	1/4+
Volts:	220
BTU Capacity LBP & MBP:	915
BTU Capacity HBP:	3100/3240
Required Refrigerant :	R12
Starting Torque:	Normal
BTU Capacity LBP & MBP:	915

• Similar Products Found

Replaces Old Numbers: 103U1905, 103U1915, 103U191501, 103U1955, 103U1965, 103U196501, 20106020, 20106025, 20106038, 20146677, 2154561, 2154562, 30-FF10BKW, 4318109, 4392052, 5303916022, 5303916411, 5303917192, 5303917938, 5303917939, 5303917941, 5304428316, 5304428317, 777980047027, A5160A, A5170A, AE1390A, AE1410CR, AE14ZF11, AE3425A, AEZ1380B, AF045, AT235, AT43, CB200, CB250, CP200, CP250, E3121A, FF10A, FF10BK, FF10BKW, FFE9A, FFS9A, FGS95AW, FR10BX, MH310, ML090, PW9K18, R7736201, SE108-1, SE109-1, SE208-1, SE209-1, SG108-1, SG109-1, SG208-1, SG209-1, VC1805A, WR87X204, YB2500C



REDMI NOTE 8
AI QUAD CAMERA

Private Picture Copyright : WWW.MBSM.PRO

ZR 57 K*	AC-R22	200-230/60/3	57,200	AVB5558EXT
ZR 57 K*	AC-R22	380-460/60/3	57,200	AVD5558EXG
ZR 61 K*	AC-R22	208-230/60/1	61,200	AGA5561EXN
ZR 61 K*	AC-R22	200-230/60/3	61,000	AGA5561EXT
ZR 61 K*	AC-R22	380-460/60/3	61,000	AGC5561EXG
ZR 11 M*	AC-R22	200-230/60/3	108,000	NA
ZR 11 M*	AC-R22	380-460/60/3	108,000	NA
ZR 12 M*	AC-R22	200-230/60/3	125,000	NA
ZR 12 M*	AC-R22	380-460/60/3	125,000	NA

Copeland Model	App-Ref	Volt/Hz/Ph	Btu/h	Tecumseh Model
HT-R12				
ARC *- 0017	HT-R12	115/60/1	1540	AEA3414AXA
ARD *- 0020	HT-R12	115/60/1	1940	AEA3417AXA
ARE *- 0023	HT-R12	115/60/1	2800	AEA3425AXA
ARF *- 0025	HT-R12	115/60/1	3100	AEA3430AXA / AEA4430AXA
ARG *- 0033	HT-R12	115/60/1	4130	AEA3440AXA / AEA4440AXA
ARH *- 0049	HT-R12	115/60/1	5400	AJA4461AXA
ARK *- 0050	HT-R12	115/60/1	5760	AJA4461AXA
ARM *- 0075	HT-R12	115/60/1	9150	AJA4492AXA
ARM *- 0075	HT-R12	208-230/60/1	8060	AJA4492AXD
ARM *- 0100	HT-R12	115/60/1	12200	NA
ARN *- 0100	HT-R12	208-230/60/1	12200	AJA4512AXD

*Denotes number in Copeland model designation not significant in determining replacement
in Copeland or Tecumseh BTU ratings may have been adjusted to reflect similar test conditions.
Replacement rating comparisons are +/- 10%.

27

Private Picture Copyright : WWW.MBSM.PRO



: WWW.MBSM.PRO



Private Picture Copyright : WWW.MBSM.PRO

40 V	80 Hz	FRECUENCIA NOMINAL:	50 Hz	80 Hz	٦٠ هرتز
56 W	230 V	VOLTAJE NOMINAL:	220/2	230 V	٢٣٠ فولت
17 W	280 W	ENTRADA NOMINAL:	235-2	260 W	٢٦٠ واط
15 A	475 W	ENTRADA NOMINAL DEL DESCONGELADOR:	435-517 W	475 W	٤٧٥ واط
	2.07 A	CORRIENTE NOMINAL PARA EL DESCONGELADOR:	1.98-2.15 A	2.07 A	٢,٠٧ أمبير
	80%	TIEMPO DE FUNCIONAMIENTO (a 90° F.-32° C.):	82%	80%	٨٠٪
N.T.		CLASIFICACION DE LA TEMPERATURA:	N.T.		
~		TIPO DE SUMINISTRO:	~		
40/80 W		TIPO DE BOMBILLA:	40/80 W		
7.5 A		TIPO DE FUSIBLE:	7.5 A		
8.8 kg		PRODUCCION DE HIELO: (24 horas)	8.8 kg		
3.2 kWh		CONSUMO DE CORRIENTE: (24 horas)	3.2 kWh		٣,٢ كيلووات ساعة
527 litres		CAPACIDAD DE ALMACENAMIENTO:	527 litres		
		Made in U.S.A.			

Private Picture Copyright : WWW.MBSM.PRO

Mbsm_dot_pro_private_PDF_Mbsm_dot_pro_private_PDF_Se209Télécharger