

Toeflex Ltd , Pw4.0vk , LMBP serie,1/10 Hp , 1Phase , r134a refrigerant , refrigeration compressor ,220~240v Ac 50hz , 112W ,RSIR

Category: Non classé,Technologie,Tester ok

written by www.mbsm.pro | 30 April 2020

Toeflex Ltd , Pw4.0vk , LMBP serie,1/10 Hp , 1Phase , r134a refrigerant , refrigeration compressor ,220~240v Ac 50hz , 112W ,RSIR

AEA3440YXC ,Tecumseh Product Co ,HBP ,Moteur HP , 1Phase, 1/3HP , High Back Pressure ,R134a ,220-240V ~ 50Hz ,Reciprocating Compressor ,996W

Category: Technologie,Tester ok

written by www.mbsm.pro | 30 April 2020

AEA3440YXC ,HBP ,Moteur HP , 1HP, 1/HP , High Back Pressure ,R134a ,220-240V ~ 50Hz ,Reciprocating Compressor

Danfoss ,Fridge Compressor ,NL7FT , 1/4 HP ,R134a

Category: Non classé,Technologie,Tester ok

written by www.mbsm.pro | 30 April 2020

Danfoss ,Fridge Compressor ,NL7FT , 1/4 HP ,R134a

Compressor ELECTROLUX, CUBIGEL ,GP12TB ,Hermetic piston ,ACC ,HMBP , moteur HP , 3/8 HP++, 1/2 hp- , 1PH , R134A , Pression 1.7 Bar , 220V

Category: compressor,Technologie,Tester ok

written by www.mbsm.pro | 30 April 2020

	Model	Refr.	HP
▶ <input type="checkbox"/>	<u>GL45PB</u>	HMBP::R134a	1/6
▶ <input type="checkbox"/>	<u>GL45PB</u>	HMBP::R134a	1/6
▶ <input type="checkbox"/>	<u>GL45TB</u>	HMBP::R134a	1/6
▶ <input type="checkbox"/>	<u>GL60PB</u>	HMBP::R134a	1/5
▶ <input type="checkbox"/>	<u>GL60TB</u>	HMBP::R134a	1/5
▶ <input type="checkbox"/>	<u>GL80PB</u>	HMBP::R134a	1/5
▶ <input type="checkbox"/>	<u>GL80TB</u>	HMBP::R134a	F
▶ <input type="checkbox"/>	<u>GL90TB</u>	HMBP::R134a	1/4
▶ <input type="checkbox"/>	<u>GP12TB</u>	HMBP::R134a	3/8

Picture5 Mbsm Dot Pro : www.mbsm.pro

Private Picture Copyright : WWW.MBSM.PRO

Compressor ELECTROLUX, CUBIGEL GP12TB ,Hermetic piston ,ACC ,HMBP , moteur HP , 3/8 HP , 1PH , R134A , Pression 1.7 Bar

**QBH57C10GPX, 1/6HP ,RSIR,
Reciprocating Fixed Speed,**

Compressors, R134a, LBP ,PANASONIC SMALL REFRIGERATOR

Category: Solutions,Tester ok

written by www.mbsm.pro | 30 April 2020

QBH57C10GPX, 1/6HP ,RSIR, Reciprocating Fixed Speed, Compressors, R134a, LBP
,PANASONIC SMALL REFRIGERATOR

HERMETIC ,AW5524EK ,Compressor , 20,950 BTU ,230/1/60 R-22 ,: 220-240 V/50 Hz. , 1 Phase , 1.7458333333 TON

Category: Technologie,Tester ok

written by www.mbsm.pro | 30 April 2020

Electrical : 220-240 V/50 Hz. 1 Phase

Nominal Performance

Capacity 6,140 / – Watts

20,950 / – BTU/Hr

5,280 / – Kcal/Hr

Power Input 2,089 / – Watts

Locked Rotor Amps 51.30 / – Amps

Max Continuous Current – / – Amps

Rated Load Amps 9.64 / – Amps

COP 2.94 / – Watts / Watts

EER 10.03 / – BTU/W-Hr

Testing Conditions

Condensing Temperature 54.40 °C 129.9 °F

Evaporating Temperature 7.20 / – °C 45.0 / – °F

Liquid Temperature 46.10 °C 115.0 °F

Return Gas Temperature 35.00 °C 95.0 °F

Ambient Temperature 35.00 °C 95.0 °F

Application

Evaporating Temp. Range HBP, A/C @ 0.00 ° C to 13.00 ° C
(32.0° F to 55.4° F)

Heat Pump -23.30 ° C to 13.00 ° C
(-9.9° F to 55.4° F)

Refrigerant R22

Refrigerant Flow Control Capillary Tube

Compressor Cooling Fan

Compressor and Motor data

Compressor Type Reciprocating

Displacement 43.10 cc.

Oil Type Mineral Oil

Oil Charge 964 cc.

Motor Type P.S.C ; 2 Pole 2,850 / – r/m

Voltage Range 198-264/- Volts 50/- Hz.

Winding Resistance at 25 ° C

Start 2.52 Ohms

Run 1.24 Ohms

Weight with Oil 27.72 Kg.

Weight with Oil and Accessories 28.05 Kg.

Electrical Components

Motor Protector

Type Internal Overload

Model Number 4042KGE661-2

Open / Close 125-135 / 50-70 ° C

1st Cycle trip at 25 ° C 50.00 Amps(main) 30.00 Amps(start)

Motor Starter

Type Potential Relay

Model Number 4043KGE681-4(RVA3G6D)

Pick Up (max.) 180.00-195.00 Volts

Drop Out (min.) 40.00-90.00 Volts

Terminal Cover KGM 901-3

Start Capacitor 88-106 μ F 330 VAC.

Disch Resistor for Start Cap –

Run Capacitor 45 μ F 370/440 VAC.

Mounting Kit

Rubber Grommet 4007KGM905-2

Sleeve Grommet 4023KGM903-2

Washer –

Since we are constantly improving our product , the specification are subject to change without notice.

REV. DATE C / N No.

ECN 01-04-14 ECN 0515/13





Dot Pro : www.mbsm.pro

DOCUMENTATION PDF

Mbsm_dot_pro_private_pictureAW5524EKTélécharger

Compresseurs Embraco, ,EMU70HLC , R134a, 220 V, 50Hz, 1/5 HP, 149 watts , 180 mL

Category: Technologie,Tester ok

written by www.mbsm.pro | 30 April 2020

Compresseurs Embraco, ,EMU70HLC , R134a, 220 V, 50Hz, 1/5 HP, 149 watts , 0.17
kW (0.2214 BHP) ,180 mL

Tableau de conversion d'unités

Category: Technologie

written by www.mbsm.pro | 30 April 2020




Tableau de conversion d'unités

PREFIXES , CONVERSION ,FACTORS

Category: Technologie

written by www.mbsm.pro | 30 April 2020



PREFIXES , CONVERSION ,FACTORS

TLES6.5FT.3 ,Energy-optimized
,Tropical , R134a 220-240V ,50Hz ,
1/4 hp , COMPRESOR DANFOSS SECOP ,
183 W , LBP

Category: Technologie,Tester ok

written by www.mbsm.pro | 30 April 2020



Private Picture Copyright : WWW.MBSM.PRO

TLES6.5FT.3 ,Energy-optimized ,Tropical , R134a 220-240V ,50Hz , 1/4 hp ,
COMPRESOR DANFOSS SECOP