

Mitsubishi, Refrigeration, Compressor, for chiller, JH527YEB, 10HP, 380 à 420 V 50 Hz, 460 V 60 Hz, 29,7 kW, 74 kg, R22

Category: compressor, Non classé

written by www.mbsm.pro | 3 January 2021

Mitsubishi Refrigeration Compressor JH527YEB 10HP

Données techniques

Model	Horsepower	Power KW	Refrigeration capacity			Voltage	Weight kg	Highth mm
	HP		Frequenc y	KW	(kcal/h)			
JH512-Y	4HP	3.2	50Hz	13.1	11.3	N.T.Y.X. J	48.5	390.4
			60Hz	15.6	13.4			
JH513-Y	5HP	3.75	50Hz	14.3	12.3	N.T.Y.X. J	49	390.4
			60Hz	17	14.6			
JH515-Y	5.5HP	4.1	50Hz	16.3	14	N.T.Y.X. J	49	390.4
			60Hz	19.3	16.6			
JH516-Y	6HP	4.5	50Hz	17.1	15.2	T.Y	49	390.4
			60Hz	20.7	17.8			
JH517-Y	6.33HP	4.75	50Hz	18.7	16.1	T.Y.X.J	49	390.4
			60Hz	22	18.9			
JH518-Y	6.5HP	4.85	50Hz	19.9	17.1	T.Y.X	54.5	415.4
			60Hz	23.3	20			
JH519-Y	7.5HP	5	50Hz	21.3	18.3	T.Y.X.J	54.5	415.4
			60Hz	24.9	21.4			
JH521-Y	7.5HP	5.5	50Hz	23.3	20	T.Y.X.J	54.5	415.4
			60Hz	27.6	23.7			
JH522-Y	8HP	6	50Hz	25.1	21.6	T.Y.X	54.5	415.4
			60Hz	29.2	25.1			
JH525-Y	9.33HP	7	50Hz	27.3	23.5	T.Y.X.J	74.5	441.6
			60Hz	32	27.5			
JH527-Y	10HP	7.5	50Hz	29.7	25.5	T.Y.X.J	74.5	441.6
			60Hz	34.8	29.9			
JH529-Y	10.67HP	8	50Hz	31.9	27.4	T.Y.X	74.5	441.6

Private Picture Copyright : WWW.MBSM.PRO

Production Description

compresseur de réfrigération mitsubishi
modèle JH527YEB pour refroidisseur

Modèle	jh527yeb
Puissance en chevaux (Hp)	10,0
Réfrigérant	R22
An	2019

Couleur	Noir
Moq	1
type	Piston
Poids (kg)	74,5
Origine	JAPON
Emballage	Dessin animé / caisse en bois





Private Picture Copyright: WWW.MBSM.PRO

Compresseur, Aspera – Embraco EMT
,EMT2121U, R290 ,1/3 HP , 220-240V 50
Hz ,Cylindrée = 5.56 CM3 , Moteur
type: CSIR,7.7LRA , Oil 180ML

Category: Technologie,Tester ok

written by www.mbsm.pro | 3 January 2021

Compresseur, Aspera – Embraco EMT ,EMT2121U, R290 ,1/3 HP , 220-240V 50 Hz
,Cylindrée = 5.56 CM3 , Moteur type: CSIR,7.7LRA , Oil 180ML

**Rsir/Rscr ,Compresseur , ACC Cubigel
,Electrolux ,HTH14AA ,R600 , 220 /
240 V/50 Hz,1/4HP ,Engine 14 cm³,LBP
,245W**

Category: Technologie,Tester ok

written by www.mbsm.pro | 3 January 2021

Rsir/Rscr ,Compresseur , ACC Cubigel ,Electrolux ,HTH14AA ,R600 , 220 / 240 V/50
Hz, 9,37kg ,1/4HP ,Engine 14 cm³,LBP ,245W

**COMPRESSOR, EMBRACO , fgs130ha, LBP
(Low Back Pressure) ,RSCR ,316 W
,1/3+ HP ,220-240 V 50 Hz ,1080 Btu/h
,11,14 c.c.,R134a**

Category: Technologie,Tester ok

written by www.mbsm.pro | 3 January 2021

Compressore	EMBRACO
Modello	FGS130HAW
Altezza (mm)	
Gas	R134a
Tensione	220-240 V 50 Hz
Applicazione	LBP (Low Back Pressure)
Test Condition	ASHRAE LBP 32
Cilindrata	11,14 c.c.
Motore	RSCR
Potenza (HP)	1/3+
Cap. Frigor. Watt	316
Cap. Frigor. Kcal	272
Cap. Frigor. Btu/h	1080
COP (W/W)	1,49
Watt assorbiti (W)	
Dispositivo di Avv.	
Condensatore	
Tipo Raffreddamento	



Embraco FGS130HAW



THERMALLY PROTECTED

10 LRA

R 134a

1 PH

220-240V~
50Hz

JOINVILLE-SC NO START WITHOUT STARTING DEVICE
MADE IN BRAZIL



513200607 FAB 1 26/JAN/05 E05DDHWA

HFC - 134a

△ 注意



高温注意

Private Picture : www.MBSM.PRO

sm.pro

Compressore

EMBRACO

Modello	FGS130HAW
Altezza (mm)	
Gas	R134a
Tensione	220-240 V 50 Hz
Applicazione	LBP (Low Back Pressure)
Test Condition	ASHRAE LBP 32
Cilindrata	11,14 c.c.
Motore	RSCR
Potenza (HP)	1/3+
Cap. Frigor. Watt	316
Cap. Frigor. Kcal	272
Cap. Frigor. Btu/h	1080
COP (W/W)	1,49
Watt assorbiti (W)	
Dispositivo di Avv.	
Condensatore	
Tipo Raffreddamento	
Imballo (Pcs/Pallet)	

HERMETIC ,AW5524EK ,Compressor , 20,950 BTU ,230/1/60 R-22 ,: 220-240 V/50 Hz. , 1 Phase , 1.7458333333 TON

Category: Technologie,Tester ok

written by www.mbsm.pro | 3 January 2021

Electrical : 220-240 V/50 Hz. 1 Phase

Nominal Performance

Capacity 6,140 / – Watts

20,950 / – BTU/Hr

5,280 / – Kcal/Hr

Power Input 2,089 / – Watts

Locked Rotor Amps 51.30 / – Amps

Max Continuous Current – / – Amps

Rated Load Amps 9.64 / – Amps

COP 2.94 / – Watts / Watts

EER 10.03 / – BTU/W-Hr

Testing Conditions

Condensing Temperature 54.40 °C 129.9 °F

Evaporating Temperature 7.20 / – °C 45.0 / – °F

Liquid Temperature 46.10 °C 115.0 °F

Return Gas Temperature 35.00 °C 95.0 °F

Ambient Temperature 35.00 °C 95.0 °F

Application

Evaporating Temp. Range HBP, A/C @ 0.00 ° C to 13.00 ° C
(32.0° F to 55.4° F)

Heat Pump -23.30 ° C to 13.00 ° C
(-9.9° F to 55.4° F)
Refrigerant R22
Refrigerant Flow Control Capillary Tube
Compressor Cooling Fan
Compressor and Motor data
Compressor Type Reciprocating
Displacement 43.10 cc.
Oil Type Mineral Oil
Oil Charge 964 cc.
Motor Type P.S.C ; 2 Pole 2,850 / – r/m
Voltage Range 198-264/- Volts 50/- Hz.
Winding Resistance at 25 ° C
Start 2.52 Ohms
Run 1.24 Ohms
Weight with Oil 27.72 Kg.
Weight with Oil and Accessories 28.05 Kg.
Electrical Components
Motor Protector
Type Internal Overload
Model Number 4042KGE661-2
Open / Close 125-135 / 50-70 ° C
1st Cycle trip at 25 ° C 50.00 Amps(main) 30.00 Amps(start)
Motor Starter
Type Potential Relay
Model Number 4043KGE681-4(RVA3G6D)
Pick Up (max.) 180.00-195.00 Volts
Drop Out (min.) 40.00-90.00 Volts
Terminal Cover KGM 901-3
Start Capacitor 88-106 µF 330 VAC.
Disch Resistor for Start Cap –
Run Capacitor 45 µF 370/440 VAC.
Mounting Kit
Rubber Grommet 4007KGM905-2
Sleeve Grommet 4023KGM903-2
Washer –
Since we are constantly improving our product , the
specification are subject to change without notice.
REV. DATE C / N No.
ECN 01-04-14 ECN 0515/13





Dot Pro : www.mbsm.pro

DOCUMENTATION PDF

Mbsm_dot_pro_private_pictureAW5524EKTélécharger

MBSM.PRO , Compressor, Electrolux-Zem GL60AA R134A ,1/6 HP , 1PH , 220-240 V 50 Hz

Category: Solutions,Tester ok

written by Jamila | 3 January 2021

MBSM.PRO , Compressor, Electrolux-Zem GL60AA R134A ,1/6 HP , 1PH , 220-240 V 50
Hz



PictureS Mbsm Dot Pro : www.mbsm.pro

- Puissance en cheval 1/6 CV
- Cylindrée 5.99 cm³
- 220-240 V 50 Hz
- Gaz R134a LBP
- Température d'utilisation max. 32°C
- Avec boîtier et système de démarrage

La photo montre l'aspect du compresseur, pas son étiquette réelle

Codes fabricants

- ACC-GL60AA
- ACC-GL60AB
- ACC-GL60AH
- CUBIGEL-GL60AA
- CUBIGEL-GL60AB
- CUBIGEL-GL60AH
- MONDIAL ELITE-4106004
- MONDIAL ELITE-1147031
- Embraco Aspera- B1112Z





PictureS Mbsm Dot Pro : www.mbsm.pro



PictureS Mbsm Dot Pro : www.mbsm.pro

Mbsm_dot_pro_private_PDF_GL60AATélécharger
Mbsm_dot_pro_private_PDF_-GL60AATélécharger

590689

GL60AA 99H27NA

GL60AA


08283

03254

267799

THERMALLY 220 - 240 V~ 50 Hz PH1
PROTECTED

R134a



Type: Hermetic piston compressors**Producer:** ACC**Series:** HMBP

Model: GL60AA

General data

Refrigerant: R134a
Discharge element: C
Cooling: S
Maximum ambient temperature [°C]: 43

Compressor's data

Cylinder capacity [cm³]: 6
Displacement [m³/h]: 1
Weight [kg]: 9,1
Oil charge [cm³]: 265
Oil type: ISO VG 19 ESTER

Engine's data

Engine type: RSIR
Power [KM]: 1/6
Starting element: LST
Power supply: 220V 50Hz
Voltage range: 187-264
Locked rotor current [A]: 9,9
Running winding resistance (25°C) [Ω]: 15,6
Starting winding resistance (25°C) [Ω]: 21,31

Electrical data

Relays: 3003
Shielding element: MRA38028, T0508, AF18FU
Starting capacitor volume [μF]:

Connections

	milimeters	inches
Suction tube:	6,5	
Service tube:	6,5	
Discharge tube:	4,9	

**Mbsm.pro , Compresseur frigorifique,
Embraco Aspera ,T2178GK , 1Hp ,PIÈCES
FRIGO, 404A , 220-240 V 50 Hz**

Category: Solutions,Tester ok

written by Jamila | 3 January 2021



Mbsm.pro , Compresseur frigorifique, Embraco Aspera ,T2178GK , 1Hp ,PIÈCES FRIGO, 404A , 220-240 V 50 Hz



Select text



GAS R-404A / R-404A GAS



- Compresor hermético / Hermetic compressor
- Monofásico / Single-phase
- Voltaje / Voltage: 220V - 50 Hz

- Serie J, equipados con
with case and valve

BAJA TEMPERATURA / LOW TEMPERATURE

Código Code	Modelos Models	HP HP	cm ³ cm ³	Temperatura de evaporación	
				-25°C	
				W	
14341	NE2125GK	1/3	8.78	300	
20792	NE2134GK	3/8	12.12	420	
20793	T2155GK	1/2	14.50	520	
20796	T2168GK	5/8	17.40	680	
21086	T2178GK	1	20.40	830	
21082	NJ2192GK	3/4	26.20	1020	
20850	NJ2212GK	1 1/4	34.37	1330	

ALTA TEMPERATURA / HIGH TEMPERATURE

Código Code	Modelos Models	HP HP	cm ³ cm ³	Temperatura de evaporación	
				-10°C	-5°C
				W	W
21069	NB6144GK	1/5	4.52	300	380
21070	NB6152GK	1/5	5.02	350	440
36596	NB6165GK	1/4	6.05	430	530
21075	NE9213GK	1/2	12.12	860	1080
20762	T6217GK	5/8	14.50	960	
36557	T6220GK	3/4	17.40	1160	
21076	NJ9226GK	1	21.70	1580	



Mbsm_dot_pro_private_PDF_compresseur-embraco-aspera-t2478gkTélécharger



Private Picture Copyright : WWW.MBSM.PRO

Détails techniques

puissance 1 HP – cylindrée 20,40 cc

220/240V 50HZ

ASPERA

FRIULINOX

Friulinox Armoire réfrigérée AF12 -20, AF12 PA, AF12-14, AF12-14 VTR, AF12-14 VTRP, AF14, AF14 -22 SILVER VTR, AF6-1, AF6-7, AF6-7 VTR, AF7, AF7 -20 VTR, AF7 -22 SILVER VTR, AF7 ICE, AF7 VTR, AF7-14, AG60 GOLD, AG60 H2O, AG60 SILVER, AG60 SILVERP, AG60P, AL-EN SUPER, AL-EN1, AL-EN1 SUPER, AL-EN1P, AL-EN2, AL-EN2 SUPER, AL-ENP, AP12-14, AP14, AP6, AP6-12, AP6-7, AP7, AP7-14, AR12-14, AR12-14 VTR, AR14, AR6-12, AR6-12 VTR, AR6-7, AR6-7 VTR, AR7, AR7-14, AR7-14 VTR, AR-EN GOLD, AR-EN SILVER, AR-EN1, AR-EN1 GOLD, AR-EN1 VTR, AR-EN2, AR-ENP, ARF142, ARF212 VTR, ARP142, ARP-EN1, ARP-EN2, ARRF21 VTR, EN GOLD, EN P, EN SILVER, EN1,

EN1 GOLD, EN1 H2O, EN1 H2O SILVER, EN1 SILVER, EN1 VTR, EN2, EN2 H2O

FriulinoxCellulede refroidissement ARP122

FriulinoxVitrineréfrigérée AFP122, AFP142, ARF122

ZANUSSI

ZanussiArmoireréfrigérée ALF110 (110071), ALNF220 (110073), ALF110 (110074), ALF120 (110075), ALNF220 (110079), ADN111 (110757), AKP110 (111000), AKS110 (111001), AKP120 (111002), AKN110 (111009), AKN120 (111010), AKP110UK (111121), AKN110UK (111123), AKNF220 (111127), AKF110UK (111129), AKF110 (111137), AKF120 (111138), ASF110 (112030), ASF110 (112032), AZP2203 (113228), AZP220360 (113229), ALN2203 (113231), AZP13430 (113234), AZF2203 (113236), AZF13430 (113237), MRF601/86 (726059), ETZ601 (726165), ETZ602 (726166), ESQC41F (726171), ESQC41FR (726172), ESQF41F (726173), ETE601 (726178), ETE602 (726179), ETE601L (726184), ETZ601L (726185), RS13RX2F (726321), RS13FX2F (726323), RS13DX2F (726335), RS13PX2F (726459), RS13PX2F6 (726461), RS13P42F (726462), RS13FX42F (726464), RS13DFX2F (726465), RS13R32F (726467), SB1300X2F (726468), RS13PW2F (726475), RS13FW2F (726476), MRF601/86 (726500), RS13FX2F6 (726688), EKZ601 (726890), EKZ602 (726891), EKE601 (726939), EKE602 (726940), EKE601L (726949), EKZ601L (726950), RS13RX2FG (726967), RS13FX2FG (726968), RS13P42F (727128), RS13FX42F (727129), RS13RX4H (727157), RS13FX4H (727158), KLP1300R (728059), KLP1300F (728060), RS13PX2FD (728063), E06C0M1V (728077), E06C1M1V (728078), E06C0D1V (728081), C06FD1G (728173), FGD36 (728271), RH06RD1G (728408), C06FD1G (728415), RS05RD1G (728433), E05N0D1C (728457), E05C0D1C (728458), E06N0D1C (728465), E06N0D2C (728466), E06N0D1V (728467), E06C0D1C (728468), E06C0D2C (728469), E06C0D1V (728470), E06N0D1C (728522), E06C0D1C (728523), KLN1300R (728605), KLP1300R (728606), KEP1300R (728607), KLP1300R (728608), KLP1300F (728609), KEP1300F (728610), KLP1300F (728611), EMVN500 (730005), DVP500V11C (730677), DVP501V11C (730678), DVP600V11C (730683), DVP601V11C (730684), DVP602V11C (730685), DVP600V12C (730686), DVP601V12C (730687), DVP602V12C (730688), DVN600V11C (730701), DVN601V11C (730702), DVN602V11C (730703), DVN600V12C (730704), DVN601V12C (730705), DVN602V12C (730706), DVN500V11C (730721), DVN501V11C (730722), MVP600V11C (730725), MVP601V11C (730726), MVP602V11C (730727), MVP600V12C (730728), MVP601V12C (730729), MVN600V11C (730741), MVN601V11C (730742), MVN600V12C (730743), MVN601V12C (730744), DVP500V11C (730768), MVP501V11C (730769), MVP502V11C (730770), MVN500V11C (730780), MVN501V11C (730781), MLC601V11C (730938), MLC602V11C (730939), DVC500V11C (731242), DVC501V11C (731243), MVC502V11C (731244), DVC600 (731250), DVC601 (731251), MVC602 (731252), DVC600 (731255), DVC601 (731256), MVC600V11C (731282), MVC601V11C (731283), MVC600V12C (731284), MVC601V12C (731285), MVC500V11C (731294), MVC501V11C (731295), DVC602 (731302), DVC602 (731303), DVNN13022C (732073), DVNN13122C (732074), MVNN13022C (732079), MVNN13122C (732080), DVNC13022C (732095), EDVC13122C (732096), MVNC13022C (732103), MVNC13122C (732110), MLC600V11C (732251), MLC601V11C (732255), MLC602V11C (732257), DVP6VP12CC (734079), PDVN901V11C (737216), PDVN901V12C (737217), PDVN907V11C (737218), PDVN907V12C (737219), PDVC901V11C (737220), PDVN907V12C (737221), PDVC907V11C (737222), PDVC907V11C (737223), ILF120 (770508), RVPE061 (771100), RSPE061 (771101), RVPE062 (771102), RVNE061 (771108), RVNE062 (771109), KVPE662 (771115), RPPE061 (771155), ILF110 (771537), ZLNF220 (771539), RD13PX2F (790018), RD13FX2F (790019)

ZanussiCellulede refroidissement ESQC41F (691044), ESQC41FR (691045), ESQF41F (691046), ESQF41FR (691047), ESQF41FR (726144)

ZanussiCongélateurcoffre MRF4808660 (726042), MRF401/86 (726058), MRF240/86 (726060), MRF480/86 (726061)

ZanussiTableréfrigérée STRP1101 (113084), STRP1102 (113088), STRP1601 (113092), TRN224C (113102), TRN224D (113103), TRN224E (113104), STRP1602 (113105), STRP1603 (113106), STRP2201 (113107), STRP2202 (113108), STRP2203 (113109), STRP1101S (113128), STRP1601S (113129), STRP2201S (113130), STRP1602R (113131), TRN132A (113150), TRN132B (113151), TRN132C (113152), TRNA132A (113153), TRNA132B (113154), TRNA132C (113155), TRRN132A (113156), TRRN132B (113157), TRRN132C (113158), TRN183A (113159), TRN183B (113160), TRN183C (113161), TRN183D (113162), TRNA183A (113163), TRNA183B (113164), TRNA183C (113165), TRNA183D (113166), TRRN183A (113167), TRRN183B (113168), TRRN183C (113169), TRRN183D (113170), TRN224A (113171), TRN224B (113172), TRNA224A (113173), TRNA224B (113174), TRRN224A (113175), TRRN224B (113176), TRF132A (113177), TRFA132A (113178), TRRF132A (113179), TRF183A (113180), TRFA183A (113181), TRRF183A (113182), TRN132AE (113183), TRN183AE (113184), TRN224AE (113185), TRF132AE (113186), TRF183AE (113187), STRP1603R (113192), STRP2201R (113193), STRP2202R (113194), STRP2203R (113195), STRP1101R (113196), STRP1102R (113197), STRP1601R (113198), TCGS/1V7T (121856), TCGS/2V7T (121857), TCGS/1VC27 (121858), TCGS/2V2C7 (121859), TCGRS/1V7T (121866), TCGRS/2V7T (121867), TCGRS/1VC2 (121868), TCGRS/2V2 (121869), TCGS2VC27T (121905), RCSN2M2 (726139), RCSN2M12 (726140), RCSN3M3 (726141), RCSN3M22 (726145), RCSN3M14 (726146), RCSN4M4 (726147), RCSN4M32 (726148), RCSN4M24 (726170), RCSN2M2U (726182), RCSN3M3U (726188), RCSN4M4U (726197), RCDR4M24 (726199), RCDR4M16 (726200), RCDR4M08 (726201), RCSN2M2R (726202), RCSN2M12R (726203), RCSN3M3R (726210), RCSN3M22R (726211), RCSN3M14R (726212), RCSN4M4R (726213), RCSN4M32R (726220), RCSN4M24R (726221), RCDR2M20 (726408), RCDR2M12 (726409), RCDR2M20U (726410), RCDR2M12U (726411), RCDR2M04R (726412), RCDR3M22 (726413), RCDR3M0U (726414), RCDR3M22U (726415), RCDE4M40 (726416), RCDR4M32 (726417), RCDR4M40U (726418), RCDR4M32U (726419), RCDFM20UX (726421), RCDF3M30U (726422), RCER2M2 (726423), RCER3M3 (726424), RCER4M4 (726425), RCEF2M2X (726426), RCEF3M3 (726427), RCDR2M20 (726550), RCDR2M12 (726551), RCDR2M04 (726552), RCDR2M20U (726553), RCDR2M12U (726554), RCDR2M04U (726555), RCDR2M20R (726556), RCDR2M12R (726557), RCDR2M04R (726558), RCDR3M30 (726559), RCDR3M22 (726560), RCDR3M14 (726561), RCDR3M06 (726562), RCDR3M0U (726563), RCDR3M22U (726564), RCDR3M14U (726565), RCDR3M06U (726566), RCDR3M30R (726567), RCDR3M22R (726568), RCDR3M14R (726569), RCDR3M06R (726570), RCDR4M40 (726571), RCDR4M32 (726572), RCDR4M40U (726573), RCDR4M32U (726574), RCDR4M40R (726575), RCDR4M32R (726576), RCDF2M20 (726577), RCDFM20U (726578), RCDF2M20R (726579), RCDF3M30 (726580), RCDF3M30U (726581), RCDF3M30R (726582), RCSER2M2 (726583), RCSER3M3 (726584), RCSER4M4 (726585), RCEF2M2 (726586), RCEF3M3 (726587), RCSN2M2T (726668), RCSN3M3T (726669), RCSN4M4T (726670), RCSER2M2U (726682), RCSER3M3U (726683), RCER4M4U (726684), RCEF2M2U (726685), RCEF3M3U (726686), RCSF2M24 (727009), RCSF3M34 (727010), HB2PNTR (727108), HB3PNTR (727109), HB4PNTR (727110), HB2P (728086), HB1P2C12 (728139), HB1P3C (728157), HB4C (728158), HB3P (728207), HB2P2C (728235), EDON590124 (728238), EDON590116 (728239), EDON590108 (728240), HB1P4C (728241), HB6C (728242), HB4P (728243), HB3P2C (728244), HB2P4C (728245), HB8C (728246), HB2PR (728247), HB1P2CR (728248), HB1P3CR (728254), HB4CR (728259), HB3PR (728264), HB2P2CR (728294), HB1P4CR (728295), HB6CR (728296), HB4PR (728297), HB3P2CR (728298), HB2P4CR (728299), HB8CR (728300), HB1P2C (728302), RCHBF1P2C (728304), RCHBF2P2C (728305), S02P200I (728352), S02P120I (728353), S04P300I (728354),

S04P220I (728361), S04P140I (728362), S05P400I (728363), S05P320I (728364), E29N200I (728368), E29N120I (728369), E29N040I (728370), E29N200IA (728371), E29N120IA (728372), E29N040IA (728373), E29N200R (728374), E29N120R (728375), E29N040R (728376), E44N300I (728377), E44N220I (728378), E44N140I (728379), E44N060I (728380), E44N300IA (728381), E44N220IA (728382), E44N140IA (728383), E44N060IA (728384), E44N300R (728385), E44N220R (728386), E44N140R (728387), E44N060R (728388), E59N400I (728389), E59N320I (728390), E59N400IA (728391), E59N320IA (728392), E59N400R (728393), E59N310R (728394), E29C200I (728395), E29C200IA (728396), E29C200R (728397), E44C300I (728398), E44C300IA (728399), E44C300R (728400), S05P240I (728401), ED0N2912SE (728492), ED0N4413SE (728493), ED0N5914SE (728494), ED0C2912SE (728495), ED0C4413SE (728496), HB2PU (728509), HB3PU (728510), HB4PU (728511), RCSF2M2 (728512), RCSF3M3 (728517), RCSF2M12 (728518), RCSF3M22 (728519), S04P220R (728536), S04P140R (728537), S05P400R (728538), S05P320R (728539), S05P240R (728540), HB1P2CRN (728552), HB1P3CRN (728554), HB4CRN (728556), HB2P2CRN (728558), HB1P4CRN (728560), HB6CRN (728562), HB3P2CRN (728564), HB2P4CRN (728566), HB8CRN (728568), HBF2PN (728569), HBF1P2CN (728570), HBF3PN (728571), RCHBF2P2CN (728573), S02P200IA (728585), S04P300IA (728586), S05P400IA (728587), S02P200R (728588), S02P120R (728589), S04P300R (728590), RCHBF2P (728635), RCHBF3P (728636)

...et d'autres dispositifs

– ALPENINOX

T2178GK – ASPERA

01AS0970 – ATEL – ELECTROLUX PROFESSIONAL

T2178GK – EMBRACO – FRIULINOX – INDESIT – UNIVERBAR – WHIRLPOOL – ZANUSSI

...numéros de fabricant supplémentaires possibles

Mbsm.pro , COMPRESSEUR , SC18CLX.2 ,DANFOSS SECOP, R404A/R507, 5/8HP ,1PH ,Deep Freeze Comptoire, Alimentation 220-240 V 50 Hz

Category: Solutions,Tester ok

written by Jamila | 3 January 2021



PictureS Mbsm Dot Pro : www.mbsm.pro

Mbsm.pro , COMPRESSEUR , SC18CLX.2 ,DANFOSS SECOP, R404A/R507, 5/8HP ,1PH ,Deep Freeze Comptoire, Alimentation 220-240 V 50 Hz

Mbsm.pro, Compressor, GM70AZ, 1/5 hp,
ZMC, Cooling, R134a, 150 W, 1.3 A,
1Ph 220-240V 50Hz, LBP capacity,
RSIR, -30°C to -10°C

Category: compressor

written by www.mbsm.pro | 3 January 2021



Private Picture Copyright : WWW.MBSM.PRO

Le ZMC GM70AZ est un compresseur hermétique à piston fonctionnant au R134a, destiné aux applications à basse pression d'aspiration dans les réfrigérateurs et congélateurs ménagers alimentés en 220–240 V, 50 Hz. Fabriqué par Misr Compressor Manufacturing Co. en Égypte, il fournit une puissance d'environ 1/5 HP et une plage d'évaporation de $-30\text{ }^{\circ}\text{C}$ à $-10\text{ }^{\circ}\text{C}$, ce qui en fait une solution courante et fiable pour le froid domestique dans la région MENA

Mbsm.pro, Compressor, HIGHLY, BSA645CR-R1EN, GBSA645CR, 840w, r134a, 1.12hp, Constant-Speed, [1ph] 100/100-110V 50/60Hz

Category: compressor

written by www.mbsm.pro | 3 January 2021



Private Picture Copyright : WWW.MBSM.PRO

Mbsm.pro, Compressor, HIGHLY, BSA645CR-R1EN, GBSA645CR, 840w, r134a, 1.12hp, Constant-Speed, [1ph] 100/100-110V 50/60Hz