


Mbsm.pro, COMPRESSOR, SECOP, FR10G,  
R134a, 1/4 Hp++, 1/3 Hp-, HMBP,  
103G6880-HST, DANFOSS, CSIR, 730  
BTU, 9.05 cc

Category: compressor

written by [www.mbsm.pro](http://www.mbsm.pro) | 7 March 2022



Private Picture Copyright: [WWW.MBSM.PRO](http://WWW.MBSM.PRO)

Mbsm.pro, COMPRESSOR, SECOP, FR10G, R134a, 1/4 Hp++, 1/3 Hp-, HMBP, 103G6880-HST, DANFOSS, CSIR, 730 BTU, 9.05 cc

# Mbsm.pro, compressor, Electrolux, ZEM, GL45AA, LBP, 1/8 hp

Category: compressor

written by [www.mbsm.pro](http://www.mbsm.pro) | 7 March 2022

# PHILIPS

Réfrigérateur

Modèle: 290 L2

Classe: ST

220 - 240V - 50Hz - 110W - 0,8A

Volume Int.	Tot.	Refr.	Cong.	CCl <sub>2</sub> F <sub>2</sub>
	250 dm <sup>3</sup>	250 dm <sup>3</sup>	dm <sup>3</sup>	0,100 Kg

n° série : 441 010312 08607

Private Picture Copyright : [WWW.MBSM.PRO](http://WWW.MBSM.PRO)

Mbsm.pro, compressor, Electrolux, ZEM, GL45AA, LBP, 1/8 hp

# Compressor, R134A, GLY12RGA, 10,7cm<sup>3</sup>, HMBP, 230V, 3/8HP, CUBIGEL, HUAYI

Category: compressor

written by www.mbsm.pro | 7 March 2022

Model	Displacement (cm <sup>3</sup> )	Refrigerant	Application	Compressor Cooling	Voltage/Frequency	Frequency (Hz)	Motor Type	Cooling (kCal/h)	COP (W/W)	Cooling (W)	COP (W/W)	Technical Data Sheet (*)
GL45MG	4,56	R134a	HBP	S	230V	50/60Hz ~1	50 CSIR	352	1,95	340	1,67	GL45MG
GL45MG	4,56	R134a	HBP	S	230V	50/60Hz ~1	60 CSIR	412	1,92	398	1,65	GL45MG
GL60MG	5,98	R134a	HBP	S	230V	50/60Hz ~1	60 CSIR	520	2,02	499	1,73	GL60MG
GL60MG	5,98	R134a	HBP	S	230V	50/60Hz ~1	50 CSIR	445	1,99	427	1,70	GL60MG
GL80MG	7,57	R134a	HBP	S	230V	50/60Hz ~1	60 CSIR	702	2,15	674	1,84	GL80MG
GL80MG	7,57	R134a	HBP	S	230V	50/60Hz ~1	50 CSIR	600	2,10	576	1,78	GL80MG
GL90MG	8,85	R134a	HBP	S	230V	50/60Hz ~1	50 CSIR	685	2,10	661	1,79	GL90MG
GL90MG	8,85	R134a	HBP	S	230V	50/60Hz ~1	60 CSIR	800	2,11	772	1,83	GL90MG
GLY12RAa	10,70	R134a	HBP	F	220-240V	50Hz ~1	50 CSIR	900	2,30	867	1,97	GLY12RAa
GLY12RAb	10,70	R134a	HBP	F	220-240V	50Hz ~1	50 CSR	900	2,57	867	2,20	GLY12RAb
GLY12RGa	10,70	R134a	HBP	F	200-220/220-230V	50/60Hz ~1	50 CSIR	900	2,19	867	1,87	GLY12RGa
GLY12RGa	10,70	R134a	HBP	F	200-220/220-230V	50/60Hz ~1	60 CSIR	1.038	2,22	1.007	1,90	GLY12RGa
GLY12RGb	10,70	R134a	HBP	F	200-220/220-230V	50/60Hz ~1	50 CSR	900	2,32	867	1,98	GLY12RGb
GLY12RGb	10,70	R134a	HBP	F	200-220/220-230V	50/60Hz ~1	60 CSR	1.038	2,40	1.007	2,07	GLY12RGb
GP14TB	14,17	R134a	HBP	F	220-240V	50Hz ~1	50 CSIR	1.030	2,03	998	1,76	GP14TB
GP16TB	16,15	R134a	HBP	F	220-240V	50Hz ~1	50 CSIR	1.240	2,09	1.204	1,80	GP16TB
GP16TE	16,15	R134a	HBP	F	115V	60Hz ~1	60 CSIR	1.450	1,96	1.408	1,69	GP16TE
GP16TG	16,15	R134a	HBP	F	200-220/230V	50/60Hz ~1	50 CSIR	1.240	2,09	1.204	1,81	GP16TG
GP16TG	16,15	R134a	HBP	F	200-220/230V	50/60Hz ~1	60 CSIR	1.450	2,00	1.408	1,74	GP16TG
GPM16RA	16,15	R134a	HBP	F	220-240V	50Hz ~1	50 CSIR	1.351	2,09	1.317	1,79	GPM16RA

(\*) Under standard conditions

## Additional information

Voltage (V)	230Vac
Frequency (hz)	50
Range	MBP
Displacement (cm3)	10,7 cm <sup>3</sup>
Cooling capacity (W)	608W
Conditions (°C)	-10 / +45C
Refrigerant	R134A
Suction line	8.1mm juotettava
Liquid line	6,5mm juotettava
Height (mm)	198mm
Weight (kg)	10,43kg
Oil	ISO VG 32 Ester

## Technical data

- Model: **GLY12RAa**
- Refrigerant Gas: **R-134a**
- Pression/temperature: **HBP**
- Power: **3/8 HP**
- Voltage: **230 V**
- Current Type: **Single-Phase**
- Frequency: **50 Hz**
- Compressor Type: **Hermetic**

- Displacement: **10.7 cm<sup>3</sup>**
- Power Cons. -10°C: **293 W**
- Power Cons. -5°C: **322 W**
- Efficiency 0°C: **351 W**
- Power Cons. +5°C: **380 W**
- Power Cons. +7,2°C: **392 W**
- T° Condensation: **40 °C**
- Cooling Cap. -15°C: **408 Kcal/h**
- Cooling Cap. -10°C: **512 Kcal/h**
- Cooling Cap. -5°C: **642 Kcal/h**
- Cooling Cap. 0°C: **797 Kcal/h**
- Cooling Cap. 5°C: **977 Kcal/h**
- Cooling Cap. 7.2°C: **1065 Kcal/h**
- Cooling Cap. 10°C: **1184 Kcal/h**
- Test Type: **Ashare 46**

Mbsm\_dot\_pro\_private\_PDF\_pdf-GLY12RAaTélécharger

Model	Displacement (cm <sup>3</sup> )	Refrigerant	Application	Compressor Cooling	Voltage/Frequency	Frequency (Hz)	Motor Type	ASHRAE (°)		CECOMAF (°)		TE Data
								Cooling (kCal/h)	COP (W/W)	Cooling (W)	COP (W/W)	
GL45MG	4.56	R134a	HBP	S	230V 50/60Hz ~1	50	CSIR	352	1.95	340	1.87	GI
GL45MG	4.56	R134a	HBP	S	230V 50/60Hz ~1	60	CSIR	412	1.92	398	1.85	GI
GL60MG	5.96	R134a	HBP	S	230V 50/60Hz ~1	60	CSIR	520	2.02	499	1.73	GI
GL60MG	5.96	R134a	HBP	S	230V 50/60Hz ~1	50	CSIR	445	1.99	427	1.70	GI
GL80MG	7.57	R134a	HBP	S	230V 50/60Hz ~1	60	CSIR	702	2.15	674	1.84	GI
GL80MG	7.57	R134a	HBP	S	230V 50/60Hz ~1	50	CSIR	600	2.10	576	1.78	GI
GL90MG	8.85	R134a	HBP	S	230V 50/60Hz ~1	50	CSIR	685	2.10	661	1.79	GI
GL90MG	8.85	R134a	HBP	S	230V 50/60Hz ~1	60	CSIR	800	2.11	772	1.83	GI
GLY12RAa	10.70	R134a	HBP	F	220-240V 50Hz ~1	50	CSIR	900	2.30	887	1.97	GL'
GLY12RAb	10.70	R134a	HBP	F	220-240V 50Hz ~1	50	CSR	900	2.57	857	2.20	GL'
GLY12RGa	10.70	R134a	HBP	F	200-220/220-230V 50/60Hz ~1	50	CSIR	900	2.19	887	1.87	GL'
GLY12RGa	10.70	R134a	HBP	F	200-220/220-230V 50/60Hz ~1	60	CSIR	1.038	2.22	1.007	1.90	GL'
GLY12RGb	10.70	R134a	HBP	F	200-220/220-230V 50/60Hz ~1	50	CSR	900	2.32	887	1.98	GL'
GLY12RGb	10.70	R134a	HBP	F	200-220/220-230V 50/60Hz ~1	60	CSR	1.038	2.40	1.007	2.07	GL'
GP14TB	14.17	R134a	HBP	F	220-240V 50Hz ~1	50	CSIR	1.030	2.03	998	1.78	GI
GP16TB	16.15	R134a	HBP	F	220-240V 50Hz ~1	60	CSIR	1.240	2.09	1.204	1.80	GI
GP16TE	16.15	R134a	HBP	F	115V 60Hz ~1	60	CSIR	1.450	1.98	1.408	1.68	GI
GP16TG	16.15	R134a	HBP	F	200-220/230V 50/60Hz ~1	50	CSIR	1.240	2.09	1.204	1.81	GI
GP16TG	16.15	R134a	HBP	F	200-220/230V 50/60Hz ~1	60	CSIR	1.450	2.00	1.408	1.74	GI
GPM16RA	16.15	R134a	HBP	F	220-240V 50Hz ~1	50	CSIR	1.351	2.09	1.317	1.79	GP



Private Picture Copyright: WWW.MBSM.PRO



Private Picture Copyright: WWW.MBSM.PRO

# COMPRESSOR, EMBRACO, 1/4 HP++ (big), 220V, R134A, EGAS 80HLR, FREEZER MOTOR

Category: compressor

written by [www.mbsm.pro](http://www.mbsm.pro) | 7 March 2022

#mbsmpro

## TECHNICAL SPECIFICATIONS

- Voltage: 220V 50 / 60Hz
- Refrigerant: R-134A
- Evaporation temperature range: -35 ° C to -10 ° C
- Power: 1/4 +

[Mbsm\\_dot\\_pro\\_private\\_PDF\\_pdf\\_embraço-compressor-egas-80-hlr](#)Télécharger

### Technical Specifications

Brand	Embraco
Production place	Brazil
Compressor Type	Hermetic Piston
Compression Line	1/4 "
Working Regime	LBP (-23,3 ° C / + 54,4 ° C)
Frequency (Hz)	50-60
Suction Line	5/16 "
Cooling Capacity (Watts)	195
good kodu	51370117399RA
Compressor Model	EGAS80HLR
Piston Diameter (cm3/rev)	6.36
Tipi Motorcycle	1 FAZ - RSIR
Refrigerant Gas	R134a
Compressor Power(Hp)	1/4 +





Private Picture Copyright: WWW.MBSM.PRO

## MBSM.PRO, All Compressor in One File , Pdf and Print

Category: compressor

written by [www.mbsm.pro](http://www.mbsm.pro) | 7 March 2022



Private Picture Copyright: WWW.MBSM.PRO

MBSM.PRO, All Compressor in One File , Pdf and Print

---

## Embraco, Compressor, Fridge, Refrigerator, 1/5HP, LBP, 1/6++,mbp R134a, FFI7.5HAK, 220-240V/50HZ

Category: compressor

written by [www.mbsm.pro](http://www.mbsm.pro) | 7 March 2022

Embraco, Compressor, Fridge, Refrigerator, 1/4HP LBP, R134a, FFI7.5HAK,  
220-240V/50HZ

---

## R134a, High Temperature, Hermetic, Compressor, TECUMSEH, AE1144E, HP 1/3 (lbp), AE3440Y, HP 1/3(Big+), HBP/CBP – High/Commercial Back Pressure, 1 Phase

Category: compressor

written by [www.mbsm.pro](http://www.mbsm.pro) | 7 March 2022

R134a, High Temperature, Hermetic, Compressor, TECUMSEH, AE1144E, HP 1/3 (lbp),  
AE3440Y, HP 1/3(Big+), HBP/CBP – High/Commercial Back Pressure, 1/3 HP/Ton , 1  
Phase

---

## Tecumseh ,Compressor Az1355D, 1/6Hp , R12 ,réfrigérateur

Category: Technologie,Tester ok

written by [www.mbsm.pro](http://www.mbsm.pro) | 7 March 2022

Tecumseh ,Compressor Az1355D, 1/6Hp , R12 ,réfrigérateur

---

## Compresseurs Embraco, ,EMU70HLC , R134a, 220 V, 50Hz, 1/5 HP, 149 watts , 180 mL

Category: Technologie,Tester ok

written by [www.mbsm.pro](http://www.mbsm.pro) | 7 March 2022

Compresseurs Embraco, ,EMU70HLC , R134a, 220 V, 50Hz, 1/5 HP, 149 watts , 0.17  
kW (0.2214 BHP) ,180 mL