

Compresseur Embraco ,Aspera,
nbm1118y, nby1118y ,coolant ,R600a
,NBY1118Y ,220-240V 50Hz, LBP ,fully
hermetic, 10,8kg ,1/4HP

Category: Technologie,Tester ok

written by www.mbsm.pro | 9 May 2020

ompresseur Embraco ,Aspera, nbm1118y, nby1118y ,coolant ,R600a ,NBY1118Y
,220-240V 50Hz, LBP ,fully hermetic, 10,8kg ,1/4HP,nbt1118y

Mbsm.pro, Compressor, Aspera, B3119Z,
234 w, 1/4 hp, r134a

Category: compressor

written by www.mbsm.pro | 9 May 2020



Private Picture Copyright : WWW.MBSM.PRO

Mbsm.pro, Compressor, Aspera, B3119Z, 234 w, 1/4 hp, r134a

Mbsm.pro, Zem, L55AV, Rough, BP1111A,
Embraco, PW5.5K9, PW5.5K11, EM55NP,
Danfoss, TL5A, AZ1345A, AZ1340A,
AEZ1343A, AE6ZA7, AE66ZD7, Necchi,
ESM5, R12, 1/6 HP, 1bp, 400 L

Category: compressor

written by www.mbsm.pro | 9 May 2020



Private Picture Copyright : WWW.MBSM.PRO

Mbsm.pro, Zem, L55AV, Rough, BP1111A, Embraco, PW5.5K9, PW5.5K11, EM55NP,
Danfoss, TL5A, AZ1345A, AZ1340A, AEZ1343A, AE6ZA7, AE66ZD7, Necchi, ESM5, R12,

1/6 HP, 1bp, 400 L

Mbsm.pro, Compressor, AE66ZD7, Tecumseh 1/6 HP, 220V, 450 BTU, R12, Hermetic

Category: compressor

written by www.mbsm.pro | 9 May 2020



R12
AE66ZD7
 208 V ~ 50Hz In 0.90A Id 8.50A
 230 V ~ 60Hz In 0.90A Id 9.00A
 CE
 S/N: 03E26150202
 6132780300
 L'UNITE HERMETIQUE
 366263

327803
 6ZD7
 60511

Private Picture Copyright: WWW.MBSM.PRO

Mbsm.pro, Compressor, AE66ZD7, Tecumseh 1/6 HP, 115V, 450 BTU, R12, Hermetic

Mbsm.pro, Compressor, cubigel, huayi, ACC, Electrolux, HPY14AA, LBP, R600a, 1/5HP, 220-240V/1/50Hz, 166 W

Category: compressor

written by www.mbsm.pro | 9 May 2020

Compressors/Compressors ACC – Electrolux HP14AH, LBP – R600a, Power consumption 1/5HP, 220-240V/1/50Hz, Motor type RSIR, Injection: Capillary operation, Displacement 14.32 cm³, Oil type ISO VG10 Mineral oil, Oil quantity 300 cm³, Power 147 W at -25 / +55 °C, Power consumption 166 W, Power 0.0 W, Cooling capacity

-10 °C	-15 °C	-20 °C	-25 °C	-30 °C	-35 °C
344	276	216	166	124	92

Shipping Class	Standard
Scope Of Application	LBP
Lieferzeit	2-3 Wochen
Type Of Construction	Piston
Condensation Temperature	55°C
Maker	ACC
Manufacturer No.	HPY14AA
Displacement In Cm³	14.32
Measuring Requirements	Ashrae
Refrigerants	R600a
Series	HPY
Condensing Units Compressors	Compressors
Suspense	220-240V
Weight In Kg	13

Compressor ACC Cubigel Huayi Electrolux ZEM HPY14AA, LBP -R600a, 220-240V/1/50Hz, 1/5 HP, discharge 14.32 cm³, motor type RSIR, oil type ISO VG10 mineral, oil charge 300 cm³, 166 W at -25 / +55 °, input power, current 147 W, 0.96 A, expansion device: capillar, cooling: static, weight 11 kg , the statutory warranty period shall apply (24 months), Delivery time Info: with “immediately available” and “scarce stock”, usually delivery within 2 days. For “currently not available” delivery time usually 2 weeks or delivery time in urgent cases contact us.

Refrigerant:	R600a
Power range(W):	101 – 200 W
Performance range (C):	-35 C to -10 C
Connecting size:	6,5 mm
Suction:	8,1 mm
Working area:	LBP
Design type:	Hermetic
Model series:	HPY
Use with:	Capillary

Power range(HP):	0-2
Power supply:	230 V
Oil type:	ISO VG 10 Mineral
Engine type:	RSIR
Article condition:	New
Info:	Oil filled
Shipping weight:	13,00 Kg
Dimensions (length × width × height):	20,40 × 16,20 × 19,60 cm
customs tariff number:	84143081
Cooling capacity condition:	T0 -25 C, Tk +55 C
Manufacturer:	ACC Cubigel Huayi Electrolux ZEM
Model:	HPY14AA
Modelname:	HP14AH
Stroke volume (cm3):	14,32
Cooling capacity (W):	147
Power (HP):	0,25
Max. Starting current (A):	11,5
Max. Operating current (A):	0,96
Engine type:	RSIR
Note:	Static cooling
Oil quantity (l):	0,3
Compressor type:	Piston
Power range:	-35 C to -10 C
Alternative:	NBM1118Y , EMX70CLC , NBM1116Y
Pressure line (mm):	6,5
Suction line (mm):	8,1





Private Picture Copyright : WWW.MBSM.PRO

Mbsm_dot_pro_private_PDF_HPYP14AA-1Télécharger

Mbsm_dot_pro_private_PDF_HPYP14AATélécharger