# Mbsm.pro, Compressor, s36G, 1/10 hp, 1ph 220v/50hz, R134a, 32g, water-cooler, BLY-F/950

Category: compressor

written by www.mbsm.pro | 2 February 2025



Information Value

Model BLY-F (905)
Rated Voltage 220-240V~
Rated Frequency 50/60Hz
Heating Power 450W
Total Power 550W
Maximum Rated Wattage of Lamps 0.5W
Cooling Capacity 1.5L/h
Cooling Consumption 0.100Kwh/H

Rated Cooling Current 0.8A

Refrigerant R134a/32g

Climate Class T
Protection Class I
Foam EPS
Waterproof Degree IPX0
Made in China

## Water Dispenser / Mini Fridge Compressor (1/10HP)

Refrigeration Compressor Type Reciprocating Compressor

Refrigerant R134A

Usage Water Dispenser / Small Fridge / Minibar / etc

Warranty N/A

Voltage 220-240V / 50Hz

Displacement 3.6 cm3
Model No. S36G / QD36

Cooling Power (W) 80W
Cooling Power (HP) 1/10 HP

Small refrigeration compressor mainly used in:

- Water Dispenser (cooling cabinet models)
- Small Refrigerator / Mini Bar / Ice Machines
- Other small refrigerating equipment

Cooling Power: 85W (1/10 HP)

Electricity required: 220-240V / 50Hz

#### Compressor (Model S36G)

- Purpose: The core component for pressurizing refrigerant in a cooling cycle.
- Model S36G: Likely a specific compressor model (possibly from a brand like Secop, Danfoss, or a regional manufacturer). Verify with manufacturer documentation for exact specs.
- **Application**: Small-scale systems (e.g., commercial water coolers, medical devices, or compact refrigeration) due to the small refrigerant charge.

#### 2. Refrigerant (R134a, 32g)

- R134a: A common hydrofluorocarbon (HFC) refrigerant used in medium-temperature systems (e.g., refrigerators, AC units, water coolers).
- 32g Charge: Indicates a small system, typical for portable or compact units. Ensure the charge matches manufacturer specifications to avoid inefficiency or damage.

#### 3. Water-Cooler System

- Water-Cooled Condenser: Uses water (instead of air) to dissipate heat, improving efficiency. Requires a water supply, pump, and possibly a cooling tower.
- Applications: Often found in commercial settings (e.g., water dispensers, industrial chillers, or high-efficiency HVAC systems).

#### 4. BLY-F/950

- Likely a component model, such as:
  - o Filter drier: Removes moisture/contaminants from refrigerant.
  - Pressure switch: Safety device to control system pressure.
  - o Control board/Valve: Part of the system's electrical or flow regulation.
  - Check manufacturer manuals or suppliers for exact function.

#### **Key Considerations**

- 1. **Compatibility**: Ensure the compressor (S36G) is designed for R134a and water-cooled operation.
- 2. **Refrigerant Charge**: Confirm 32g is correct (undercharging/overcharging affects performance).
- 3. Water Cooling: Check for scale buildup, water flow rate, and pump functionality.
- 4. **BLY-F/950 Replacement**: Cross-reference with OEM parts or contact the system manufacturer.

#### **Troubleshooting Tips**

- Low Cooling Efficiency: Check refrigerant charge, water flow, or condenser cleanliness.
- Component Failure: Test the BLY-F/950 part (e.g., continuity for switches, clogging in filter driers).
- Noise/Leaks: Inspect the compressor and refrierant lines.

-			
Prod	ucts	Introc	luction:

	Horsepower	orsepower (hp) Model	Displacement			g capacity+/-5% RAE(-23.3°C)		Input Power +/-5%	COP+/-7% ASHRAE(-23.3°C)			Cooling	
	(hp)		(cc/rev)	type	(kcal/h)	(W)	(Btu/h)	w	(kcal/h)	(W)	(Btu/h)		
220-240V~ 50/60Hz	1/14hp	ASV20H	2.0cc	RSIR	41	48	164.00	56.00	0.73	0.85	2.9	ST	
	1/13hp	ASV25H	2.5cc	RSIR	50	58	198.00	68.00	0.73	0.85	2.9	ST	
	1/12hp	ASV30H	3.0cc	RSIR	60	70	239.00	82.00	0.73	0.85	2.9	ST	
	1/12hp	S30G	3.0cc	RSIR	56	65	222.00	72.00	0.77	0.9	3.07	ST	
	1/10hp	S36G	3.6cc	RSIR	69	80	273.00	89.00	0.77	0.9	3.07	ST	
	1/8hp	ASW43H	4.3cc	RSIR	106	123	420.00	98.00	1.08	1.25	4.27	ST	
	1/6hp	ASW53H	5.3cc	RSIR	120	140	478.00	112.00	1.08	1.25	4.27	ST	
	1/5hp	ASW65H	6.5cc	RSIR	143	165	566.00	132.00	1.08	1.25	4.27	ST	
	1/4hp	ASW75H	7.5cc	RSIR	168	190	665.00	152.00	1.08	1.25	4.27	ST	
	1/4+hp	ASQ91H	9.1cc	RSIR	189	220	751.00	176.00	1.08	1.25	4.27	ST	
	1/3hp	ASQ110H	11.0cc	RSIR	241	280	955.00	215.00	1.11	1.3	4.43	ST	
	1/3+hp	ASQ128H	12.8cc	RSIR	280	326	1112.00	251.00	1.11	1.3	4.43	ST	
115-127V/60Hz	1/14hp	ASV20HD	2.0cc	RSIR	47	55	188.00	65.00	0.73	0.85	2.9	ST	
	1/10hp	ASV25HD	2.5cc	RSIR	56	65	222.00	78.00	0.77	0.9	3.07	ST	
	1/12hp	ASV30HD	3.0cc	RSIR	69	80	273.00	100.00	0.77	0.9	3.07	ST	
	1/8hp	ASW43HD	4.3cc	RSIR	116	135	460.00	108.00	1.08	1.25	4.27	ST	
	1/6hp	ASW53HD	5.3cc	RSIR	138	160	546.00	128.00	1.08	1.25	4.27	ST	
	1/5hp	ASW65HD	6.5cc	RSIR	167	194	662.00	147.00	1.14	1.32	4.5	ST	
	1/4hp	ASW75HD	7.5cc	RSIR	196	228	777.00	173.00	1.14	1.32	4.5	ST	
FC:Fancooling	RSIF	RSIR:ResistanceStartInductionRun				EvaporatingTemp.:-23.3°C(-10°F)			1watt=3.41Btu/Hr				
OC:Oilcooling	RSCI	RSCR:ResistanceStartCapacitorRun					CondensingTemp.:54.4°C(130°F)			1watt=0.86Kcal/Hr			
ST:Static	CSIR:CapacitorStartInductionRun				GasSuperheatedto:32.2°C(90°F)		1Kcal/Hr=3.97Btu/Hr						
	CSR:CapacitorStartCapacitorRun				Liquidsub-cooledto:32.2°C(90°F)								
						An	nbientTemp	o.:32.2°C(90°F)					

As a result of Asbeila policy of constant development, technical specifications may be subject to change.







• File uploaded successfully: Open file in a new window

File Information:

File Name: Mbsm-tn-media-\_Compressor-s36G-R134a-32g-water-cooler-BLY-F-950.jpg

File Type: image/jpeg File Size: 436.6 KB File Extension: jpg

File uploaded successfully: Open file in a new window

File Information:

File Name: Mbsm-tn-media-Compressor-s36G-R134a-32g-water-cooler-BLY-F-950.jpg

File Type: image/jpeg File Size: 435.14 KB File Extension: jpg File uploaded successfully: Open file in a new window

File Information:

File Name: Mbsm-tn-media-Compressor-s36G-R134a-32g-water-cooler-BLY-F-950.jpg

File Type: image/jpeg File Size: 549.08 KB File Extension: jpg

File uploaded successfully: Open file in a new window

File Information:

File Name: Mbsm-tn-media-Compressor-s36G-R134a-32g-water-cooler-BLY-F-950.pdf

File Type: application/pdf

File Size: 296.7 KB File Extension: pdf

Refrigerator, Embraco, Compressor, 1/4 hp, FF17.5HAK, FF18.5HAK FFU70HAK, 1/3 hp, FG95HAK, FEU100HAK, 1/6 hp, EM65HNR, EMI50HEP, 1/5 hp, FG65HAK, FF165HAK, EMI70, EM20HHR, 1/12 hp, EM30HHR, 1/10 hp, EM40HEP, EM45HNR

Category: compressor, expertise



Private Picture Copyright: WWW.MBSM.PRO

Refrigerator, Embraco, Compressor, 1/4 hp, FF17.5HAK, FF18.5HAK, FFUZOHAK, 1/3 hp, FG95HAK

FEU100HAK, 1/6 hp, EM65HNR, EMI50HEP, 1/5 hp, FG65HAK, FF165HAK, EMI70, EM20HHR, 1/12 hp,

EM30HHR, 1/10 hp, EM40HEP, EM45HNR,

# Mbsm.pro, Compressor, embraco, aspera, emx32clc, 1/10 hp, r600a, 88 w

Category: compressor

written by www.mbsm.pro | 2 February 2025



Mbsm.pro, Compressor, embraco, aspera, emx32clc, 1/10 hp, r600a, 88 w

## Compressor, 1/10 hp, 88 w, ZBS1111CY, JIAXIPERA, r600a

Category: expertise



Private Picture Copyright: WWW.MBSM.PRO

# Refrigeration, Compressor, 1/10 HP, R-134A, Samsung, CD130C-L1Z2

Category: compressor

written by Amina | 2 February 2025



Private Picture Copyright: WWW.MBSM.PRO

Refrigeration, Compressor, 1/10 HP, R-134A, Samsung, CD130C-L1Z2

### Mbsm.pro, D40CY1, compressor, Donper, R600a, 40cc, 1/10 HP

Category: compressor

written by www.mbsm.pro | 2 February 2025



Mbsm.pro, D40CY1, compressor, Donper, R600a, 40cc, 1/10 HP

Mbsm.pro, Refrigerator, Mini compressor, GMCC, C Series, TOSHIBA, SZ55C1J, 75 w, 1/10 hp, LBP, r600a, Refrigerator-Freezer, HRD-071S, 64 L

Category: compressor



Mbsm.pro, Refrigerator, Mini compressor, GMCC, C Series, TOSHIBA, SZ55C1J, HRD-071S, 75 w, 1/10 hp, LBP, r600a

#### Mbsm.pro, Tecumseh, AZ1330Y, Compressor, 1/10 hp, lbp, R134a, 90w

Category: compressor



Private Picture Copyright: WWW.MBSM.PRO

### Mbsm.pro, Compressor, qd30h, 1/10 Hp, Lbp, 75 w

Category: compressor

written by www.mbsm.pro | 2 February 2025



Mbsm.pro, Compressor, gd30h, 1/10 Hp, Lbp, 75 w

Mbsm.pro, FW-16vcd, FRESH WATER, DISPENSER, 3 SPIGOTS, COLD/HOT/WARM, Compressor, 1/10 hp, r134a, 28 g

Category: Chaud&Froid,compressor



Private Picture Copyright: WWW.MBSM.PRO

Mbsm.pro, FW-16vcd, FRESH WATER, DISPENSER, 3 SPIGOTS, COLD/HOT/WARM, Compressor, 1/10 hp, r134a, 28 g