

Compressor, r600a, 1/5HP, LBP, 149W, htk12aa, Electrolux, Brandt, 220-240V 50Hz, Run Capacitor: 4.0 µF (5.0 µF as alternative) , Motor type RSCR/RSIR

written by Lilianne | 2 December 2021

compressor/compressor ACC – Electrolux HTK12AA, LBP – R600a,
Power consumption 1/5HP++, 220-240V/1/50Hz, Motor type RSIR,
Injection: Capillary operation, Displacement 11.1 cm³, Oil
type mineral oil, Oil quantity 170 cm³, Power 116 W at -25 /
+55°C, Power consumption 149 W, Current 0.77, Weight
8.6Cooling capacity

−10 °C	−15 °C	−20 °C	−25 °C	−30 °C	−35 °C
300	240	188	144	107	78
Shipping Class				Standard	
Scope Of Application				LBP	
Lieferzeit				2-3 Wochen	
Type Of Construction				Piston	
Condensation Temperature				55°C	
Maker				ACC	
Manufacturer No.				HPY12AA	
Displacement In Cm3				11.1	
Measuring Requirements				Ashrae	
Refrigerants				R600a	
Series				HPY	

Condensing Units Compressors	Compressors
Suspense	220-240V
Weight In Kg	12.7

1. Be the first to review this product

Mbsm_dot_pro_private_PDF_HTK12AA-1-1Télécharger

Mbsm_dot_pro_private_PDF_HTK12aa-1Télécharger



Private Picture Copyright : WWW.MBSM.PRO

Verdichter - Cubigel

Hermetische Verdichter für Kapillarrohrbetrieb.
Hochleistungs-Verdichter mit Betriebskondensatoren.
LBP Temperaturbereich -30 °C bis -10 °C.
Netzspannung 220 - 240 V / 50 Hz.



R-600a, LBP

Artikelnr.	Typ	Leistung (PS)	Kälteleistung [W] T _o -25 °C, T _k +45 °C
			-25
47-32 HQY45AA	HQY 45 AA	1/12	52
47-32 HQY55AA	HQY 55 AA	1/9	62
47-32 HQY70AA	HQY 70 AA	1/8	80
47-32 HQY80AA	HQY 80 AA	1/7	99
47-32 HQY90AA	HQY 90 AA	1/7	109
47-32 HQY99AA	HQY 99 AA	1/6	119
47-32 HPY12AA	HPY 12 AA	1/5	144
47-32 HPY14AA	HPY 14 AA	1/5	166
47-32 HPY16AA	HPY 16 AA	1/4	181

Gesamtkatalog jetzt anfordern unter info@kaeltepartner.net!

 **Hinweis: Bilder Können vom Produkt abweichen**

Private Picture Copyright : WWW.MBSM.PRO