

**Mbsm.pro, compressor,
MT160HW4D , 13 hp, MT160,
Displacement: 271.55cm³/rev**

written by Lilianne | 30 August 2022

*Mbsm.pro, Danfoss, Compressor, MT100HS4D, 8.3HP, R22, 380V,
3PH*



Danfoss

MADE IN FRANCE

380-400V 3-50 Hz
460V 3-60 Hz

LR 130A 36A MAX

LR 130A 38A MAX
THERMALLY PROTECTED

P.E.D. LP side HP side


Marking	LP side	11.5 bar
	12.5 bar	27.8 bar

PS	18.4 bar	27.8 °C
TS max	60 °C	68 °C

TS max	50 °C	60 °C
TS min	-35 °C	-35 °C

IS mill	-55 °C	1.21
Volume	31 l	

Lubricant: MINERAL OIL 160 P

CE  EAC

Refrigerant: R22(ULrating)-R417A with160P2

Maneurop

⚠ WARNING

WARNING

Read and understand all instructions before using this product. Failure to follow instructions may result in injury or property damage. Use only as directed. Do not use if the product is damaged or if the instructions are not followed. For more information, see the instructions for use.

© 2000 The McGraw-Hill Companies, Inc. All rights reserved. Printed in the United States of America. This publication is protected by copyright. Any unauthorized reproduction or distribution of this publication without the written permission of The McGraw-Hill Companies, Inc. is prohibited. For more information, contact The McGraw-Hill Companies, Inc., 1221 Avenue of the Americas, New York, NY 10020-1095.



▲ CAUTION

CAUTION

Use only manufacturer's approved refrigerant
hvac oils and electrical components. Disconnect
refrigerant tubing from condenser coil.
Do not touch, weld, or cut any part of the unit.

For details visit us today! www.hvacr.com

