

# Mbsm.pro, DONPER, Refrigeration, Compressor, S96CY1, H170CY1, R600a (56 g), LBP, 240V 50HZ, 1/5 HP, 155W, CHEST FREEZER, Nikai, NCF340N5, Nikai 340L Chest Freezer

Category: compressor

written by [www.mbsm.pro](http://www.mbsm.pro) | 22 June 2024



Mbsm.pro, DONPER, Refrigeration, Compressor, S96CY1, H170CY1, R600a (56 g), LBP, 240V 50HZ, 1/5 HP, 155W, CHEST FREEZER, Nikai, NCF340N5, Nikai 340L Chest Freezer

---

# Mbsm.pro, Compressor, 155w, 1/5 hp, 1bp, R600a, New Dongbei, HU155CY1, LC111CY, LW60CY

Category: compressor

written by [www.mbsm.pro](http://www.mbsm.pro) | 22 June 2024



Private Picture Copyright : [WWW.MBSM.PRO](http://WWW.MBSM.PRO)

Mbsm.pro, Compressor, 155w, 1/5 hp, 1bp, R600a, New Dongbei, HU155CY1, LC111CY, LW60CY



Private Picture Copyright : [WWW.MBSM.PRO](http://WWW.MBSM.PRO)



Private Picture Copyright : [WWW.MBSM.PRO](http://WWW.MBSM.PRO)



Private Picture Copyright : [WWW.MBSM.PRO](http://WWW.MBSM.PRO)

ZMC, zanussi, Made in Egypt,  
Compressor, Frost Free Freezer,  
GM90AZ, EGM90AZ, 155W, 1/5Hp, 134A,

150G, Electrostar Freezer, 260L  
CRoss, 235L SStorage , 220v-50H, 1.2A,  
Class T

Category: compressor

written by [www.mbsm.pro](http://www.mbsm.pro) | 22 June 2024



OO HUAWEI NOVA 5T  
OO AI QUAD CAMERA

Private Picture Copyright : [WWW.MBSM.PRO](http://WWW.MBSM.PRO)

## COMPRESSOR TECHNICAL DATA

General Data

Refrigerant: R134a

Application: LBP

**Evaporating Temperature Range:** -30°C to -10°C  
**Voltage/Frequency:** 220/240V/50 HZ  
**Compressor Cooling:** Static  
**Expansion Device:** Capillary Tube  
**Packaging Quantity:** Multi – 96:120 pcs  
**Approvals:** CE-VDE-GOST

## Mechanical Data

**Oil Charge:** 300 cm<sup>3</sup>  
**Oil Type Configuration:** ester  
**Oil Type Viscosity:** 19 cSt  
**Weight:** 10 kg

## Electrical Data

**Motor Type:** RSIR / RSCR\*  
**Voltage working range at 50 Hz:** 187-264V  
**Maximum Motor Temperature:** 130°C  
**Locked Rotor Current:** 14.46 / 9.86 A  
**Start Winding Resistance:** 23.40Ω at 25°C  
**Run Winding Resistance:** 8.08 Ω at 25°C  
**Phase:** 1 ph

## External Characteristics

**Internal Diameter** (mm)  
**Suction Connector** 6.5  
**Discharge Connector** 4.9  
**Process Connector** 6.5  
**Material** Copper

## Electrical Components

**Starting Device:** PTC 14Ω  
**Motor Protection:** T0490/xx

**ZMC**

**GM90AZ**

1137

**R 134 a**


220-240V-50Hz



474

0002263

OO HUAWEI NOVA 5T  
OO AI QUAD CAMERA



Made In Egypt

Frost Free Freezer

Model **ES 260 NF** طراز

Voltage **220 V - 50 HZ** **1.2A** **155 W**

Freezing Capacity 22 Kg/24Hr Freezer Stopage Volume 235 Lit.

Total Gross Volume 260 Lit Refrig. Storage Volume



024287

R134a **150g** وزن وسيط

التبريد

Class T صنع في مصر

max. lamp input	Without	15 W
Protection Rating	IPX 4	
According To	ES 6000 / 2008 - ISO 15502 / 2005	

OO HUAWEI NOVA 5T  
OO AI QUAD CAMERA

Private Picture Copyright : WWW.MBSM.PRO

# Hitachi Compressor, LBP, R134a, FL1152-RG, 1/6 Hp, 155W, série R012

Category: compressor

written by [www.mbsm.pro](http://www.mbsm.pro) | 22 June 2024

Code No.	Model	HP	Capacity (W)	Current (A)	Efficiency COP (w/w)	Voltage / Frequency
<b>R134a Models</b>						
R012001	FL 06S34-TAB	1/12	85	0.70	0.93	220V – 240V / 50Hz
R012002	FL 0739-SQ	1/10	114	0.72	1.20	
R012003	FL 0847-SD	1/8	130	0.83	1.19	
R012005	FL 1152-SB	1/6	143	0.82	1.27	
R012006	FL 1257-SR	1/5	160	0.90	1.25	
R012007	FL 14S62-TAD	1/5	175	0.95	1.30	
R012008	FL 1568-SQ	1/4	200	1.11	1.30	
R012009	FL 20S88-TAC	1/3	255	1.50	1.25	
R012010	FL1888-SE	1/3	245	1.51	1.25	
<b>R600a Models</b>						
	CL 0545-SZ	1/12	62	0.70	1.12	220V – 240V / 50Hz
	CL 1297-SA	1/5	156	0.90	1.46	
	CL 1310-SA	1/5+	163	0.95	1.48	
<b>R600a Models (Inverter)</b>						
	CL 1588-DZ	1/6	134	0.83	1.62	220V – 240V / 50Hz
	CL 1610-DL	1/5	160	0.90	1.65	

Private Picture Copyright: [WWW.MBSM.PRO](http://WWW.MBSM.PRO)

Code No.	Model	HP	Capacity (W)	Current (A)	Efficiency COP (w/w)	Voltage / Frequency
<b>R134a Models</b>						
R012001	FL 06S34-TAB	1/12	85	0.70	0.93	220V – 240V / 50Hz
R012002	FL 0739-SQ	1/10	114	0.72	1.20	
R012003	FL 0847-SD	1/8	130	0.83	1.19	
R012005	FL 1152-SB	1/6	143	0.82	1.27	
R012006	FL 1257-SR	1/5	160	0.90	1.25	
R012007	FL 14S62-TAD	1/5	175	0.95	1.30	
R012008	FL 1568-SQ	1/4	200	1.11	1.30	
R012009	FL 20S88-TAC	1/3	255	1.50	1.25	
R012010	FL1888-SE	1/3	245	1.51	1.25	
<b>R600a Models</b>						
	CL 0545-SZ	1/12	62	0.70	1.12	220V – 240V / 50Hz
	CL 1297-SA	1/5	156	0.90	1.46	
	CL 1310-SA	1/5+	163	0.95	1.48	
<b>R600a Models (Inverter)</b>						
	CL 1588-DZ	1/6	134	0.83	1.62	220V – 240V / 50Hz
	CL 1610-DL	1/5	160	0.90	1.65	

Private Picture Copyright: [WWW.MBSM.PRO](http://WWW.MBSM.PRO)

HITACHI FL1152-RG

220V 50/60Hz OIL 2010.04.27



SERIAL NO. 00542 HFC-134a

⚠ WARNING | HIGH TEMPERATURE  
ELECTRIC SHOCK  
DO NOT TOUCH H24

60Hz	FL1462-P*	6.2	180	154	615	350	St	RSR	10.5	200	
	FL1462-P*	6.2	210	180	717	310	St	RSCR	11.8	216	
	FL1568-P*	6.8	210	180	717	310	St	RSCR	11.5	217	
	FL1675-P*	7.5	233	200	795	300		OC	RSR	10.8	216
	FL1875-P*	7.5	225	193	768	300		OC	RSR	11.9	211
	FL1875-P*	7.5	255	219	871	300		OC	RSCR	11.9	216
	FL0634-U*	3.4	98	84	335	270	St	RSR	8.3	179	
	FL0739-U*	3.9	114	98	389	270	St	RSR	8.3	179	
	FL1052-U*	5.2	147	126	502	270	St	RSR	8.1	179	
127V	FL1152-U*	5.2	155	133	529	240	St	RSR	9.0	180	
60Hz	FL1262-U*	6.2	173	148	591	320	St	RSR	9.8	195	
	FL1462-U*	6.2	180	154	615	350	St	RSR	10.5	200	
	FL1568-U*	6.8	208	178	710	310	St	RSCR	11.5	216	
	FL1568-U*	6.8	228	196	778	310	St	RSR	10.5	200	
	FL1875-U*	7.5	225	193	768	300		OC	RSR	11.1	216
200V	FL1875-T*	7.5	200	232	172	683	300	OC	IR	11.1	211
50/60Hz	FL2088-T*	8.8	263	290	226	898	300	OC	IR	11.1	211
	FL0634-R*	3.4	98	84	335	270	St	RSR	8.0	179	
	FL0739-R*	3.9	115	99	393	270	St	RSR	8.0	179	
	FL0845-R*	4.5	122	105	417	240	St	RSR	8.7	180	
220V	FL1052-R*	5.2	150	129	512	240	St	RSR	8.9	180	
60Hz	FL1152-R*	5.2	155	133	529	270	St	RSR	8.1	179	
	FL1262-R*	6.2	162	139	553	320	St	RSR	9.8	195	
	FL1462-R*	6.2	207	178	707	300	St	RSR	10.6	196	
	FL1568-R*	6.8	228	196	778	310	St	RSR	10.5	200	
	FL1568-R*	6.8	181	155	618	300	St	RSCR	11.5	216	
	FL1875-R*	7.5	238	204	813	300		OC	RSR	11.1	216
	FL0634-S*	3.4	95	82	324	240	St	RSCR	9.0	180	
	FL0634-S*	3.4	82	70	280	270	St	RSR	7.8	179	
	FL0734-S*	3.4	95	82	326	240	St	RSCR	9.0	180	



Private Picture Copyright: WWW.MBSM.PRO

Mbsm\_dot\_pro\_private\_PDF\_FL1152-RGTélécharger

www.mbsm.pro, COMPRESSOR , 1/5Hp  
,EGL75AA , R134A, 155W, LBP, 7.39CM3

Category: Solutions,Tester ok  
written by www.mbsm.pro | 22 June 2024



PictureS Mbsm Dot Pro : www.mbsm.pro

Low-temperature refrigerator compressor with a cylinder capacity of 7.39cm<sup>3</sup> and a cooling capacity of 155W. Works with refrigerant R134a.