

Mbsm.pro, LG, CMA057LHEG, 1/5 hp, R134A, 135 g, Alu Wire, compressor, lbp, 160 w, 1ph, BCD-192, SWAIDY, REFRIGERATOR

Category: compressor

written by www.mbsm.pro | 30 January 2024



Private Picture Copyright : WWW.MBSM.PRO

Mbsm.pro, LG, CMA057LHEG, 1/5 hp, R134A, 135 g, Alu Wire, compressor, lbp, 160 w, 1ph, BCD-192, SWAIDY, REFRIGERATOR

Mbsm.pro, Whirlpool, ATD60XL, W13M, Refrigerator, Compressor, 160 w, 1/5 hp, hbp

Category: compressor,expertise

written by www.mbsm.pro | 30 January 2024



Mbsm.pro, Whirlpool, ATD60XL, W13M, Refrigerator, Compressor, 160 w, 1/5 hp, hbp

Mbsm.pro, Compressor, MA57LABM, 1/5 hp, 160 w, Lbp, Refrigerator, LG, GR-B562YC

Category: compressor,Refrigerator

written by www.mbsm.pro | 30 January 2024



Private Picture Copyright : WWW.MBSM.PRO

Mbsm.pro, Compressor, MA57LABM, 1/5 hp, 160 w, Lbp, Refrigerator, LG, GR-B562YC

Mbsm.pro, Compressor Acc, hmk95at, 1/5 hp, r600a, 160 w

Category: compressor

written by mahdi miled | 30 January 2024



● ○ REDMI NOTE 8
∞ AI QUAD CAMERA

Private Picture Copyright : WWW.MBSM.PRO

Technical data

Click over each model for complete details and technical sheet.

Model	Refrigerant	Rated Voltage	Frequency	Displacement	Motor Type	Cooling Capacity		COP without R.C.		COP with R.C.		Approval	Height	Net Weight
						ASHRAE	CECOMAF	ASHRAE	CECOMAF	ASHRAE	CECOMAF			
						-23.3° [W]	-25° [W]	-23.3° [W/W]	-25° [W/W]	-23.3° [W/W]	-25° [W/W]			
HMK70AA	R600a	220-240	50	6.6	RSIR	116	87	1.49	1.18	-	-	VDE, EAC, CE	159	7.2
HMK80AA	R600a	220-240	50	8.1	RSIR	136	102	1.50	1.18	-	-	VDE, EAC, CE	159	7.2
HMK95AA	R600a	220-240	50	9.6	RSIR	167	125	1.53	1.20	-	-	VDE, EAC, CE	159	7.5
HMK12AA	R600a	220-240	50	11.1	RSIR	198	149	1.53	1.20	-	-	VDE, EAC, CE	167	8.4
HMK95AT	R600a	200-240	50	9.6	RSIR	167	126	1.53	1.20	-	-	CE	167	8.4



Private Picture Copyright : WWW.MBSM.PRO



ht : WWW.MBSM.PRO



REDMI NOTE 8
AI QUAD CAMERA

Private Picture Copyright : WWW.MBSM.PRO



Private Picture Copyright : WWW.MBSM.PRO



Private Picture Copyright : WWW.MBSM.PRO

Sangchai refrigeration, Fl series, Rl series, Cl series, Hitachi Compressor, FL1675-sc, 1/5 Hp, R-134A, Low back pressure, 160 w, Displacement 7.5 cm cube, 220-240 v 50 hz

Category: compressor

written by www.mbsm.pro | 30 January 2024

Hitachi Hermetic Compressors

FL Series

STANDARD MODEL

Application & Refrigerant LBP R134a

Model	Nominal Power		F	Cooling Capacity			D	Cooling			O	Wg	Motor Type	Power Source					Dimension
	HP	W		Hz	W	Kcal/h		BTU/h	cm3	N				Oil	Fan	cm3	Kg	1	
FL0634	1/12	65	50	78	67	266	3.42				200	6.8		•				•	Type1-165
				60	90	77								307	•				
FL0739	1/10	75	50	95	82	324	3.94				270	7.8		•				•	Type1-179
				60	108	93								368	•				
FL0845	1/8	85	50	105	90	358	4.50				270	8.1	RSIR	•				•	Type2-180
				60	118	101								403	•				
FL1052	1/6	100	50	120	103	409	5.19	•			240	8.3	CSIR	•				•	Type1-195
				60	140	120								478	•				
FL1157	1/6	110	50	135	116	461	5.70				240	8.7		•				•	Type2-200
				60	158	136								539	•				
FL1262	1/5	125	50	150	129	512	6.23	•			320	9.5		•				•	Type3-211
				60	170	146								580	•				
FL1675	1/5	160	50	185	159	631	7.47		•	•	300	10.6		•				•	Type4-216
				60	210	181								717	•				
FL1888	1/4	180	50	215	185	734	8.83		•	•	300	11.1		•				•	Type4-216
				60	250	215								853	•				

Private Picture Copyright: WWW.MBSM.PRO

Sangchai refrigeration, Fl series, Rl series, Cl series, Hitachi Compressor, FL1675-sc, 1/5 Hp, R-134A, Low back pressure, 160 w, Displacement 7.5, 220-240 v 50 hz

Hitachi Hermetic Compressors

FL Series

STANDARD MODEL

Application & Refrigerant LBP R134a

Model	Nominal Power		F	Cooling Capacity			D	Cooling			O	Wg	Motor Type	Power Source					Dimension
	HP	W		Hz	W	Kcal/h		BTU/h	cm3	N				Oil	Fan	cm3	Kg	1	
FL0634	1/12	65	50	78	67	266	3.42				200	6.8		•				•	Type1-165
				60	90	77								307	•				
FL0739	1/10	75	50	95	82	324	3.94				270	7.8		•				•	Type1-179
				60	108	93								368	•				
FL0845	1/8	85	50	105	90	358	4.50				270	8.1	RSIR	•				•	Type2-180
				60	118	101								403	•				
FL1052	1/6	100	50	120	103	409	5.19	•			240	8.3	CSIR	•				•	Type1-195
				60	140	120								478	•				
FL1157	1/6	110	50	135	116	461	5.70				240	8.7		•				•	Type2-200
				60	158	136								539	•				
FL1262	1/5	125	50	150	129	512	6.23	•			320	9.5		•				•	Type3-211
				60	170	146								580	•				
FL1675	1/5	160	50	185	159	631	7.47		•	•	300	10.6		•				•	Type4-216
				60	210	181								717	•				
FL1888	1/4	180	50	215	185	734	8.83		•	•	300	11.1		•				•	Type4-216
				60	250	215								853	•				

Private Picture Copyright: WWW.MBSM.PRO



Private Picture Copyright : WWW.MBSM.PRO

Detail of Label

F L 14 62 - S B

Series name/Refrigerant

- F =R134a
- R =R404A
- C =R600a

Application category:

- L = Low back pressure
- H = High back pressure

Development

- A = With oil charge
- T = With out oil charge

Nominal power (Out. psat)			
Sign	Output(W)	Sign	Output(W)
04	45	15	150
05	55	16	160
06	65	17	170
07	75	18	180
08	85	20	200
10	100	25	250
11	110	35	350
12	125	40	400
14	140	45	450

Nominal voltages / Power source			
Sign	Phase/voltage/frequency	Sign	Phase/voltage/frequency
H	1Ø 100 V 50/60 Hz	S	1Ø 220 - 240 V 50 Hz
P	1Ø 110 V 120 V 60 Hz	D	1Ø 100 V 50/60 Hz
U	1Ø 127 V 60 Hz	T	3Ø 200 V 50/60 Hz
R	1Ø 200 - 220 V 60 Hz		

Displacement			
Sign	Displacement(Cm ³)	Sign	Displacement(Cm ³)
24	2.4	62	6.2
26	2.6	66	6.6
34	3.4	75	7.5
39	3.9	86	8.6
45	4.5	97	9.7
52	5.2	11	11.0
57	5.7		

Private Picture Copyright : WWW.MBSM.PRO

Mbsm_dot_pro_private_PDF_Hitachi-catalogueTélécharger
 Mbsm_dot_pro_private_PDF_FL1675Télécharger