

MBSM.pro, Compressor, 13HP, Danfoss,
Performer, Scroll Compressor, Sm160,
Sm161t4vc, Refrigeration Chiller, 3
ph, 380 v, 38BB 055 – 240, 38bb-250
9e/k, 38BB 250, 250 = 250000 kBtu/hr,
30 Ton, r22, 19 Kg, suction 1-1/8"–2,
refoulement 5/8"–2

Category: Archivation,compressor
written by www.mbsm.pro | 19 April 2022

Danfoss
MADE IN CHINA

Model no: **SM161T4VC**



Serial no: **GD2503110072**



M 380-400 V 3 ~ 50 Hz
460 V 3 ~ 60 Hz
LR 145 A MAX OPER. 31 A
Thermally protected system
P.E.D. LP side HP side
Marking 25 bar 27.8 bar
PS 63 °C 150 °C
TS max -35 °C -35 °C
TS min 17.6 L 20 L
Volume 17.6 L 20 L
Lubricant: MINERAL OIL 160P

CE ENEC
0062



2016 Refrigerant: R22 (UL rating) - R417A with 160S2
PROTECTED BY DOMESTIC AND FOREIGN PATENTS

WARNING

Installation and servicing shall be performed by trained personnel only. Failure to observe these safety warnings could result in serious injury or death.
ELECTRIC SHOCK HAZARD: Turn off power before servicing. Observe all electrical safety rules.
FLAME HAZARD: Do not smoke or use open flame near the equipment until it has cooled and pressure has been released.
HIGH PRESSURE: System contains refrigerant and oil under pressure. Pressure increases when the high and low side valves are opened or when the system is disturbed.
FLAME HAZARD: Use tubing cutter to remove refrigerant. Do not use torch or heat to remove refrigerant.



CAUTION
This unit is designed for use in a controlled environment. It is not intended for use in a hazardous or explosive atmosphere. Do not use in a hazardous or explosive atmosphere.
Do not use in a hazardous or explosive atmosphere. Do not use in a hazardous or explosive atmosphere.

Private Picture Copyright: WWW.MBSM.PRO

MBSM.pro, Compressor, 13HP, Danfoss, Performer, Scroll Compressor, Sm160, Sm161t4vc, Refrigeration Chiller, 3 ph, 380 v, 38BB 055 – 240, 38bb-250 9e/k, 38BB 250, 250 = 250000 kBTu/hr, 30 Ton, r22, 19 Kg, suction 1-1/8"–2, refoulement 5/8"–2