

Embraco FMXY9C Compressor: R600a, 1/6 HP

Category: Refrigeration

written by www.mbsm.pro | 8 January 2026



Private Picture Copyright : WWW.MBSM.PRO

Mbsmpro.com, Compressor, FMXY9C, Embraco, R600a, 1/6 hp, Cooling, 220-240V, 1Ph 50Hz, LBP, Fullmotion, Inverter, -35°C to -10°C, CE UL, Austria

Mbsm.pro, COMPRESSOR, 1/8 hp, SECOP, HTK70AA, LBP , R600A, 220 – 240V, 50HZ

Category: compressor

written by www.mbsm.pro | 8 January 2026

Verdichter - Cubigel

R-600a, LBP

Hermetische Verdichter für Kapillarrohrbetrieb.
Hochleistungs-Verdichter mit Betriebskondensatoren.
LBP Temperaturbereich -30 °C bis -10 °C.
Netzspannung 220 - 240 V / 50 Hz.



Artikelnr.	Typ	Leistung (PS)	Kälteleistung [W] T _s -25 °C, T _e +45 °C
			-25
47-32 HQY45AA	HQY 45 AA	1/12	52
47-32 HQY55AA	HQY 55 AA	1/9	62
47-32 HQY70AA	HQY 70 AA	1/8	80
47-32 HQY80AA	HQY 80 AA	1/7	99
47-32 HQY90AA	HQY 90 AA	1/7	109
47-32 HQY99AA	HQY 99 AA	1/6	119
47-32 HPY12AA	HPY 12 AA	1/5	144
47-32 HPY14AA	HPY 14 AA	1/5	166
47-32 HPY16AA	HPY 16 AA	1/4	181

Private Picture Copyright : WWW.MBSM.PRO

Mbsm.pro, COMPRESSOR, 1/8 hp, SECOP, HTK70AA, LBP , R600A, 220 – 240V, 50HZ

Mbsm.pro, CUBIGEL, NUh55LA, compressor, R290, 1/3HP, 1bp, 220-240V

Category: compressor

written by www.mbsm.pro | 8 January 2026

cubigel
compressors

NUH55LA



THERMALLY 220-240V~ 50 Hz PH1
PROTECTED



NUH55LA 17062802121



SHOT ON MI 8 LITE
AI DUAL CAMERA

Private Picture Copyright : WWW.MBSM.PRO

Mbsm.pro, CUBIGEL, NUH55LA, compressor, R290, 1/3HP, 1bp, 220-240V

Mbsm.pro, Compressor, hpk190A, 1/4 hp++, 1/3 hp-, R600, HMBP, 220/240V, 50Hz, 12.11 cc , unionaire, UR-350, 340 L, R600a/48g, 0.87 A

Category: expertise

written by www.mbsm.pro | 8 January 2026



Private Picture Copyright : WWW.MBSM.PRO

Mbsm.pro, Compressor, hpk190A, 1/4 hp++, 1/3 hp-, R600, HMBP, 220/240V, 50Hz, 12.11 cc , unionaire, UR-350, 340 L, R600a/48g, 0.87 A

Bsa357cv-r1an Smal compressor replaced by qx36h

Category: compressor

written by www.mbsm.pro | 8 January 2026



Private Picture Copyright : WWW.MBSM.PRO

Mbsm.pro, Compressor, bsa357cv-r1an, Highly, Hitachi, R134a, Rotary Compressor, for Air Condition, 220/240V, 1245BTU, run capacitor 5 mF/38, replaced by qx36h

Mbsm.pro, LG, NS30LAEG, 1/10 hp, Small Fridge/freezer, mini bar, Compressor, 1ph, 220-240v, 70 w, R134a

Category: compressor

written by www.mbsm.pro | 8 January 2026



ate Picture Copyright : WWW.MBSM.PRO

Mbsm.pro, LG, NS30LAEG, 1/10 hp, Small Fridge/freezer Compressor, 1ph, 220-240v, 70 w, R134a

Mbsm.pro, Compressor, ZEL, GML160G, 1/6 hp, 129 w, LBP, R134a, 220-240V, KONOR CATALOG

Category: Archivation,compressor

written by www.mbsm.pro | 8 January 2026



Private Picture Copyright : WWW.MBSM.PRO

Mbsm.pro, Compressor, ZEL, GML160G, 1/6 hp, 129 w, LBP, R134a, 220-240V, KONOR CATALOG

Mbsm.pro, Compressor, 105g 6728,
NL7FT, 1/4hp, 105g6728, Danfoss,
R134A, 220-240V, 1bp

Category: Archivation,compressor

written by www.mbsm.pro | 8 January 2026



Private Picture Copyright: WWW.MBSM.PRO

Mbsm.pro, Compressor, 105g 6728, NL7FT, 1/4hp, 105g6728, Danfoss, R134A,
220-240V

COMPRESSOR, MX21TBa, R404A, 1HP,
CUBIGEL, HMBP, 220/240V, 50Hz, 20,72
cm³

Category: compressor

written by www.mbsm.pro | 8 January 2026



Private Picture Copyright : WWW.MBSM.PRO

Détails techniques

220/240V 50Hz

puissance 1 HP – cylindrée 21,75 cc

gaz R404a/R507 HMBP

...et d'autres dispositifs

MX21TB – ACC – CELLI

MX21TB – CUBIGEL – ELECTROLUX

605093 – GEV – ITV



Private Picture Copyright: WWW.MBSM.PRO


Mbsm_dot_pro_private_PDF_danfoss_MX21TBa_R404A_220_50Télécharger

Brand:	Cubigel
UPC:	3070063
Manufacturer reference:	MX21TBa
Application:	HMBP
Power supply:	220/240V 50Hz
Cooling capacity:	3047 W
Horsepower:	1 Hp
Displacement:	21.7 cm ³
Refrigerant:	R404a/R507
Weight:	17.5 kg
Motor type:	CSR
Type:	Hermetic reciprocating compressor

Compressor, ACC, Cubigel, GL60AN, R134a, 220-240V, HMBP, 1/6HP

Category: Non classé

written by www.mbsm.pro | 8 January 2026



Private Picture Copyright : WWW.MBSM.PRO

Type: Hermetic piston compressors Producer: ACC Series: HMBP

Model: GL60AN

General data

Refrigerant: R134a

Discharge element: C

Cooling: S
Maximum ambient temperature [°C]: 50

Compressor's data

Cylinder capacity [cm³]: 6
Displacement [m³/h]: 1
Weight [kg]: 9,9
Oil charge [cm³]: 345
Oil type: ISO VG 19 ESTER

Engine's data


Engine type: RSIR
Power [KM]: 1/6
Starting element: LST
Power supply: 220V 50Hz
Voltage range: 170-264
Locked rotor current [A]: 14,6
Running winding resistance (25°C) [Ω]: 9,33
Starting winding resistance (25°C) [Ω]: 10,81

Electrical data

Relays: 3003
Shielding element: MRA38085, T0515, AF11BJ
Starting capacitor volume [μF]:

Connections

	milimeters	inches
Suction tube:	6,5	
Service tube:	6,5	
Discharge tube:	4,9	



Private Picture Copyright : WWW.MBSM.PRO

Mbsm_dot_pro_private_PDF_GL60ANTélécharger