

NL8.4FT ,Tropical , 1/4 Hp Compressor
R134a 220-240V 50Hz ,HERMETIC ,143 W
-25/+55 °C , LBP, 105g6866, 105g6865

Category: Technologie,Tester ok
written by www.mbsm.pro | 21 April 2020

NL8.4FT

220-240V~50Hz



SECOP

LBP LST/HST R134a

SUCTION



ERL



MKB56203



105G

6865

CE

MADE IN SLOVAKIA

PictureS Mbsm Dot Pro : www.mbsm.pro

NL8.4FT ,Tropical , 1/4 Hp Compressor R134a 220-240V 50Hz ,HERMETIC ,143 W
-25/+55 °C , LBP

Mbsm.pro , Compressors ZMC, EGL90AA, R-134a ,1/4 HP LBP, 220 – 240 V

Category: Solutions, Tester ok
written by www.mbsm.pro | 21 April 2020



PictureS Mbsm Dot Pro : www.mbsm.pro

Mbsm.pro , Compressors ZMC, EGL90AA, R-134a ,1/4 HP LBP, 220 – 240 V

BRAND

◦ – ZMC

TECHNICAL SPECIFICATIONS :

- MODEL: EGL 90 AA
- POWER: 1/4 Hp
- VOLTAGE: 220 – 240 V
- WATT: 227.00 W
- REFRIGERANT GAS: R 134
- K.CAL: 195.00 Cal.

Features : The compressors form the basis of the refrigerant system and function to compress the gas from the evaporation to the condensation pressure.

USAGE PLACES :

It is used in Refrigerator devices belonging to all brands and models.

INSTRUCTIONS FOR USE:

Zmc EGL90AA; It is recommended to be used by a specialist authorized or authorized service.



Picture5 Mbsm Dot Pro : www.mbsm.pro

[Mbsm_dot_pro_private_PDF_catalogo_cubigel_R134aTélécharger](#)
[Mbsm_dot_pro_private_PDF_cubigel-katalogTélécharger](#)

MBSM.PRO , Compressor, Electrolux-Zem GL60AA R134A , 1/6 HP , 1PH , 220-240 V 50 Hz

Category: Solutions, Tester ok
written by Jamila | 21 April 2020



PictureS Mbsm Dot Pro : www.mbsm.pro

MBSM.PRO , Compressor, Electrolux-Zem GL60AA R134A ,1/6 HP , 1PH , 220-240 V 50 Hz



- Puissance en cheval 1/6 CV
- Cylindrée 5.99 cm³
- 220-240 V 50 Hz
- Gaz R134a LBP
- Température d'utilisation max. 32°C
- Avec boîtier et système de démarrage

La photo montre l'aspect du compresseur, pas son étiquette réelle

Codes fabricants

- ACC-GL60AA
- ACC-GL60AB
- ACC-GL60AH
- CUBIGEL-GL60AA
- CUBIGEL-GL60AB
- CUBIGEL-GL60AH
- MONDIAL ELITE-4106004
- MONDIAL ELITE-1147031
- Embraco Aspera- B1112Z





PictureS Mbsm Dot Pro : www.mbsm.pro



PictureS Mbsm Dot Pro : www.mbsm.pro

Mbsm_dot_pro_private_PDF_GL60AATélécharger
Mbsm_dot_pro_private_PDF_-GL60AATélécharger

590689

GL60AA 99H271A

GL60AA

08283

03254

267799

THERMALLY 220 - 240 V~ 50 Hz PH1
PROTECTED

R134a



CE H



Type: Hermetic piston compressors **Producer: ACC** **Series: HMBP**

Model: GL60AA

General data

Refrigerant: R134a
Discharge element: C
Cooling: S
Maximum ambient temperature [°C]: 43

Compressor's data

Cylinder capacity [cm³]: 6
Displacement [m³/h]: 1
Weight [kg]: 9,1
Oil charge [cm³]: 265
Oil type: ISO VG 19 ESTER

Engine's data

Engine type: RSIR
Power [KM]: 1/6
Starting element: LST
Power supply: 220V 50Hz
Voltage range: 187-264
Locked rotor current [A]: 9,9
Running winding resistance (25°C) [Ω]: 15,6
Starting winding resistance (25°C) [Ω]: 21,31

Electrical data

Relays: 3003
Shielding element: MRA38028, T0508, AF18FU
Starting capacitor volume [μF]:

Connections

	milimeters	inches
Suction tube:	6,5	
Service tube:	6,5	
Discharge tube:	4,9	