

MBSM.pro, Compressor, 13HP, Danfoss, Performer, Scroll Compressor, Sm160, Sm161t4vc, Refrigeration Chiller, 3 ph, 380 v, 38BB 055 – 240, 38bb-250 9e/k, 38BB 250, 250 = 250000 kBtu/hr, 30 Ton, r22, 19 Kg, suction 1-1/8"–2, refoulement 5/8"–2

Category: Archivation,compressor

written by www.mbsm.pro | 19 April 2022

Danfoss
MADE IN CHINA

Model no: **SM161T4VC**



Serial no: **GD2503110072**



M 380-400 V 3 ~ 50 Hz
460 V 3 ~ 60 Hz
LR 145 A MAX OPER. 31 A
Thermally protected system
P.E.D. LP side HP side
Marking 25 bar 27.8 bar
PS 63 °C 150 °C
TS max -35 °C -35 °C
TS min 17.6 L 20 L
Volume 17.6 L 20 L
Lubricant: MINERAL OIL 160P

CE ENEC
0062



2016 Refrigerant: R22 (UL rating) - R417A with 160S2
PROTECTED BY DOMESTIC AND FOREIGN PATENTS

WARNING

Installation and servicing shall be performed by trained personnel only. Failure to observe these safety warnings could result in serious injury or death.
ELECTRIC SHOCK HAZARD: Turn off power before servicing. Disconnect all conductors.
Keep terminal cover in place and securely fastened. Refrigerant power is applied to the compressor but the refrigerant unit is grounded system only.
HIGH PRESSURE: System contains refrigerant and oil under pressure. Pressure increases from both the high and low side before servicing when safety devices.
FIRE HAZARD: Use tubing cutter to remove refrigerant. Do not use torches or cut using sharp tools.



CAUTION
Use only manufacturer's recommended oil and refrigerant. Do not mix different types of oil or refrigerant. Do not use refrigerant from different sources. Do not use refrigerant from different sources.

Private Picture Copyright: WWW.MBSM.PRO

MBSM.pro, Compressor, 13HP, Danfoss, Performer, Scroll Compressor, Sm160, Sm161t4vc, Refrigeration Chiller, 3 ph, 380 v, 38BB 055 – 240, 38bb-250 9e/k, 38BB 250, 250 = 250000 kBTu/hr, 30 Ton, r22, 19 Kg, suction 1-1/8"–2, refoulement 5/8"–2