

MBSM.pro, Compressor, 13HP, Danfoss, Performer, Scroll Compressor, Sm160, Sm161t4vc, Refrigeration Chiller, 3 ph, 380 v, 38BB 055 – 240, 38bb-250 9e/k, 38BB 250, 250 = 250000 kBtu/hr, 30 Ton, r22, 19 Kg, suction 1-1/8"–2, refoulement 5/8"–2

Category: Archivation,compressor
written by www.mbsm.pro | 19 April 2022

Danfoss
MADE IN CHINA

Model no: **SM161T4VC**



Serial no: **GD2503110072**



M 380-400 V 3 ~ 50 Hz
460 V 3 ~ 60 Hz
LR 145 A MAX OPER. 31 A
Thermally protected system
P.E.D. LP side HP side
Marking 25 bar 27.8 bar
PS 63 °C 150 °C
TS max -35 °C -35 °C
TS min 17.6 L 20 L
Volume 17.6 L 20 L
Lubricant: MINERAL OIL 1600

CE C US EAC
0062



2016 Refrigerant: R22 (UL rating) - R417A with 160SZ
PROTECTED BY DOMESTIC AND FOREIGN PATENTS

WARNING

Installation and servicing shall be performed by trained personnel only. Failure to observe these safety warnings could result in serious injury or death.
ELECTRIC SHOCK HAZARD: Turn off power before servicing. Disconnect all conductors.
Wear personal safety gear and properly grounded equipment prior to working on the compressor. Use the equipment with grounded systems only.
HIGH PRESSURE: System contains refrigerant and oil under pressure. Service pressure from both the high and low side before servicing any safety devices.
FIRE HAZARD: Use tubing cutter to remove refrigerant. Do not use torch or oil near torch line.



CAUTION
This unit is not to be used for...
...refrigeration / laboratory...
...food, drug, medical, pharmaceutical...

Private Picture Copyright: WWW.MBSM.PRO

MBSM.pro, Compressor, 13HP, Danfoss, Performer, Scroll Compressor, Sm160, Sm161t4vc, Refrigeration Chiller, 3 ph, 380 v, 38BB 055 – 240, 38bb-250 9e/k, 38BB 250, 250 = 250000 kBtu/hr, 30 Ton, r22, 19 Kg, suction 1-1/8"-2, refoulement 5/8"-2