MBSM.PRO , Compressor, Electrolux-Zem GL60AA R134A ,1/6 HP , 1PH , 220-240 V 50 Hz

written by Jamila | 1 October 2018
MBSM.PRO , Compressor, Electrolux-Zem GL60AA R134A ,1/6 HP , 1PH , 220-240 V 50 Hz

- Puissance en cheval 1/6 CV
- Cylindrée 5.99 cm³
- 220-240 V 50 Hz
- Gaz R134a LBP
- Température d’utilisation max. 32°C
- Avec boitier et système de démarrage

La photo montre l’aspect du compresseur, pas son étiquette réelle

Codes fabricants

- ACC-GL60AA
- ACC-GL60AB
- ACC-GL60AH
- CUBIGEL-GL60AA
- CUBIGEL-GL60AB
- CUBIGEL-GL60AH
- MONDIAL ELITE-4106004
- MONDIAL ELITE-1147031
- Embraco Aspera- B1112Z

PictureS Mbsm Dot Pro : www.mbsm.pro

PictureS Mbsm Dot Pro : www.mbsm.pro

PictureS Mbsm Dot Pro : www.mbsm.pro

Mbsm_dot_pro_private_PDF_GL60AATélécharger
Mbsm_dot_pro_private_PDF_-GL60AATélécharger

Private Picture Copyright : WWW.MBSM.PRO

Type: Hermetic piston compressorsProducer: ACCSeries: HMBP
Model: GL60AA

General data

Refrigerant:	R134a
Discharge element:	C
Cooling:	S
Maximum ambient temperature [ºC]:	43

Compressor’s data

Cylinder capacity [cm³]:	6
Displacement [m³/h]:	1
Weight [kg]:	9,1
Oil charge [cm³]:	265
Oil type:	ISO VG 19 ESTER

Engine’s data

Engine type:	RSIR
Power [KM]:	1/6
Starting element:	LST
Power supply:	220V 50Hz
Voltage range:	187-264
Locked rotor current [A]:	9,9
Running winding resistance (25ºC) [Ω]:	15,6
Starting winding resistance (25ºC) [Ω]:	21,31

Electrical data

Relays:	3003
Shielding element:	MRA38028, T0508, AF18FU
Starting capacitor volume [µF]:	

Connections

	milimeters	inches	
Suction tube:	6,5		
Service tube:	6,5		
Discharge tube:	4,9		