

Mbsm.pro, compressor, EM Series, Embraco, EMY75HLC, 211 w, 1/4 hp, lbp, 750 btu, r134a

Category: compressor

written by www.mbsm.pro | 30 May 2022

| | | | | | | | | | | | | | | | |
|--------|------------|------------|------------|------------|-------|-------|-------|------|------|--------|---------|---------|------|------|------|
| R 134a | EMZ | EMZ 66 CLP | 220~240/50 | 10.61 | 190 | 163.4 | 1.74 | 1.50 | 4 | | ISO 5 | CCC/VDE | 171 | 6.73 | |
| | | EMX | EMX 32 CLC | 220~240/50 | 5.96 | 102 | 87.7 | 1.78 | 1.53 | 2.5 | | ISO 5 | CCC | 166 | 6.54 |
| | | | EMX 40 CLC | 220~240/50 | 7.24 | 128 | 110.1 | 1.80 | 1.55 | 4 | | ISO 5 | CCC | 166 | 6.54 |
| | EMB | EMB 32 CLC | 220~240/50 | 5.96 | 103 | 88.6 | 1.88 | 1.62 | 2.5 | | ISO 5 | CCC | 166 | 6.54 | |
| | | EMB 40 CLC | 220~240/50 | 7.24 | 128 | 110.1 | 1.92 | 1.65 | 4 | | ISO 5 | CCC/VDE | 171 | 6.73 | |
| | | EMB 46 CLC | 220~240/50 | 7.96 | 142 | 122.1 | 1.90 | 1.63 | 4 | | ISO 5 | CCC/VDE | 171 | 6.73 | |
| | | EMB 55 CLC | 220~240/50 | 9.05 | 163 | 140.2 | 1.88 | 1.62 | 4 | | ISO 5 | CCC/VDE | 171 | 6.73 | |
| | | EMB 66 CLC | 220~240/50 | 10.61 | 190 | 163.4 | 1.87 | 1.61 | 4 | | ISO 5 | CCC/VDE | 171 | 6.73 | |
| R 290 | EMT | EMT 45 HLP | 220~240/50 | 4.85 | 145 | 124.7 | 1.40 | 1.20 | | | ISO 7 | CCC/VDE | 158 | 6.22 | |
| | | EMU 45 HLP | 220~240/50 | 4.85 | 145 | 124.7 | 1.50 | 1.29 | | | ISO 7 | CCC/VDE | 158 | 6.22 | |
| | | EMU 55 HLP | 220~240/50 | 5.20 | 161 | 138.5 | 1.50 | 1.29 | | | ISO 7 | CCC/VDE | 166 | 6.54 | |
| | | EMU 65 HLP | 220~240/50 | 5.96 | 185 | 159.1 | 1.47 | 1.26 | | | ISO 7 | CCC/VDE | 166 | 6.54 | |
| | | EMU 45 HLP | 200~230/50 | 4.85 | 145 | 124.7 | 1.45 | 1.25 | | | ISO 22 | CCC/VDE | 158 | 6.22 | |
| | | EMU 55 HLP | 200~230/50 | 5.20 | 161 | 138.5 | 1.45 | 1.25 | | | ISO 22 | CCC/VDE | 166 | 6.54 | |
| | | EMU 65 HLP | 200~230/50 | 5.96 | 185 | 159.1 | 1.45 | 1.25 | | | ISO 22 | CCC/VDE | 166 | 6.54 | |
| | EMU | EMU 55 HLP | 115~127/60 | 4.15 | 148 | 127.3 | 1.46 | 1.26 | | | ISO 7 | UL | 158 | 6.22 | |
| | | EMY 55 HLC | 220~240/50 | 5.20 | 161 | 138.5 | 1.60 | 1.38 | 4 | | ISO 7 | CCC/VDE | 166 | 6.54 | |
| | | EMY 65 HLC | 220~240/50 | 5.96 | 185 | 159.1 | 1.60 | 1.38 | 4 | | ISO 7 | CCC/VDE | 166 | 6.54 | |
| | | EMY 75 HLC | 220~240/50 | 7.00 | 215 | 184.9 | 1.60 | 1.38 | 4 | | ISO 7 | CCC/VDE | 171 | 6.73 | |
| | | EMY 50 HLP | 115~127/60 | 4.15 | 140 | 120.4 | 1.60 | 1.38 | 12 | | ISO 7 | UL | 158 | 6.22 | |
| | | EMY 55 HLP | 115~127/60 | 4.50 | 160 | 137.6 | 1.60 | 1.38 | 12 | | ISO 7 | UL | 158 | 6.22 | |
| | | EMY 60 HLP | 115~127/60 | 4.85 | 180 | 154.8 | 1.60 | 1.38 | 12 | | ISO 7 | UL | 166 | 6.54 | |
| | EMH | EMH 60 HER | 115~127/60 | 5.19 | 189 | 162.5 | 1.47 | 1.26 | | | ISO 7 | CCC | 166 | 6.54 | |
| EMT | EMT 2121 U | 220~240/50 | 5.57 | 256 | 220.0 | 1.42 | 1.22 | | 48 | ISO 22 | CCC/VDE | 166 | 6.54 | | |
| | EMT 2125 U | 220~240/50 | 5.96 | 301 | 259.0 | 1.48 | 1.28 | | 58 | ISO 22 | CCC/VDE | 166 | 6.54 | | |

测试条件: 蒸发-23.3° C (-10° F) 冷凝54.4° C (130° F) 吸气/环境32.2° C (90° F) 液体32.2° C (90° F)

Test Conditions: Evaporating: -23.3°C (-10°F) | Condensing: 54.4°C (130°F) | Gas and Ambient: 32.2°C (90°F) | Liquid: 32.2°C (90°F)

Private Picture Copyright: WWW.MBSM.PRO

Mbsm.pro, compressor, EM Series, Embraco, EMY75HLC, 211 w, 1/4 hp, lbp, 750 btu, r134a