

Mbsm.pro, Refrigerator, ref-88-04,  
Newal, BRANDT, W433253, 68L, 100W,  
r600a, 27g, Compressor, PW58BMF, 1/8  
hp, lbp

Category: compressor

written by www.mbsm.pro | 21 March 2024



Mbsm.pro, Refrigerator, ref-88-04, Newal, BRANDT, W433253, 68L, 100W, r600a,  
27g, Compressor, PW58BMF, 1/8 hp, lbp

Compressor, r600a, 1/5HP, LBP, 149W,  
htk12aa, Electrolux, Brandt, 220-240V  
50Hz, Run Capacitor: 4.0  $\mu$ F ( 5.0  $\mu$ F  
as alternative ) , Motor type

# RSCR/RSIR

Category: compressor

written by [www.mbsm.pro](http://www.mbsm.pro) | 21 March 2024



Private Picture Copyright : [WWW.MBSM.PRO](http://WWW.MBSM.PRO)

compressor/compressor ACC – Electrolux HTK12AA, LBP – R600a, Power consumption 1/5HP++, 220-240V/1/50Hz, Motor type RSIR, Injection: Capillary operation, Displacement 11.1 cm<sup>3</sup>, Oil type mineral oil, Oil quantity 170 cm<sup>3</sup>, Power 116 W at -25 / +55°C, Power consumption 149 W, Current 0.77, Weight 8.6Cooling capacity

-10 °C	-15 °C	-20 °C	-25 °C	-30 °C	-35 °C
300	240	188	144	107	78

Shipping Class                      Standard

<b>Scope Of Application</b>	LBP
<b>Lieferzeit</b>	2-3 Wochen
<b>Type Of Construction</b>	Piston
<b>Condensation Temperature</b>	55°C
<b>Maker</b>	ACC
<b>Manufacturer No.</b>	HPY12AA
<b>Displacement In Cm3</b>	11.1
<b>Measuring Requirements</b>	Ashrae
<b>Refrigerants</b>	R600a
<b>Series</b>	HPY
<b>Condensing Units Compressors</b>	Compressors
<b>Suspense</b>	220-240V
<b>Weight In Kg</b>	12.7

1. Be the first to review this product

[Mbsm\\_dot\\_pro\\_private\\_PDF\\_HTK12AA-1-1Télécharger](#)

[Mbsm\\_dot\\_pro\\_private\\_PDF\\_HTK12aa-1Télécharger](#)



Private Picture Copyright : [WWW.MBSM.PRO](http://WWW.MBSM.PRO)

## Verdichter - Cubigel

R-600a, LBP

Hermetische Verdichter für Kapillarrohrbetrieb.  
Hochleistungs-Verdichter mit Betriebskondensatoren.  
LBP Temperaturbereich -30 °C bis -10 °C.  
Netzspannung 220 - 240 V / 50 Hz.



Artikelnr.	Typ	Leistung (PS)	Kälteleistung [W] T <sub>e</sub> -25 °C, T <sub>k</sub> +45 °C	
				-25
47-32 HQY45AA	HQY 45 AA	1/12		52
47-32 HQY55AA	HQY 55 AA	1/9		62
47-32 HQY70AA	HQY 70 AA	1/8		80
47-32 HQY80AA	HQY 80 AA	1/7		99
47-32 HQY90AA	HQY 90 AA	1/7		109
47-32 HQY99AA	HQY 99 AA	1/6		119
47-32 HPY12AA	HPY 12 AA	1/5		144
47-32 HPY14AA	HPY 14 AA	1/5		166
47-32 HPY16AA	HPY 16 AA	1/4		181

Gesamtkatalog jetzt anfordern unter [info@kaeltepartner.net](mailto:info@kaeltepartner.net)!

 **Hinweis: Bilder Können vom Produkt abweichen**

Private Picture Copyright: [WWW.MBSM.PRO](http://WWW.MBSM.PRO)

Compressor, nbu1118y, réfrigérateur,  
brandt, BRANDT, MA-45CA562COMP-KU950,  
R600a, 1/4 Ch, 11,2 cm<sup>3</sup>, ACC,  
HMK12AA, SECOP, EMBRACO, NBU1118Y  
DANFOSS, NLE13KK3

Category: Non classé

written by [www.mbsm.pro](http://www.mbsm.pro) | 21 March 2024

**Embraco®** NBU1118Y

THERMALLY PROTECTED		0-240V-50Hz
CE	800a	
MIN. OIL 200°C / PH		

SUCTION SKM NO START WITHOUT STARTING DEVICE



815DA42 16/SEP/08 PA8LC10P

CAUTION RISK OF FIRE



R 600a

Compressor, nbu1118y, réfrigérateur, brandt, BRANDT, MA-45CA562COMP-KU950,  
R600a, 1/4 Ch, 11,2 cm<sup>3</sup>, ACC, HMK12AA, SECOP, EMBRACO, NBU1118Y DANFOSS,  
NLE13KK3

Modèles d'appareils concernés: 42X0249 – DZN4710XE – DZN4710XE/1 Pièce d'origine  
constructeur

Référence : MA-45CA562COMP-KU950

COMPRESSEUR R600a – 1/4 Ch – 11,2 cm<sup>3</sup>

ACC HMK12AA SECOP

Equivalent :

EMBRACO NBU1118Y

DANFOSS NLE13KK3 – NLE15K – HMK12AA

ELECTROLUX HP16AH

SECOP HMK12AA

**Embraco®** NBU1118Y

THERMALLY PROTECTED		0-240V-50Hz
CE	800a	
MIN. OIL 200°C / PH		

SUCTION SKM NO START WITHOUT STARTING DEVICE



815DA42 16/SEP/08 PA8LC10P

CAUTION RISK OF FIRE



R 600a



Private Picture Copyright: [WWW.MBSM.PRO](http://WWW.MBSM.PRO)

[Mbsm\\_dot\\_pro\\_private\\_PDF\\_NBU1118y-ametist-produse-doc1702-5Télécharger](#)

[Mbsm\\_dot\\_pro\\_private\\_PDF\\_NBU1118y-EMBRACO-ASPERATélécharger](#)

[Mbsm\\_dot\\_pro\\_private\\_PDF\\_NBU1118y-embraco-r600-compressorsTélécharger](#)