mbsm.pro , Compresseur Aspera , Embraco ,NEK2168GK , R404a/R507 , LBP ,3/4 HP,nominal output: 707 W

Category: Technologie, Tester ok

written by www.mbsm.pro | 18 April 2019

EMBRACO is a company specialized in cooling solutions and world leader in the hermetic compressor market. Our mission:

provide innovative solutions for a better quality of life, always

attentive to technological excellence and sustainability.

Technological leadership, operational excellence and sustainability are some of the pillars

which ensure the EMBRACO differential over other companies in the world market. Its

products are now considered the favorite leading home appliance manufacturers by major

automakers and are spotlighted by manufacturers of commercial refrigeration equipment.

With global operations and production capacity exceeding 34 million units a year, the

company offers solutions that are differentiated for their innovation and low energy

consumption. Its 11.500 employees work in factories and offices located in Brazil

(headquarters), China, Italy, Slovakia, Mexico, the United States and Russia. Energy efficiency is constantly sought in the processes, products and relationships with

the communities where it operates. Our company is the absolute leader in this segment,

being able to offer products that meet the most restrictive international standards

regarding energy consumption.

As a worldwide leader, EMBRACO tries to anticipate market changes, and in doing so, our

company is in a state of permanent transformation. We continuously assess our processes

in order to maintain our leadership within the industry and promote growth, without

forgetting the pillars of our organization.

Compressor ASPERA NEK2168GK | NEK 2168 GK

Refigerant	R404/R507	
Working range[stC] LBP	-40 to -10	
Nominal capacity [W] (evaporating temperature -23,3C, Condensing temperatur +54,4C)	688	
Power supply	220-240V 50Hz	
Engine type	CSIR	
Displacement [cm³]	14,28	


Weight [kg] 11,6

Evaporating temperature +55 C

Evaporating Temperature	Cooling Capacity +/-5%	Power Consumption +/-5%	Current Consumption +/-5%		+/-7%			
°C	(kcal/h)	(W)	(Btu/h)	(W)	(A)	(kg/h)	(kcal/Wh)	(W/W)
-40	226	263	897	370	3,46	6,01	0,61	0,71
-35	309	359	1.224	435	3,57	8,22	0,71	0,82
-30	413	481	1.640	506	3,73	11,06	0,82	0,95
- 25	541	629	2.146	584	3,95	14,52	0,93	1,08
-20	691	803	2.740	668	4,21	18,64	1,03	1,20
- 15	863	1.004	3.424	759	4,53	23,43	1,14	1,32
- 10	1.058	1.230	4.197	856	4,90	28,92	1,24	1,44

Refrigerant: R404A, R507

	R404A / R507									
	LBP	VOLT. FREQ.	COOL. CAP. [W]	DISPL. [cc]	мвр	VOLT. FREQ.	COOL. CAP. [W]	DISPL [cc]		
	NEK2117GK	А	125	4,51	NEK6144GK	A	550	4,51		
	NEK2121GK	А	151	5,44	NEK6165GK	A	743	6,20		
NE	NEK2125GK	Α	182	6,20	NEK6181GK	A	841	7,28		
NEK	NEK2130GK	Α	213	7,37	NEK6210GK	A/N	1.005	8,77		
NI-A	NEK2134GK	A/N	248	8,77	NEK6213GK	A	1.337	12,11		
	NEK2150GK	А	329	12,11	NEK6217GK	A/N	1.164	14,28		
	NEK2168GK	А	378	14,28						
	NEK2172GK	C	819	16,80						



PictureS Mbsm Dot Pro : WWW.mbsm.pro

embraco NEK



R404A

LBP

PictureS Mbsm Dot Pro : WWW.mbsm.pro



PictureS Mbsm Dot Pro : WWW.mbsm.pro

mbsm.pro , Compresseur Aspera , Embraco NEK2168GK , R404A , LBP ,3/4 HP Compresseur hermetique de Aspera — Embraco NEK2168GK — R404A $3/4\ HP$

220-240V 50 Hz

Cylindrée = 14.3 CM3 APPLICATIONS = LBP Moteur type: CSR

Mbsm.pro , Compresseur Aspera , Embraco NT6220Z , R134a ,power 3/4 Hp, displacement 22.40 cc , gas R134a HMBP , 220/240V

Category: Solutions, Tester ok
written by www.mbsm.pro | 18 April 2019
Mbsm.pro , Compresseur Aspera , Embraco NT6220Z , R134a ,power 3/4 Hp,
displacement 22.40 cc , gas R134a HMBP , 220/240V
Compresseur hermetique de Aspera — Embraco NT6220Z — R134a
3/4 HP
220V 50Hz 1~
Cylindrée = 22.37 CM3

APPLICATIONS = HBP Moteur type: CSIR

EMBRACO Asprea Compressor NT6220Z

Technical Details

- 220/240V
- 50Hz
- power 3/4 Hp, displacement 22.40 cc
- gas R134a HMBP
- ASPERA

SKU: 3070180

Suitable For/Compatible With

- NT6220Z ASPERA
- NT6220Z-CSIR ASPERA
- NT6220Z EMBRACO
- NT6220Z-CSIR EMBRACO




embraco NT



R134a

HBP

PictureS Mbsm Dot Pro : WWW.mbsm.pro



	R134a										
50Hz 50-60Hz	LBP	VOLT. FREQ.	COOL. CAP. [W]	DISPL. [cc]	НВР	VOLT. FREQ.	COOL. CAP. [W]	DISPL.			
					NT6215Z	C/N	1.405	17,39			
NT					NT6217Z	A/N	1.619	20,44			
NTU					NT6220Z	N	1.744	22,37			
					NTU6222ZV	A	2.117	23,70			
					NTU6224ZV	Α	2.582	27,80			

PictureS Mbsm Dot Pro : www.mbsm.pro