

# MBSM.PRO , HYE69YL ,Compressor (LBP) , China R134a ,Huayi Compressor Co., Ltd, 69 YL ,1/4 Hp ,168Kcal , 220V

Category: Solutions,Tester ok  
written by Jamila | 6 October 2018



Picture5 Mbsm Dot Pro : www.mbsm.pro

MBSM.PRO , HYE69YL ,Compressor (LBP) , China R134a ,Huayi Compressor Co., Ltd,  
69 YL ,1/4 Hp ,168Kcal , 220V

Test conditions	According to ASHRAE
Evaporating temperature	-23.3[°C]
Condensing temperature	54.4[°C]
Subcooling temperature	32.2[°C]
Suction temperature	32.2[°C]
Ambient temperature	32.2[°C]
Working condition limit:R134a	
Max ambient temperature	43[°C]
Evaporation temperature range	-35~-15[°C]
Working voltage range.	187~254/98~127[V]
Max discharge pressure	2.0[Mpa](gauge pressure)
Max allowable housing temperature	95[°C]
Max discharge temperature	125[°C]
Max pressure housing endured	2.7[Mpa](gauge pressure)

Low voltage start

0.4/0.4Mpa(gauge pressure)187V/98V

Product model:HYE69YL

Cooling capacity:195W

COP[W/W]:1.15

Voltage[V]:220-240~

Frequency(Hz):50




Products

- R134a Compressor (LBP)
  - HYE Serie
  - HY Serie
  - HYB Serie
  - HYS Serie
- R600a Compressor (LBP)
  - HYE Serie
  - HY Serie
  - HYB Serie
  - HYS Serie
- R134a Compressor (MBP,HBP)
  - HY Serie
  - HYE Serie

[Newest Catalog Download](#)



5.5



Product model:HYE69YL  
 Cooling capacity:195W  
 COP (W/W) :1.15  
 Voltage (V) :220-240-  
 Frequency(Hz):50

Test conditions	According to ASHRAE
Evaporating temperature	-23.3°C
Condensing temperature	54.4°C
Subcooling temperature	32.2°C
Suction temperature	32.2°C
Ambient temperature	32.2°C
<b>Working condition limit:R134a</b>	
Max ambient temperature	43[°C]
Evaporation temperature range	-35~-15[°C]
Working voltage range.	187~254/98~127[V]
Max discharge pressure	2.0[Mpa](gauge pressure)
Max allowable housing temperature	95[°C]
Max discharge temperature	125[°C]
Max pressure housing endured	2.7[Mpa](gauge pressure)
Low voltage start	0.40.4Mpa(gauge pressure)187V/98V



**AE 1330 Y**

**1 / 12 HP**



**AE 1340 Y**

**1 / 6 HP**



**AE 1350 Y**

**1 / 6 HP**



**AE 1360 Y**

**1 / 5 HP**



**AE 1370 Y**

**1 / 4 HP**



**AE 1390 Y**

**1 / 4 HP**





**HY 81 Y**

**1 / 4 HP**



**HYE 55 YL 63**

**1 / 6 HP**



**HYE 60 YL 63**

**1 / 5 HP**



**HYE 69 YL**

**1 / 4 HP**



**HYE 125 MSU**

**1 / 4 HP**





Huayi HYE 69 YL 1/4 Hp 168Kcal R134a 220V

Huayi - Huayi

---

Huayi HYE 55 YL 63 1/6 Hp 129Kcal R134a 220V

Huayi - Huayi

---

Huayi HYE 60 YL 63 1/5 Hp 146Kcal R134a 220V

Huayi - Huayi

---

Huavi HY 81 Y 1/4+ Hp 202Kcal R134a 220V

PictureS Mbsm Dot Pro : [www.mbsm.pro](http://www.mbsm.pro)



---

HYE 125 MSU

HYE 69 YL

HYE 60 YL 63

HYE 55 YL 63

HY 81 Y

AE 1390 Y

AE 1370 Y

AE 1360 Y

AE 1350 Y

AE 1340 Y

AE 1330 Y

PictureS Mbsm Dot Pro : [www.mbsm.pro](http://www.mbsm.pro)



# Features

# 1/4 HP

Energy Efficient

Wide Voltage Range

Low Noise & Low Vibration

High Overload Capacity

Designed for High Ambient conditions

5

Handle with care



شركة النيوغ  
للتجارة العامة المحدودة