

3HP , 2CC-3.2 , Bitzer , Semi hermetic , Refrigeration , Compressor , for cold storage

Category: Technologie, Tester ok
written by www.mbsm.pro | 12 May 2020



Private Picture Copyright: WWW.MBSM.PRO

3HP , 2CC-3.2 , Bitzer , Semi hermetic , Refrigeration , Compressor , for cold storage

NL10MF , 1/3 HP , 10,5kg 1/3HP
, Hermétique, Compressor , DANFOSS
, SECOP , R134a , 220-240V 50Hz ,
208-230V 60Hz , MBP (Medium Back
Pressure) , CSIR – RSIR (Resistance
Start – Capacitor Run)

Category: Technologie, Tester ok
written by www.mbsm.pro | 12 May 2020



Private Picture : www.MBSM.PRO

NL10MF ,1/3 HP ,10,5kg 1/3HP ,Hermétique,Compressor , DANFOSS ,SECOP ,R134a ,220-240V 50Hz , 208-230V 60Hz ,MBP (Medium Back Pressure) ,CSIR – RSIR

(Resistance Start – Capacitor Run)

Compressor ,Embraco Aspera ,NJ2212GK,
LBP – R404A, R507, 220-240V/1/50Hz,
1.5 HP, 34.38 cm³, LRA 36.0 A, CSR,
lubricant charge 750ml POE 22, 1547 W
,at -23.3 / +54.4 °

Category: Technologie,Tester ok
written by www.mbsm.pro | 12 May 2020



Private Picture Copyright : WWW.MBSM.PRO

Compressor ,Embraco Aspera ,NJ2212GK, LBP – R404A, R507, 220-240V/1/50Hz, 1.5
HP, 34.38 cm³, LRA 36.0 A, CSR, lubricant charge 750ml POE 22, 1547 W ,at -23.3
/ +54.4 °

Compresseur, Samsung , 1/5 HP,
155/160w , r600a ,220/240v~50,
Mk4a5qr1u, Mk4a5q-R1u, 5.5Lra, 1PHASE

Category: Technologie,Tester ok
written by www.mbsm.pro | 12 May 2020



Private Picture : www.MBSM.PRO

Compresseur, Samsung , 1/5 HP, 155/160w , r600a ,220/240v~50, Mk4a5qr1u, Mk4a5q-R1u, 5.5Lra, 1PHASE

Tecumseh , CAJ4511A ,Compressor , 1 HP, 208-230V, 1 PHASE, R12, Hermetic ,Reciprocating Compressor Replacement

Category: Technologie,Tester ok
written by www.mbsm.pro | 12 May 2020



Tecumseh , CAJ4511A ,Compressor , 1 HP, 208-230V, 1 PHASE, R12, Hermetic ,Reciprocating Compressor Replacement

Compressor ,ACC Cubigel ,Huayi Electrolux ,ZEM GL80AA / GUY75AA, LBP – R134a, 220 – 240V/1/50Hz, 1/4 HP, discharge 7.52 cm³, motor type RSIR / RSCR, oil type ester, oil charge 180 cm³, 150 W at -25 / +55 °, input power, current 146 W, 1.16 A, expansion device: capillary, cooling: static, weight 8.6 kg

Category: Technologie,Tester ok
written by www.mbsm.pro | 12 May 2020

cubigel compressors			ORIGINAL INSTRUCTIONS MANUAL / MANUAL DE INSTRUCCIONES ORIGINAL / MANUALE D'ISTRUZIONI ORIGINALE / MANUAL D'INSTRUCTIONS ORIGINAL / ORIGINALES ANWEISUNGEN – HANDBUCH / Оригинальное руководство по эксплуатации / 原版操作规程		RANGE / GAMA / GAMMA / GAMME / BAUREIHE / ДИАПАЗОН / 系列 "D"/"L"/"P"/"S"/"X"	
<p>RSIR / RSCR PTC "D"/"L"/"P"</p>		<p>RSIR / CSIR "D"/"L"/"P"/"X"</p>		<p>CSR "L"/"P"</p>		<p>ENGLISH</p> <ul style="list-style-type: none"> a-Compressor 1-White b-Overload 2-Blue c-PTC 3-Black d-Relay 4-Orange e-Start capacitor yellow f-Run capacitor g-Thermostat h-Earth connection <p>SPANISH</p> <ul style="list-style-type: none"> a-Compresor 1-Blanco b-Protector 2-Azul c-PTC 3- Negro d-Relé 4-Verde e-Condens. arranque amarillo f-Condens. permanente g-Termostato h-Tierra <p>ITALIANO</p> <ul style="list-style-type: none"> a-Compressore 1-Bianco b-Protettore 2-Azzurro c-PTC 3-Nero d-Relè 4-Verde e-Condens. avviamento giallo f-Condens. permanente g-Termistato h-Terza <p>FRANCAIS</p> <ul style="list-style-type: none"> a-Compresseur 1-Blanc b-Protecteur 2-Bleu c-PTC 3-Noir d-Relais 4-Vert e-Condens. démarrage jaune f-Condens. permanent g-Thermostat h-Terza <p>DEUTSCH</p> <ul style="list-style-type: none"> a-Kompressor 1-Weiß b-Überlastschutz 2-Blau c-PTC 3-Schwarz d-Relais 4-Grün e-Startkondensator gelb f-Laufkondensator g-Thermostat h-Erdleiteranschluss <p>РУССКИЙ</p> <ul style="list-style-type: none"> a-компрессор 1-Белый b-перегрузка 2-Синий c-PTC резистор 3-Черный d-реле 4-Зелено-желтый e-стартовый конденсатор f-рабочий конденсатор g-термостат h-земля <p>中文</p> <ul style="list-style-type: none"> 1-压缩机 白色 2-过载保护器 蓝色 3-启动器 黑色 4-继电器 黄-绿色 5-启动电容 6-运行电容 7-温控器 8-接地
<p>EXTERNAL CONNECTING BOX / CAJAS CONEXIONES / SCATOLE CONNESSIONI / BOÎTIER ELECTRIQUE / EXTERNE ELEKTRIKBOX / ВНЕШНЯЯ КЛЕММНАЯ КОРОБКА / 外置接线盒</p>						
<p>CSIR "S"</p>		<p>CSIR / CSR "S"</p>		<p>CSR "P"/"S"/"X"</p>		<p>PSC</p>

Private Picture : www.MBSM.PRO

mult-our web site: www.cubigel.com

02/2010 1164133

Compressor ,ACC Cubigel ,Huayi Electrolux ,ZEM GL80AA / GUY75AA, LBP – R134a, 220 – 240V/1/50Hz, 1/5 HP, discharge 7.52 cm³, motor type RSIR / RSCR, oil type ester, oil charge 180 cm³, 150 W at -25 / +55 °, input power, current 146 W, 1.16 A, expansion device: capillary, cooling: static, weight 8.6 kg

Danfoss Refrigeration, R134a, GL90TG , 220-240V 50-60Hz, R134A , HBP , CSIR , compressor Haute pression avec condensateur

Category: Technologie, Tester ok
written by www.mbsm.pro | 12 May 2020



Danfoss Refrigeration, R134a, GL90TG, 220-240V 50-60Hz, R134A, HBP, CSIR, compressor Haute pression avec condensateur

Compresor Embraco, T/M-B FFU160HAX 1/2 HP, 1,533 BTU/h, R-134 A ,MBP

Category: Technologie, Tester ok
written by www.mbsm.pro | 12 May 2020



Compresor Embraco, T/M-B FFU160HAX 1/2 HP, 1,533 BTU/h, R-134 A ,MBP

Compressor ,Moteur HP ,CSIR ,Avec Condensateur ,CUBIGEL ,GL80TB ,R-134a 1/5HP ,230V ,HMBP ,High-Medium Back Pressure

Category: Technologie, Tester ok
written by www.mbsm.pro | 12 May 2020



Private Picture Copyright : WWW.MBSM.PRO

Compressor ,Moteur HP ,CSIR ,Avec Condensateur ,CUBIGEL ,GL80TB ,R-134a 1/5HP
,230V ,HMBP ,High-Medium Back Pressure

**COMPRESSOR, EMBRACO , fgs130ha, LBP
(Low Back Pressure) ,RSCR ,316 W
,1/3+ HP ,220-240 V 50 Hz ,1080 Btu/h
,11,14 c.c.,R134a**

Category: Technologie,Tester ok

Embraco FGS130HAW

CE

THERMALLY PROTECTED		220-240V~ 50Hz
10 LRA		
R 134a	1 PH	

JOINVILLE-SC NO START WITHOUT STARTING DEVICE
MADE IN BRAZIL



513200607 FAB 1 26/JAN/05 E05DDHWA

HFC - 134a

△ 注意 △ 高温注意

Compressore	EMBRACO
Modello	FGS130HAW
Altezza (mm)	
Gas	R134a
Tensione	220-240 V 50 Hz
Applicazione	LBP (Low Back Pressure)
Test Condition	ASHRAE LBP 32
Cilindrata	11,14 c.c.
Motore	RSCR
Potenza (HP)	1/3+
Cap. Frigor. Watt	316
Cap. Frigor. Kcal	272
Cap. Frigor. Btu/h	1080
COP (W/W)	1,49
Watt assorbiti (W)	
Dispositivo di Avv.	
Condensatore	
Tipo Raffreddamento	



Embraco FGS130HAW



THERMALLY PROTECTED

10 LRA

R 134a

1 PH

220-240V~

50Hz

JOINVILLE-SC NO START WITHOUT STARTING DEVICE
MADE IN BRAZIL



513200607 FAB 1 26/JAN/05 E05DDHWA

HFC - 134a

△ 注意

△ 高温注意

Private Picture : www.MBSM.PRO

sm.pro

Compressore

EMBRACO

Modello	FGS130HAW
Altezza (mm)	
Gas	R134a
Tensione	220-240 V 50 Hz
Applicazione	LBP (Low Back Pressure)
Test Condition	ASHRAE LBP 32
Cilindrata	11,14 c.c.
Motore	RSCR
Potenza (HP)	1/3+
Cap. Frigor. Watt	316
Cap. Frigor. Kcal	272
Cap. Frigor. Btu/h	1080
COP (W/W)	1,49
Watt assorbiti (W)	
Dispositivo di Avv.	
Condensatore	
Tipo Raffreddamento	
Imballo (Pcs/Pallet)	